



# NXT® Primer

DS-502-0124

**Globally Proven  
Construction Solutions**



## 1. PRODUCT NAME

NXT® Primer

## 2. MANUFACTURER

LATICRETE International, Inc.  
1 LATICRETE Park North  
Bethany, CT 06524-3423 USA

Telephone: +1.203.393.0010, ext. 1235

Toll Free: 1.800.243.4788, ext. 1235

Fax: +1.203.393.1684

Website: [laticrete.com](http://laticrete.com)

## 3. PRODUCT DESCRIPTION

NXT Primer is a concentrated premium quality, water-based primer designed to be applied prior to the installation of NXT Underlayments. NXT Primer penetrates deeply into substrates and maximizes bond strength.

### Uses

- With NXT Underlayments
- Interior Applications Only

### Advantages

- NXT Primer is multi-purpose and can be used on a wide range of substrates.
- NXT Primer may be broom, roller, or spray applied.
- Direct replacement for DRYTEK LEVELEX Primer

### Suitable Substrates

- Cement Backer Board
- Cement Mortar Bed
- Cement Terrazzo

- Ceramic Tile and Stone
- Ceramic Tile and Stone
- Concrete
- Vinyl Tile
- Exterior Glue Plywood (Interior Only)
- Gypsum Underlayments
- Oriented Strand Board (OSB)
- Oriented Strand Board (OSB)

### Packaging

4X1GAL (4X3.8L) JUG / 28 cartons per pallet

Part #: 0905-0401-2

5GAL (19L) PAIL / 36 per pallet

Part #: 0905-0005-2

245GAL (927.4L) TOTE

Part #: 0905-0245-2

### Shelf Life

Containers are to be kept tightly sealed and stored in a cool, dry place. Shelf life is one year when stored properly, between 40-105 °F (4-41°C). Keep from freezing.

### Limitations

- Do not install when surface temperature is below 40°F (4°C), when ambient temperature is expected to be below 50°F (10°C) during placement or before material takes final set or when temperature will be above 90°F (32°C).
- Adhesives/mastics, mortars and grouts for ceramic tile, pavers, brick and stone are not replacements for waterproofing membranes. When a waterproofing membrane is required, use a LATICRETE Waterproofing Membrane on top of the dry NXT underlayment.
- Do not install NXT Primer or underlayments over particleboard, chipboard, hardboard (Masonite), Luan panels, asbestos, interior glue plywood, gypsum-based patching materials, asphalt, coal tar, or lightweight insulating concrete or any other dimensionally unstable materials.
- Not for submerged applications.

## Cautions

- Read and understand the Product Data Sheet and Safety Data Sheet.
- Perform a mock-up to ensure product will perform as required.
- Check [www.laticrete.com](http://www.laticrete.com) for any technical bulletins or updated information about the product and its application.
- NXT PRIMER is water based.
- Wear gloves and protective goggles.
- When spraying the product, avoid breathing the fine mist and use a NIOSH approved respirator.
- Contact your local LATICRETE Technical Sales Representative with any questions.
- Keep out of reach of children.

## 4. TECHNICAL DATA

### VOC/LEED Product Information

Meets all Federal, State & Local requirements for VOC. Actual field performance will depend on installation methods and site conditions. Specifications are subject to change without notification. Technical data shown in LATICRETE product data sheets and technical data sheets are typical but reflect laboratory test procedures conducted in laboratory conditions. Actual field performance and test results will depend on installation methods and site conditions. Field test results will vary greatly due to variability of critical job site factors.

Specifications subject to change without notification. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation methods and site conditions.

## 5. INSTALLATION

### Surface Preparation

- Refer to TDS230 Substrate Preparation and Primer Guide for LATICRETE Self-Leveling Products for more detailed substrate preparation instructions.
- NXT® self-leveling underlayments shall be installed over NXT Primer once cured; typically, 1 to 3 hours after application depending on ambient and substrate conditions. The primer turns from milky white to clear and is dry to the touch. There should be no release of primer from the substrate.
- Refer to TDS230 Substrate Preparation and Primer Guide for LATICRETE Self-Leveling Products.

### Mixing

NXT® Primer is a concentrate and must be diluted with clean potable water. Dilution ratio varies depending on the substrate. Mix/stir concentrate thoroughly prior to diluting.

### Application

For proper application instructions refer to TDS230 SUBSTRATE PREPARATION AND PRIMER GUIDE for LATICRETE SELF-LEVELING PRODUCTS. Field visits

by LATICRETE personnel are for the purpose of making technical recommendations only and not for supervising or providing quality control on the jobsite.

**Note:** NXT Primer can be installed over concrete that measures up to 100% relative humidity (RH) per ASTM F2170 provided there is no visible surface water on the slab. NXT Primer is not a moisture mitigation coating. If the finished flooring system requires protection from high RH in the concrete slab, use our VAPOR BAN series of moisture mitigation.

### Cleaning

All tools and equipment should be cleaned promptly with water.

### Coverage

Approximate Yield, Dilution, and Spread Rate				
SUITABLE SUBSTRATES	Approximate yield of concentrate + water per gallon <sup>1</sup>	Dilution Ratio = Primer: Water	Approximate Spread Rate Diluted <sup>2</sup>	<div><u>WATER DROP TEST</u> To help determine the appropriate primer dilution, please see TDS230 Substrate Preparation and Primer Guide for LATICRETE Self-Leveling Products</div> <div>  &lt;</div>

**NXT Primer is sold as a concentrate**

## 6. AVAILABILITY AND COST

### Availability

LATICRETE materials are available worldwide.

**For Distributor Information, Call:**

Toll Free: 1.800.243.4788

Telephone: +1.203.393.0010

For on-line distributor information, visit LATICRETE at

[laticrete.com](http://laticrete.com)**Cost**

Contact a LATICRETE Distributor in your area.

**7. WARRANTY**

See 10. FILING SYSTEM:

- 25 Year System Warranty (US - English)
- 5 Year System Warranty (US - English)
- 10 Year System Warranty (US - English)
- 1 Year Product Warranty (US - English)
- LATICRETE Lifetime System Warranty (US - English)
- Concrete Remediation 5 Year System Warranty (United States)
- Concrete Remediation 5 Year System Warranty (Canada - English)
- Concrete Remediation\_10 Year System Warranty (United States)
- Concrete Remediation 10 Year System Warranty (Canada - English)
- Concrete Remediation Lifetime System Warranty (United States)
- Concrete Remediation Lifetime System Warranty (Canada - English)
- Concrete Remediation 5 Year System Warranty (Estados Unidos - Español)
- Concrete Remediation 10 Year System Warranty (Estados Unidos - Español)
- Concrete Remediation Lifetime System Warranty (Estados Unidos - Español)

**8. MAINTENANCE**

Non-finish LATICRETE and LATAPOXY installation materials require no maintenance but installation performance and durability may depend on properly maintaining products supplied by other manufacturers.

**9. TECHNICAL SERVICES****Technical Assistance**

Information is available by calling the LATICRETE

Technical Service Hotline:

Toll Free: 1.800.243.4788, ext. 1235

Telephone: +1.203.393.0010, ext. 1235

Fax: +1.203.393.1948

**Technical and Safety Literature**

To acquire technical and safety literature, please visit our website at [laticrete.com](http://laticrete.com).

**10. FILING SYSTEM**

Additional product information is available on our website at [laticrete.com](http://laticrete.com). The following is a list of related documents:

- DS 230.13: LATICRETE 1 Year Product Warranty
- DS 230.05: LATICRETE 5 Year System Warranty
- DS 230.10: LATICRETE 10 Year System Warranty
- DS 025.0: LATICRETE 25 Year System Warranty
- DS 230.99: LATICRETE Lifetime System Warranty
- TDS 230: Substrate Preparation and Primer Guide for LATICRETE Self-Leveling Products

---

LATICRETE International, Inc.One LATICRETE Park North, Bethany, CT 06524-3423 USA • 1.800.243.4788 • +1.203.393.0010 • [www.laticrete.com](http://www.laticrete.com)

© 2024 LATICRETE International, Inc. All trademarks shown are the intellectual properties of their respective owners.