



Sellador Acrílico Premium

DS-6257E-0724

**Globally Proven
Construction Solutions**



1. NOMBRE DEL PRODUCTO

Sellador Acrílico Premium

2. FABRICANTE

LATICRETE International, Inc.
1 LATICRETE Park North
Bethany, CT 06524-3423 USA

Teléfono: +1.203.393.0010, ext. 1235

Línea telefónica gratuita: 1.800.243.4788, ext.

1235

Fax: +1.203.393.1684

Sitio de Internet: laticrete.com

3. DESCRIPCIÓN DEL PRODUCTO

Premium Acrylic Caulk is a high performance siliconized acrylic latex sealant designed for interior applications for ceramic tile and stone. Premium Acrylic Caulk is ideal for a variety of caulking applications in bathrooms, kitchens and floors.

Usos

- For caulking around sinks, tubs and showers
- Great for sealing joints between countertop and backsplashes
- Corner joints where walls meet

Ventajas

- Resists mold & mildew growth
- Stain resistant
- Matches all 40 LATICRETE® grout colors
- Easy to smooth and tool
- Adheres well to plumbing fixtures
- Resistant to staining and cracking

- Flexible

Sustratos adecuados

Presentación

Tubos de 310 ml (10.3 oz)

Rendimiento aproximado

- Coverage will vary depending upon joint size and width. Consult LATICRETE Technical Services for exact coverage.
- Approximately 25 lineal feet (7.62 m) per tube at 1/4" x 1/4" (6 x 6 mm) joint width.

Limitaciones

- For interior use only.
- Not for submerged and or permanent wet area applications. Use LATASIL™.
- Sealants are not replacements for waterproofing membranes. When a waterproofing membrane is required, use a LATICRETE Waterproofing Membrane (see Section 10 FILING SYSTEMS).
- For sensitive porous substrates such as limestone and sandstone, test sealant on a small area for any indication of fluid migration prior to job commencement.
- Not for joint applications where physical abuse or abrasion is likely.
- Not a structural glazing adhesive.
- Joint width should not exceed 1/2" (12.77 mm) thickness and no thinner than 1/8" (3.2 mm).
- For perimeter sealing or expansion joint design, the ratio of the joint width to sealant depth should be no greater than 2 times the width than depth.

Precauciones

- Protect finished work from traffic until fully cured.
- Uncured sealant causes skin irritation and serious eye damage. Avoid contact with sealant until cured. Wash thoroughly after handling.
- KEEP OUT OF REACH OF CHILDREN.
- Check with SDS sheet for further cautions.

4. DATOS TÉCNICOS

Propiedades físicas

Service Temperature Range	Unsanded -20°F (-28°C) to 180°F (82°C) Sanded 0°F (-17°C) to 180°F (82°C)
Application Temperature Range	40°F (4°C)–90°F (32°C)
Open Time	10–20 Minutes
Set Time	48 Hours
Full Cure	2 Weeks
Clean Up	Soapy Water
Mildew Resistance	Good
Consistency	Non-sag

Las especificaciones están sujetas a cambios sin notificación. Los resultados exhibidos son representativos pero reflejan los procedimientos de prueba utilizados. El desempeño real en el área de trabajo dependerá de los métodos de instalación y de las condiciones del lugar.

5. INSTALACIÓN

• Preparation

- Clean all joints and glazing pockets, removing all foreign matter and contaminants such as grease, oil, dust, water, frost, surface dirt, old sealants and protective coatings.
- In all cases where utilized, solvents should be wiped on and off with clean, oil and lint free cloths.
- When using any cleaning solvent always follow solvent manufacturer's safety and handling recommendations.
- For stone, or agglomerate tile test small area to check for any fluid migration.

Application

General installation instructions:

- Apply masking tape to the face of the veneer to protect it from the sealant. Masking tape will allow for easier removal of sealant if any comes into contact with the face of the tile. Sealant should only be applied into the joints, adhering on the flanks of the veneer. Applying the masking tape results in a cleaner look and allows for easy tooling without spillage onto the face of the veneer.
- Apply sealant to the joint, filling completely.

- "Tool" when complete (within 5–7 minutes) for a smooth professional finish.
- Remove masking tape immediately after tooling. Wipe any sealant off the face of the stone immediately.

6. DISPONIBILIDAD Y COSTO

Disponibilidad

Los materiales LATICRETE® y LATAPOXY® están disponibles en todo el mundo.

Para obtener información sobre los distribuidores, llame a:

Línea telefónica gratuita: 1.800.243.4788
Teléfono: +1.203.393.0010

Para obtener información sobre los distribuidores en Internet, visite LATICRETE en laticrete.com

Costo

Comuníquese con un distribuidor de LATICRETE de su zona.

7. GARANTÍA

Consulte la Sección 10. SISTEMAS ESPECIALES:

- 1 Year Product Warranty (US) (English)

8. MANTENIMIENTO

Joints should be cleaned regularly with common cleaners on a regular basis.

9. DEPARTAMENTO DE ASISTENCIA TÉCNICA

Asistencia técnica

Para obtener más información, comuníquese con la Línea Directa del Departamento de Asistencia Técnica de LATICRETE:

Línea telefónica gratuita:
1.800.243.4788, ext. 1235
Teléfono: +1.203.393.0010, ext. 1235
Fax: +1.203.393.1948

Material informativo sobre aspectos técnicos y de seguridad

Para obtener material sobre aspectos técnicos y de seguridad, visite nuestro sitio web en laticrete.com.

10. SISTEMAS ESPECIALES

Podrá obtener más información sobre los productos en nuestro sitio web laticrete.com. A continuación, encontrará una lista de documentos afines:

- DS 230.13: LATICRETE Product Warranty (United States and Canada)
- DS 236.0: 9235 Waterproofing Membrane
- DS 663.0: HYDRO BAN®

LATICRETE International, Inc.

One LATICRETE Park North, Bethany, CT 06524-3423 USA • 1.800.243.4788 • +1.203.393.0010 • www.laticrete.com

© 2024 LATICRETE International, Inc. All trademarks shown are the intellectual properties of their respective owners.

- DS 6200.1: LATASIL™