



STONETECH® Removedor de Manchas de Aceite

DS-214E-0624

Globally Proven
Construction Solutions



1. NOMBRE DEL PRODUCTO

STONETECH® Removedor de Manchas de Aceite

2. FABRICANTE

LATICRETE International, Inc.

1 LATICRETE Park North

Bethany, CT 06524-3423 USA

Teléfono: +1.203.393.0010, ext. 1235

Línea telefónica gratuita: 1.800.243.4788, ext.

1235

Fax: +1.203.393.1684

Sitio de Internet: laticrete.com

3. DESCRIPCIÓN DEL PRODUCTO

STONETECH® Oil Stain Remover is the ready-to-use, problem solving solution to removing deep-set oil-based stains from natural stone, masonry and grout. Just stir, apply and wait to pull out tough, deep-set organic oil and grease stains and avoid costly restoration fees.

Usos

- Countertops
- Floors
- Walls
- Interior and exterior

Ventajas

- For natural stone, masonry and grout
- Pulls out deep-set oil and grease stains
- Ready-to-use, just stir and apply
- Leaves no permanent residue

Sustratos adecuados

Presentación

Lata de 85 g (3 oz), lata de 1/2 l (1 pinta)

Rendimiento aproximado

- 1/2-1 ft² (0.05 – 0.09 m²) of surface at 1/4" (6mm) thickness per pint (473 mL).
- 15-30 in² (97-194 cm²) of surface at 1/4" (6mm) thickness per 3oz. can (88.7 mL).

Precauciones

- Consult SDS for more safety information.
- Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.
- Skin contact: Take off immediately all contaminated clothing. Wash contaminated clothing before reuse. If skin rash or an allergic skin reaction develops, get medical attention.
- Eye contact: Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention.
- Ingestion: Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical attention if any discomfort continues.

4. DATOS TÉCNICOS

Información del producto VOC/LEED

Not Regulated

Propiedades físicas

Form	Paste
Color	Grey
Odor	Lemon

Las especificaciones están sujetas a cambios sin notificación. Los resultados exhibidos son representativos pero reflejan los procedimientos de prueba utilizados. El desempeño real en el área de trabajo dependerá de los métodos de instalación y de las condiciones del lugar.

5. INSTALACIÓN

Surface Preparation

Read entire label before using. Use only as directed. Always test in a small inconspicuous area to determine that the desired results will be achieved. Make sure surface is clean, dry, and free of waxes and coatings. Ensure that area is well-ventilated and keep children and pets away from the area during application and until surface is clean and dry.

Directions

1. Using a plastic or wood spatula, stir thoroughly to mix the paste.
2. Apply a ¼" (6mm) thick layer of paste to the stain. Ensure that the paste extends at least 1–2" (25–50mm) beyond the edge of the stain.
3. Do not cover.
4. Allow 48–72 hours for paste to completely dry.
5. Using a plastic spatula, remove dried product and discard.
6. Allow solvent to completely dry from the stone.
7. If stain is not completely gone after drying, repeat process.
8. Clean up residue and tools with mineral spirits.
9. Once the surface is dry, reseal the cleaned area with a STONETECH Sealer (e.g. STONETECH® BulletProof® Sealer).

6. DISPONIBILIDAD Y COSTO

Disponibilidad

Los materiales LATICRETE® y LATAPOXY® están disponibles en todo el mundo.

Para obtener información sobre los distribuidores, llame a:

Línea telefónica gratuita: 1.800.243.4788
Teléfono: +1.203.393.0010

Para obtener información sobre los distribuidores en Internet, visite LATICRETE en laticrete.com

Costo

Comuníquese con un distribuidor de LATICRETE de su zona.

7. GARANTÍA

Consulte la Sección 10. SISTEMAS ESPECIALES:

8. MANTENIMIENTO

Please note: Prior to using any cleaning material on a tile, stone, etc. installation, test a discrete area or scrap piece of tile to insure desired results. For additional

information, please refer to the TDS 262 Stone and Tile Care Guide.

9. DEPARTAMENTO DE ASISTENCIA TÉCNICA

Asistencia técnica

Para obtener más información, comuníquese con la Línea Directa del Departamento de Asistencia Técnica de LATICRETE:

Línea telefónica gratuita:

1.800.243.4788, ext. 1235

Teléfono: +1.203.393.0010, ext. 1235

Fax: +1.203.393.1948

Material informativo sobre aspectos técnicos y de seguridad

Para obtener material sobre aspectos técnicos y de seguridad, visite nuestro sitio web en laticrete.com.

10. SISTEMAS ESPECIALES

Podrá obtener más información sobre los productos en nuestro sitio web laticrete.com. A continuación, encontrará una lista de documentos afines:

- DS 230.13: LATICRETE Product Warranty
- TDS 262: Stone and Tile Care Guide
- DS 282.0: STONETECH® BulletProof® Sealer

LATICRETE International, Inc.

One LATICRETE Park North, Bethany, CT 06524-3423 USA • 1.800.243.4788 • +1.203.393.0010 • www.laticrete.com

© 2024 LATICRETE International, Inc. All trademarks shown are the intellectual properties of their respective owners.