STONETECH® Polishing Powder

DS-224.5-1125

Globally Proven Construction Solutions

Discontinued

1. PRODUCT NAME
STONETECH® Polishing Powder

2. MANUFACTURER
LATICRETE International, Inc.
1 LATICRETE Park North
Bethany, CT 06524-3423 USA
Telephone: +1.203.393.0010, ext. 1235
Toll Free: 1.800.243.4788, ext. 1235
Fax: +1.203.393.1684
Website: laticrete.com

3. PRODUCT DESCRIPTION
STONETECH® Polishing Powder is the stone restoration powder that eliminates etch marks and light wear patterns and creates a smooth, satin finish. This non-acidic powder is designed for professional use on natural stone and terrazzo surfaces. Recommended for use following STONETECH honing powders to produce a natural polished finish.

Uses
- Countertops
- Backsplashes
- Floors
- Walls

Advantages
- Creates a smooth, satin finish
- Eliminates etch marks and light wear patterns
- Non-acidic for natural stone
- Designed for professional use

Suitable Substrates
- Marble
- Limestone
- Travertine
- Terrazzo

Packaging
US and CANADA
- ST326-0625: 1lb 9oz (708G) Canister - 6 / Case

Approximate Coverage
- Up to 1000 ft^2 per lb (205 m^2/kg), depending on the porosity of the surface

Shelf Life
Factory sealed containers of this product are guaranteed to be of first quality for two (2) years if stored at temperatures >50°F (10°C) and <90°F (32°C).

Cautions
- Eye contact: Do not rub eyes. Flush eyes thoroughly with water for at least 15 minutes. Get medical attention if irritation develops or persists

4. TECHNICAL DATA
Physical Properties

Form	Powder
Color	White
Odor	none
Specific Gravity	3.6

Specifications subject to change without notification. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation methods and site conditions.

5. INSTALLATION
Surface Preparation
Read entire label before using. Use only as directed. Always test in a small inconspicuous area to determine ease of application and desired results. Allow

new grout installations to cure for a minimum of 72 hours prior to application. Make sure surface is clean, dry and free of waxes and coatings.

Directions

1. If surface is heavily soiled, pre-clean with STONETECH® KlenzAll™ Cleaner if needed.
2. Mask off and protect any baseboards or adjacent areas to avoid splashing and overspray onto surfaces not intended to be treated.
3. If STONETECH Polishing Powder is used following the use of STONETECH Honing Powder, ensure that the surface is well rinsed and a new pad is used.
4. Apply approximately 1/2 cup (113 g) STONETECH Polishing Powder and 1 cup (237 ml) of clean water to stone surface.
5. Refinish using a hand orbital sander or weighted floor machine at 130-140 lbs (59 – 64 kg), 175 rpm, fitted with a natural hair pad.
6. Keep compound wet while refinishing with plenty of water. Add STONETECH Polishing Powder as needed.
7. Refinish area until the desired level of polish has been achieved.
8. Rinse well and use a wet vacuum or hot water extraction unit to remove all remaining compound.

6. AVAILABILITY AND COST

Availability

LATICRETE materials are available worldwide.

For Distributor Information, Call:

Toll Free: 1.800.243.4788
Telephone: +1.203.393.0010

For on-line distributor information, visit LATICRETE at **laticrete.com**

Cost

Contact a LATICRETE Distributor in your area.

7. WARRANTY

See 10. FILING SYSTEM:

- 1 Year Product Warranty (US) (English)

8. MAINTENANCE

Highly alkaline, acidic, ammoniated, and/or abrasive cleaners are not necessary for daily maintenance and may also degrade the sealer, adversely affecting stain resistance. Tile and stone routine cleaning with a neutral pH cleaner such as STONETECH® Stone & Tile Cleaner is recommended. For tough or difficult to remove soil use STONETECH KlenzAll™ Cleaner, and a nylon scrubbing pad or a long handled stiff bristle brush. Please note: Prior to using any cleaning material on a tile, stone, etc. installation, test a discrete area or scrap piece of tile to insure desired results. For additional information, please refer to the TDS 262 Stone and Tile Care Guide.

9. TECHNICAL SERVICES

Technical Assistance

Information is available by calling the LATICRETE Technical Service Hotline:

Toll Free: 1.800.243.4788, ext. 1235
Telephone: +1.203.393.0010, ext. 1235
Fax: +1.203.393.1948

Technical and Safety Literature

To acquire technical and safety literature, please visit our website at **laticrete.com.**

10. FILING SYSTEM

Additional product information is available on our website at laticrete.com. The following is a list of related documents:

- DS 230.13: LATICRETE Product Warranty
- DS 211.0: STONETECH Stone & Tile Cleaner
- DS 215.0: STONETECH KlenzAll Cleaner
- TDS 262: Stone and Tile Care Guide

LATICRETE International, Inc.
One LATICRETE Park North, Bethany, CT 06524-3423 USA • 1.800.243.4788 • +1.203.393.0010 • www.laticrete.com
© 2025 LATICRETE International, Inc. All trademarks shown are the intellectual properties of their respective owners.