

# STRATA\_HEAT™ Thermostat

DS-26.3-0324

# Globally Proven Construction Solutions



# **1. PRODUCT NAME**

STRATA\_HEAT™ Thermostat

# 2. MANUFACTURER

LATICRETE International, Inc. 1 LATICRETE Park North Bethany, CT 06524-3423 USA Telephone: +1.203.393.0010, ext. 1235 Toll Free: 1.800.243.4788, ext. 1235 Fax: +1.203.393.1684 Website: laticrete.com

# **3. PRODUCT DESCRIPTION**

The STRATA\_HEAT Thermostats are dual voltage 120V/240V and simple to use; the STRATA\_HEAT Programmable Thermostat is a digital programmable thermostat and the STRATA\_HEAT Wi-Fi Thermostat can be controlled through smart phone technology. The STRATA\_HEAT Thermostats are designed to be used with the STRATA\_HEAT Thermostats are designed to be used with the STRATA\_HEAT Wire whether it is installed with the STRATA\_MAT Spacing Strips or the STRATA HEAT Mat. All electrical connections must be made by a licensed electrician. Failure to do so will void all warranties and claims. Comply with all applicable building and electrical codes.

# Parts

One (1) power base One (1) Sensor Probe Two (2) screws

# Advantages

- Advanced floor control maximizes comfort and energy savings
- 15 A (res.) 60 Hz
- 15 ft. (4.5 m) sensor included
- · Easily accessible floor sensor connector
- Built-in GFCI with test light
- 7-day easy to program
- User friendly set-up
- Digital picture frame

#### Suitable Substrates

Physical Properties							
	Mod el	Туре	Supply	Max Loa d	Floor Senso r	GFC I	
	0802 - 0403 -T	Programmab le	120V/240 V	15A, 60 Hz	NTC (10K)	5 mA	
	0802 - 0404 -T	Wi-Fi Compatible	120V/240 V	15A, 60 Hz	NTC (10K)	5 mA	

Storage: -4°F to 140°F (-20°C to 60°C)

Size (H x W x D) 3.54 x 4.72 x 0.85 in. (90 x 120 x 21.7 mm)

2 ¾" (7 cm) double gang box is recommended

Specifications subject to change without notification. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation methods and site conditions.

# 5. INSTALLATION

Guidelines

# 4. TECHNICAL DATA

### Physical Properties

Turn off power to the heating system at the main electrical panel to avoid electrical shock. The installation should be carried out by an electrician. See Easy Set Up Guide DS-46.4 and DS-0507 provided with unit. Also go to www.laticrete.com for the following information:

Description	Numbe r	Туре
STRATA_HEA T Wi-Fi Thermostat	DS- 046.4	Easy Set Up Guide
STRATA_HEA T Programmable Thermostat	DS- 050.7	Easy Set Up Guide
STRATA_HEA T Wi-Fi Thermostat	DS- 046.2	Operating Manual
STRATA_HEA T Programmable Thermostat	DS- 050.4	Operating Manual
STRATA_HEA T Wi-Fi Thermostat	DS- 044.8	Troubleshootin g guide

# 6. AVAILABILITY AND COST

#### Availability LATICRETE materials are available worldwide.

# For Distributor Information, Call:

Toll Free: 1.800.243.4788 Telephone: +1.203.393.0010 For on-line distributor information, visit LATICRETE at laticrete.com

#### Cost

Contact a LATICRETE Distributor in your area.

#### 7. WARRANTY

See 10. FILING SYSTEM: • 1 Year Product Warranty (US - English)

#### 8. MAINTENANCE

The Internal STRATA\_HEAT<sup>™</sup> Thermostat GFCI (Ground Fault Circuit Interrupt) should be tested monthly to ensure continued safe operation. If an external GFCI is utilized, it should also be tested monthly.

#### 9. TECHNICAL SERVICES

#### **Technical Assistance**

Information is available by calling the LATICRETE Technical Service Hotline:

Toll Free:	1.800.243.4788, ext. 1235
Telephone:	+1.203.393.0010, ext. 1235
Fax:	+1.203.393.1948

#### **Technical and Safety Literature**

To acquire technical and safety literature, please visit our website at <u>laticrete.com</u>.

#### **10. FILING SYSTEM**

Additional product information is available on our website at <u>laticrete.com</u>. The following is a list of related documents:

- DS 230.13: LATICRETE Product Warranty (United States and Canada)
- DS 605.0: Floor Warming Mat
- DS 601.1: Installation Instruction Guide