



LATASIL 9118 Primer

DS-65445-1124

**Globally Proven
Construction Solutions**



1. PRODUCT NAME

LATASIL 9118 Primer

2. MANUFACTURER

LATICRETE International, Inc.

1 LATICRETE Park North

Bethany, CT 06524-3423 USA

Telephone: +1.203.393.0010, ext. 1235

Toll Free: 1.800.243.4788, ext. 1235

Fax: +1.203.393.1684

Website: laticrete.com

3. PRODUCT DESCRIPTION

LATASIL 9118 Primer is a one component primer designed to increase adhesion of LATASIL to various substrates.

Uses

- Increases adhesion & bond strength for dependable long lasting installations
- For all underwater and permanent wet area applications such as pools, fountains, showers, tubs, spas, saunas and steam rooms
- Ideal for stone applications
- Ideal for harsh environment

Advantages

- Ready to use
- Fast dry time
- Durable bond is unaffected by water

Suitable Substrates

- Tile or Stone
- Ceramic Tile
- Porcelain tile
- Quarry Tile
- Glass Tile
- Limestone
- Granite
- Marble
- Backer Board
- Concrete
- Brick
- Pavers
- Metal/Steel

Packaging

8 oz. (240 ml) bottle; 5 bottles per carton.

Approximate Coverage

Each bottle will cover approximately 350 linear feet (106 linear meters).

Limitations

- Adhesives/mastics, mortars and grouts for ceramic tile, pavers, brick and stone are not replacements for waterproofing membranes.
- When a waterproofing membrane is required, use a LATICRETE® Waterproofing Membrane (see Section 9 FILING SYSTEMS).
- Flammable—cannot be shipped air freight.

Cautions

- Consult SDS for more safety information.
- Keep out of reach of children
- **DANGER:** Highly flammable liquid and vapor. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure. Toxic to aquatic life. Harmful to aquatic life with long lasting effects. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep

away from heat/hot surfaces/sparks/open flames/and other ignition sources. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist or vapor. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Avoid release to the environment. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing and wash before reuse. Rinse skin with water. If skin irritation occurs: Get medical attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. If exposed or concerned: Get medical advice/attention. In case of fire: Use carbon dioxide for extinction. Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/ international regulations.

- **WARNING:** This product can expose you to ethylbenzene, which is known to the State of California to cause cancer, and toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

4. TECHNICAL DATA

VOC/LEED Product Information

598 g/L

Specifications subject to change without notification. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation methods and site conditions.

5. INSTALLATION

For use with LATASIL, 100% silicone sealant.

Surface Preparation:

- Thoroughly clean all surfaces of dust, dirt tar, oils, and other debris. Remove rust and scale from metal surfaces by abrasive cleaning or wire brushing. Masonry surfaces should also be wire brushed and blown with compressed air to remove dust.
- Thoroughly clean and degrease all surfaces with an industrial solvent such as naphtha, mineral spirits, xylene, toluene or MEK on a clean oil-free rag.

Application:

Sealant must be installed in the manner indicated for intended performance. Consult the following details at www.laticrete.com for guidance on specific sealant installation applications.

- Shower Receptor–Waterproofing–Cement Backer Unit Walls: ES B415
- Shower Receptor–Waterproofing Above Mortar Bed: ES B421
- Bathtub/Shower Wall Waterproofing: ES B412
- Waterproofing Membrane–Typical Pipe Penetration: ES WP300
- Drain Detail–Exploded View: ES WP302
- Waterproofing and Secondary Waterproofing Membrane - Drain Detail: ES WP303
- Swimming Pool–Tank: ES P601
- Swimming Pool–Pool Deck/Trench Drain: ES P601c

For underwater applications, submerged applications, and steam rooms, the use of polyethylene foam backer rod is recommended. Use polyethylene tape on joints too shallow to accommodate foam rod. Polyethylene backer rod is a “closed” cell foam which is water repellent.

Apply LATASIL™ 9118 Primer to clean, dry surfaces by brushing or spraying. Ensure an even, thin application to the substrate; avoid excessive thickness, as it may compromise the bond.

Allow the primer to dry fully, ensuring that all solvent has evaporated and the surface is dry to the touch. Typical dry time is 30-60 minutes at 70°F (21°C). Drying time may vary depending on temperature, humidity, and substrate porosity.

Apply LATASIL as outlined in the application instructions found in DS 6200.1.

6. AVAILABILITY AND COST

Availability

LATICRETE materials are available worldwide.

For Distributor Information, Call:

Toll Free: 1.800.243.4788

Telephone: +1.203.393.0010

For on-line distributor information, visit LATICRETE at laticrete.com

Cost

Contact a LATICRETE Distributor in your area.

7. WARRANTY

See 10. FILING SYSTEM:

- 25 Year System Warranty (US) (English)
- 10 Year System Warranty (US) (English)
- 1 Year Product Warranty (US) (English)

9. TECHNICAL SERVICES

Technical Assistance

Information is available by calling the LATICRETE Technical Service Hotline:

Toll Free: 1.800.243.4788, ext. 1235
Telephone: +1.203.393.0010, ext. 1235
Fax: +1.203.393.1948

Technical and Safety Literature

To acquire technical and safety literature, please visit our website at laticrete.com.

10. FILING SYSTEM

Additional product information is available on our website at laticrete.com. The following is a list of related documents:

- DS 6200.1: LATASIL
- DS 230.13: LATICRETE Product Warranty (United States and Canada)

A component of:

- DS 230.05APD: LATICRETE 5 Year Tile & Stone System
- DS 230.15APD: LATICRETE 15 Year Tile & Stone System
- DS 230.15SPD: LATICRETE 15 Year System Warranty – MVIS For Steel or Wood Framed Exterior Facades (United States and Canada)
- DS 025.0APD: LATICRETE 25 Year Tile & Stone System Warranty (United States and Canada)
- DS 025.0SPD: LATICRETE 25 Year System Warranty- MVIS (United States and Canada)
- DS 230.99: LATICRETE Lifetime Tile & Stone System Warranty (United States and Canada)

LATICRETE International, Inc.

One LATICRETE Park North, Bethany, CT 06524-3423 USA • 1.800.243.4788 • +1.203.393.0010 • www.laticrete.com

© 2024 LATICRETE International, Inc. All trademarks shown are the intellectual properties of their respective owners.