



# LATASIL 9118 Primer

DS-65445-0624

**Globally Proven  
Construction Solutions**



## 1. PRODUCT NAME

LATASIL 9118 Primer

## 2. MANUFACTURER

LATICRETE International, Inc.  
1 LATICRETE Park North  
Bethany, CT 06524-3423 USA

Telephone: +1.203.393.0010, ext. 1235

Toll Free: 1.800.243.4788, ext. 1235

Fax: +1.203.393.1684

Website: [laticrete.com](http://laticrete.com)

## 3. PRODUCT DESCRIPTION

LATASIL 9118 Primer is a one component primer designed to increase adhesion of LATASIL to various substrates.

### Uses

- Increases adhesion & bond strength for dependable long lasting installations
- For all underwater and permanent wet area applications such as pools, fountains, showers, tubs, spas, saunas and steam rooms
- Ideal for stone applications
- Ideal for harsh environment

### Advantages

- Ready to use
- Fast dry time
- Durable bond is unaffected by water

### Suitable Substrates

#### Packaging

8 oz. (240 ml) bottle; 5 bottles per carton.

#### Approximate Coverage

Each bottle will cover approximately 350 linear feet (106 linear meters).

### Limitations

- Adhesives/mastics, mortars and grouts for ceramic tile, pavers, brick and stone are not replacements for waterproofing membranes.
- When a waterproofing membrane is required, use a LATICRETE® Waterproofing Membrane (see Section 9 FILING SYSTEMS).
- Flammable—cannot be shipped air freight.

### Cautions

- Consult SDS for more safety information.
- Causes serious eye irritation. If contact with eyes occurs, immediately flush with water and seek medical attention.
- Causes skin irritation. In case of skin contact, wash affected area as soon as possible.
- Keep away from heat, sparks and open flames.
- Use with adequate ventilation, do not breathe vapors.
- Highly flammable—store in safe location.
- Test a small area when applying to stone for compatibility.
- Keep out of reach of children.

## 4. TECHNICAL DATA

Specifications subject to change without notification. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation methods and site conditions.

## 5. INSTALLATION

### Preparation:

- Thoroughly clean all surfaces of dust, dirt tar, oils, and other debris. Remove rust and scale from metal

surfaces by abrasive cleaning or wire brushing. Masonry surfaces should also be wire brushed and blown with compressed air to remove dust.

- Thoroughly clean and degrease all surfaces with an industrial solvent such as naphtha, mineral spirits, xylene, toluene or MEK on a clean oil-free rag.

#### Application:

- Sealant must be installed in the manner indicated for intended performance.
- Data Sheets are subject to change without notice. For latest revision, visit [www.laticrete.com](http://www.laticrete.com). DS-6528.1-0414

Consult the following details at [www.laticrete.com](http://www.laticrete.com) for specific sealant installation applications:

- Shower Receptor–Waterproofing-Cement Backer Unit Walls ES B415
- Shower Receptor–Waterproofing Above Mortar Bed ES B421
- Bathtub/Shower Wall Waterproofing ES B412
- Waterproofing Membrane-Typical Pipe Penetration ES WP300
- Drain Detail-Exploded View ES WP302
- Waterproofing and Secondary Waterproofing Membrane - Drain Detail ES WP303
- Swimming Pool-Tank ES P601
- Swimming Pool-Pool Deck/Trench Drain ES P601c
- For underwater applications and steam rooms, polyethylene foam backer rod is recommended. Use polyethylene tape on joints too shallow to accommodate foam rod. Polyethylene backer rod is a “closed” cell which is water repellent.
- Apply LATAFIL™ 9118 Primer to clean, dry surfaces by brushing, dipping, or spraying.
- Apply a thin layer evenly to the substrate-do not apply too thick as bond will break.
- Take care not to contaminate the veneer surface.
- Allow the primer to dry until all the solvent evaporates and is dry to the touch (generally 30–60 minutes at 70°F/21°C). Drying time depends on temperature, humidity conditions and the porosity of the substrate.
- Apply sealant as directed (see DS 6200.1).

## 6. AVAILABILITY AND COST

### Availability

LATICRETE materials are available worldwide.

### For Distributor Information, Call:

Toll Free: 1.800.243.4788

Telephone: +1.203.393.0010

For on-line distributor information, visit LATICRETE at [laticrete.com](http://laticrete.com)

### Cost

Contact a LATICRETE Distributor in your area.

## 7. WARRANTY

See 10. FILING SYSTEM:

- 25 Year System Warranty (US) (English)
- 10 Year System Warranty (US) (English)
- 1 Year Product Warranty (US) (English)

## 8. MAINTENANCE

- Adhesives/mastics, mortars and grouts for ceramic tile, pavers, brick and stone are not replacements for waterproofing membranes. When a waterproofing membrane is required, use a LATICRETE® Waterproofing Membrane (see Section 9 FILING SYSTEMS).
- Flammable—cannot be shipped air freight.

## 9. TECHNICAL SERVICES

### Technical Assistance

Information is available by calling the LATICRETE Technical Service Hotline:

Toll Free: 1.800.243.4788, ext. 1235

Telephone: +1.203.393.0010, ext. 1235

Fax: +1.203.393.1948

### Technical and Safety Literature

To acquire technical and safety literature, please visit our website at [laticrete.com](http://laticrete.com).

## 10. FILING SYSTEM

Additional product information is available on our website at [laticrete.com](http://laticrete.com). The following is a list of related documents:

See 9. FILING SYSTEM:

DS 230.13: LATICRETE Product Warranty (United States and Canada)

A component of:

DS 230.05APD: LATICRETE 5 Year Tile & Stone System

Warranty (United States and Canada)

DS 230.15APD: LATICRETE 15 Year Tile & Stone System

Warranty for Steel or Wood Framed Exterior Facades

(United States and Canada) DS 230.15SPD:

LATICRETE 15 Year System Warranty – MVIS For Steel or Wood Framed Exterior Facades (United States and Canada)

DS 025.0APD: LATICRETE 25 Year Tile & Stone System Warranty (United States and Canada)

DS 025.0SPD: LATICRETE 25 Year System Warranty-MVIS (United States and Canada)

DS 230.99: LATICRETE Lifetime Tile & Stone System Warranty (United States and Canada)

LATICRETE International, Inc.

One LATICRETE Park North, Bethany, CT 06524-3423 USA • 1.800.243.4788 • +1.203.393.0010 • [www.laticrete.com](http://www.laticrete.com)

© 2024 LATICRETE International, Inc. All trademarks shown are the intellectual properties of their respective owners.

