

# STRATA\_HEAT Programmable LCD Thermostat

DS-65448-0824

## Globally Proven Construction Solutions



#### 1. PRODUCT NAME

STRATA\_HEAT Programmable LCD Thermostat

#### 2. MANUFACTURER

LATICRETE International, Inc. 1 LATICRETE Park North Bethany, CT 06524-3423 USA

Telephone: +1.203.393.0010, ext. 1235 Toll Free: 1.800.243.4788, ext. 1235

Fax: +1.203.393.1684 Website: laticrete.com

#### 3. PRODUCT DESCRIPTION

The STRATA\_HEAT Programmable LCD Thermostat is dual voltage 120V/240V Wifi enabled thermostat that is both easy to install and to use. It features a minimalistic LED touch-panel that centers around ease of use. The STRATA\_HEAT Thermostats are designed to be used with the STRATA\_HEAT Wire whether it is installed with the STRATA\_MAT Spacing Strips or the STRATA HEAT Mat. All electrical connections must be made by a licensed electrician. Failure to do so will void all warranties and claims. Comply with all applicable building and electrical codes.

#### **Parts**

One (1) power base

One (1) Sensor Probe

One (1) Instruction Manual

Two (2) screws

#### **Advantages**

- 120v/240v Compatibility
- User-friendly touch pad display
- Full color LCD screen

- Optional temperature settings by week, weekday/weekend, and daily
- Built in Ground Fault Control (GFC)
- Complete STRATA\_HEAT™ radiant heating system can be used a primary heat source

#### Suitable Substrates (Interior Use Only)

Radiant Heated Floors (Interior Only)

### Packaging

#### **Parts**

One (1) power base

One (1) Sensor Probe

One (1) Instruction Manual

Two (2) screws

#### 4. TECHNICAL DATA

**Physical Properties** 

Model	Туре	Supply	Max. Load	Floor Sensor	GFCI
0402-	Programmable LCD Thermostat	120V/240V	15A, 60 Hz	NTC (10K)	5 mA
0804- 0403- TW	Wifi Thermostat	120V/240V	15A, 60 Hz	NTC (10K)	5 mA
0804- 0404- TW	Smart LCD Thermostat	120V/240V	15A, 60 Hz	NTC (10K)	5 mA

Storage: -4°F to 140°F (-20°C to 60°C)

Size (H x W x D) 3.54 x 4.72 x 0.85 in. (90 x 120 x 21.7

mm)

2 3/4" (7 cm) double gang box is recommended

Specifications subject to change without notification. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation methods and site conditions.

#### 5. INSTALLATION

Guidelines

Turn off power to the heating system at the main electrical panel to avoid electrical shock. The installation should be carried out by an electrician. See Easy Set Up Guide DS-46.4 and DS-0507 provided with unit. Also go to www.laticrete.com for the following information:

Description	Number	per Type	
STRATA_HEAT Wi-	DS-	Easy Set Up	
Fi Thermostat	046.4	Guide	
STRATA_HEAT Programmable Thermostat	DS- 050.7	Easy Set Up Guide	
STRATA_HEAT Wi-	DS-	Operating	
Fi Thermostat	046.2	Manual	
STRATA_HEAT Programmable Thermostat	DS- 050.4	Operating Manual	
STRATA_HEAT Wi-	DS-	Troubleshooting	
Fi Thermostat	044.8	guide	

#### **Technical and Safety Literature**

To acquire technical and safety literature, please visit our website at **laticrete.com**.

#### **10. FILING SYSTEM**

Additional product information is available on our website at <u>laticrete.com</u>. The following is a list of related documents:

- DS 230.13: LATICRETE Product Warranty (United States and Canada)
- DS 605.0: Floor Warming Mat
- DS 601.1: Installation Instruction Guide

#### 6. AVAILABILITY AND COST

#### **Availability**

LATICRETE materials are available worldwide.

#### For Distributor Information, Call:

Toll Free: 1.800.243.4788 Telephone: +1.203.393.0010

For on-line distributor information, visit LATICRETE at

laticrete.com

#### Cost

Contact a LATICRETE Distributor in your area.

#### 7. WARRANTY

See 10. FILING SYSTEM:

- 1 Year Product Warranty (US) (English)
- LATICRETE Lifetime System Warranty (US) (English)

#### 8. MAINTENANCE

The Internal STRATA\_HEAT™ Thermostat GFCI (Ground Fault Circuit Interrupt) should be tested monthly to ensure continued safe operation. If an external GFCI is utilized, it should also be tested monthly.

#### 9. TECHNICAL SERVICES

#### **Technical Assistance**

Information is available by calling the LATICRETE Technical Service Hotline:

Toll Free: 1.800.243.4788, ext. 1235 Telephone: +1.203.393.0010, ext. 1235

Fax: +1.203.393.1948