



NXT® Pedestal Mini

DS-65454-0425

**Globally Proven
Construction Solutions**



1. PRODUCT NAME

NXT® Pedestal Mini

2. MANUFACTURER

LATICRETE International, Inc.

1 LATICRETE Park North

Bethany, CT 06524-3423 USA

Telephone: +1.203.393.0010, ext. 1235

Toll Free: 1.800.243.4788, ext. 1235

Fax: +1.203.393.1684

Website: laticrete.com

3. PRODUCT DESCRIPTION

Designed to meet lower height requirements, with an adjustable range from $\frac{3}{4}$ inch (20mm) to 1-3/4 inches (45mm). Offering the same durability and effortless installation as the Max unit, it seamlessly integrates into any flooring project. Ideal for areas requiring minimal elevation, this unit provides dependable support and reliability without compromise.

Uses

Pedestal paver systems are highly versatile and can be installed over various substrates, provided they are structurally sound and capable of supporting the system's load.

Applications include:

- Paved areas or raised timber
- Pavers (Porcelain, stone, concrete, etc)
- Timber decking

Advantages

- Adjustable head – accommodates up to 5 degrees of slope
- Triple screw adjustment – enables superior fine-tuning elevation adjustment
- 5/32" spacer tab included
- Built in sound dampening head pad
- "Click and connect" – easily combine with Extenders to achieve a full range of install elevations
- Superior durability and load rated up to 2,200 psi
- Rapid water outflow
- Provides increased thermal insulation and expansion absorption
- Ideal for various materials including concrete, porcelain, natural stone, marble, granite, and decking
- Easily install over existing or new surfaces
- Can be installed over liquid, bituminous, and synthetic membrane systems
- Compatible with our full line of accessories including Rubber Shims, Slope Correctors, Timber Joist Brackets, Wind Uplift Anchors, and Base Protection Pads
- High Speed Chuck tool enables quick height adjustment, saving installers time
- Maintenance Key provides ease of maintenance. Pedestals can be adjusted after the tile or decking has been installed

Suitable Substrates

- Concrete and Masonry Surfaces
- Exterior Glue Plywood decks that have been waterproofed with a primary roof waterproofing membrane
- Metal/Steel

Packaging

72 Pieces per carton

Approximate Coverage

Coverage will vary based on surface finish type and dimensions.

Limitations

DO NOT

- Install any NXT Pedestals upside down for any reason.
- Cut the pedestal for any application.
- Use 4" extenders without a pedestal body and base.

4. TECHNICAL DATA

Physical Properties

Test No.	Maximus Force (kN)	Maximus Weight (Kg)
1	20.04	2,043kg
2	21.00	2,141kg

**NATA accredited for compliance with ISO/IEC 17025 by
ATTAR - Advanced Technology Testing and Research**

Load Capacity

Test no.1: Load ratings taken at fully extended position centrally loaded and force applied

Test no.2: Load ratings taken at fully extended position centrally loaded and force applied

Working Properties

Specifications subject to change without notification. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation methods and site conditions.

5. INSTALLATION

Installation Instructions

STEP 1:

Ensure the substrate is clean, smooth and free of building debris. NXT Pedestals are not suitable for soft surfaces ie. grass, loose gravel, crushed rock, etc. If the substrate is membraned - we recommend using the NXT Pedestal – Base Pad.

STEP 2:

Measure the area into equal parts based on tile size. Using a chalk line aids in set out and finding the best pedestal placement.

Note The NXT Pedestal system has 5/32" spacer joints.

STEP 3:

It is recommended to start in the corner and ensure the pedestal and tile is place against a solid perimeter.

STEP 4:

Lay suitable tiles/pavers/stone on top of the pedestals ensuring the material is level.

6. AVAILABILITY AND COST

Availability

LATICRETE materials are available worldwide.

For Distributor Information, Call:

Toll Free: 1.800.243.4788

Telephone: +1.203.393.0010

For on-line distributor information, visit LATICRETE at laticrete.com

Cost

Contact a LATICRETE Distributor in your area.

7. WARRANTY

See 10. FILING SYSTEM:

- 5 Year Product Warranty - Pedestals

9. TECHNICAL SERVICES

Technical Assistance

Information is available by calling the LATICRETE Technical Service Hotline:

Toll Free: 1.800.243.4788, ext. 1235

Telephone: +1.203.393.0010, ext. 1235

Fax: +1.203.393.1948

Technical and Safety Literature

To acquire technical and safety literature, please visit our website at laticrete.com.

LATICRETE International, Inc.

One LATICRETE Park North, Bethany, CT 06524-3423 USA • 1.800.243.4788 • +1.203.393.0010 • www.laticrete.com

© 2025 LATICRETE International, Inc. All trademarks shown are the intellectual properties of their respective owners.