



170 Sound & Crack Isolation Mat

DS-65495-0226

**Globally Proven
Construction Solutions**



- To isolate cracks in tile work and reduce noise transmission, 170 Sound & Crack Isolation Mat should be applied to the entire substrate prior to the installation of ceramic tile, marble, stone, terrazzo and brick.

Advantages

- Isolates transmission of substrate cracks of up to 1/8" (3 mm) from transferring to the finished floor
- Delta IIC rating per ASTM E2179 (See PHYSICAL PROPERTIES)
- IIC rating per ASTM E492/ E989 (See PHYSICAL PROPERTIES)
- Load bearing - Rating per ASTM C627/TCA (See PHYSICAL PROPERTIES)
- Meets ANSI A118.12 specifications*
- Meets ANSI A118.13 specifications*
- Easy and fast to install with standard tools
- * Interior dry applications only

Suitable Substrates

- Concrete
- Mortar Bed
- Exterior Glue Plywood (Interior Only)
- Cement Backer Board
- Cement Terrazzo
- Ceramic Tile and Stone

Packaging

Roll Size:
4 ft x 50 ft (200 ft² per roll (3mm))
4 ft x 25 ft (100 ft²) (5mm, 10mm, 12mm)
 Sheet Size:
30" x 48" (10 ft²)

Approximate Coverage:

Rolls:
200 ft² - 3mm
100 ft² - 5mm, 10mm, 12mm
 Sheets:
10 ft² - 3mm, 5mm, 10mm, 12mm

Approximate Coverage

	3mm	5mm	10mm	12mm
Sheet	30" x 48" (10 sqft)	30" x 48" (10 sqft)	30" x 48" (10 sqft)	30" x 48" (10 sqft)
Roll	4' x 50' (200 sqft)	4' x 25' (100 sqft)	4' x 25' (100 sqft)	4' x 25' (100 sqft)

1. PRODUCT NAME

170 Sound & Crack Isolation Mat

2. MANUFACTURER

LATICRETE International, Inc.
 1 LATICRETE Park North
 Bethany, CT 06524-3423 USA
 Telephone: +1.203.393.0010, ext. 1235
 Toll Free: 1.800.243.4788, ext. 1235
 Fax: +1.203.393.1684
 Website: laticrete.com

3. PRODUCT DESCRIPTION

170 Sound & Crack Isolation Mat is a rubberized high performance acoustical underlayment membrane that muffles impact noises through ceramic tiles, stone and other hard surfacing materials. It also minimizes the transmission of cracks from the substrate to the tile installation up to 1/8" (3 mm), non-movement cracks. 170 Sound & Crack Isolation Mats are comprised of 94% post-consumer materials and offered in both sheet and roll configurations. Thickness offered: 3 mm, 5 mm, 10 mm, 12 mm.

Uses

- Designed to be used under thin-bed adhesive for interior floor installations of ceramic tile, marble, stone, and brick to eliminate the transmission of impact noise from one floor to the floor below
- Isolates the transmission of stresses from the concrete base slab to the tile installation
- Combines low installed weight with minimal "above substrate" thickness

Limitations

- DO NOT bond to particle board, OSB, luan, Masonite® or hardwood surfaces.
- For horizontal use over suitable interior substrates only.
- DO NOT double stack pallets.
- Not for use over expansion joints or structural movement cracks.
- 170 Sound & Crack Isolation Mat is not intended for use as a waterproofing membrane.
- Adhesives/mastics, mortars and grouts for ceramic tile, pavers, brick and stone are not replacements for waterproofing membranes. When a waterproofing membrane is required, use a LATICRETE® Waterproofing Membrane (see Section 10 FILING SYSTEMS).
- Minimum tile size to be installed over 170 Sound & Crack Isolation mat is 4"x4" (102 x 102 mm).

Cautions

- During cold weather, protect finished work from traffic until fully cured.
- For green marble, resin backed or other moisture sensitive tile or stone, use LATAPOXY® 300 Adhesive, refer to Data Sheet 633.0.
- For white and light-colored marbles use 254 Platinum (WHITE).
- Keep out of reach of children.

4. TECHNICAL DATA

Applicable Standard

- ASTM E2179, ASTM C 627, ANSI A 118.13, ANSI A 118.12

Physical Properties

Tested with LATICRETE polymer fortified thinset

Property	Test Method	Result*
Shear Bond	ANSI A118,13	Pass*
Point Load	ANSI A118.12	High Performance*
Impact Insulation Classes	ASTM E2179 (Delta) ASTM E989	Delta IIC 28*
Sound Transmission Class (STC)	ASTM E90 ASTM E143	64*
Impact Insulation Class (IIC)	ASTM E492 ASTM E989	63*

* IIC Rating based on independent laboratory tests.

Complete test report available upon request.

* Contact customer service for details on specific applications

Specifications subject to change without notification. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation methods and site conditions.

5. INSTALLATION

- Surface Preparation Concrete shall be in place for 28 days (minimum) and shall be dry. The surface shall have a smooth finish and be free of voids, sharp protrusions and loose aggregate. All surfaces should be between 40°F (4°C) and 90°F (32°C) and structurally sound, clean and free of all dirt, oil, grease, paint, concrete sealers or curing compounds and cement laitance. Rough or uneven concrete surfaces should be made smooth with a modified Portland cement underlayment to provide a wood float or better finish. Do not level with gypsum or asphalt based products. Refer to Technical Data Sheet 152 "Bonding Ceramic Tile, Stone or Brick Over Wood Floors" (refer to section 10, FILING SYSTEMS). Installer must verify that deflection under all live, dead and impact loads of interior plywood floors does not exceed industry standards of L/360 for ceramic tile and brick or L/480 for stone installations where L=span length. Minimum construction for interior plywood floors. SUBFLOOR: 5/8" (15 mm) thick exterior glue plywood, either plain with all sheet edges blocked or tongue and groove, over bridged joists spaced 16" (400 mm) o.c. maximum; fasten plywood 6" (150 mm) o.c. along sheet ends and 8" (200 mm) o.c. along intermediate supports with 8d ring-shank, coated or hot dip galvanized nails (or screws); allow 1/8" (3 mm) between sheet ends and 1/4" (6 mm) between sheets edges; all sheet ends must be supported by a framing member; glue sheets to joists with construction adhesive. UNDERLAYMENT: 5/8" (15 mm) thick exterior glue plywood fastened 6" (150 mm) o.c. along sheet ends and 8" (200 mm) o.c. in the panel field (both directions) with 8d ring-shank, coated or hot dip galvanized nails (or screws); allow 1/8" (3 mm) to 1/4" (6 mm) between sheets and 1/4" (6 mm) between sheet edges and any abutting surfaces; offset underlayment joists from joints in subfloor and stagger joints between sheet ends; glue underlayment to subfloor with construction adhesive. Refer to Technical Data Sheet 152 "Requirements for Direct Bonding of Ceramic or Stone Tiles Over Wood Floors" for complete details. Application Perimeter Isolation Strip It is essential that all walls and building elements are isolated from the floor. The use of acoustical ceiling panels in the space below would provide additional sound control. Note: It is recommended to install a perimeter isolation strip before placing and trimming 170 Sound & Crack Isolation Mat. Attach the perimeter isolation strip to the perimeter wall of the entire subfloor, as well as around the perimeter of any protrusions, in order to isolate or break the vibration transmission path between the floor and the wall.

Temporarily fasten perimeter isolation strip in place with masking, duct, or carpet tape. The perimeter isolation strip can then be removed after the tiles have set firm. The joints can then be filled with an appropriate acoustical sealant. Note: As an alternative to perimeter isolation strip, the installer may run the sheets of 170 Sound & Crack Isolation mat up the wall approximately 3" (75 mm). This should take place throughout the entire perimeter of the room as well as around the perimeter of any protrusions in order to isolate or break the vibration transmission path between the floor and the wall. 170 Sound & Crack Isolation Mat Installation instructions: Use a polymer fortified multipurpose thin set adhesive (e.g. 254 Platinum) to adhere the 170 Sound & Crack Isolation Mat to the substrate. Use a 1/4" x 1/4" (6 mm x 6 mm) notched trowel and comb mortar over substrate, apply only enough mortar as can be covered within 25 minutes. Unroll or place sheet into place, in the thin set adhesive mortar. Once installed, use a 25–45 lbs (11.3–20 kg) roller to embed the 170 Sound & Crack Isolation Mat firmly into the thin set adhesive mortar. Allow to cure for 24 hrs at 70°F (21°C). Install 170.3 Sound & Crack Isolation Mat over the area to be treated, do not overlap edges but be sure edges of each piece but firmly together. Trim length of mat to desired length and width. Once fully cured, install ceramic tile, porcelain or stone finish directly over the 170 Sound & Crack Isolation Mat using a polymer fortified multipurpose thin set adhesive. Follow instructions on adhesive packaging (refer to section 10, FILING SYSTEMS).

6. AVAILABILITY AND COST

Availability

LATICRETE materials are available worldwide.

For Distributor Information, Call:

Toll Free: 1.800.243.4788

Telephone: +1.203.393.0010

For on-line distributor information, visit LATICRETE at laticrete.com

Cost

Contact a LATICRETE Distributor in your area.

7. WARRANTY

See 10. FILING SYSTEM:

- 25 Year System Warranty (US) (English)
- 10 Year System Warranty (US) (English)
- 5 Year System Warranty (US) (English)
- 1 Year Product Warranty (US) (English)

8. MAINTENANCE

LATICRETE and LATAPOXY grouts require routine cleaning with a neutral pH soap and water. All other LATICRETE and LATAPOXY materials require no maintenance but installation performance and durability may depend on properly maintaining products supplied by other manufacturers.

9. TECHNICAL SERVICES

Technical Assistance

Information is available by calling the LATICRETE Technical Service Hotline:

Toll Free: 1.800.243.4788, ext. 1235

Telephone: +1.203.393.0010, ext. 1235

Fax: +1.203.393.1948

Technical and Safety Literature

To acquire technical and safety literature, please visit our website at laticrete.com.

10. FILING SYSTEM

Additional product information is available on our website at laticrete.com. The following is a list of related documents:

- DS 230.13: LATICRETE Product Warranty
- DS 230.05: LATICRETE 5 Year System Warranty
- DS 230.10: LATICRETE 10 Year System Warranty
- DS 025.0: LATICRETE 25 Year System Warranty

LATICRETE International, Inc.

One LATICRETE Park North, Bethany, CT 06524-3423 USA • 1.800.243.4788 • +1.203.393.0010 • www.laticrete.com

© 2026 LATICRETE International, Inc. All trademarks shown are the intellectual properties of their respective owners.