



L&M™ CITREX™

DS-176.6E-1224

**Globally Proven
Construction Solutions**



steel mills, sewage plants, or oil burning power plants. It is also recommended for use in warehouses to remove rubber tire marks and other contaminants.

Ventajas

- Removes oil and grease accumulations
- Pleasant citrus odor
- Concentrated for economy and ease of use
- USDA authorized

Sustratos adecuados

Presentación

3.8 l (1 gal.), 18.9 l (5 gal.), 208 l (55 gal.)

Rendimiento aproximado

Cleaning Agent: 150 ft²/gal (3.7 m²/L) (Diluted)

Limitaciones

- Do not use on resilient tile, rubber or asphalt, and painted wall surfaces
- Do not use in the presence of open foodstuffs
- Remove food before using
- For commercial and industrial use only

Precauciones

- CITREX contains citrus terpenes
- Wear protective gloves and goggles
- Do not use on rubber, resilient tiles, or asphalt surfaces
- Do not use near fire or flame
- Harmful if swallowed
- Do not use in presence of open foodstuffs
- For industrial use only by trained personnel
- Please refer to Safety Data Sheet (SDS) before using
- Mock-ups and field test areas are required in order to validate performance and appearance related characteristics (including but not limited to color, inherent surface variations, wear, anti-dusting, abrasion resistance, chemical resistance, stain resistance, coefficient of friction, etc.) to ensure system performance as specified for the intended use, and to determine approval of the decorative flooring system.

1. NOMBRE DEL PRODUCTO

L&M™ CITREX™

2. FABRICANTE

LATICRETE International, Inc.

1 LATICRETE Park North

Bethany, CT 06524-3423 USA

Teléfono: +1.203.393.0010, ext. 1235

Línea telefónica gratuita: 1.800.243.4788, ext.

1235

Fax: +1.203.393.1684

Sitio de Internet: laticrete.com

3. DESCRIPCIÓN DEL PRODUCTO

CITREX is a heavy duty, citrus based degreaser and cleaner for both specialized cleaning and every day maintenance. This pleasantly fragrant cleaner is formulated to include low foaming emulsifiers and degreasing agents in high concentrations. CITREX is concentrated to maintain high activity at various dilutions with water to effectively remove accumulations of built-up grease, grime, oil and rubber burns.

Usos

- Use CITREX to deeply penetrate surfaces to dissolve dirt and emulsify fats and greases quickly and easily in food processing plants, meat packing plants, canneries, restaurants, kitchens, bakeries, dairy, cheese and fish processors where thorough cleanliness is critical. CITREX is also effective in removing grime, oil and contaminants from concrete, masonry or other surfaces in parking garages, truck and automotive plants, warehouses, industrial plants,

4. DATOS TÉCNICOS

Propiedades físicas

Property	Observed
Color	Amber
Odor	Orange
Phosphate	None
Film	None
USDA approved	Yes
pH 5% emulsion	6-7

Las especificaciones están sujetas a cambios sin notificación. Los resultados exhibidos son representativos pero reflejan los procedimientos de prueba utilizados. El desempeño real en el área de trabajo dependerá de los métodos de instalación y de las condiciones del lugar.

5. INSTALACIÓN

As a cleaner: For general cleanup applications, dilute CITREX™ with water to suit the extent of the accumulated dirt. A solution of 1 part CITREX to 5 parts water is usually adequate for most cleaning jobs. Experiment with varied concentrations to determine which strength is most suitable for the cleaning and degreasing task. Add a minimum of 15 oz/gal (117 ml/L). This cleaner may be applied using automatic floor scrubbers, sprayers or conventional methods. Heavily caked grease should be first scraped from surfaces. Apply diluted CITREX at the rate of 150 ft²/gal (3.7m²/l).

Application: Allow to stand 2-10 minutes. Scrub contaminated area. Flush with water or vacuum loosened contaminants, dirt, oil and grease after scrubbing. Redo areas where heavy accumulation of tire marks, sealer film, oil, grease or other contaminants has occurred and some stubborn stains remain.

6. DISPONIBILIDAD Y COSTO

Disponibilidad

Los materiales LATICRETE® y LATAPOXY® están disponibles en todo el mundo.

Para obtener información sobre los distribuidores, llame a:

Línea telefónica gratuita: 1.800.243.4788
Teléfono: +1.203.393.0010

Para obtener información sobre los distribuidores en Internet, visite LATICRETE en laticrete.com

Costo

Comuníquese con un distribuidor de LATICRETE de su zona.

7. GARANTÍA

Consulte la Sección 10. SISTEMAS ESPECIALES:

9. DEPARTAMENTO DE ASISTENCIA TÉCNICA

Asistencia técnica

Para obtener más información, comuníquese con la Línea Directa del Departamento de Asistencia Técnica de LATICRETE:

Línea telefónica gratuita:

1.800.243.4788, ext. 1235

Teléfono: +1.203.393.0010, ext. 1235

Fax: +1.203.393.1948

Material informativo sobre aspectos técnicos y de seguridad

Para obtener material sobre aspectos técnicos y de seguridad, visite nuestro sitio web en laticrete.com.

10. SISTEMAS ESPECIALES

Podrá obtener más información sobre los productos en nuestro sitio web laticrete.com. A continuación, encontrará una lista de documentos afines:

- DS 230.13: LATICRETE Product Warranty

LATICRETE International, Inc.

One LATICRETE Park North, Bethany, CT 06524-3423 USA • 1.800.243.4788 • +1.203.393.0010 • www.laticrete.com

© 2024 LATICRETE International, Inc. All trademarks shown are the intellectual properties of their respective owners.