



# L&M™ CITREX™

DS-176.6F-1224

**Globally Proven  
Construction Solutions**



## 1. NOM DU PRODUIT

L&M™ CITREX™

## 2. FABRICANT

LATICRETE International, Inc.

1 LATICRETE Park North

Bethany, CT 06524-3423 États-Unis

Téléphone: +1.203.393.0010, poste 1235

Numéro sans frais: 1.800.243.4788, poste 1235

Télécopieur: +1.203.393.1684

Site Web: [laticrete.com](http://laticrete.com)

## 3. DESCRIPTION DU PRODUIT

CITREX is a heavy duty, citrus based degreaser and cleaner for both specialized cleaning and every day maintenance. This pleasantly fragrant cleaner is formulated to include low foaming emulsifiers and degreasing agents in high concentrations. CITREX is concentrated to maintain high activity at various dilutions with water to effectively remove accumulations of built-up grease, grime, oil and rubber burns.

### Utilisation

- Use CITREX to deeply penetrate surfaces to dissolve dirt and emulsify fats and greases quickly and easily in food processing plants, meat packing plants, canneries, restaurants, kitchens, bakeries, dairy, cheese and fish processors where thorough cleanliness is critical. CITREX is also effective in removing grime, oil and contaminants from concrete, masonry or other surfaces in parking garages, truck and automotive plants, warehouses, industrial plants, steel mills, sewage plants, or oil burning power plants.

It is also recommended for use in warehouses to remove rubber tire marks and other contaminants.

### Avantages

- Removes oil and grease accumulations
- Pleasant citrus odor
- Concentrated for economy and ease of use
- USDA authorized

### Supports Appropriés

### Conditionnement

3,8 L (1 gal), 18,9 L (5 gal), 208,2 L (55 gal)

### Couverture approximative

Cleaning Agent: 150 ft<sup>2</sup>/gal (3.7 m<sup>2</sup>/L) (Diluted)

### Restrictions

- Do not use on resilient tile, rubber or asphalt, and painted wall surfaces
- Do not use in the presence of open foodstuffs
- Remove food before using
- For commercial and industrial use only

### Mises en garde

- CITREX contains citrus terpenes
- Wear protective gloves and goggles
- Do not use on rubber, resilient tiles, or asphalt surfaces
- Do not use near fire or flame
- Harmful if swallowed
- Do not use in presence of open foodstuffs
- For industrial use only by trained personnel
- Please refer to Safety Data Sheet (SDS) before using
- Mock-ups and field test areas are required in order to validate performance and appearance related characteristics (including but not limited to color, inherent surface variations, wear, anti-dusting, abrasion resistance, chemical resistance, stain resistance, coefficient of friction, etc.) to ensure system performance as specified for the intended use, and to determine approval of the decorative flooring system.

## 4. DONNÉES TECHNIQUES

### Propriétés physiques

Property	Observed
Color	Amber
Odor	Orange
Phosphate	None
Film	None
USDA approved	Yes
pH 5% emulsion	6-7

Caractéristiques sous réserve de modification sans préavis. Les résultats présentés sont typiques, mais ils reflètent les procédures d'essai utilisées. Les performances réelles sur le terrain dépendent des méthodes de pose et des conditions locales.

## 5. POSE

**As a cleaner:** For general cleanup applications, dilute CITREX™ with water to suit the extent of the accumulated dirt. A solution of 1 part CITREX to 5 parts water is usually adequate for most cleaning jobs. Experiment with varied concentrations to determine which strength is most suitable for the cleaning and degreasing task. Add a minimum of 15 oz/gal (117 ml/L). This cleaner may be applied using automatic floor scrubbers, sprayers or conventional methods. Heavily caked grease should be first scraped from surfaces. Apply diluted CITREX at the rate of 150 ft<sup>2</sup>/gal (3.7m<sup>2</sup>/l).

**Application:** Allow to stand 2-10 minutes. Scrub contaminated area. Flush with water or vacuum loosened contaminants, dirt, oil and grease after scrubbing. Redo areas where heavy accumulation of tire marks, sealer film, oil, grease or other contaminants has occurred and some stubborn stains remain.

## 6. DISPONIBILITÉ ET COÛT

### Disponibilité

Les produits LATICRETE® et LATAPOXY® sont proposés dans le monde entier.

### Appeler un des numéros suivants pour obtenir des informations relatives aux distributeurs:

Numéro sans frais: 1.800.243.4788

Téléphone: +1.203.393.0010

Pour obtenir de l'information en ligne de distributeurs, visiter LATICRETE à l'adresse suivante [laticrete.com](http://laticrete.com)

### Coût

Communiquez avec le distributeur LATICRETE le plus proche.

## 7. GARANTIE

Voir 10. SYSTÈME DE CLASSIFICATION:

## 9. SERVICES TECHNIQUES

### Soutien technique

Pour tout renseignement, appeler la ligne d'aide du service technique de LATICRETE:

Numéro sans frais: 1.800.243.4788, ext. 1235

Téléphone: +1.203.393.0010, ext. 1235

Télécopieur: +1.203.393.1948

### Documentation technique et de sécurité

Pour obtenir la documentation technique et les consignes de sécurité, visiter notre site Web à [laticrete.com](http://laticrete.com).

## 10. SYSTÈME DE CLASSIFICATION

Des informations supplémentaires sur les produits sont disponibles sur notre site Web à [laticrete.com](http://laticrete.com). Liste des documents connexes:

- DS 230.13: LATICRETE Product Warranty

LATICRETE International, Inc.

One LATICRETE Park North, Bethany, CT 06524-3423 USA • 1.800.243.4788 • +1.203.393.0010 • [www.laticrete.com](http://www.laticrete.com)

© 2024 LATICRETE International, Inc. All trademarks shown are the intellectual properties of their respective owners.