



L&M™ PERMAGUARD SPS™

DS-177.7-0524

**Globally Proven
Construction Solutions**



1. PRODUCT NAME

L&M™ PERMAGUARD SPS™

2. MANUFACTURER

LATICRETE International, Inc.

1 LATICRETE Park North

Bethany, CT 06524-3423 USA

Telephone: +1.203.393.0010, ext. 1235

Toll Free: 1.800.243.4788, ext. 1235

Fax: +1.203.393.1684

Website: laticrete.com

3. PRODUCT DESCRIPTION

PERMAGUARD SPS is the answer to the common floor staining problems of concrete, stone, marble and terrazzo surfaces due to spillage and penetration of varied common contaminants found in grocery complexes, school cafeterias and restaurants.

PERMAGUARD SPS is a low odor, VOC compliant, topical sealer consisting of low molecular emulsified cross-linking, coupling polymers that effectively protect concrete and other natural stone floor surfaces from the damaging effects of staining, defacing and deterioration due to contaminant penetration. PERMAGUARD SPS extends protection to bare concrete floor surfaces that have been treated with chemical densifiers such as SEAL HARD® and on floors that have been ground and polished using FGS PERMASHINE™ Polished Concrete System.

Floors treated with PERMAGUARD SPS are easier to clean and keep clean. It develops a long lasting high gloss finish that improves light reflectance and eliminates the need for floor waxes, polishes and conventional epoxy

based coatings. The intensity of the colored and dyed floors will be enhanced with the application of PERMAGUARD SPS. Routine maintenance is simple, when using FGS CONCRETE CONDITIONER™.

Uses

- PERMAGUARD SPS protects bare concrete and other surfaces from contaminant penetration and effectively resists oil, water, wine and other liquid penetration in warehouses, grocery stores, restaurants, school service cafeterias, wine shops, rest rooms and display rooms with polished decorative concrete. Other typical applications include vehicle repair facilities, machine shops, bus terminals, concrete pavers and natural stone surfaces.

Advantages

- Excellent repellency protection from fluids (wines, vinegar, fruit juices and organic acids) and will also protect surface gloss from deteriorating
- Excellent oil and grease repellency to resist staining and improve aesthetics
- Quickly opens to traffic
- Non-slip performance
- Exceptional scuff and scratch resistant
- fruit juices and organic acids) and will also protect surface gloss from deteriorating
- Enhances stained and colored concrete
- Compatible with floors previously treated with chemical hardeners and densifiers
- Minimizes UV attack on dyed concrete surfaces

Suitable Substrates

Packaging

1 Gal (3.8 L)

5 Gal (19 L)

Approximate Coverage

Typical coverage rates, depending upon substrate porosity and anticipated conditions are:

Concrete: 800-1500 ft²/gal (19.5 - 36.6 m²/L)

Stone: 1000-1500 ft²/gal (24.4 - 36.6 m²/L)

Shelf Life

Shelf life of up to 12 months provided it is stored in a tightly closed container and protected from sunlight, and stored at temperatures between 40°F (4°C) and 100°F (38°C).

Limitations

- Clean up spills as quickly as possible to minimize potential staining.
- Apply within temperature range of 50(F (10(C) and 100(F (38(C).
- Maximum protection is normally realized after 48 hours of curing time has elapsed.
- Cool, humid conditions may prolong dry time and result in a haze. Concrete must be fully cured (28 days).
- Burnish with black synthetic or hogs hair pad to increase protection from contaminant penetration and to increase gloss.
- For interior use only.
- Use of ammonia or amine based cleaners will remove this product over time.
- Regularly maintain PERMAGUARD SPS™ surfaces with FGS CONCRETE CONDITIONER™ with soft, white scrubbing pads.

Cautions

- Applicators should wear rubber gloves and eye protection
- Keep from freezing
- Keep container closed when not in use
- Protect glass, plastic products, shrubbery and plant life from overspray
- Do not expose to ammonia or amine based cleaners or film damage and removal will result
- Please refer to Product Safety Data Sheet (SDS) before using

4. TECHNICAL DATA

Applicable Standard

- US Environmental Protection Agency
- California Air Resources Board SCM Districts
- Northeast Ozone Transportation Zone
- Maricopa County Arizona
- ADA and OSHA compliant non-slip performance
- NSF (Supersedes USDA Approval)

Physical Properties

Property	Observed
Color	Milky White
Total Solids	24%
Viscosity	Water like
pH	8.5
Slip coefficient of friction	>.6
Film	Yes
VOC	<50

Specifications subject to change without notification. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation methods and site conditions.

5. INSTALLATION

• Surface Preparation:

Surfaces should be clean from dust, dirt, oils, grease, curing compounds, other coatings, efflorescence, and laitance before applying PERMAGUARD SPS. Wait a minimum 28 days on new concrete before applying PERMAGUARD SPS. On chemically hardened, polished concrete allow a minimum of 48 hours between application of hardener and the application of PERMAGUARD SPS.

Pre-moisten micro-fiber pad with PERMAGUARD SPS. Working from joint to joint, apply evenly and thinly with the pad. Do not puddle. Burnish after final coat has dried a minimum of 4 hours, using a high speed, 2000 RPM burnisher with soft white pad or soft natural hogs hair. Burnishing is necessary for enhanced gloss and improved durability and chemical resistance. If multiple coats are to be installed, allow previous coat to dry, normally 15 to 30 minutes, at 70°F (21°C).

Cleanup: Thoroughly rinse equipment with clean water before PERMAGUARD SPS dries. To remove dried film, scrub with ammonia or amine based cleaner over areas where PERMAGUARD SPS has dried.

6. AVAILABILITY AND COST

Availability

LATICRETE materials are available worldwide.

For Distributor Information, Call:

Toll Free: 1.800.243.4788

Telephone: +1.203.393.0010

For on-line distributor information, visit LATICRETE at laticrete.com

Cost

Contact a LATICRETE Distributor in your area.

7. WARRANTY

See 10. FILING SYSTEM:

8. MAINTENANCE

The long term performance, appearance, and life expectancy of wear surface products are critically dependent upon a good routine maintenance program designed specifically for the installed wear surface type, traffic, and other conditions. Properly placed walk-off

mats, inside and outside will help increase the life of the floor. Some cleaning products and equipment or improper use of products can damage a wear surface appearance over time. Recommended maintenance program consists of frequent and thorough cleanings utilizing FGS CONCRETE CONDITIONER. Frequency of washing will vary, as it may be necessary daily, weekly or less frequently depending on floor usage and age. A mechanical walk-behind or ride-on scrubber is an efficient and economical means of regularly cleaning concrete floors. Only soft scrubbing or soft brush attachments should be used when mechanically scrubbing your floor. Do not use aggressive abrasive pads or brushes. The use of black scrubbing pads, diamond impregnated pads or carbide impregnated type brushes may dull the surface gloss. Wet mops work well on small floors or places where a mechanical scrubber will not fit.

9. TECHNICAL SERVICES

Technical Assistance

Information is available by calling the LATICRETE Technical Service Hotline:

Toll Free: 1.800.243.4788, ext. 1235
Telephone: +1.203.393.0010, ext. 1235
Fax: +1.203.393.1948

Technical and Safety Literature

To acquire technical and safety literature, please visit our website at laticrete.com.

10. FILING SYSTEM

Additional product information is available on our website at laticrete.com. The following is a list of related documents:

- DS 174.6: SEAL HARD®
- DS 177.1: FGS CONCRETE CONDITIONER™
- DS 230.13: LATICRETE Product Warranty

LATICRETE International, Inc.

One LATICRETE Park North, Bethany, CT 06524-3423 USA • 1.800.243.4788 • +1.203.393.0010 • www.laticrete.com

© 2024 LATICRETE International, Inc. All trademarks shown are the intellectual properties of their respective owners.