



LATAPOXY® 310 Cordless Mixer

DS-683-0524

**Globally Proven
Construction Solutions**



- Great for tight spaces and on scaffolding
- * Consult LATICRETE Technical Services for approval prior to all exterior applications.

Advantages

- Unmatched speed & productivity for vertical installations
- Cordless for convenience—great for scaffolding and tight areas
- Patented design and gear system
- High output motor for long life
- Automatic reverse
- Speed and dosing controls for easier operation

Suitable Substrates

- Concrete
- Concrete Masonry Units (CMU)
- Brick Masonry
- Exterior Glue Plywood (Interior Only)
- Cement Backer Board
- Steel

Packaging

- 9.5LB (4.3KG) CARTON

Approximate Coverage

Approximate Dab Diameter Required To Achieve 10% Coverage With 5 Dabs:

Tile/Stone Size	Dab Diameter
12" x 12" (300 mm x 300 mm)	2" (50 mm)
24" x 24" (600 mm x 600 mm)	4" (100 mm)
36" x 36" (900 mm x 900 mm)	6" (150 mm)

Note: Pull off the first stone installed to measure the diameter of each dab. Adjust the quantity of LATAPOXY® 310 Stone Adhesive to achieve the appropriate coverage. Once the correct amount has been determined, set Dosing Knob to obtain the consistent level for all stones.

Limitations

- Consult LATICRETE Technical Services for approval on exterior applications.

1. PRODUCT NAME

LATAPOXY® 310 Cordless Mixer

2. MANUFACTURER

LATICRETE International, Inc.
1 LATICRETE Park North
Bethany, CT 06524-3423 USA

Telephone: +1.203.393.0010, ext. 1235

Toll Free: 1.800.243.4788, ext. 1235

Fax: +1.203.393.1684

Website: laticrete.com

3. PRODUCT DESCRIPTION

The LATAPOXY 310 Cordless Mixer is an exclusive dual component cordless mixer that quickly and easily dispenses LATAPOXY 310 Stone Adhesive onto ceramic tile, porcelain and stone veneers. Hundreds of square feet can be installed per day with less effort and greater success with this system. Compared to other cladding installation systems such as mechanical anchors, plaster & wire and thin-set, the LATAPOXY 310 system provides unmatched speed, versatility and productivity. Perfect for all interior cladding of tile, stone and porcelain veneers as well as approved exterior applications.

Uses

- Used exclusively with LATAPOXY 310 Stone Adhesive to install various stone and tile on vertical surfaces
- Virtually any interior cladding application of stone or tile in lobbies, malls, store fronts, banks, schools, hospitals etc
- For cladding exterior veneer facades*
- Jobs requiring fast turnaround time

- Not for use with any adhesives other than LATAPOXY 310 Stone Adhesive.
- LATAPOXY 310 Stone Adhesive MUST be conditioned to at least 65°F (18°C) prior to use. Consult LATAPOXY 310 Stone Adhesive data sheet DS 679.0 and DS 679.3.
- Do not abuse, misuse, or modify tool in anyway
- Do not use for any application other than those described herein.
- Follow proper installation and operation instructions in Owner's Manual DS 683.5.
- Repairs may only be made by approved LATICRETE personnel.

Cautions

- Read & understand battery pack and charger manual included in LATAPOXY 310 Cordless Mixer fully prior to use.
- Failure to condition material to 65°F (18°C) prior to use will cause failure of cartridge and incomplete adhesive mix.

4. TECHNICAL DATA

Physical Properties

Cordless Mixer Tool Weight	9 lbs (4.05 kg)
Cordless Mixer Dimensions	17" x 3.5" x 13.5 (43 x 9 x 34 cm)
Battery Information	14.4 Volt Nicad
Charger information	One hour quick charge
Capacity	22 oz (616 grams) 1:1 ratio only

Specifications subject to change without notification. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation methods and site conditions.

5. INSTALLATION

- **Storage**
Condition LATAPOXY® 310 Stone Adhesive at 65°F (18°C) to allow for easier application prior to use. Surface Preparation See LATAPOXY 310 Stone Adhesive DS 679.0 and DS 679.3. Operating Instructions Battery and Charging Use only the 20 V battery in the charger provided. Other battery types may cause personal injury and or damage. Please read the charging manual included with each Cordless Mixer for specific information regarding safety and charging. Charge battery to full capacity prior to use. Charging time will vary according to voltage supply, the amount of the charge needed for that battery and temperature. Temperature will affect battery life. It is

best to charge when temperature is between 60–80°F (15–27°C). Do not charge when temperature drops below 40°F (5°C) or above 105°F (40°C). Estimate roughly 30 minutes to fully charge a battery

Tool Set Up & Loading

Open clutch lever. Grasp rack handle and pull outward until fully open. Insert one LATAPOXY 310 Cartridge Pack into the Cartridge Housing, pushing tip through the hole at end of housing. Push rack forward until pistons make contact with back of cartridge. Close clutch. Remove protective tip by inserting screwdriver tip into slot on top of cartridge and simply pry off to open both sides of cartridge. Screw mixing nozzle onto the thread tightly. Note: Remember to condition the material to at least 65°F (18°C) prior to using.

Dispensing

Squeeze trigger to begin dispensing material. Adjust the dispensing speed as desired by turning the dial on side of tool. You will see the red and white components mix as they are pushed through the static mixer. Make sure material is uniform in color when dispensed from the nozzle. Hold the Mixer at an angle on the tile or stone to be adhered. Push the material into the veneer by using a circle motion and using the edge of the nozzle to “key” the material as it is dispensing. Apply dabs evenly distributed on back of the stone or tile; 5 dabs minimum, each corner and center. Cover at least 10% of the area of each piece (compressed dab). Finished dab thickness must be a minimum of 1/8" (3 mm). Note: LATAPOXY 310 Cordless Mixer is equipped with an automatic reverse that engages after trigger is released to reduce any leakage. Build height of dab as needed to achieve plumb surface. Approximate Dab Diameter Required To Achieve 10% Coverage With 5 Dabs: Tile/Stone Size Dab Diameter 12" x 12" (300 mm x 300 mm) 2" (50 mm) 24" x 24" (600 mm x 600 mm) 4" (100 mm) 36" x 36" (900 mm x 900 mm) 6" (150 mm) Note: Pull off the first stone installed to measure the diameter of each dab. Adjust the quantity of LATAPOXY® 310 Stone Adhesive to achieve the appropriate coverage. Once the correct amount has been determined, set Dosing Knob to obtain the consistent level for all stones. Dispense all the material until the rack drive is completely at the end of the cartridge and cannot move any longer. You are now ready to remove the used cartridge and replace with a new one. Cartridge Removal and Replacement Tool will automatically turn off once cartridge is emptied and the rack drive has reached its maximum extension. Unscrew Mixing Nozzle and set aside. Open clutch and pull rack handle to full open position. Remove emptied cartridge. Insert new cartridge and follow instructions in Operating Instructions, section 2. Make sure to snap off protective tip of cartridge before screwing on Mixing Nozzle.

6. AVAILABILITY AND COST

Availability

LATICRETE materials are available worldwide.

For Distributor Information, Call:

Toll Free: 1.800.243.4788

Telephone: +1.203.393.0010

For on-line distributor information, visit LATICRETE at

laticrete.com

Cost

Contact a LATICRETE Distributor in your area.

7. WARRANTY

See 10. FILING SYSTEM:

- 1 Year Product Warranty (US) (English)

8. MAINTENANCE

Your LATAPOXY 310 Cordless Mixer has been designed to provide dependable operation. There is no regular maintenance needed however it is important to keep the tool clean and free from adhesive build up. Effort must be made to keep adhesive, dirt and foreign objects off rack drive which may get caught in motor. Observe the following:

9. TECHNICAL SERVICES

Technical Assistance

Information is available by calling the LATICRETE

Technical Service Hotline:

Toll Free: 1.800.243.4788, ext. 1235

Telephone: +1.203.393.0010, ext. 1235

Fax: +1.203.393.1948

Technical and Safety Literature

To acquire technical and safety literature, please visit our website at laticrete.com.

10. FILING SYSTEM

Additional product information is available on our website at laticrete.com. The following is a list of related documents:

- DS 230.13: LATICRETE® Product Warranty (United States and Canada)
- DS 679.0: LATAPOXY 310 Stone Adhesive
- DS 679.3: LATAPOXY 310 Rapid Stone Adhesive

LATICRETE International, Inc.

One LATICRETE Park North, Bethany, CT 06524-3423 USA • 1.800.243.4788 • +1.203.393.0010 • www.laticrete.com

© 2024 LATICRETE International, Inc. All trademarks shown are the intellectual properties of their respective owners.