



# STONETECH® Finish & Sealer - Matte

## Safety Data Sheet

According To Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules And Regulations And According To The Hazardous Products Regulation (December 15, 2022).

Revision Date: 07/07/2026

Date of Issue: 06/18/2019

Supersedes Date: 02/23/2026

Version: 3.0

## SECTION 1: IDENTIFICATION

### 1.1. Product Identifier

**Product Form:** Mixture

**Product Name:** STONETECH® Finish & Sealer - Matte

### 1.2 Recommended Use and Restrictions on Use

**Use Of The Substance/Mixture** : Treatment of natural stone surfaces.

**Restrictions On Use** : No additional information available

### 1.3. Name, Address, and Telephone of the Responsible Party

#### Company

LATICRETE International

1 Laticrete Park, N

Bethany, CT 06524

T (203)-393-0010

[www.laticrete.com](http://www.laticrete.com)

#### Company

LATICRETE Canada ULC

PO Box 129, Emeryville, Ontario, Canada

N0R-1A0

(833)-254-9255

### 1.4. Emergency Telephone Number

**Emergency Number** : For Chemical Emergency call VelocityEHS day or night:

(800)255-3924 (North America)

(800)-099-0731 (Mexico)

+1 (813)248-0585 (International - collect calls accepted)

## SECTION 2: HAZARDS IDENTIFICATION

### 2.1. Classification of the Substance or Mixture

#### GHS-US/CA Classification

Skin sensitization, Category 1A

H317

Specific target organ toxicity, Repeated exposure, Category 1

H372

Hazardous to the aquatic environment, Acute Hazard, Category 3

H402

Hazardous to the aquatic environment, Chronic Hazard, Category 3

H412

### 2.2. Label Elements

#### GHS-US/CA Labeling

**Hazard Pictograms (GHS-US/CA)** :



GHS07



GHS08

**Signal Word (GHS-US/CA)** :

Danger

**Hazard Statements (GHS-US/CA)** :

H317 - May cause an allergic skin reaction.

H372 - Causes damage to organs (kidneys) through prolonged or repeated exposure (oral).

H402 - Harmful to aquatic life.

H412 - Harmful to aquatic life with long lasting effects.

**Precautionary Statements (GHS-US/CA)** : P260 - Do not breathe mist, spray, or vapors.

P264 - Wash hands, forearms and face thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P273 - Avoid release to the environment.

P280 - Wear eye protection, protective clothing, protective gloves.

P302+P352 - IF ON SKIN: Wash with plenty of water.

P314 - Get medical advice or attention if you feel unwell.

P321 - Specific treatment (see supplemental first aid instruction on this label).

P333+P313 - If skin irritation or rash occurs: Get medical advice or attention.

P362+P364 - Take off contaminated clothing and wash it before reuse.

# STONETECH® Finish & Sealer - Matte

## Safety Data Sheet

According To Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules And Regulations And According To The Hazardous Products Regulation (December 15, 2022).

P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

### 2.3 Hazards associated with known or reasonably anticipated uses

If this product is used in unforeseeable chemical processes and not used as intended or reasonable, the hazards listed in Section 2.3 cannot cover all chemistries. Therefore, a Process Hazard Analysis (PHA) or other hazard assessment for additional specific end uses should be performed to ensure that hazards are fully understood, and adequate safety measures are in place. See Section 10 for relevant reactivity and stability information.

### 2.4. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

### 2.5 Unknown Acute Toxicity (GHS-US/CA)

No additional information available

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1. Substance

Not applicable

### 3.2. Mixture

| Name                          | Product Identifier   | % *     |
|-------------------------------|----------------------|---------|
| Silica, amorphous             | (CAS-No.) 7631-86-9  | 1 - 5   |
| Ethylene glycol               | (CAS-No.) 107-21-1   | 1 - 5   |
| 3(2H)-Isothiazolone, 2-octyl- | (CAS-No.) 26530-20-1 | < 0.025 |

Full text of H-statements: see section 16

\*Percentages are listed in weight by weight percentage (w/w%). The actual concentration of ingredient(s) is withheld as a trade secret in accordance with the Hazardous Products Regulations (HPR) SOR/2022-272 and 29 CFR 1910.1200.

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of First-aid Measures

**General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

**Inhalation:** When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

**Skin Contact:** Remove contaminated clothing. Wash affected area with soap and water for at least 15 minutes. Obtain medical attention if irritation/rash develops or persists.

**Eye Contact:** Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with water for at least 15 minutes. Obtain medical attention.

**Ingestion:** Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

### 4.2. Most Important Symptoms and Effects Both Acute and Delayed

**General:** Skin sensitization. Causes damage to organs (kidney) through prolonged or repeated exposure (oral).

**Inhalation:** Prolonged exposure may cause irritation.

**Skin Contact:** May cause an allergic skin reaction.

**Eye Contact:** May cause slight irritation to eyes.

**Ingestion:** Acute exposure of humans to ethylene glycol by ingesting large quantities causes three stages of health effects. CNS depression, including such symptoms as vomiting, drowsiness, coma, respiratory failure, convulsions, metabolic changes, and gastrointestinal upset are followed by cardiopulmonary effects and later renal damage.

**Chronic Symptoms:** Repeated and prolonged exposure may cause an allergic skin reaction. Causes damage to organs (kidneys) through prolonged or repeated exposure (oral).

### 4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

## SECTION 5: FIRE-FIGHTING MEASURES

### 5.1. Extinguishing Media

**Suitable Extinguishing Media:** Water spray, fog, carbon dioxide (CO<sub>2</sub>), alcohol-resistant foam, or dry chemical.

**Unsuitable Extinguishing Media:** Do not use a heavy water stream. Use of heavy stream of water may spread fire.

### 5.2. Special Hazards Arising From the Substance or Mixture

**Fire Hazard:** Not considered flammable but may burn at high temperatures.

**Explosion Hazard:** Product is not explosive.

# STONETECH® Finish & Sealer - Matte

## Safety Data Sheet

According To Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules And Regulations And According To The Hazardous Products Regulation (December 15, 2022).

**Reactivity:** Hazardous reactions will not occur under normal conditions.

### 5.3. Advice for Firefighters

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire.

**Firefighting Instructions:** Use water spray or fog for cooling exposed containers.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

**Hazardous Combustion Products:** Ammonia. Carbon oxides (CO, CO<sub>2</sub>). Nitrogen oxides.

**Other Information:** Do not allow run-off from fire fighting to enter drains or water courses.

### 5.4. Reference to Other Sections

Refer to Section 9 for flammability properties.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal Precautions, Protective Equipment and Emergency Procedures

**General Measures:** Do not breathe vapor, mist or spray. Do not get in eyes, on skin, or on clothing.

#### 6.1.1. For Non-Emergency Personnel

**Protective Equipment:** Use appropriate personal protective equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel.

#### 6.1.2. For Emergency Personnel

**Protective Equipment:** Equip cleanup crew with proper protection.

**Emergency Procedures:** Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area.

### 6.2. Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

### 6.3. Methods and Materials for Containment and Cleaning Up

**For Containment:** Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

**Methods for Cleaning Up:** Clean up spills immediately and dispose of waste safely. Absorb and/or contain spill with inert material. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

### 6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

## SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for Safe Handling

**Precautions for Safe Handling:** Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not breathe mist, spray, or vapors. Avoid contact with eyes, skin and clothing.

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures.

### 7.2. Conditions for Safe Storage, Including Any Incompatibilities

**Technical Measures:** Comply with applicable regulations.

**Storage Conditions:** Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Do not freeze.

**Incompatible Materials:** Strong acids, strong bases, strong oxidizers.

### 7.3. Specific End Use(s)

Treatment of natural stone surfaces.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), or Canadian provincial governments.

| Ethylene glycol (107-21-1) |                          |                                                                   |
|----------------------------|--------------------------|-------------------------------------------------------------------|
| USA ACGIH                  | ACGIH® TLV® TWA          | 25 ppm (vapor fraction)                                           |
| USA ACGIH                  | ACGIH® TLV® STEL         | 10 mg/m <sup>3</sup> (inhalable particulate matter, aerosol only) |
| USA ACGIH                  | ACGIH® TLV® STEL         | 50 ppm (vapor fraction)                                           |
| USA ACGIH                  | ACGIH® chemical category | Not Classifiable as a Human Carcinogen                            |
| Alberta                    | OEL C                    | 100 mg/m <sup>3</sup>                                             |
| British Columbia           | OEL C                    | 100 mg/m <sup>3</sup> (total; aerosol only)                       |

# STONETECH® Finish & Sealer - Matte

## Safety Data Sheet

According To Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules And Regulations And According To The Hazardous Products Regulation (December 15, 2022).

|                                      |                 |                                                                                                                                                                                   |
|--------------------------------------|-----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| British Columbia                     | OEL C           | 50 ppm (vapour)                                                                                                                                                                   |
| British Columbia                     | OEL STEL        | 20 mg/m <sup>3</sup> (total; aerosol only)                                                                                                                                        |
| British Columbia                     | OEL TWA         | 10 mg/m <sup>3</sup> (total; aerosol only)                                                                                                                                        |
| Manitoba                             | OEL STEL        | 10 mg/m <sup>3</sup> (inhalable particulate matter, aerosol only)                                                                                                                 |
| Manitoba                             | OEL STEL        | 50 ppm (vapor fraction)                                                                                                                                                           |
| Manitoba                             | OEL TWA         | 25 ppm (vapor fraction)                                                                                                                                                           |
| New Brunswick                        | OEL C           | 100 mg/m <sup>3</sup> (aerosol only)                                                                                                                                              |
| Newfoundland & Labrador              | OEL STEL        | 10 mg/m <sup>3</sup> (inhalable particulate matter, aerosol only)                                                                                                                 |
| Newfoundland & Labrador              | OEL STEL        | 50 ppm (vapor fraction)                                                                                                                                                           |
| Newfoundland & Labrador              | OEL TWA         | 25 ppm (vapor fraction)                                                                                                                                                           |
| Nova Scotia                          | OEL STEL        | 10 mg/m <sup>3</sup> (inhalable particulate matter, aerosol only)                                                                                                                 |
| Nova Scotia                          | OEL STEL        | 50 ppm (vapor fraction)                                                                                                                                                           |
| Nova Scotia                          | OEL TWA         | 25 ppm (vapor fraction)                                                                                                                                                           |
| Nunavut                              | OEL C           | 100 mg/m <sup>3</sup> (aerosol)                                                                                                                                                   |
| Northwest Territories                | OEL C           | 100 mg/m <sup>3</sup> (aerosol)                                                                                                                                                   |
| Ontario                              | OEL TWAEV       | 10 mg/m <sup>3</sup> (inhalable particulate matter, aerosol only)                                                                                                                 |
| Ontario                              | OEL TWAEV       | 50 ppm (vapor fraction)                                                                                                                                                           |
| Ontario                              | OEL TWAEV       | 25 ppm (vapor fraction)                                                                                                                                                           |
| Prince Edward Island                 | OEL STEL        | 10 mg/m <sup>3</sup> (inhalable particulate matter, aerosol only)                                                                                                                 |
| Prince Edward Island                 | OEL STEL        | 50 ppm (vapor fraction)                                                                                                                                                           |
| Prince Edward Island                 | OEL TWA         | 25 ppm (vapor fraction)                                                                                                                                                           |
| Québec                               | Plafond (OEL C) | 127 mg/m <sup>3</sup> (mist and vapour)                                                                                                                                           |
| Québec                               | Plafond (OEL C) | 50 ppm (mist and vapour)                                                                                                                                                          |
| Saskatchewan                         | OEL C           | 100 mg/m <sup>3</sup> (aerosol)                                                                                                                                                   |
| Yukon                                | OEL STEL        | 20 mg/m <sup>3</sup> (particulate)<br>325 mg/m <sup>3</sup> (vapour)                                                                                                              |
| Yukon                                | OEL STEL        | 10 ppm (particulate)<br>125 ppm (vapour)                                                                                                                                          |
| Yukon                                | OEL TWA         | 10 mg/m <sup>3</sup> (particulate)<br>250 mg/m <sup>3</sup> (vapour)                                                                                                              |
| Yukon                                | OEL TWA         | 100 ppm (vapour)                                                                                                                                                                  |
| <b>Silica, amorphous (7631-86-9)</b> |                 |                                                                                                                                                                                   |
| USA OSHA                             | OSHA PEL TWA    | 6 mg/m <sup>3</sup>                                                                                                                                                               |
| USA OSHA                             | OSHA PEL TWA    | 20 mppcf (80mg/m <sup>3</sup> /%SiO <sub>2</sub> )                                                                                                                                |
| USA NIOSH                            | NIOSH REL TWA   | 6 mg/m <sup>3</sup>                                                                                                                                                               |
| USA IDLH                             | IDLH            | 3000 mg/m <sup>3</sup>                                                                                                                                                            |
| Yukon                                | OEL TWA         | 300 particle/mL (as measured by Konimeter instrumentation (Silica)<br>20 mppcf (as measured by Impinger instrumentation (Silica)<br>2 mg/m <sup>3</sup> (respirable mass (Silica) |

## 8.2. Exposure Controls

**Appropriate Engineering Controls:** Suitable eye/body wash equipment should be available in the vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed.

**Personal Protective Equipment:** Gloves. Protective clothing. Protective goggles.



**Materials for Protective Clothing:** Chemically resistant materials and fabrics.

**Hand Protection:** Wear protective gloves.

**Eye and Face Protection:** Chemical safety goggles or safety glasses with side shields.

**Skin and Body Protection:** Wear suitable protective clothing.

# STONETECH® Finish & Sealer - Matte

## Safety Data Sheet

According To Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules And Regulations And According To The Hazardous Products Regulation (December 15, 2022).

**Respiratory Protection:** If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

**Other Information:** When using, do not eat, drink or smoke.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on Basic Physical and Chemical Properties

|                                        |                          |
|----------------------------------------|--------------------------|
| Physical State                         | : Liquid                 |
| Color                                  | : White                  |
| Odor                                   | : Sweet/latex            |
| Odor Threshold                         | : No data available      |
| pH                                     | : 8.02 – 8.39            |
| Evaporation Rate                       | : No data available      |
| Melting Point                          | : Not applicable         |
| Freezing Point                         | : No data available      |
| Boiling Point                          | : Not applicable         |
| Flash Point                            | : Not applicable         |
| Auto-ignition Temperature              | : No data available      |
| Decomposition Temperature              | : No data available      |
| Flammability (solid, gas)              | : Not applicable         |
| Lower Flammable Limit                  | : No data available      |
| Upper Flammable Limit                  | : No data available      |
| Vapor Pressure                         | : No data available      |
| Relative Vapor Density at 20 °C        | : No data available      |
| Relative Density                       | : 1.06 – 1.09 (water =1) |
| Specific Gravity                       | : No data available      |
| Solubility                             | : No data available      |
| Partition Coefficient: N-Octanol/Water | : No data available      |
| Viscosity, Kinematic                   | : No data available      |
| Particle Characteristics               | : No data available      |

## SECTION 10: STABILITY AND REACTIVITY

### 10.1. Reactivity:

Hazardous reactions will not occur under normal conditions.

### 10.2. Chemical Stability:

Stable under recommended handling and storage conditions (see section 7).

### 10.3. Possibility of Hazardous Reactions, Including those Associated with Foreseeable Emergencies:

Hazardous polymerization will not occur.

### 10.4. Conditions to Avoid:

Direct sunlight, extremely high or low temperatures, and incompatible materials.

### 10.5. Incompatible Materials:

Strong acids, strong bases, strong oxidizers.

### 10.6. Hazardous Decomposition Products:

Thermal decomposition may produce: Ammonia. Carbon oxides (CO, CO<sub>2</sub>). Nitrogen oxides.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on Toxicological Effects - Product

**Likely routes of exposure:** Dermal, Eye Contact, Inhalation, Oral.

**Acute Toxicity (Oral):** Not classified.

**Acute Toxicity (Dermal):** Not classified.

**Acute Toxicity (Inhalation):** Not classified.

**LD50 and LC50 Data:** No additional information available.

**Skin Corrosion/Irritation:** Not classified.

**Eye Damage/Irritation:** Not classified.

**Respiratory or Skin Sensitization:** 3(2H)-Isothiazolone, 2-octyl- (CAS-No. 26530-20-1) has shown to cause an allergic skin reaction at or above 0.0015 %.

# STONETECH® Finish & Sealer - Matte

## Safety Data Sheet

According To Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules And Regulations And According To The Hazardous Products Regulation (December 15, 2022).

**Germ Cell Mutagenicity:** Not classified.

**Carcinogenicity:** Not classified.

**Specific Target Organ Toxicity (Repeated Exposure):** Causes damage to organs (kidneys) through prolonged or repeated exposure (oral).

**Reproductive Toxicity:** Not classified.

**Specific Target Organ Toxicity (Single Exposure):** Not classified.

**Aspiration Hazard:** Not classified.

**Symptoms/Injuries After Inhalation:** Prolonged exposure may cause irritation.

**Symptoms/Injuries After Skin Contact:** May cause an allergic skin reaction.

**Symptoms/Injuries After Eye Contact:** May cause slight irritation to eyes.

**Symptoms/Injuries After Ingestion:** Acute exposure of humans to ethylene glycol by ingesting large quantities causes three stages of health effects. CNS depression, including such symptoms as vomiting, drowsiness, coma, respiratory failure, convulsions, metabolic changes, and gastrointestinal upset are followed by cardiopulmonary effects and later renal damage.

**Chronic Symptoms:** Repeated and prolonged exposure may cause an allergic skin reaction. Causes damage to organs (kidneys) through prolonged or repeated exposure (oral).

### 11.2. Information on Toxicological Effects - Ingredient(s)

#### LD50 and LC50 Data:

|                                                   |                                 |
|---------------------------------------------------|---------------------------------|
| <b>Ethylene glycol (107-21-1)</b>                 |                                 |
| LD50 Oral Rat                                     | 4700 mg/kg (Source: NLM_CIP)    |
| LD50 Dermal Rat                                   | 10600 mg/kg (Source: JAPAN_GHS) |
| LC50 Inhalation Rat                               | > 2.5 mg/l (Exposure time: 6 h) |
| ATE US/CA (Oral)                                  | 500 mg/kg body weight           |
| <b>Silica, amorphous (7631-86-9)</b>              |                                 |
| LD50 Oral Rat                                     | 7900 mg/kg (Source: ATSDR)      |
| LD50 Dermal Rabbit                                | > 2000 mg/kg (No deaths)        |
| LC50 Inhalation Rat                               | > 5.01 mg/l/4h                  |
| <b>3(2H)-Isothiazolone, 2-octyl- (26530-20-1)</b> |                                 |
| LD50 Oral Rat                                     | 550 mg/kg                       |
| LD50 Dermal Rat                                   | 311 mg/kg                       |
| LD50 Dermal Rabbit                                | 690 mg/kg (Source: NZ_CCID)     |
| LC50 Inhalation Rat                               | 0.27 mg/l/4h                    |

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity

**Ecology - General:** Harmful to aquatic life with long lasting effects.

|                                                   |                                                                                        |
|---------------------------------------------------|----------------------------------------------------------------------------------------|
| <b>Ethylene glycol (107-21-1)</b>                 |                                                                                        |
| LC50 Fish                                         | 41000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss Source: IUCLID)         |
| EC50 Crustacea                                    | 46300 mg/l (Exposure time: 48 h - Species: Daphnia magna)                              |
| LC50 Fish                                         | 14 – 18 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static] Source: EPA) |
| NOEC Chronic Crustacea                            | 4.2 mg/l                                                                               |
| <b>Silica, amorphous (7631-86-9)</b>              |                                                                                        |
| LC50 Fish                                         | 5000 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [static] Source: IUCLID)   |
| EC50 Crustacea                                    | 7600 mg/l (Exposure time: 48 h - Species: Ceriodaphnia dubia)                          |
| <b>3(2H)-Isothiazolone, 2-octyl- (26530-20-1)</b> |                                                                                        |
| LC50 Fish                                         | 0.047 mg/kg (Exposure Time: 96 h - Species: Oncorhynchus mykiss [Flow-through])        |
| LC50 Fish                                         | 0.05 ppm Exposure Time: 96 h - Species: Oncorhynchus mykiss [static])                  |
| NOEC Chronic Fish                                 | < 0.05                                                                                 |
| NOEC Chronic Algae                                | < 0.011 (Test Duration: 120 h - Species: Selenastrum capricornutum [static])           |

### 12.2. Persistence and Degradability

|                                               |                  |
|-----------------------------------------------|------------------|
| <b>STONETECH® Finish &amp; Sealer - Matte</b> |                  |
| Persistence and Degradability                 | Not established. |

# STONETECH® Finish & Sealer - Matte

## Safety Data Sheet

According To Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules And Regulations And According To The Hazardous Products Regulation (December 15, 2022).

### 12.3. Bioaccumulative Potential

|                                                 |                              |
|-------------------------------------------------|------------------------------|
| STONETECH® Finish & Sealer - Matte              |                              |
| Bioaccumulative Potential                       | Not established.             |
| Ethylene glycol (107-21-1)                      |                              |
| Partition coefficient n-octanol/water (Log Pow) | -1.36                        |
| Silica, amorphous (7631-86-9)                   |                              |
| BCF Fish                                        | No bioaccumulation expected. |

### 12.4. Mobility in Soil

No additional information available

### 12.5. Other Adverse Effects

Other Information: Avoid release to the environment.

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

**Sewage Disposal Recommendations:** Do not dispose of waste into sewer. Do not empty into drains.

**Waste Disposal Recommendations:** Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

**Ecology - Waste Materials:** Avoid release to the environment. This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

## SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

### 14.1. In Accordance with DOT

Not regulated for transport

### 14.2. In Accordance with IMDG

Not regulated for transport

### 14.3. In Accordance with IATA

Not regulated for transport

### 14.4. In Accordance with TDG

Not regulated for transport

## SECTION 15: REGULATORY INFORMATION

### 15.1. US Federal Regulations

|                                                                                                                                                                   |                                                                                                                                   |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|
| STONETECH® Finish & Sealer - Matte                                                                                                                                |                                                                                                                                   |
| SARA Section 311/312 Hazard Classes                                                                                                                               | Health hazard - Respiratory or skin sensitization<br>Health hazard - Specific target organ toxicity (single or repeated exposure) |
| Ethylene glycol (107-21-1)                                                                                                                                        |                                                                                                                                   |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active<br>Subject to reporting requirements of United States SARA Section 313 |                                                                                                                                   |
| CERCLA RQ                                                                                                                                                         | 5000 lb                                                                                                                           |
| SARA Section 313 - Emission Reporting                                                                                                                             | 1 %                                                                                                                               |
| Silica, amorphous (7631-86-9)                                                                                                                                     |                                                                                                                                   |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active                                                                        |                                                                                                                                   |
| 3(2H)-Isothiazolone, 2-octyl- (26530-20-1)                                                                                                                        |                                                                                                                                   |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active                                                                        |                                                                                                                                   |

### 15.2. US State Regulations

#### California Proposition 65



**WARNING:** This product can expose you to Ethylene glycol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

| Chemical Name (CAS No.)    | Carcinogenicity | Developmental Toxicity | Female Reproductive Toxicity | Male Reproductive Toxicity |
|----------------------------|-----------------|------------------------|------------------------------|----------------------------|
| Ethylene glycol (107-21-1) |                 | X                      |                              |                            |

# STONETECH® Finish & Sealer - Matte

## Safety Data Sheet

According To Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules And Regulations And According To The Hazardous Products Regulation (December 15, 2022).

|                                                                       |
|-----------------------------------------------------------------------|
| <b>Ethylene glycol (107-21-1)</b>                                     |
| U.S. - New Jersey - Right to Know Hazardous Substance List            |
| U.S. - Pennsylvania - RTK (Right to Know) List                        |
| U.S. - Massachusetts - Right To Know List                             |
| U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List |
| <b>Silica, amorphous (7631-86-9)</b>                                  |
| U.S. - Pennsylvania - RTK (Right to Know) List                        |
| U.S. - Massachusetts - Right To Know List                             |

### 15.3. Canadian Regulations

|                                                       |
|-------------------------------------------------------|
| <b>Ethylene glycol (107-21-1)</b>                     |
| Listed on the Canadian DSL (Domestic Substances List) |
| <b>Silica, amorphous (7631-86-9)</b>                  |
| Listed on the Canadian DSL (Domestic Substances List) |
| <b>3(2H)-Isothiazolone, 2-octyl- (26530-20-1)</b>     |
| Listed on the Canadian DSL (Domestic Substances List) |

## SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

**Date of Preparation or Latest Revision** : 07/07/2026

**Other Information** : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200 and Canada’s Hazardous Products Regulations (HPR) SOR/2022-272.

| GHS Full Text Phrases: |                                                                 |
|------------------------|-----------------------------------------------------------------|
| H317                   | May cause an allergic skin reaction                             |
| H372                   | Causes damage to organs through prolonged or repeated exposure. |
| H402                   | Harmful to aquatic life                                         |
| H412                   | Harmful to aquatic life with long lasting effects               |

### Glossary of Data Source Abbreviations

|                                                                                                                                           |                                                                                                                    |
|-------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------|
| ATSDR: Agency for Toxic Substances and Disease Registry (U.S. Department of Health and Human Services)                                    | FOOD_JOURN: Food Research Journal (1956)                                                                           |
| AU_WES: Australia WES                                                                                                                     | IARC: The International Agency for Research on Cancer                                                              |
| CHEMVIEW: ChemView (U.S. Environmental Protection Agency)                                                                                 | IDLH: National Institute for Occupational Health and Safety Immediately Dangerous to Life or Health Value Profiles |
| EC_RAR: European Commission Renewal Assessment Report                                                                                     | IUCLID: International Uniform Chemical Information Database                                                        |
| EC_SCOEL: European Commission Scientific Committee on Occupational Exposure Limits                                                        | JAPAN_GHS: Japan GHS Basis for Classification Data                                                                 |
| ECETOC: European Centre for Ecotoxicology and Toxicology of Chemicals Reports                                                             | JP_J-CHECK: Japan J-Check                                                                                          |
| ECHA_API: European Chemicals Agency API                                                                                                   | KR_NIER: South Korea National Institute of Environmental Research Evaluations                                      |
| ECHA_RAC: ECHA Committee for Risk Assessment                                                                                              | NICNAS: Australia National Industrial Chemicals Notification and Assessment Scheme                                 |
| EFSA: European Food Safety Authority                                                                                                      | NIOSH: National Institute for Occupational Health and Safety (U.S. Department of Health and Human Services)        |
| EPA: U.S. Environmental Protection Agency                                                                                                 | NLM_CIP: National Library of Medicine ChemID plus database                                                         |
| EPA_AEGL: Acute Exposure Guideline Levels (U.S. Environmental Protection Agency)                                                          | NLM_HSDB: National Library of Medicine Hazardous Substance Data Bank                                               |
| EPA_FIFRA: Federal Insecticide, Fungicide, and Rodenticide Act Reregistration Eligibility Decision (U.S. Environmental Protection Agency) | NLM_PUBMED: National Library of Medicine PubMed database                                                           |
| EPA_HPVL: High Production Volume Chemicals (U.S. Environmental Protection Agency)                                                         | NTP: National Toxicology Program                                                                                   |
| EPA_TRED: Risk Assessment for Tolerance Reassessment Eligibility Decision (U.S. Environmental Protection Agency)                          | NZ_CCID: New Zealand Chemical Classification and Information Database                                              |
| EU_CLH: European Union Harmonised Classification and Labelling Proposal                                                                   | OECD_EHSP: Environment, Health, and Safety Publication (Organisation for Economic Co-operation and Development)    |
| EU_RAR: European Union Risk Assessment Report                                                                                             | OECD_SIDS: Screening Information Data Sets (Organisation for Economic Co-operation and Development)                |
|                                                                                                                                           | WHO: World Health Organization                                                                                     |

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*