



Poids de sous-couches autonivelantes durcies par profondeur

Produit	NXT® Level Flow	NXT Level	NXT Level Plus	NXT Level Plus Lite	SUPERCAP® SC500	SUPERCAP SC500 Plus	SUPERCAP SC500-LW
Densité : Livres par pied cube	125	130	130	70	125	130	87
Profondeur en millimètres (pouces)	Pounds per Square Feet						
6.4 mm (1/4")	1.2 kg (2.6)	1.2 kg (2.7)	1.2 kg (2.7)	0.7 kg (1.5)	1.2 kg (2.6)	1.2 kg (2.7)	0.8 kg (1.8)
12.7 mm (1/2")	2.4 kg (5.2)	2.5 kg (5.4)	2.5 kg (5.4)	1.3 kg (2.9)	2.4 kg (5.2)	2.5 kg (5.4)	1.6 kg (3.6)
19.1 mm (3/4")	3.5 kg (7.8)	3.7 kg (8.1)	3.7 kg (8.1)	2.0 kg (4.4)	3.5 kg (7.8)	3.7 kg (8.1)	2.5 kg (5.4)
25.4 mm (1")	4.7 kg (10.4)	4.9 kg (10.8)	4.9 kg (10.8)	2.6 kg (5.8)	4.7 kg (10.4)	4.9 kg (10.8)	3.3 kg (7.3)
31.8 mm (1-1/4")	5.9 kg (13.0)	6.1 kg (13.5)	6.1 kg (13.5)	3.3 kg (7.3)	5.9 kg (13.0)	6.1 kg (13.5)	4.1 kg (9.1)
38.1 mm (1-1/2")	7.1 kg (15.6)	7.4 kg (16.3)	7.4 kg (16.3)	4.0 kg (8.8)	7.1 kg (15.6)	7.4 kg (16.3)	5.0 kg (10.9)
44.5 mm (1-3/4")	8.3 kg (18.2)	8.6 kg (19.0)	8.6 kg (19.0)	4.6 kg (10.2)	8.3 kg (18.2)	8.6 kg (19.0)	5.8 kg (12.7)
50.8 mm (2")	9.4 kg (20.8)	9.8 kg (21.7)	9.8 kg (21.7)	5.3 kg (11.7)	9.4 kg (20.8)	9.8 kg (21.7)	6.6 kg (14.5)
57.2 mm (2-1/4")		11.1 kg (24.4)		5.9 kg (13.1)	10.1 kg (23.4)	11.1 kg (24.4)	7.4 kg (16.3)
63.5 mm (2-1/2")		12.3 kg (27.1)		6.6 kg (14.6)	11.8 kg (26.0)	12.3 kg (27.1)	8.2 kg (18.1)
69.9 mm (2-3/4")		13.5 kg (29.8)		7.3 kg (16.0)	13.0 kg (28.6)	13.5 kg (29.8)	9.0 kg (19.9)
76.2 mm (3")		14.7 kg (32.4)		7.9 kg (17.5)	14.2 kg (31.2)	14.7 kg (32.4)	9.9 kg (21.8)
82.6 mm (3-1/4")				8.6 kg (19.0)			10.7 kg (23.6)
88.9 mm (3-1/2")				9.3 kg (20.4)			11.5 kg (25.4)
95.3 mm (3-3/4")				9.9 kg (21.9)			12.3 kg (27.2)
101.6 mm (4")				10.6 kg (23.3)			13.2 kg (29.0)

Autres produits de construction	Densité : Livres par pied cube	Livres par pied cube à 1 po
Béton	145	5.5 kg (12.1)
Sous-couches autonivelantes à base de gypse	110	4.2 kg (9.2)
Béton léger	90 to 100	3.6 kg (8.0)

