

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous

Products Regulation (February 11, 2015).

Revision Date: 08/12/2019 Date of Issue: 01/30/2019 Supersedes Date: 07/22/2019 Version: 2.1

SECTION 1: IDENTIFICATION

1.1. Product Identifier Product Form: Mixture Product Name: 253 Gold

Product Code: 0253-0050-11 (105), 0253-0050-21 (105)

1.2. Intended Use of the Product Tile adhesive, for professional use only.

1.3. Name, Address, and Telephone of the Responsible Party

Company Company

LATICRETE International LATICRETE Canada ULC

1 Laticrete Park, N PO Box 129, Emeryville, Ontario, Canada

Bethany, CT 06524 NOR-1A0 T (203)-393-0010 (833)-254-9255

www.laticrete.com

1.4. Emergency Telephone Number

Emergency Number: For Chemical Emergency call ChemTel Inc. day or night:

(800)255-3924 (North America) (800)-099-0731 (Mexico)

+1 (813)248-0585 (International - collect calls accepted)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

GHS-US/CA Classification

 Skin Corr. 1C
 H314

 Eye Dam. 1
 H318

 Skin Sens. 1
 H317

 Carc. 1A
 H350

 STOT SE 3
 H335

 STOT RE 1
 H372

Full text of hazard classes and H-statements: see section 16

2.2. Label Elements

GHS-US/CA Labeling

Hazard Pictograms (GHS-US/CA)



GHS07



Signal Word (GHS-US/CA) : Danger

Hazard Statements (GHS-US/CA) : H314 - Causes severe skin burns and eye damage.

H317 - May cause an allergic skin reaction.
H318 - Causes serious eye damage.
H335 - May cause respiratory irritation.
H350 - May cause cancer (Inhalation).

H372 - Causes damage to organs (lungs) through prolonged or repeated exposure

(Inhalation).

Precautionary Statements (GHS-US/CA): P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P260 - Do not breathe vapors, mist, or spray.

P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product. P271 - Use only outdoors or in a well-ventilated area.

08/12/2019 EN (English US) 1/14

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

P272 - Contaminated work clothing should not be allowed out of the workplace.

P280 - Wear protective gloves, protective clothing, and eye protection.

P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 - If exposed or concerned: Get medical advice/attention.

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

P362+P364 - Take off contaminated clothing and wash it before reuse.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P405 - Store locked up.

P501 - Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

2.4. Unknown Acute Toxicity (GHS-US/CA)

No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

3.2. Mixture

Name	Product Identifier		GHS Ingredient Classification	
Quartz	(CAS-No.) 14808-60-7	<= 62	Carc. 1A, H350	
			STOT SE 3, H335	
			STOT RE 1, H372	
Cement, portland, chemicals	(CAS-No.) 65997-15-1	15 - 40	Skin Irrit. 2, H315	
			Eye Dam. 1, H318	
			Skin Sens. 1, H317	
			STOT SE 3, H335	
Calcium oxide	(CAS-No.) 1305-78-8	19 - 24	Skin Irrit. 2, H315	
			Eye Dam. 1, H318	
			STOT SE 3, H335	
			Aquatic Acute 3, H402	
Copolymer of vinyl acetate and	(CAS-No.) Not assigned	1 - 5	Comb. Dust	
ethylene with mineral additives and				
protective colloid				
Limestone	(CAS-No.) 1317-65-3	<= 2	Not classified	
Silicic acid (H4SiO4), calcium salt (1:2)	(CAS-No.) 10034-77-2	1 - 2	Eye Irrit. 2A, H319	
Calcium sulfate dihydrate	(CAS-No.) 13397-24-5	<= 2	Not classified	
Magnesium oxide (MgO)	(CAS-No.) 1309-48-4	<= 1	Not classified	
Lithium carbonate	(CAS-No.) 554-13-2	0.03	Acute Tox. 4 (Oral), H302	
			Acute Tox. 4 (Inhalation:dust,mist), H332	
			Eye Irrit. 2B, H320	
			Aquatic Acute 2, H401	
			Aquatic Chronic 2, H411	
Chromium, ion (Cr6+)	(CAS-No.) 18540-29-9	< 0.00003	Skin Sens. 1, H317	
			Carc. 1B, H350	
			Aquatic Acute 1, H400	
			Aquatic Chronic 1, H410	

Full text of H-phrases: see section 16

08/12/2019 EN (English US) 2/14

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

- *Percentages are listed in weight by weight percentage (w/w%) for liquid and solid ingredients. Gas ingredients are listed in volume by volume percentage (v/v%).
- ** The actual concentration of ingredient(s) is withheld as a trade secret in accordance with the Hazardous Products Regulations (HPR) SOR/2015-17 and 29 CFR 1910.1200.

SECTION 4: FIRST AID MEASURES

4.1. Description of First-aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Inhalation: Using proper respiratory protection, move the exposed person to fresh air at once. Encourage exposed person to cough, spit out, and blow nose to remove dust. Immediately call a poison center, physician, or emergency medical service.

Skin Contact: Immediately remove contaminated clothing. Immediately flush skin with plenty of water for at least 30 minutes. Get immediate medical advice/attention.

Eye Contact: Immediately rinse with water for at least 30 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.

Ingestion: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

General: Causes severe skin burns and eye damage. May cause respiratory irritation. May cause cancer. Skin sensitization. Causes damage to organs through prolonged or repeated exposure.

Inhalation: May be corrosive to the respiratory tract. Accelerated Silicosis can occur with exposure to high concentrations of respirable crystalline silica over a relatively short period; lung lesions can appear within five years of the initial exposure. The progression can be rapid. Accelerated silicosis is similar to chronic or ordinary silicosis, except that lung lesions appear earlier and the progression is more rapid.

Acute Silicosis can occur with exposures to very high concentrations of respirable crystalline silica over a very short time period, sometimes as short as a few months. The symptoms of acute silicosis include progressive shortness of breath, fever, cough and weight loss. Acute silicosis can be fatal.

Skin Contact: May cause an allergic skin reaction. Redness, pain, swelling, itching, burning, dryness, and dermatitis. Concrete may cause dry skin, discomfort, irritation, severe burns, and dermatitis. Unhardened concrete is capable of causing dermatitis by irritation and allergy. Concrete dust, in association with sweat and friction, can lead to skin irritation and dermatitis. Skin affected by dermatitis may include symptoms such as, redness, itching, rash, scaling, and cracking. Allergic contact dermatitis is caused by sensitization to hexavalent chromium (chromate) present in concrete. The reaction can range from a mild rash to severe skin ulcers.

Eye Contact: Causes permanent damage to the cornea, iris, or conjunctiva. Concrete may cause immediate or delayed irritation or inflammation. Eye contact with wet concrete can cause moderate eye irritation, chemical burns and blindness. Eye exposures require immediate first aid and medical attention to prevent significant damage to the eye.

Ingestion: May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.

Chronic Symptoms: Causes damage to organs (lungs) through prolonged or repeated exposure (Inhalation). May cause cancer. Repeated exposure to respirable (airborne) crystalline silica dust will cause lung damage in the form of silicosis. Some studies show that exposure to respirable crystalline silica (without silicosis) or that the disease silicosis may be associated with the increased incidence of several autoimmune disorders such as scleroderma (thickening of the skin), systemic lupus erythematosus, rheumatoid arthritis and diseases affecting the kidneys. Silicosis increases the risk of tuberculosis. Some studies show an increased incidence of chronic kidney disease and end-stage renal disease in workers exposed to respirable crystalline silica.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire. Reacts with water to form corrosive alkalis.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not considered flammable but may burn at high temperatures.

Explosion Hazard: Product is not explosive.

08/12/2019 EN (English US) 3/14

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Reactivity: Hydrofluoric acid will react with and dissolve glass, and other silica containing material. May react exothermically with water releasing heat. Adding an acid to a base or base to an acid may cause violent reaction.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Silicon oxides. Carbon oxides (CO, CO₂). Sulfur oxides. Calcium oxides.

Other Information: Do not allow run-off from fire fighting to enter drains or water courses.

5.4. Reference to Other Sections

Refer to Section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not breathe dust. Do not get in eyes, on skin, or on clothing. Avoid generating dust. Do not handle until all safety precautions have been read and understood.

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protective equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area.

6.2. Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

6.3. Methods and Materials for Containment and Cleaning Up

For Containment: Contain solid spills with appropriate barriers and prevent migration and entry into sewers or streams. As an immediate precautionary measure, isolate spill or leak area in all directions. Avoid generation of dust during clean-up of spills. **Methods for Cleaning Up:** Clean up spills immediately and dispose of waste safely. Cautiously neutralize spilled solid. Use explosion proof vacuum during cleanup, with appropriate filter. Do not mix with other materials. Vacuum clean-up is preferred. If sweeping is

required use a dust suppressant. Contact competent authorities after a spill. **6.4.** Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Additional Hazards When Processed: May release corrosive vapors.

Precautions for Safe Handling: Obtain special instructions before use. Do not breathe dust. Do not get in eyes, on skin, or on clothing. Do not handle until all safety precautions have been read and understood. Avoid creating or spreading dust. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Handle empty containers with care because they may still present a hazard.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations. Avoid creating or spreading dust.

Storage Conditions: Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store locked up/in a secure area. Store in original container or corrosive resistant and/or lined container.

Incompatible Materials: Strong acids, strong bases, strong oxidizers. fluorinated compounds. Ammonia. Ammonium salts. Aluminum.

7.3. Specific End Use(s)

Tile adhesive, for professional use only.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

08/12/2019 EN (English US) 4/14

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), or Canadian provincial governments.

ACGIH TWA (mg/m³)	0.025 mg/m³ (respirable particulate matter)	
ACGIH chemical category	A2 - Suspected Human Carcinogen	
OSHA PEL (TWA) (mg/m³)	50 μg/m³ (Respirable crystalline silica)	
NIOSH REL (TWA) (mg/m³)	0.05 mg/m³ (respirable dust)	
US IDLH (mg/m³)	50 mg/m³ (respirable dust)	
OEL TWA (mg/m³)	0.025 mg/m³ (respirable particulate)	
OEL TWA (mg/m³)	0.025 mg/m³ (respirable)	
OEL TWA (mg/m³)	0.025 mg/m³ (respirable particulate matter)	
OEL TWA (mg/m³)	0.1 mg/m³ (respirable fraction)	
OEL TWA (mg/m³)	0.025 mg/m³ (respirable particulate matter)	
OEL TWA (mg/m³)	0.025 mg/m³ (respirable particulate matter)	
OEL TWA (mg/m³)	0.05 mg/m³ (respirable fraction (Silica - crystalline)	
	0.05 mg/m³ (respirable fraction (Silica - crystalline)	
OEL TWA (mg/m³)	0.1 mg/m³ (designated substances regulation-respirable	
, , ,	(Silica, crystalline)	
OEL TWA (mg/m³)	0.025 mg/m³ (respirable particulate matter)	
	0.1 mg/m³ (respirable dust)	
OEL TWA (mg/m³)	0.05 mg/m³ (respirable fraction (Silica - crystalline	
, ,	(Trydimite removed))	
OEL TWA (mg/m³)	300 particle/mL (Silica - Quartz, crystalline)	
s (65997-15-1)		
	1 mg/m³ (particulate matter containing no asbestos and	
, ,	<1% crystalline silica, respirable particulate matter)	
ACGIH chemical category	Not Classifiable as a Human Carcinogen	
	15 mg/m³ (total dust)	
, , , ,	5 mg/m³ (respirable fraction)	
NIOSH REL (TWA) (mg/m³)	10 mg/m³ (total dust)	
	5 mg/m³ (respirable dust)	
US IDLH (mg/m³)	5000 mg/m ³	
OEL TWA (mg/m³)	10 mg/m ³	
OEL TWA (mg/m³)	1 mg/m³ (particulate matter containing no Asbestos and	
	<1% Crystalline silica-respirable particulate)	
OEL TWA (mg/m³)	1 mg/m³ (particulate matter containing no Asbestos and	
	<1% Crystalline silica, respirable particulate matter-	
	particulate matter, respirable particulate matter)	
OEL TWA (mg/m³)	10 mg/m³ (particulate matter containing no Asbestos and	
	<1% Crystalline silica)	
OEL TWA (mg/m³)	1 mg/m³ (particulate matter containing no Asbestos and	
	<1% Crystalline silica, respirable particulate matter-	
	particulate matter, respirable particulate matter)	
OEL TWA (mg/m³)	1 mg/m³ (particulate matter containing no Asbestos and	
	<1% Crystalline silica, respirable particulate matter-	
200	particulate matter, respirable particulate matter)	
	20 mg/m³	
	10 mg/m³	
	20 mg/m³	
	10 mg/m³	
OEL TWA (mg/m³)	1 mg/m³ (containing no Asbestos and <1% Crystalline	
	ACGIH chemical category OSHA PEL (TWA) (mg/m³) NIOSH REL (TWA) (mg/m³) OEL TWA (mg/m³) OEL TWA (mg/m³)	

08/12/2019 EN (English US) 5/14

Safety Data Sheet
According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

		silica-respirable)	
Prince Edward Island	OEL TWA (mg/m³)	1 mg/m³ (particulate matter containing no Asbestos and	
Fillice Lawara Islana	OLL TWA (IIIg/III)	<1% Crystalline silica, respirable particulate matter-	
		particulate matter, respirable particulate matter)	
Québec	VEMP (mg/m³)	10 mg/m³ (containing no Asbestos and <1% Crystalline	
Quebee	VEIVII (IIIg/III)	silica-total dust)	
		5 mg/m³ (containing no Asbestos and <1% Crystalline	
		silica-respirable dust)	
Saskatchewan	OEL STEL (mg/m³)	20 mg/m³	
Saskatchewan	OEL TWA (mg/m³)	10 mg/m ³	
Yukon	OEL STEL (mg/m³)	20 mg/m³	
Yukon	OEL TWA (mg/m³)	30 mppcf	
	, ,	10 mg/m ³	
Calcium oxide (1305-78-8)		1 3	
USA ACGIH	ACGIH TWA (mg/m³)	2 mg/m³	
USA OSHA	OSHA PEL (TWA) (mg/m³)	5 mg/m ³	
USA NIOSH	NIOSH REL (TWA) (mg/m³)	2 mg/m³	
USA IDLH	US IDLH (mg/m³)	25 mg/m³	
Alberta	OEL TWA (mg/m³)	2 mg/m³	
British Columbia	OEL TWA (mg/m³)	2 mg/m³	
Manitoba	OEL TWA (mg/m³)	2 mg/m ³	
New Brunswick	OEL TWA (mg/m³)	2 mg/m³	
Newfoundland & Labrador	OEL TWA (mg/m³)	2 mg/m³	
Nova Scotia	OEL TWA (mg/m³)	2 mg/m³	
Nunavut	OEL STEL (mg/m³)	4 mg/m ³	
Nunavut	OEL TWA (mg/m³)	2 mg/m³	
Northwest Territories	OEL STEL (mg/m³)	4 mg/m³	
Northwest Territories	OEL TWA (mg/m³)	2 mg/m³	
Ontario	OEL TWA (mg/m³)	2 mg/m³	
Prince Edward Island	OEL TWA (mg/m³)	2 mg/m³	
Québec	VEMP (mg/m³)	2 mg/m³	
Saskatchewan	OEL STEL (mg/m³)	4 mg/m ³	
Saskatchewan	OEL TWA (mg/m³)	2 mg/m³	
Yukon	OEL STEL (mg/m³)	4 mg/m ³	
Yukon	OEL TWA (mg/m³)	2 mg/m ³	
Calcium sulfate dihydrate (1	3397-24-5)		
USA ACGIH	ACGIH TWA (mg/m³)	10 mg/m³ (inhalable particulate matter (Calcium sulfate)	
USA OSHA	OSHA PEL (TWA) (mg/m³)	15 mg/m³ (total dust)	
		5 mg/m³ (respirable fraction)	
USA NIOSH	NIOSH REL (TWA) (mg/m³)	10 mg/m³ (total dust)	
		5 mg/m³ (respirable dust)	
Alberta	OEL TWA (mg/m³)	10 mg/m³ (Calcium sulphate)	
British Columbia	OEL STEL (mg/m³)	20 mg/m³ (total)	
British Columbia	OEL TWA (mg/m³)	10 mg/m³ (total dust)	
		3 mg/m³ (respirable fraction)	
Manitoba	OEL TWA (mg/m³)	10 mg/m³ (inhalable particulate matter (Calcium sulfate)	
Newfoundland & Labrador	OEL TWA (mg/m³)	10 mg/m³ (inhalable particulate matter (Calcium sulfate)	
Nova Scotia	OEL TWA (mg/m³)	10 mg/m³ (inhalable particulate matter (Calcium sulfate)	
Ontario	OEL TWA (mg/m³)	10 mg/m³ (inhalable (Calcium sulfate)	
Prince Edward Island	OEL TWA (mg/m³)	10 mg/m³ (inhalable particulate matter (Calcium sulfate)	
Québec	VEMP (mg/m³)	10 mg/m³ (containing no Asbestos and <1% Crystalline	
		silica-total dust)	

08/12/2019 EN (English US) 6/14

Safety Data Sheet
According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

According to reactal negister / vol. //, No	. 307 Monday, March 20, 2012 / Rules And Regulation	ons And According To The Hazardous Products Regulation (February 11, 2015).
silica-respirable dust)		5 mg/m³ (containing no Asbestos and <1% Crystalline
Caskatahawan	OFI STEL /ma/m3\	20 mg/m ³
Saskatchewan Saskatchewan	OEL STEL (mg/m³) OEL TWA (mg/m³)	10 mg/m³
Yukon	OEL TWA (mg/m²) OEL STEL (mg/m³)	20 mg/m ³
Yukon	OEL TWA (mg/m³)	30 mppcf
TUKOII	OEL TWA (IIIg/III)	10 mg/m ³
Limentone (1217 CF 2)		10 Hig/III
Limestone (1317-65-3) USA OSHA	OSHA PEL (TWA) (mg/m³)	15 mg/m³ (total dust)
USA USHA	OSHA PEL (TWA) (Mg/M²)	5 mg/m³ (respirable fraction)
USA NIOSH	NIOSH REL (TWA) (mg/m³)	10 mg/m³ (total dust)
OSA NIOSII	NIOSITICE (TWA) (IIIg/III)	5 mg/m³ (respirable dust)
Alberta	OEL TWA (mg/m³)	10 mg/m ³
British Columbia	OEL STEL (mg/m³)	20 mg/m³ (total)
British Columbia	OEL TWA (mg/m³)	10 mg/m³ (total dust)
Dittish Columbia	OLL TWA (mg/m)	3 mg/m³ (respirable fraction)
New Brunswick	OEL TWA (mg/m³)	10 mg/m³ (particulate matter containing no Asbestos and
)	<1% Crystalline silica)
Nunavut	OEL STEL (mg/m³)	20 mg/m³
Nunavut	OEL TWA (mg/m³)	10 mg/m³
Northwest Territories	OEL STEL (mg/m³)	20 mg/m³
Northwest Territories	OEL TWA (mg/m³)	10 mg/m ³
Québec	VEMP (mg/m³)	10 mg/m³ (Limestone, containing no Asbestos and <1%
•	, ,	Crystalline silica-total dust)
Saskatchewan	OEL STEL (mg/m³)	20 mg/m ³
Saskatchewan	OEL TWA (mg/m³)	10 mg/m ³
Yukon	OEL STEL (mg/m³)	20 mg/m ³
Yukon	OEL TWA (mg/m³)	30 mppcf
		10 mg/m³
Magnesium oxide (MgO) (13	809-48-4)	
USA ACGIH	ACGIH TWA (mg/m³)	10 mg/m³ (inhalable particulate matter)
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA OSHA	OSHA PEL (TWA) (mg/m³)	15 mg/m³ (fume, total particulate)
USA IDLH	US IDLH (mg/m³)	750 mg/m³ (fume)
Alberta	OEL TWA (mg/m³)	10 mg/m³ (fume)
British Columbia	OEL STEL (mg/m³)	10 mg/m³ (respirable dust and fume)
British Columbia	OEL TWA (mg/m³)	10 mg/m³ (fume, inhalable)
		3 mg/m³ (respirable dust and fume)
Manitoba	OEL TWA (mg/m³)	10 mg/m³ (inhalable particulate matter)
New Brunswick	OEL TWA (mg/m³)	10 mg/m³ (fume)
Newfoundland & Labrador	OEL TWA (mg/m³)	10 mg/m³ (inhalable particulate matter)
Nova Scotia	OEL TWA (mg/m³)	10 mg/m³ (inhalable particulate matter)
Nunavut	OEL STEL (mg/m³)	20 mg/m³ (inhalable fraction)
Nunavut	OEL TWA (mg/m³)	10 mg/m³ (inhalable fraction)
Northwest Territories	OEL STEL (mg/m³)	20 mg/m³ (inhalable fraction)
Northwest Territories	OEL TWA (mg/m³)	10 mg/m³ (inhalable fraction)
Ontario	OEL TWA (mg/m³)	10 mg/m³ (inhalable)
Prince Edward Island	OEL TWA (mg/m³)	10 mg/m³ (inhalable particulate matter)
Québec	VEMP (mg/m³)	10 mg/m³ (fume)
Saskatchewan	OEL STEL (mg/m³)	20 mg/m³ (inhalable fraction)
Saskatchewan	OEL TWA (mg/m³)	10 mg/m³ (inhalable fraction)
Yukon	OEL STEL (mg/m³)	10 mg/m³ (fume)

08/12/2019 EN (English US) 7/14

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Yukon	OEL TWA (mg/m³)	10 mg/m³ (fume)	
Chromium, ion (Cr6+) (18540)-29-9)		
USA OSHA	OSHA PEL (TWA) (mg/m³)	5 μg/m³	
Particulates not otherwise cl	lassified (PNOC) (Not applicable)		
USA ACGIH ACGIH TWA (mg/m³) 3 mg/m³ Respirable fra		3 mg/m ³ Respirable fraction	
		10 mg/m³ Total Dust	
USA OSHA	OSHA PEL (TWA) (mg/m³)	5 mg/m³ Respirable fraction	
		15 mg/m³ Total Dust	
Alberta	OEL TWA (mg/m³)	10 mg/m³ (total)	
		3 mg/m³ (respirable)	
British Columbia	OEL TWA (mg/m³)	10 mg/m³ (nuisance dust-total dust)	
		3 mg/m³ (nuisance dust-respirable fraction)	
Manitoba	OEL TWA (mg/m³)	10 mg/m³ (inhalable particles, recommended)	
		3 mg/m³ (respirable particles, recommended)	
New Brunswick	OEL TWA (mg/m³)	3 mg/m³ (particulate matter containing no Asbestos and	
		<1% Crystalline silica, respirable fraction)	
		10 mg/m³ (particulate matter containing no Asbestos and	
		<1% Crystalline silica, inhalable fraction)	
Newfoundland & Labrador	OEL TWA (mg/m³)	10 mg/m³ (inhalable particles, recommended)	
		3 mg/m³ (respirable particles, recommended)	
Nova Scotia	OEL TWA (mg/m³)	10 mg/m³ (inhalable particles, recommended)	
		3 mg/m³ (respirable particles, recommended)	
Nunavut	OEL STEL (mg/m³)	20 mg/m³ (insoluble or poorly soluble-inhalable fraction)	
		6 mg/m³ (insoluble or poorly soluble-respirable fraction)	
Nunavut	OEL TWA (mg/m³)	10 mg/m³ (insoluble or poorly soluble-inhalable fraction)	
		3 mg/m³ (insoluble or poorly soluble-respirable fraction)	
Northwest Territories	OEL STEL (mg/m³)	20 mg/m³ (insoluble or poorly soluble-inhalable fraction)	
		6 mg/m³ (insoluble or poorly soluble-respirable fraction)	
Northwest Territories	OEL TWA (mg/m³)	10 mg/m³ (insoluble or poorly soluble-inhalable fraction)	
		3 mg/m³ (insoluble or poorly soluble-respirable fraction)	
Ontario	OEL TWA (mg/m³)	10 mg/m³ (inhalable)	
		3 mg/m³ (respirable)	
Prince Edward Island	OEL TWA (mg/m³)	10 mg/m³ (inhalable particles, recommended)	
		3 mg/m³ (respirable particles, recommended)	
Québec	VEMP (mg/m³)	10 mg/m³ (including dust, inert or nuisance particulates-	
		total dust)	
Saskatchewan	OEL STEL (mg/m³)	20 mg/m³ (insoluble or poorly soluble-inhalable fraction)	
		6 mg/m³ (insoluble or poorly soluble-respirable fraction)	
Saskatchewan	OEL TWA (mg/m³)	10 mg/m³ (insoluble or poorly soluble-inhalable fraction)	
		3 mg/m³ (insoluble or poorly soluble-respirable fraction)	

8.2. Exposure Controls

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed

Personal Protective Equipment: Gloves. Protective clothing. Protective goggles. Face shield. Insufficient ventilation: wear respiratory protection.











Materials for Protective Clothing: Chemically resistant materials and fabrics. Corrosion-proof clothing. **Hand Protection:** Wear protective gloves.

08/12/2019 EN (English US) 8/14

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Eye and Face Protection: Chemical safety goggles and face shield.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

Other Information: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State: SolidAppearance: GrayOdor: None

Odor **Odor Threshold** Not available Not available рН **Evaporation Rate** Not available **Melting Point** Not available **Freezing Point** Not available **Boiling Point** Not available **Flash Point** Not available **Auto-ignition Temperature** Not available **Decomposition Temperature** Not available Flammability (solid, gas) Not available **Lower Flammable Limit** Not available **Upper Flammable Limit** Not available **Vapor Pressure** Not available Relative Vapor Density at 20°C Not available **Relative Density** Not available 1.2 - 1.5Density **Specific Gravity** Not available Solubility Water: Insoluble **Partition Coefficient: N-Octanol/Water** Not available

SECTION 10: STABILITY AND REACTIVITY

Viscosity

10.1. Reactivity: Hydrofluoric acid will react with and dissolve glass, and other silica containing material. May react exothermically with water releasing heat. Adding an acid to a base or base to an acid may cause violent reaction.

Not available

- **10.2.** Chemical Stability: Stable under recommended handling and storage conditions (see section 7).
- **10.3.** Possibility of Hazardous Reactions: Hazardous polymerization will not occur.
- 10.4. Conditions to Avoid: Direct sunlight, extremely high or low temperatures, and incompatible materials.
- **10.5. Incompatible Materials:** Strong acids, strong bases, strong oxidizers. fluorinated compounds. Ammonia. Ammonium salts. Aluminum.
- **10.6. Hazardous Decomposition Products:** Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on Toxicological Effects - Product

Acute Toxicity (Oral): Not classified
Acute Toxicity (Dermal): Not classified
Acute Toxicity (Inhalation): Not classified
LD50 and LC50 Data: Not available

Skin Corrosion/Irritation: Causes severe skin burns and eye damage.

Eye Damage/Irritation: Causes serious eye damage.

08/12/2019 EN (English US) 9/14

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Respiratory or Skin Sensitization: May cause an allergic skin reaction.

Germ Cell Mutagenicity: Not classified

Carcinogenicity: May cause cancer (Inhalation).

Specific Target Organ Toxicity (Repeated Exposure): Causes damage to organs (lungs) through prolonged or repeated exposure

(Inhalation).

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): May cause respiratory irritation.

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: May be corrosive to the respiratory tract. Accelerated Silicosis can occur with exposure to high concentrations of respirable crystalline silica over a relatively short period; lung lesions can appear within five years of the initial exposure. The progression can be rapid. Accelerated silicosis is similar to chronic or ordinary silicosis, except that lung lesions appear earlier and the progression is more rapid.

Acute Silicosis can occur with exposures to very high concentrations of respirable crystalline silica over a very short time period, sometimes as short as a few months. The symptoms of acute silicosis include progressive shortness of breath, fever, cough and weight loss. Acute silicosis can be fatal.

Symptoms/Injuries After Skin Contact: May cause an allergic skin reaction. Redness, pain, swelling, itching, burning, dryness, and dermatitis. Concrete may cause dry skin, discomfort, irritation, severe burns, and dermatitis. Unhardened concrete is capable of causing dermatitis by irritation and allergy. Concrete dust, in association with sweat and friction, can lead to skin irritation and dermatitis. Skin affected by dermatitis may include symptoms such as, redness, itching, rash, scaling, and cracking. Allergic contact dermatitis is caused by sensitization to hexavalent chromium (chromate) present in concrete. The reaction can range from a mild rash to severe skin ulcers.

Symptoms/Injuries After Eye Contact: Causes permanent damage to the cornea, iris, or conjunctiva. Concrete may cause immediate or delayed irritation or inflammation. Eye contact with wet concrete can cause moderate eye irritation, chemical burns and blindness. Eye exposures require immediate first aid and medical attention to prevent significant damage to the eye.

Symptoms/Injuries After Ingestion: May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract. Chronic Symptoms: Causes damage to organs (lungs) through prolonged or repeated exposure (Inhalation). May cause cancer. Repeated exposure to respirable (airborne) crystalline silica dust will cause lung damage in the form of silicosis. Some studies show that exposure to respirable crystalline silica (without silicosis) or that the disease silicosis may be associated with the increased incidence of several autoimmune disorders such as scleroderma (thickening of the skin), systemic lupus erythematosus, rheumatoid arthritis and diseases affecting the kidneys. Silicosis increases the risk of tuberculosis. Some studies show an increased incidence of chronic kidney disease and end-stage renal disease in workers exposed to respirable crystalline silica.

11.2. Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

LD30 and LC30 Data.		
Quartz (14808-60-7)		
LD50 Oral Rat	> 5000 mg/kg	
LD50 Dermal Rat	> 5000 mg/kg	
Calcium oxide (1305-78-8)		
LD50 Oral Rat	> 2000 mg/kg	
LD50 Dermal Rabbit	> 2500 mg/kg	
Magnesium oxide (MgO) (1309-48-4)		
LD50 Oral Rat 3870 mg/kg		
Lithium carbonate (554-13-2)		
LD50 Oral Rat	525 mg/kg	
LD50 Dermal Rabbit	> 3000 mg/kg	
LC50 Inhalation Rat	> 2.17 mg/l/4h	
ATE US/CA (dust, mist)	1.50 mg/l/4h	
Quartz (14808-60-7)		
IARC Group	1	
National Toxicology Program (NTP) Status	Known Human Carcinogens.	
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.	
Chromium, ion (Cr6+) (18540-29-9)		

08/12/2019 EN (English US) 10/14

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

IARC Group	1
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.
OSHA Specifically Regulated Carcinogen List	In OSHA Specifically Regulated Carcinogen list.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - General: Not classified.

Calcium oxide (1305-78-8)	
LC50 Fish 1	50.6 mg/l
Lithium carbonate (554-13-2)	
LC50 Fish 1	8.1 mg/l
Chromium, ion (Cr6+) (18540-29-9)	
LC50 Fish 1	36.2 mg/l (Exposure time: 96 h - Species: Pimephales promelas)
LC50 Fish 2	7.6 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)

12.2. Persistence and Degradability

253 Gold	
Persistence and Degradability	Not established.

12.3. Bioaccumulative Potential

253 Gold		
Bioaccumulative Potential	Not established.	
Calcium oxide (1305-78-8)		
BCF Fish 1	(no bioaccumulation)	

12.4. Mobility in Soil Not available

12.5. Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste Disposal Recommendations: Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

Ecology - Waste Materials: Avoid release to the environment. This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

14.1. In Accordance with DOT
 14.2. In Accordance with IMDG
 14.3. In Accordance with IATA
 14.4. In Accordance with TDG
 Not regulated for transport
 Not regulated for transport
 Not regulated for transport

SECTION 15: REGULATORY INFORMATION

15.1. US Federal Regulations

Cement, portland, chemicals (65997-15-1)

253 Gold	
SARA Section 311/312 Hazard Classes	Health hazard - Specific target organ toxicity (single or repeated exposure) Health hazard - Carcinogenicity Health hazard - Respiratory or skin sensitization Health hazard - Serious eye damage or eye irritation Health hazard - Skin corrosion or Irritation
Quartz (14808-60-7)	
Listed on the United States TSCA (Toxic Substances	Control Act) inventory

08/12/2019 EN (English US) 11/14

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Calcium oxide (1305-78-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Silicic acid (H4SiO4), calcium salt (1:2) (10034-77-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Limestone (1317-65-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Magnesium oxide (MgO) (1309-48-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Lithium carbonate (554-13-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Subject to reporting requirements of United States SARA Section 313

SARA Section 313 - Emission Reporting

1 %

15.2. US State Regulations

California Proposition 65



WARNING: This product can expose you to Chromium, ion (Cr6+), which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Chemical Name (CAS No.)	Carcinogenicity	Developmental Toxicity	Female Reproductive Toxicity	Male Reproductive Toxicity
Quartz (14808-60-7)	X			
Lithium carbonate (554-13-2)		Х		
Chromium, ion (Cr6+) (18540-	X	Х		
29-9)				

Quartz (14808-60-7)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Cement, portland, chemicals (65997-15-1)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Calcium oxide (1305-78-8)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Calcium sulfate dihydrate (13397-24-5)

- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Limestone (1317-65-3)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Magnesium oxide (MgO) (1309-48-4)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Lithium carbonate (554-13-2)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List

Chromium, ion (Cr6+) (18540-29-9)

08/12/2019 EN (English US) 12/14

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List

15.3. Canadian Regulations

Quartz (14808-60-7)

Listed on the Canadian DSL (Domestic Substances List)

Cement, portland, chemicals (65997-15-1)

Listed on the Canadian DSL (Domestic Substances List)

Calcium oxide (1305-78-8)

Listed on the Canadian DSL (Domestic Substances List)

Calcium sulfate dihydrate (13397-24-5)

Listed on the Canadian DSL (Domestic Substances List)

Silicic acid (H4SiO4), calcium salt (1:2) (10034-77-2)

Listed on the Canadian DSL (Domestic Substances List)

Limestone (1317-65-3)

Listed on the Canadian NDSL (Non-Domestic Substances List)

Magnesium oxide (MgO) (1309-48-4)

Listed on the Canadian DSL (Domestic Substances List)

Lithium carbonate (554-13-2)

Listed on the Canadian DSL (Domestic Substances List)

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Date of Preparation or Latest

Revision

: 08/12/2019

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA

Hazard Communication Standard 29 CFR 1910.1200 and Canada's Hazardous Products

Regulations (HPR) SOR/2015-17.

GHS Full Text Phrases:

Acute Tox. 4	Acute toxicity (inhalation:dust,mist) Category 4
(Inhalation:dust,mist)	
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Carc. 1A	Carcinogenicity Category 1A
Carc. 1B	Carcinogenicity Category 1B
Comb. Dust	Combustible Dust
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Eye Irrit. 2B	Serious eye damage/eye irritation Category 2B
Skin Corr. 1C	Skin corrosion/irritation Category 1C
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization, Category 1
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation

08/12/2019 EN (English US) 13/14

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H320	Causes eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H350	May cause cancer
H372	Causes damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

NA GHS SDS 2015 (Can, US)

08/12/2019 EN (English US) 14/14