

HYDRO BAN[®] Cementitious Water Proofing Membrane

Safety Data Sheet According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015). Date of Issue: 01/29/2018 Revision Date: 10/08/2018 Version: 1.1

SECTION 1: IDENTIFICATION

1.1. **Product Identifier** Product Form: Mixture

Product Name: HYDRO BAN® Cementitious Water Proofing Membrane

Intended Use of the Product 1.2.

Waterproofing Membrane

1.3. Name, Address, and Telephone of the Responsible Party

Company

LATICRETE International 1 Laticrete Park. N Bethany, CT 06524 T (203)-393-0010

Company LATICRETE Canada ULC PO Box 129, Emeryville, Ontario, Canada NOR-1A0

www.laticrete.com

Emergency Telephone Number 1.4.

Emergency Number : For Chemical Emergency Call CHEMTREC day or night Within USA and Canada: 1.800.424.9300 Mexico: 1.800.681.9531 Outside USA and Canada: 1.703.527.3887 (collect calls accepted)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture 2.1.

GHS-US/CA Classification			
Skin Irrit. 2	H315		
Eye Dam. 1	H318		
Skin Sens. 1	H317		
Carc. 1A	H350		
STOT SE 3	H335		
STOT RE 1	H372		

Full text of hazard classes and H-statements : see section 16

2.2. Label Elements

GHS-US/CA Labeling

Hazard Pictograms (GHS-US/CA)



Signal Word (GHS-US/CA)	: Danger
Hazard Statements (GHS-US/CA)	: H315 - Causes skin irritation.
	H317 - May cause an allergic skin reaction.
	H318 - Causes serious eye damage.
	H335 - May cause respiratory irritation.
	H350 - May cause cancer (inhalation).
	H372 - Causes damage to organs (inhalation) through prolonged or repeated exposure.
Precautionary Statements (GHS-US/CA)	: P201 - Obtain special instructions before use.
	P202 - Do not handle until all safety precautions have been read and understood.
	P260 - Do not breathe dust.
	P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.
	P270 - Do not eat, drink or smoke when using this product.
	P271 - Use only outdoors or in a well-ventilated area.
	P272 - Contaminated work clothing should not be allowed out of the workplace.
	P280 - Wear protective gloves, protective clothing, and eye protection.

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

P302+P352 - IF ON SKIN: Wash with plenty of water.

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 - If exposed or concerned: Get medical advice/attention.

P310 - Immediately call a POISON CENTER or doctor.

P314 - Get medical advice/attention if you feel unwell.

P321 - Specific treatment (see section 4 on this SDS).

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

P362+P364 - Take off contaminated clothing and wash it before reuse.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P405 - Store locked up.

P501 - Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

2.4. Unknown Acute Toxicity (GHS-US/CA)

No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

3.2. Mixture

Name	Product Identifier	% *	GHS Ingredient Classification
Quartz	(CAS-No.) 14808-60-7	39.8 - 79.7	Carc. 1A, H350
			STOT SE 3, H335
			STOT RE 1, H372
Limestone	(CAS-No.) 1317-65-3	0.03 - 39.9	Not classified
Cement, portland, chemicals	(CAS-No.) 65997-15-1	25	Skin Irrit. 2, H315
			Eye Dam. 1, H318
			Skin Sens. 1, H317
Calcium oxide	(CAS-No.) 1305-78-8	0.03 - 24.9	Skin Irrit. 2, H315
			Eye Dam. 1, H318
			STOT SE 3, H335
			Aquatic Acute 3, H402
Magnesium oxide (MgO)	(CAS-No.) 1309-48-4	0.03 - 24.9	Not classified
Calcium sulfate hemihydrate	(CAS-No.) 13397-24-5	0.03 - 24.9	Not classified

Full text of H-phrases: see section 16

*Percentages are listed in weight by weight percentage (w/w%) for liquid and solid ingredients. Gas ingredients are listed in volume by volume percentage (v/v%).

SECTION 4: FIRST AID MEASURES

4.1. Description of First-aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Inhalation: When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

Skin Contact: Remove contaminated clothing. Immediately drench affected area with water for at least 15 minutes. If exposed or concerned: Get medical advice/attention.

Eye Contact: Immediately rinse with water for at least 30 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.

Ingestion: Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

4.2. Most Important Symptoms and Effects Both Acute and Delayed

General: May cause respiratory irritation. May cause cancer. Causes damage to organs through prolonged or repeated exposure. Skin sensitization. Causes skin irritation. Causes serious eye damage.

Inhalation: Dust may be harmful or cause irritation. Irritation of the respiratory tract and the other mucous membranes.

Skin Contact: May cause an allergic skin reaction. Redness, pain, swelling, itching, burning, dryness, and dermatitis.

Eye Contact: Causes permanent damage to the cornea, iris, or conjunctiva.

Ingestion: Ingestion may cause adverse effects.

Chronic Symptoms: May cause cancer by inhalation. Causes damage to organs through prolonged or repeated exposure (inhalation). Repeated exposure to respirable (airborne) crystalline silica dust will cause lung damage in the form of silicosis.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Water spray, fog, carbon dioxide (CO₂), alcohol-resistant foam, or dry chemical.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not considered flammable but may burn at high temperatures.

Explosion Hazard: Product is not explosive.

Reactivity: Hazardous reactions will not occur under normal conditions.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO₂). Sulfur oxides. Metal oxides. Silicon oxides. Formaldehyde. Hydrocarbons. Reference to Other Sections

Refer to Section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not breathe dust. Do not get in eyes, on skin, or on clothing. Do not handle until all safety precautions have been read and understood.

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protective equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Ventilate area. Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

6.2. Environmental Precautions

Prevent entry to sewers and public waters.

6.3. Methods and Materials for Containment and Cleaning Up

For Containment: Contain solid spills with appropriate barriers and prevent migration and entry into sewers or streams. **Methods for Cleaning Up:** Clean up spills immediately and dispose of waste safely. Recover the product by vacuuming, shoveling or sweeping. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Precautions for Safe Handling: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust. Do not get in eyes, on skin, or on clothing. Avoid creating or spreading dust. Keep away from heat, sparks, open flames, hot surfaces. – No smoking.

HYDRO BAN[®] Cementitious Water Proofing Membrane

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store locked up/in a secure area.

Incompatible Materials: Strong acids, strong bases, strong oxidizers.

7.3. Specific End Use(s)

Waterproofing Membrane

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), or Canadian provincial governments.

0		
Quartz (14808-60-7)		
USA ACGIH	ACGIH TWA (mg/m³)	0.025 mg/m ³ (respirable particulate matter)
USA ACGIH	ACGIH chemical category	A2 - Suspected Human Carcinogen
USA OSHA	OSHA PEL (TWA) (mg/m³)	50 μg/m³
USA NIOSH	NIOSH REL (TWA) (mg/m³)	0.05 mg/m ³ (respirable dust)
USA IDLH	US IDLH (mg/m ³)	50 mg/m ³ (respirable dust)
Alberta	OEL TWA (mg/m³)	0.025 mg/m ³ (respirable particulate)
British Columbia	OEL TWA (mg/m³)	0.025 mg/m ³ (respirable)
Manitoba	OEL TWA (mg/m³)	0.025 mg/m ³ (respirable particulate matter)
New Brunswick	OEL TWA (mg/m³)	0.1 mg/m ³ (respirable fraction)
Newfoundland & Labrador	OEL TWA (mg/m³)	0.025 mg/m ³ (respirable particulate matter)
Nova Scotia	OEL TWA (mg/m³)	0.025 mg/m ³ (respirable particulate matter)
Nunavut	OEL TWA (mg/m³)	0.05 mg/m ³ (respirable fraction)
Northwest Territories	OEL TWA (mg/m³)	0.05 mg/m ³ (respirable fraction)
Ontario	OEL TWA (mg/m³)	0.1 mg/m ³ (designated substances regulation-respirable)
Prince Edward Island	OEL TWA (mg/m³)	0.025 mg/m ³ (respirable particulate matter)
Québec	VEMP (mg/m ³)	0.1 mg/m ³ (respirable dust)
Saskatchewan	OEL TWA (mg/m³)	0.05 mg/m ³ (respirable fraction)
Yukon	OEL TWA (mg/m³)	300 particle/mL
Limestone (1317-65-3)		
USA OSHA	OSHA PEL (TWA) (mg/m³)	15 mg/m ³ (total dust)
		5 mg/m ³ (respirable fraction)
USA NIOSH	NIOSH REL (TWA) (mg/m³)	10 mg/m ³ (total dust)
		5 mg/m ³ (respirable dust)
Alberta	OEL TWA (mg/m³)	10 mg/m ³
British Columbia	OEL STEL (mg/m³)	20 mg/m ³ (total dust)
British Columbia	OEL TWA (mg/m³)	10 mg/m³ (total dust)
		3 mg/m ³ (respirable fraction)
New Brunswick	OEL TWA (mg/m³)	10 mg/m ³ (particulate matter containing no Asbestos and
		<1% Crystalline silica)
Nunavut	OEL STEL (mg/m³)	20 mg/m ³
Nunavut	OEL TWA (mg/m³)	10 mg/m ³
Northwest Territories	OEL STEL (mg/m³)	20 mg/m ³
Northwest Territories	OEL TWA (mg/m³)	10 mg/m³
Québec	VEMP (mg/m³)	10 mg/m ³ (Limestone, containing no Asbestos and <1%
		Crystalline silica-total dust)
Saskatchewan	OEL STEL (mg/m³)	20 mg/m ³
Saskatchewan	OEL TWA (mg/m³)	10 mg/m³
Yukon	OEL STEL (mg/m³)	20 mg/m ³
10/08/2018	FN (English LIS)	۵/11

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

	· · ·	20 manuf
Yukon	OEL TWA (mg/m³)	30 mppcf
		10 mg/m ³
Calcium oxide (1305-78-8)		
USA ACGIH	ACGIH TWA (mg/m ³)	2 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	2 mg/m ³
USA IDLH	US IDLH (mg/m ³)	25 mg/m ³
Alberta	OEL TWA (mg/m³)	2 mg/m³
British Columbia	OEL TWA (mg/m³)	2 mg/m ³
Manitoba	OEL TWA (mg/m³)	2 mg/m³
New Brunswick	OEL TWA (mg/m³)	2 mg/m ³
Newfoundland & Labrador	OEL TWA (mg/m³)	2 mg/m ³
Nova Scotia	OEL TWA (mg/m³)	2 mg/m ³
Nunavut	OEL STEL (mg/m³)	4 mg/m³
Nunavut	OEL TWA (mg/m³)	2 mg/m ³
Northwest Territories	OEL STEL (mg/m³)	4 mg/m³
Northwest Territories	OEL TWA (mg/m³)	2 mg/m³
Ontario	OEL TWA (mg/m³)	2 mg/m ³
Prince Edward Island	OEL TWA (mg/m³)	2 mg/m ³
Québec	VEMP (mg/m³)	2 mg/m ³
Saskatchewan	OEL STEL (mg/m³)	4 mg/m ³
Saskatchewan	OEL TWA (mg/m³)	2 mg/m ³
Yukon	OEL STEL (mg/m³)	4 mg/m ³
Yukon	OEL TWA (mg/m³)	2 mg/m ³
Cement, portland, chemicals	s (65997-15-1)	
USA ACGIH	ACGIH TWA (mg/m ³)	1 mg/m ³ (particulate matter containing no asbestos and
		<1% crystalline silica, respirable particulate matter)
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA OSHA	OSHA PEL (TWA) (mg/m³)	15 mg/m³ (total dust)
		5 mg/m ³ (respirable fraction)
USA NIOSH	NIOSH REL (TWA) (mg/m³)	10 mg/m ³ (total dust)
		5 mg/m ³ (respirable dust)
USA IDLH	US IDLH (mg/m ³)	5000 mg/m³
Alberta	OEL TWA (mg/m³)	10 mg/m³
British Columbia	OEL TWA (mg/m³)	1 mg/m ³ (particulate matter containing no Asbestos and
		<1% Crystalline silica-respirable particulate)
Manitoba	OEL TWA (mg/m³)	1 mg/m ³ (particulate matter containing no Asbestos and
		<1% Crystalline silica-respirable particulate matter)
New Brunswick	OEL TWA (mg/m³)	10 mg/m ³ (particulate matter containing no Asbestos and
		<1% Crystalline silica)
Newfoundland & Labrador	OEL TWA (mg/m³)	1 mg/m ³ (particulate matter containing no Asbestos and
		<1% Crystalline silica-respirable particulate matter)
Nova Scotia	OEL TWA (mg/m³)	1 mg/m ³ (particulate matter containing no Asbestos and
		<1% Crystalline silica-respirable particulate matter)
Nunavut	OEL STEL (mg/m ³)	20 mg/m ³
Nunavut	OEL TWA (mg/m ³)	10 mg/m ³
Northwest Territories	OEL STEL (mg/m ³)	20 mg/m ³
Northwest Territories	OEL TWA (mg/m ³)	10 mg/m ³
Ontario	OEL TWA (mg/m³)	1 mg/m ³ (containing no Asbestos and <1% Crystalline
		silica-respirable)
Prince Edward Island	OEL TWA (mg/m³)	1 mg/m ³ (particulate matter containing no Asbestos and
		<1% Crystalline silica-respirable particulate matter)

EN (English US)

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Québec	VEMP (mg/m ³)	10 mg/m ³ (containing no Asbestos and <1% Crystalline
		silica-total dust)
		5 mg/m ³ (containing no Asbestos and <1% Crystalline
		silica-respirable dust)
Saskatchewan	OEL STEL (mg/m³)	20 mg/m ³
Saskatchewan	OEL TWA (mg/m³)	10 mg/m ³
Yukon	OEL STEL (mg/m³)	20 mg/m ³
Yukon	OEL TWA (mg/m³)	30 mppcf 10 mg/m ³
Magnesium oxide (MgO) (13	809-48-4)	10 116/11
USA ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³ (inhalable particulate matter)
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (fume, total particulate)
USA IDLH	US IDLH (mg/m ³)	750 mg/m ³ (fume)
Alberta	OEL TWA (mg/m ³)	10 mg/m ³ (fume)
British Columbia	OEL STEL (mg/m ³)	10 mg/m ³ (respirable dust and fume)
British Columbia	OEL TWA (mg/m ³)	10 mg/m ³ (fume, inhalable)
		3 mg/m ³ (respirable dust and fume)
Manitoba	OEL TWA (mg/m³)	10 mg/m ³ (inhalable particulate matter)
New Brunswick	OEL TWA (mg/m ³)	10 mg/m ³ (fume)
Newfoundland & Labrador	OEL TWA (mg/m ³)	10 mg/m ³ (inhalable particulate matter)
Nova Scotia	OEL TWA (mg/m ³)	10 mg/m ³ (inhalable particulate matter)
Nunavut	OEL STEL (mg/m ³)	20 mg/m ³ (inhalable fraction)
Nunavut	OEL TWA (mg/m ³)	10 mg/m ³ (inhalable fraction)
Northwest Territories	OEL STEL (mg/m ³)	20 mg/m ³ (inhalable fraction)
Northwest Territories	OEL TWA (mg/m ³)	10 mg/m ³ (inhalable fraction)
Ontario	OEL TWA (mg/m ³)	10 mg/m ³ (inhalable)
Prince Edward Island	OEL TWA (mg/m ³)	10 mg/m ³ (inhalable particulate matter)
Québec	VEMP (mg/m ³)	10 mg/m ³ (fume)
Saskatchewan	OEL STEL (mg/m ³)	20 mg/m ³ (inhalable fraction)
Saskatchewan	OEL TWA (mg/m ³)	10 mg/m ³ (inhalable fraction)
Yukon	OEL STEL (mg/m ³)	10 mg/m ³ (fume)
Yukon	OEL TWA (mg/m ³)	10 mg/m ³ (fume)
Calcium sulfate hemihydrate		
	ACGIH TWA (mg/m ³)	10 mg/m ³ (inhalable particulate matter)
USA OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (total dust)
		5 mg/m ³ (respirable fraction)
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	10 mg/m ³ (total dust)
		5 mg/m ³ (respirable dust)
Alberta	OEL TWA (mg/m³)	10 mg/m ³
British Columbia	OEL STEL (mg/m ³)	20 mg/m ³ (total dust)
British Columbia	OEL TWA (mg/m ³)	10 mg/m ³ (total dust)
		3 mg/m ³ (respirable fraction)
Manitoba	OEL TWA (mg/m³)	10 mg/m ³ (inhalable particulate matter)
Newfoundland & Labrador	OEL TWA (mg/m ³)	10 mg/m ³ (inhalable particulate matter)
Nova Scotia	OEL TWA (mg/m ³)	10 mg/m ³ (inhalable particulate matter)
Ontario	OEL TWA (mg/m ³)	10 mg/m ³ (inhalable)
Prince Edward Island	OEL TWA (mg/m ³)	10 mg/m ³ (inhalable particulate matter)
Québec	VEMP (mg/m ³)	10 mg/m ³ (containing no Asbestos and <1% Crystalline
• • • •		silica-total dust)
		5 mg/m ³ (containing no Asbestos and <1% Crystalline
		silica-respirable dust)

HYDRO BAN[®] Cementitious Water Proofing Membrane

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Saskatchewan	OEL STEL (mg/m ³)	20 mg/m ³		
Saskatchewan	OEL TWA (mg/m³)	10 mg/m³		
Yukon	OEL STEL (mg/m ³)	20 mg/m ³		
Yukon	OEL TWA (mg/m ³)	30 mppcf		
		10 mg/m ³		
Silica, crystalline (general form)				
USA OSHA	OSHA PEL (TWA) (mg/m³)	50 μg/m ³ (excludes construction work, agricultural operations, and exposures that result from the processing of sorptive clays)		

8.2. Exposure Controls

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. In accordance with the National Materials Advisory Board (NMAB) 353-3-80, Classification of Combustible Dusts in Accordance with the National Electrical Code, this material is not an appreciable explosion hazard requiring electrical equipment suitable for Class II locations.

Personal Protective Equipment: Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.



Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear protective gloves.

Eye and Face Protection: Chemical safety goggles.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

Other Information: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and	Chemical Properties
Physical State	: Solid
Appearance	: White
Odor	: Not available
Odor Threshold	: Not available
рН	: Not available
Evaporation Rate	: Not available
Melting Point	: Not available
Freezing Point	: Not available
Boiling Point	: Not available
Flash Point	: Not available
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not available
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: Not available
Relative Vapor Density at 20°C	: Not available
Relative Density	: Not available
Specific Gravity	: Not available
Solubility	: Insoluble
Partition Coefficient: N-Octanol/Water	: Not available
Viscosity	: Not available
Explosive Properties	: Product is not explosive

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Ignition sensitivity	:	0.01
Explosive sensitivity	:	0.04
SECTION 10: STABILITY AND REACTIVITY		

10.1. Reactivity: Hazardous reactions will not occur under normal conditions.

10.2. Chemical Stability: Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

10.4. Conditions to Avoid: Direct sunlight, extremely high or low temperatures, and incompatible materials.

10.5. Incompatible Materials: Strong acids, strong bases, strong oxidizers.

10.6. Hazardous Decomposition Products: None expected under normal conditions of use.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on Toxicological Effects - Product

Acute Toxicity (Oral): Not classified

Acute Toxicity (Dermal): Not classified

Acute Toxicity (Inhalation): Not classified

LD50 and LC50 Data: Not available

Skin Corrosion/Irritation: Causes skin irritation.

Eye Damage/Irritation: Causes serious eye damage.

Respiratory or Skin Sensitization: May cause an allergic skin reaction.

Germ Cell Mutagenicity: Not classified

Carcinogenicity: May cause cancer.

Specific Target Organ Toxicity (Repeated Exposure): Causes damage to organs through prolonged or repeated exposure.

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): May cause respiratory irritation.

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: Dust may be harmful or cause irritation. Irritation of the respiratory tract and the other mucous membranes.

Symptoms/Injuries After Skin Contact: May cause an allergic skin reaction. Redness, pain, swelling, itching, burning, dryness, and dermatitis.

Symptoms/Injuries After Eye Contact: Causes permanent damage to the cornea, iris, or conjunctiva.

Symptoms/Injuries After Ingestion: Ingestion may cause adverse effects.

Chronic Symptoms: May cause cancer by inhalation. Causes damage to organs through prolonged or repeated exposure (inhalation). Repeated exposure to respirable (airborne) crystalline silica dust will cause lung damage in the form of silicosis.

11.2. Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Quartz (14808-60-7)	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rat	> 5000 mg/kg
Calcium oxide (1305-78-8)	
LD50 Oral Rat	> 2000 mg/kg
LD50 Dermal Rabbit	> 2500 mg/kg
Magnesium oxide (MgO) (1309-48-4)	
LD50 Oral Rat	3870 mg/kg
Quartz (14808-60-7)	
IARC Group	1
National Toxicology Program (NTP) Status	Known Human Carcinogens.
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.
Silica, crystalline (general form)	
IARC Group	1
National Toxicology Program (NTP) Status	Known Human Carcinogens.
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.
OSHA Specifically Regulated Carcinogen List	In OSHA Specifically Regulated Carcinogen list.

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

According To	Federal Register / Vol. 77, No. 58 / Monday, I	March 26, 2012 / Rules A	And Regula	tions And According To The Hazardous Products Regulation (February 11, 2015).
SECTIO	N 12: ECOLOGICAL INFORM	MATION		
12.1.	Toxicity			
Ecology	- General: Not classified.			
Calcium	oxide (1305-78-8)			
LC50 Fis	sh 1	50.6 mg/l		
12.2.	Persistence and Degradabi	lity		
LATICRE	TE [®] Cementitious Water Proof	ing Membrane		
Persiste	ence and Degradability	Not establishe	ed.	
12.3.	Bioaccumulative Potential			
HYDRO	BAN [®] Cementitious Water Proc	ofing Membrane		
Bioaccu	mulative Potential	Not establishe	ed.	
Calcium	oxide (1305-78-8)			
BCF Fish	11	(no bioaccum	ulation)	
12.4.	Mobility in Soil Not a	available		
12.5.	Other Adverse Effects			
Other Ir	nformation: Avoid release to the	e environment.		
SECTIO	N 13: DISPOSAL CONSIDER	ATIONS		
13.1.	Waste treatment methods			
Waste D	Disposal Recommendations: Dis	pose of contents	/contai	ner in accordance with local, regional, national, territorial, provincial,
and inte	ernational regulations.			
				empty. Continue to observe all precautions.
	- Waste Materials: Avoid release		ment.	
	N 14: TRANSPORT INFORM			
-				rdance with certain assumptions at the time the SDS was authored,
	•	-	-	ot have been known at the time the SDS was issued.
14.1.	In Accordance with DOT	Not regulated for		·
14.2.	In Accordance with IMDG	Not regulated for		
14.3.	In Accordance with IATA	Not regulated for		-
14.4.	In Accordance with TDG	Not regulated for	or trans	port
SECTIO	N 15: REGULATORY INFOR	MATION		
15.1.	US Federal Regulations			
	BAN® Cementitious Water Proc	ofing Membrane		
SARA Se	ection 311/312 Hazard Classes			hazard - Skin corrosion or Irritation
				hazard - Serious eye damage or eye irritation
				hazard - Carcinogenicity
			Healtr	hazard - Specific target organ toxicity (single or repeated exposure)
	(14808-60-7)			
	n the United States TSCA (Toxic	Substances Cont	rol Act)	inventory
	one (1317-65-3)			
	n the United States TSCA (Toxic	Substances Cont	rol Act)	inventory
	oxide (1305-78-8)			
	n the United States TSCA (Toxic		rol Act)	inventory
Cement	, portland, chemicals (65997-15	5-1)		
Listed o	n the United States TSCA (Toxic	Substances Cont	rol Act)	inventory
Magnes	ium oxide (MgO) (1309-48-4)			
Listed on the United States TSCA (Toxic Substances Control Act) inventory				
15.2.	US State Regulations			
-	(14808-60-7)			
U.S Ca	alifornia - Proposition 65 - Carci	nogens List		WARNING: This product contains chemicals known to the State of
				California to cause cancer.
10/08/2018	2	EN (English U	5)	9/11

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Silica, crystalline (general form)	
U.S California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the State of
	California to cause cancer.
Quartz (14808-60-7)	
U.S Massachusetts - Right To Know List	
U.S New Jersey - Right to Know Hazardous Substance List	
U.S Pennsylvania - RTK (Right to Know) List	
Limestone (1317-65-3)	
U.S Massachusetts - Right To Know List	
U.S New Jersey - Right to Know Hazardous Substance List	
U.S Pennsylvania - RTK (Right to Know) List	
Calcium oxide (1305-78-8)	
U.S Massachusetts - Right To Know List	
U.S New Jersey - Right to Know Hazardous Substance List	
U.S Pennsylvania - RTK (Right to Know) List	
Cement, portland, chemicals (65997-15-1)	
U.S Massachusetts - Right To Know List	
U.S New Jersey - Right to Know Hazardous Substance List	
U.S Pennsylvania - RTK (Right to Know) List	
Magnesium oxide (MgO) (1309-48-4)	
U.S Massachusetts - Right To Know List	
U.S New Jersey - Right to Know Hazardous Substance List	
U.S Pennsylvania - RTK (Right to Know) List	
Calcium sulfate hemihydrate (13397-24-5)	
U.S New Jersey - Right to Know Hazardous Substance List	
U.S Pennsylvania - RTK (Right to Know) List	
15.3. Canadian Regulations	
Quartz (14808-60-7)	
Listed on the Canadian DSL (Domestic Substances List)	
Limestone (1317-65-3)	
Listed on the Canadian NDSL (Non-Domestic Substances List	t)
Calcium oxide (1305-78-8)	,
Listed on the Canadian DSL (Domestic Substances List)	
Cement, portland, chemicals (65997-15-1)	
Listed on the Canadian DSL (Domestic Substances List)	
Magnesium oxide (MgO) (1309-48-4)	
Listed on the Canadian DSL (Domestic Substances List)	
Calcium sulfate hemihydrate (13397-24-5)	
Listed on the Canadian DSL (Domestic Substances List)	
SECTION 16: OTHER INFORMATION, INCLUDING D	DATE OF PREPARATION OR LAST REVISION
Date of Preparation or Latest Revision : 10/08/2018	
•	has been prepared in accordance with the SDS requirements of the
	ommunication Standard 29 CFR 1910.1200 and Canada's Hazardous
Products Regula	ations (HPR) SOR/2015-17.

GHS Full Text Phrases:

Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Carc. 1A	Carcinogenicity Category 1A
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Skin Irrit. 2	Skin corrosion/irritation Category 2

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Skin Sens. 1	Skin sensitization, Category 1
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H335	May cause respiratory irritation
H350	May cause cancer
H372	Causes damage to organs through prolonged or repeated exposure
H402	Harmful to aquatic life

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

NA GHS SDS 2015 (Can, US)