

HYDRO BARRIER[™] Plus

Safety Data Sheet According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Date of Issue: 03/15/2021

Version: 1

SECTION 1: IDENTIFICATION

1.1. **Product Identifier**

Product Form: Mixture Product Name: HYDRO BARRIER™ Plus

Intended Use of the Product 1.2.

Waterproofing Membrane.

Name, Address, and Telephone of the Responsible Party 1.3.

Company

LATICRETE International 1 Laticrete Park, N Bethany, CT 06524 T (203)-393-0010

Company LATICRETE Canada ULC PO Box 129, Emeryville, Ontario, Canada NOR-1A0 (833)-254-9255

www.laticrete.com

1.4. **Emergency Telephone Number**

Emergency Number	: For Chemical Emergency Call ChemTel day or night		
	Within USA and Canada: 1.800.255.3924		
	Mexico: 1.800.099.0731		
	Outside USA and Canada: 1.813.248.0585 (collect calls accepted)		

SECTION 2: HAZARDS IDENTIFICATION

2.1. **Classification of the Substance or Mixture**

GHS-US/CA Classification			
Skin Sens. 1A	H317		
Aquatic Acute 3	H402		
Aquatic Chronic 3	H412		

Full text of hazard classes and H-statements : see section 16

Label Elements 2.2.

GHS-US/CA Labeling

Hazard Pictograms (GHS-US/CA)

GHS07

:

Signal Word (GHS-US/CA)	: Warning
Hazard Statements (GHS-US/CA)	: H317 - May cause an allergic skin reaction.
	H402 - Harmful to aquatic life.
	H412 - Harmful to aquatic life with long lasting effects.
Precautionary Statements (GHS-US/CA)	: P261 - Avoid breathing spray, mist, vapors.
	P272 - Contaminated work clothing should not be allowed out of the workplace.
	P273 - Avoid release to the environment.
	P280 - Wear protective gloves, protective clothing, and eye protection.
	P302+P352 - IF ON SKIN: Wash with plenty of water.
	P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
	P362+P364 - Take off contaminated clothing and wash it before reuse.
	P501 - Dispose of contents/container in accordance with local, regional, national,
	territorial, provincial, and international regulations.

2.3. **Other Hazards**

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

Unknown Acute Toxicity (GHS-US/CA) 2.4.

No data available

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

3.2. Mixture

Name	Product Identifier	% *	GHS Ingredient Classification
Limestone	(CAS-No.) 1317-65-3	15 - 40	Not classified
Titanium dioxide	(CAS-No.) 13463-67-7	0.5 - 1.5	Not classified
Zinc oxide (ZnO)	(CAS-No.) 1314-13-2	0.61 - 0.63	Aquatic Acute 1, H400
			Aquatic Chronic 1, H410
Ethylene glycol	(CAS-No.) 107-21-1	0.1 - 1	Acute Tox. 4 (Oral), H302
			STOT RE 2, H373
Potassium hydroxide	(CAS-No.) 1310-58-3	0.1 - 1	Met. Corr. 1, H290
			Acute Tox. 3 (Oral), H301
			Skin Corr. 1, H314
			Eye Dam. 1, H318
			STOT SE 1, H370
Quartz	(CAS-No.) 14808-60-7	>= 0.04	Carc. 1A, H350
			STOT SE 3, H335
			STOT RE 1, H372
3(2H)-Isothiazolone, 2-methyl-	(CAS-No.) 2682-20-4	0.001 - 0.011	Acute Tox. 3 (Oral), H301
			Acute Tox. 3 (Dermal), H311
			Acute Tox. 2 (Inhalation:dust,mist), H330
			Skin Corr. 1B, H314
			Eye Dam. 1, H318
			Skin Sens. 1A, H317
			STOT SE 3, H335
			Aquatic Acute 1, H400
Octamethylcyclotetrasiloxane	(CAS-No.) 556-67-2	0.0008 -	Flam. Liq. 3, H226
		0.0009	Acute Tox. 4 (Oral), H302
			Repr. 2, H361
			Aquatic Chronic 4, H413

Full text of H-phrases: see section 16

*Percentages are listed in weight by weight percentage (w/w%) for liquid and solid ingredients. Gas ingredients are listed in volume by volume percentage (v/v%).

** The actual concentration of ingredient(s) is withheld as a trade secret in accordance with the Hazardous Products Regulations (HPR) SOR/2015-17 and 29 CFR 1910.1200.

SECTION 4: FIRST AID MEASURES

4.1. Description of First-aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Inhalation: When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Obtain medical attention if irritation/rash develops or persists.

Eye Contact: Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with water for at least 15 minutes. Obtain medical attention.

Ingestion: Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

General: Skin sensitization.

Inhalation: Prolonged exposure may cause irritation.

Skin Contact: May cause an allergic skin reaction.

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Eye Contact: May cause slight irritation to eyes.

Ingestion: Acute exposure of humans to ethylene glycol by ingesting large quantities causes three stages of health effects. CNS depression, including such symptoms as vomiting, drowsiness, coma, respiratory failure, convulsions, metabolic changes, and gastrointestinal upset are followed by cardiopulmonary effects and later renal damage.

Chronic Symptoms: None known.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Water spray, fog, carbon dioxide (CO₂), alcohol-resistant foam, or dry chemical. **Unsuitable Extinguishing Media:** Do not use a heavy water stream. Use of heavy stream of water may spread fire.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not considered flammable but may burn at high temperatures. **Explosion Hazard:** Product is not explosive.

Reactivity: Hazardous reactions will not occur under normal conditions.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection. **Hazardous Combustion Products**: Carbon oxides (CO, CO₂). Metal oxides. Sulfur oxides.

Other Information: Do not allow run-off from fire fighting to enter drains or water courses.

5.4. Reference to Other Sections

Refer to Section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Avoid breathing (vapor, mist, spray). Do not get in eyes, on skin, or on clothing.

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protective equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area.

6.2. Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

6.3. Methods and Materials for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Precautions for Safe Handling: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid prolonged contact with eyes, skin and clothing. Avoid breathing vapors, mist, spray.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Incompatible Materials: Strong acids, strong bases, strong oxidizers. Aluminum.

7.3. Specific End Use(s)

Waterproofing Membrane.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), or Canadian provincial governments.

Quartz (14808-60-7)				
USA ACGIH	ACGIH TWA (mg/m ³)	0.025 mg/m ³ (respirable particulate matter)		
USA ACGIH	ACGIH chemical category	A2 - Suspected Human Carcinogen		
USA OSHA	OSHA PEL (TWA) (mg/m³)	50 μg/m ³ (Respirable crystalline silica)		
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	0.05 mg/m ³ (respirable dust)		
USA IDLH	US IDLH (mg/m ³)	50 mg/m ³ (respirable dust)		
Alberta	OEL TWA (mg/m³)	0.025 mg/m ³ (respirable particulate)		
British Columbia	OEL TWA (mg/m³)	0.025 mg/m ³ (respirable)		
Manitoba	OEL TWA (mg/m³)	0.025 mg/m ³ (respirable particulate matter)		
New Brunswick	OEL TWA (mg/m³)	0.1 mg/m ³ (respirable fraction)		
Newfoundland & Labrador	OEL TWA (mg/m³)	0.025 mg/m ³ (respirable particulate matter)		
Nova Scotia	OEL TWA (mg/m³)	0.025 mg/m ³ (respirable particulate matter)		
Nunavut	OEL TWA (mg/m³)	0.05 mg/m ³ (respirable fraction (Silica - crystalline)		
Northwest Territories	OEL TWA (mg/m³)	0.05 mg/m ³ (respirable fraction (Silica - crystalline)		
Ontario	OEL TWA (mg/m³)	0.1 mg/m ³ (designated substances regulation-respirable		
		(Silica, crystalline)		
Prince Edward Island	OEL TWA (mg/m³)	0.025 mg/m ³ (respirable particulate matter)		
Québec	VEMP (mg/m ³)	0.1 mg/m ³ (respirable dust)		
Saskatchewan	OEL TWA (mg/m³)	0.05 mg/m ³ (respirable fraction (Silica - crystalline		
		(Trydimite removed))		
Yukon	OEL TWA (mg/m³)	300 particle/mL (Silica - Quartz, crystalline)		
Limestone (1317-65-3)				
USA OSHA	OSHA PEL (TWA) (mg/m³)	15 mg/m ³ (total dust)		
		5 mg/m ³ (respirable fraction)		
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	10 mg/m ³ (total dust)		
		5 mg/m ³ (respirable dust)		
Alberta	OEL TWA (mg/m³)	10 mg/m ³		
British Columbia	OEL STEL (mg/m ³)	20 mg/m ³ (total)		
British Columbia	OEL TWA (mg/m³)	10 mg/m ³ (total dust)		
		3 mg/m ³ (respirable fraction)		
New Brunswick	OEL TWA (mg/m³)	10 mg/m ³ (particulate matter containing no Asbestos and		
		<1% Crystalline silica)		
Nunavut	OEL STEL (mg/m ³)	20 mg/m ³		
Nunavut	OEL TWA (mg/m ³)	10 mg/m ³		
Northwest Territories	OEL STEL (mg/m ³)	20 mg/m ³		
Northwest Territories	OEL TWA (mg/m³)	10 mg/m ³		
Québec	VEMP (mg/m ³)	10 mg/m ³ (Limestone, containing no Asbestos and <1% Crystalline silica-total dust)		
Saskatchewan	OEL STEL (mg/m³)	20 mg/m ³		
Saskatchewan	OEL TWA (mg/m ³)	10 mg/m ³		
Yukon	OEL STEL (mg/m ³)	20 mg/m ³		
Yukon	OEL TWA (mg/m ³)	30 mppcf		
		10 mg/m ³		
		±v m8/ m		

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Zinc oxide (ZnO) (1314-13-2)	
	ACGIH TWA (mg/m ³)	2 mg/m ³ (respirable particulate matter)
USA ACGIH	ACGIH STEL (mg/m ³)	10 mg/m ³ (respirable particulate matter)
USA OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³ (fume)
		15 mg/m ³ (total dust)
		5 mg/m ³ (respirable fraction)
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	5 mg/m ³ (dust and fume)
USA NIOSH	NIOSH REL (STEL) (mg/m ³)	10 mg/m ³ (fume)
USA NIOSH	NIOSH REL (ceiling) (mg/m ³)	15 mg/m ³ (dust)
USA IDLH	US IDLH (mg/m ³)	500 mg/m ³
Alberta	OEL STEL (mg/m ³)	10 mg/m ³ (respirable)
Alberta	OEL TWA (mg/m ³)	2 mg/m ³ (respirable)
British Columbia	OEL STEL (mg/m ³)	10 mg/m ³ (respirable)
British Columbia	OEL TWA (mg/m ³)	2 mg/m ³ (respirable)
Manitoba	OEL STEL (mg/m ³)	10 mg/m ³ (respirable particulate matter)
Manitoba	OEL TWA (mg/m ³)	2 mg/m ³ (respirable particulate matter)
New Brunswick	OEL STEL (mg/m ³)	10 mg/m ³ (fume)
New Brunswick	OEL TWA (mg/m ³)	10 mg/m ³ (particulate matter containing no Asbestos and
		<1% Crystalline silica, dust)
		5 mg/m³ (fume)
Newfoundland & Labrador	OEL STEL (mg/m ³)	10 mg/m ³ (respirable particulate matter)
Newfoundland & Labrador	OEL TWA (mg/m³)	2 mg/m ³ (respirable particulate matter)
Nova Scotia	OEL STEL (mg/m ³)	10 mg/m ³ (respirable particulate matter)
Nova Scotia	OEL TWA (mg/m³)	2 mg/m ³ (respirable particulate matter)
Nunavut	OEL STEL (mg/m ³)	10 mg/m ³ (dust and fume; respirable fraction)
Nunavut	OEL TWA (mg/m³)	2 mg/m ³ (dust and fume; respirable fraction)
Northwest Territories	OEL STEL (mg/m ³)	10 mg/m ³ (dust and fume; respirable fraction)
Northwest Territories	OEL TWA (mg/m³)	2 mg/m ³ (dust and fume; respirable fraction)
Ontario	OEL STEL (mg/m ³)	10 mg/m ³ (respirable)
Ontario	OEL TWA (mg/m³)	2 mg/m ³ (respirable)
Prince Edward Island	OEL STEL (mg/m³)	10 mg/m ³ (respirable particulate matter)
Prince Edward Island	OEL TWA (mg/m³)	2 mg/m ³ (respirable particulate matter)
Québec	VECD (mg/m ³)	10 mg/m³ (fume)
Québec	VEMP (mg/m ³)	10 mg/m ³ (containing no Asbestos and <1% Crystalline
		silica-total dust)
		5 mg/m ³ (fume)
Saskatchewan	OEL STEL (mg/m ³)	10 mg/m ³ (dust and fume, respirable fraction)
Saskatchewan	OEL TWA (mg/m³)	2 mg/m ³ (dust and fume, respirable fraction)
Yukon	OEL STEL (mg/m ³)	10 mg/m ³ (fume)
Yukon	OEL TWA (mg/m³)	5 mg/m³ (fume)
		30 mppcf (dust)
		10 mg/m ³ (dust)
Titanium dioxide (13463-67	-7)	
USA ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA OSHA	OSHA PEL (TWA) (mg/m³)	15 mg/m ³ (total dust)
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	2.4 mg/m ³ (CIB 63-fine)
		0.3 mg/m ³ (CIB 63-ultrafine, including engineered
		nanoscale)
USA IDLH	US IDLH (mg/m ³)	5000 mg/m ³
Alberta	OEL TWA (mg/m³)	10 mg/m ³

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

	S/ Monday, March 26, 2012 / Rules And Regulations And Act			
British Columbia	OEL TWA (mg/m³)	10 mg/m ³ (total dust)		
Manitoha	O[1,T]	3 mg/m ³ (respirable fraction)		
Manitoba New Brunewick	OEL TWA (mg/m ³)	10 mg/m ³		
New Brunswick	OEL TWA (mg/m ³)	10 mg/m ³		
Newfoundland & Labrador	OEL TWA (mg/m ³)	10 mg/m ³		
Nova Scotia	OEL TWA (mg/m ³)	10 mg/m ³		
Nunavut	OEL STEL (mg/m ³)	20 mg/m ³		
Nunavut	OEL TWA (mg/m ³)	10 mg/m ³		
Northwest Territories	OEL STEL (mg/m ³)	20 mg/m ³		
Northwest Territories	OEL TWA (mg/m ³)	10 mg/m ³		
Ontario	OEL TWA (mg/m ³)	10 mg/m ³		
Prince Edward Island	OEL TWA (mg/m ³)	10 mg/m ³		
Québec	VEMP (mg/m ³)	10 mg/m ³ (containing no Asbestos and <1% Crystalline		
		silica-total dust)		
Saskatchewan	OEL STEL (mg/m ³)	20 mg/m ³		
Saskatchewan	OEL TWA (mg/m ³)	10 mg/m ³		
Yukon	OEL STEL (mg/m ³)	20 mg/m ³		
Yukon	OEL TWA (mg/m³)	30 mppcf		
		10 mg/m ³		
Ethylene glycol (107-21-1)				
USA ACGIH	ACGIH TWA (ppm)	25 ppm (vapor fraction)		
USA ACGIH	ACGIH STEL (mg/m ³)	10 mg/m ³ (inhalable particulate matter, aerosol only)		
USA ACGIH	ACGIH STEL (ppm)	50 ppm (vapor fraction)		
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen		
Alberta	OEL Ceiling (mg/m ³)	100 mg/m ³		
British Columbia	OEL Ceiling (mg/m ³)	100 mg/m ³ (aerosol)		
British Columbia	OEL Ceiling (ppm)	50 ppm (vapour)		
British Columbia	OEL STEL (mg/m ³)	20 mg/m ³ (particulate)		
British Columbia	OEL TWA (mg/m³)	10 mg/m ³ (particulate)		
Manitoba	OEL STEL (mg/m ³)	10 mg/m ³ (inhalable particulate matter, aerosol only)		
Manitoba	OEL STEL (ppm)	50 ppm (vapor fraction)		
Manitoba	OEL TWA (ppm)	25 ppm (vapor fraction)		
New Brunswick	OEL Ceiling (mg/m ³)	100 mg/m ³ (aerosol)		
Newfoundland & Labrador	OEL STEL (mg/m ³)	10 mg/m ³ (inhalable particulate matter, aerosol only)		
Newfoundland & Labrador	OEL STEL (ppm)	50 ppm (vapor fraction)		
Newfoundland & Labrador	OEL TWA (ppm)	25 ppm (vapor fraction)		
Nova Scotia	OEL STEL (mg/m ³)	10 mg/m ³ (inhalable particulate matter, aerosol only)		
Nova Scotia	OEL STEL (ppm)	50 ppm (vapor fraction)		
Nova Scotia	OEL TWA (ppm)	25 ppm (vapor fraction)		
Nunavut	OEL Ceiling (mg/m ³)	100 mg/m ³ (aerosol)		
Northwest Territories	OEL Ceiling (mg/m ³)	100 mg/m ³ (aerosol)		
Ontario	OEL Ceiling (mg/m ³)	100 mg/m ³ (aerosol only)		
Prince Edward Island	OEL STEL (mg/m ³)	10 mg/m ³ (inhalable particulate matter, aerosol only)		
Prince Edward Island	OEL STEL (ppm)	50 ppm (vapor fraction)		
Prince Edward Island	OELTWA (ppm)	25 ppm (vapor fraction)		
Québec	PLAFOND (mg/m ³)	127 mg/m ³ (mist and vapour)		
Québec	PLAFOND (ppm)	50 ppm (mist and vapour)		
Saskatchewan	OEL Ceiling (mg/m ³)	100 mg/m ³ (aerosol)		
Yukon	OEL STEL (mg/m ³)	20 mg/m ³ (particulate)		
-		325 mg/m ³ (vapour)		
Yukon	OEL STEL (ppm)	10 ppm (particulate)		
	- wr 7	125 ppm (vapour)		
L				

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Yukon	OEL TWA (mg/m³)	10 mg/m ³ (particulate)
		250 mg/m ³ (vapour)
Yukon	OEL TWA (ppm)	100 ppm (vapour)
Octamethylcyclotetrasiloxar	ne (556-67-2)	
USA AIHA	WEEL TWA (ppm)	10 ppm
Potassium hydroxide (1310-	58-3)	
USA ACGIH	ACGIH Ceiling (mg/m ³)	2 mg/m ³
USA NIOSH	NIOSH REL (ceiling) (mg/m ³)	2 mg/m ³
Alberta	OEL Ceiling (mg/m ³)	2 mg/m ³
British Columbia	OEL Ceiling (mg/m ³)	2 mg/m ³
Manitoba	OEL Ceiling (mg/m ³)	2 mg/m ³
New Brunswick	OEL Ceiling (mg/m ³)	2 mg/m ³
Newfoundland & Labrador	OEL Ceiling (mg/m ³)	2 mg/m ³
Nova Scotia	OEL Ceiling (mg/m ³)	2 mg/m ³
Nunavut	OEL Ceiling (mg/m ³)	2 mg/m ³
Northwest Territories	OEL Ceiling (mg/m ³)	2 mg/m ³
Ontario	OEL Ceiling (mg/m ³)	2 mg/m ³
Prince Edward Island	OEL Ceiling (mg/m ³)	2 mg/m ³
Québec	PLAFOND (mg/m³)	2 mg/m ³
Saskatchewan	OEL Ceiling (mg/m ³)	2 mg/m ³
Yukon	OEL Ceiling (mg/m ³)	2 mg/m ³

8.2. Exposure Controls

Appropriate Engineering Controls: Suitable eye/body wash equipment should be available in the vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed.

Personal Protective Equipment: Gloves. Protective clothing. Protective goggles.



Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear protective gloves.

Eye and Face Protection: Chemical safety goggles.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

Other Information: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State	:	Liquid
Appearance	:	Blue Liquid
Odor	:	Styrene Butadiene rubber
Odor Threshold	:	Not available
рН	:	8.0 - 9.0
Evaporation Rate	:	Not available
Melting Point	:	0 °C (32 °F)
Freezing Point	:	Not available
Boiling Point	:	100 °C (212 °F)
Flash Point	:	Not available
Auto-ignition Temperature	:	Not available

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Decomposition Temperature	:	Not available
Flammability (solid, gas)	:	Not applicable
Lower Flammable Limit	:	Not available
Upper Flammable Limit	:	Not available
Vapor Pressure	:	Not available
Relative Vapor Density at 20°C	:	Not available
Relative Density	:	Not available
Specific Gravity	:	1.34
Solubility	:	Water: Soluble
Partition Coefficient: N-Octanol/Water	:	Not available
Viscosity	:	Not available

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity: Hazardous reactions will not occur under normal conditions.

10.2. Chemical Stability: Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

- **10.4.** Conditions to Avoid: Direct sunlight, extremely high or low temperatures, and incompatible materials.
- 10.5. Incompatible Materials: Strong acids, strong bases, strong oxidizers. Aluminum.
- 10.6. Hazardous Decomposition Products: Thermal decomposition generates: Irritating fumes.

SECTION 11: TOXICOLOGICAL INFORMATION

Acute Toxicity (Oral): Not classified Acute Toxicity (Dermal): Not classified

Acute Toxicity (Inhalation): Not classified

LD50 and LC50 Data: Not available

Skin Corrosion/Irritation: Not classified

pH: 8.0 - 9.0

Eye Damage/Irritation: Not classified

pH: 8.0 - 9.0

Respiratory or Skin Sensitization: May cause an allergic skin reaction.

Germ Cell Mutagenicity: Not classified

Carcinogenicity: Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: Prolonged exposure may cause irritation.

Symptoms/Injuries After Skin Contact: May cause an allergic skin reaction.

Symptoms/Injuries After Eye Contact: May cause slight irritation to eyes.

Symptoms/Injuries After Ingestion: Acute exposure of humans to ethylene glycol by ingesting large quantities causes three stages of health effects. CNS depression, including such symptoms as vomiting, drowsiness, coma, respiratory failure, convulsions, metabolic changes, and gastrointestinal upset are followed by cardiopulmonary effects and later renal damage. **Chronic Symptoms:** None known.

11.2. Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Quartz (14808-60-7)		
LD50 Oral Rat	> 5000 mg/kg	
LD50 Dermal Rat	> 5000 mg/kg	
Zinc oxide (ZnO) (1314-13-2)		
LD50 Oral Rat	> 5000 mg/kg	
LD50 Dermal Rat	> 2000 mg/kg	

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

LD50 Oral Rat	> 10000 mg/kg
Ethylene glycol (107-21-1)	
LD50 Dermal Rat	10600 mg/kg
ATE US/CA (oral)	500.00 mg/kg body weight
Octamethylcyclotetrasiloxane (556-67-2)	
LD50 Oral Rat	1540 mg/kg
LD50 Dermal Rabbit	794 μl/kg
LC50 Inhalation Rat	36 g/m ³ (Exposure time: 4 h)
Potassium hydroxide (1310-58-3)	
LD50 Oral Rat	284 mg/kg
3(2H)-Isothiazolone, 2-methyl- (2682-20-4)	
LD50 Oral Rat	120 mg/kg
LD50 Dermal Rabbit	200 mg/kg
LC50 Inhalation Rat	0.11 mg/l/4h
Quartz (14808-60-7)	
IARC Group	1
National Toxicology Program (NTP) Status	Known Human Carcinogens.
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.
Titanium dioxide (13463-67-7)	
IARC Group	2B
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - General: Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

Zinc oxide (ZnO) (1314-13-2)		
LC50 Fish 1	970 μg/l (780 ug Zn/L; Exposure time: 96 h - Species: Pimephales promelas)	
LC50 Fish 2	1.793 mg/l (Exposure time: 96 h - Species: Zebrafish)	
NOEC Chronic Fish	0.026 mg/l (Species: Jordanella floridae)	
Ethylene glycol (107-21-1)		
LC50 Fish 1	41000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)	
EC50 Daphnia 1	46300 mg/l (Exposure time: 48 h - Species: Daphnia magna)	
LC50 Fish 2	14 - 18 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])	
NOEC Chronic Crustacea	4.2 mg/l	
Octamethylcyclotetrasiloxane (556-67-2)		
LC50 Fish 1	> 500 mg/l (Exposure time: 96 h - Species: Brachydanio rerio)	
LC50 Fish 2	> 1000 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus)	

12.2. Persistence and Degradability

HYDRO BARRIER™ Plus	
Persistence and Degradability May cause long-term adverse effects in the environment.	
12.3. Bioaccumulative Potential	
HYDRO BARRIER™ Plus	

HIDRO BARNIER Plus		
Bioaccumulative Potential	Not established.	
Ethylene glycol (107-21-1)		
Log Pow	-1.93	
Octamethylcyclotetrasiloxane (556-67-2)		
BCF Fish 1	12400	
Log Pow	5.1	
Potassium hydroxide (1310-58-3)		

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Log Pow	0.65
---------	------

12.4. **Mobility in Soil** Not available

12.5. **Other Adverse Effects**

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste Disposal Recommendations: Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

Additional Information: Container may remain hazardous when empty. Continue to observe all precautions.

Ecology - Waste Materials: Avoid release to the environment. This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

- In Accordance with DOT 14.1. Not regulated for transport
- 14.2. In Accordance with IMDG Not regulated for transport
- 14.3. In Accordance with IATA Not regulated for transport
- 14.4. In Accordance with TDG Not regulated for transport

SE(

15

ECTION 15: REGULATORY INFORMATION				
15.1. US Federal Regulations				
HYDRO BARRIER™ Plus				
CARA Section 311/312 Hazard Classes Health hazard - Respiratory or skin sensitization				
Quartz (14808-60-7)				
Listed on the United States TSCA (Toxic Substances Control Act) inventory			
Limestone (1317-65-3)				
Listed on the United States TSCA (Toxic Substances Control Act) inventory			
Zinc oxide (ZnO) (1314-13-2)				
Listed on the United States TSCA (Toxic Substances Control Act) inventory			
Titanium dioxide (13463-67-7)				
Listed on the United States TSCA (Toxic Substances Control Act) inventory			
Ethylene glycol (107-21-1)				
Listed on the United States TSCA (Toxic Substances Control Act				
Subject to reporting requirements of United States SARA Section 313				
CERCLA RQ 5000 lb				
SARA Section 313 - Emission Reporting 1 %				
Octamethylcyclotetrasiloxane (556-67-2)				
Listed on the United States TSCA (Toxic Substances Control Act) inventory				
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a final TSCA			
	section 4 test rule.			
Potassium hydroxide (1310-58-3)				
Listed on the United States TSCA (Toxic Substances Control Act) inventory				
CERCLA RQ 1000 lb				
3(2H)-Isothiazolone, 2-methyl- (2682-20-4)				
Listed on the United States TSCA (Toxic Substances Control Act) inventory			
EPA TSCA Regulatory Flag	PMN - PMN - indicates a commenced PMN substance.			
	SP - SP - indicates a substance that is identified in a proposed			
	Significant New Uses Rule.			

15.2. **US State Regulations**

California Proposition 65

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).



WARNING: This product can expose you to Titanium dioxide, which is known to the State of California to cause cancer, and Ethylene glycol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Chemical Name (CAS No.)	Carcinogenicity	Developmental	Female Reproductive	Male Reproductive
	v	Toxicity	Toxicity	Toxicity
Quartz (14808-60-7)	X X			
Titanium dioxide (13463-67-7)	X	V		
Ethylene glycol (107-21-1)		Х		
Quartz (14808-60-7)	· · · ·			
U.S Massachusetts - Right To Know List				
U.S New Jersey - Right to Know Hazardous Substance List U.S Pennsylvania - RTK (Right to Know) List				
· · · ·	lo Khow) List			
Limestone (1317-65-3)	(
U.S Massachusetts - Right To K		. 1 : . t		
U.S New Jersey - Right to Know		LIST		
U.S Pennsylvania - RTK (Right t				
Zinc oxide (ZnO) (1314-13-2) U.S Massachusetts - Right To K	(now link			
U.S New Jersey - Right to Know		alist		
U.S Pennsylvania - RTK (Right t				
U.S Pennsylvania - RTK (Right t				
Titanium dioxide (13463-67-7)				
U.S Massachusetts - Right To k	(now List			
U.S New Jersey - Right to Know		list		
U.S Pennsylvania - RTK (Right t				
Ethylene glycol (107-21-1)				
U.S Massachusetts - Right To Know List				
U.S New Jersey - Right to Know Hazardous Substance List				
U.S Pennsylvania - RTK (Right to Know) - Environmental Hazard List				
U.S Pennsylvania - RTK (Right t	to Know) List			
Potassium hydroxide (1310-58-3)				
U.S Massachusetts - Right To Know List				
U.S New Jersey - Right to Know Hazardous Substance List				
U.S Pennsylvania - RTK (Right to Know) - Environmental Hazard List				
U.S Pennsylvania - RTK (Right to Know) List				
5.3. Canadian Regulations	5			
Quartz (14808-60-7)				
Listed on the Canadian DSL (Don	nestic Substances List)			
Limestone (1317-65-3)				
Listed on the Canadian NDSL (No	on-Domestic Substance	es List)		
Zinc oxide (ZnO) (1314-13-2)				
Listed on the Canadian DSL (Don	nestic Substances List)			
Titanium dioxide (13463-67-7)	· · · ·			
Listed on the Canadian DSL (Don	nestic Substances List)			
Ethylene glycol (107-21-1)				

Listed on the Canadian DSL (Domestic Substances List)

Octamethylcyclotetrasiloxane (556-67-2) Listed on the Canadian DSL (Domestic Substances List)

Potassium hydroxide (1310-58-3)

Listed on the Canadian DSL (Domestic Substances List)

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

3(2H)-Isothiazolone, 2-methyl- (2682-20-4)

Listed on the Canadian DSL (Domestic Substances List)

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Date of Preparation or Latest Revision **Other Information**

: 03/15/2021

: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200 and Canada's Hazardous Products Regulations (HPR) SOR/2015-17.

GHS Full Text Phrases:

Acute Tox. 2 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 2
Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (definal) category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Aquatic Chronic 4	Hazardous to the aquatic environment - Chronic Hazard Category 4
Carc. 1A	Carcinogenicity Category 1A
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Flam. Liq. 3	Flammable liquids Category 3
Met. Corr. 1	Corrosive to metals Category 1
Repr. 2	Reproductive toxicity Category 2
Skin Corr. 1	Skin corrosion/irritation Category 1
Skin Corr. 1B	Skin corrosion/irritation Category 1B
Skin Sens. 1A	Skin sensitization, category 1A
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 1	Specific target organ toxicity (single exposure) Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H226	Flammable liquid and vapour
H290	May be corrosive to metals
H301	Toxic if swallowed
H302	Harmful if swallowed
H311	Toxic in contact with skin
H314	Causes severe skin burns and eye damage
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H330	Fatal if inhaled
H335	May cause respiratory irritation
H350	May cause cancer
H361	Suspected of damaging fertility or the unborn child
H370	Causes damage to organs
H372	Causes damage to organs through prolonged or repeated exposure
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H402	Harmful to aquatic life

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

H410	Very toxic to aquatic life with long lasting effects	
H412	Harmful to aquatic life with long lasting effects	
H413	May cause long lasting harmful effects to aquatic life	

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

NA GHS SDS 2015 (Can, US)