

SAFETY DATA SHEET

1. Identification

Product identifier LATICRETE 1600 Unsanded Grout

Other means of identification Not available.

Recommended use Grout.

Recommended restrictions None known.

Manufacturer / Importer / Supplier / Distributor information

Company Name

LATICRETE International

1 Laticrete Park, N

Bethany, CT 06524 (203)-393-0010

Telephone (203)-393-0010
Contact person Steve Fine
Website www.laticrete.com

Emergency phone number Call CHEMTREC day or night

USA/Canada - 1.800.424.9300 Mexico - 1.800.681.9531 Outside USA/Canada 1.703.527.3887

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 1
Sensitization, skin Category 1

Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Causes skin irritation. Causes serious eye damage. May cause an allergic skin reaction. May

cause respiratory irritation.

Precautionary statement

Prevention Do not breathe dust/fume. Wash thoroughly after handling. Use only outdoors or in a

well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

Contaminated work clothing must not be allowed out of the workplace.

Response If inhaled: Remove person to fresh air and keep comfortable for breathing. If on skin: Wash with

plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Take off

contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a

poison center/doctor.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

Not classified.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Portland Cement	65997-15-1	28 - 38
Calcium hydroxide	1305-62-0	2 - 3
Magnesium hydroxide	1309-42-8	2 - 2.25

LATICRETE 1600 Unsanded Grout SDS US

Composition comments

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a physician

if symptoms develop or persist.

Skin contact

Wash off with soap and plenty of water. If skin irritation or rash occurs: Get medical

advice/attention. Take off contaminated clothing and wash before reuse.

Eye contact

Do not rub eyes. Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control

center immediately.

Ingestion

Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and

delayed

Rash. Coughing. Irritant effects. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Prolonged exposure may cause chronic effects.

Indication of immediate

medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Symptoms may be delayed.

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

None known

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire-fighting

equipment/instructions

In case of fire and/or explosion do not breathe fumes.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep upwind. Avoid formation of dust. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation.

Methods and materials for containment and cleaning up

Stop the flow of material, if this is without risk. Sweep or shovel up material and place in a clearly labeled container for waste. Collect dust using a vacuum cleaner. Following product recovery, flush area with water.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Minimize dust generation and accumulation. Wear appropriate personal protective equipment. Do not breathe dust. Avoid contact with eyes, skin, and clothing. Provide adequate ventilation. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Keep container tightly closed. Store in a cool, dry place out of direct sunlight.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form
Calcium hydroxide (CAS 1305-62-0)	PEL	5 mg/m3	Respirable fraction.
,		15 mg/m3	Total dust.
Portland Cement (CAS 65997-15-1)	PEL	5 mg/m3	Respirable fraction.
,		15 mg/m3	Total dust.
US. OSHA Table Z-3 (29 CFR 19	10.1000)		
Components	Туре	Value	
Portland Cement (CAS 65997-15-1)	TWA	50 millions of particle	

917334 Version #: 01 Revision date: - Issue date: 05-December-2013

SDS US

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Calcium hydroxide (CAS 1305-62-0)	TWA	5 mg/m3	
Portland Cement (CAS 65997-15-1)	TWA	1 mg/m3	Respirable fraction.

US NIOSH Pocket Guide to Chemical Hazards: Recommended exposure limit (REL)

Components	Туре	Value	Form
Calcium hydroxide (CAS 1305-62-0)	TWA	5 mg/m3	
Portland Cement (CAS 65997-15-1)	TWA	5 mg/m3	Respirable.
,		10 mg/m3	Total

Biological limit values No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear chemical-resistant, impervious gloves. Other Wear appropriate chemical resistant clothing.

Respiratory protection Wear a dust mask if dust is generated above exposure limits. Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state Solid. **Form** Powder. Color Colored. Odor Not available. Odor threshold Not available. Not available. pН Melting point/freezing point Not available. Not available. Initial boiling point and boiling

range

Flash point Not flammable or combustible.

Evaporation rate Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%) Not available. Not available. Explosive limit - upper (%)

Not available. Vapor pressure Vapor density Not available. Not available. Relative density Solubility(ies) Insoluble

917334 Version #: 01 Revision date: - Issue date: 05-December-2013

LATICRETE 1600 Unsanded Grout SDS US **Partition coefficient** (n-octanol/water)

Not available.

Not available. **Auto-ignition temperature** Not available. **Decomposition temperature** Not available. **Viscosity**

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Ingestion Swallowing may cause gastrointestinal irritation.

Inhalation Dust irritates the respiratory system, and may cause coughing and difficulties in breathing.

Skin contact Causes skin irritation. May cause an allergic skin reaction. Prolonged contact with wet

cement/mixture may cause burns.

Eye contact Causes serious eye damage. Prolonged contact with wet cement/mixture may cause burns.

Symptoms related to the physical, chemical and toxicological characteristics Rash. Coughing. Irritant effects. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Prolonged exposure may

cause chronic effects.

Information on toxicological effects

Acute toxicity May cause respiratory irritation.

Components Species **Test Results**

Calcium hydroxide (CAS 1305-62-0)

Acute Oral

LD50 Rat 7340 mg/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Causes serious eye damage.

Respiratory sensitization No data available.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Not classified.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

May cause respiratory irritation.

Specific target organ toxicity -

repeated exposure

Not classified

Aspiration hazard Due to the physical form of the product it is not an aspiration hazard.

Chronic effects Frequent inhalation of dust over a long period of time increases the risk of developing lung

diseases.

Further information No other specific acute or chronic health impact noted.

12. Ecological information

Ecotoxicity Not expected to be harmful to aquatic organisms.

Components **Species Test Results**

Calcium hydroxide (CAS 1305-62-0)

Aquatic

LATICRETE 1600 Unsanded Grout

Fish LC50 Zambezi barbel (Clarias gariepinus) 33.8844 mg/l, 96 hours

4/6

SDS US

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available for this product. Mobility in soil The product is not mobile in soil.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Dispose of contents/container in accordance with local/regional/national/international regulations.

Do not contaminate ponds, waterways or ditches with chemical or used container.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

Not regulated as a hazardous material by DOT.

IATA

Not regulated as a dangerous good.

IMDG

Not regulated as a dangerous good.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

This substance/mixture is not intended to be transported in bulk.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely

hazardous substance

SARA 311/312 Hazardous

Yes

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

(SDWA)

Not regulated.

Food and Drug

LATICRETE 1600 Unsanded Grout

Not regulated.

Administration (FDA)

US state regulations California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

US. Massachusetts RTK - Substance List

Calcium hydroxide (CAS 1305-62-0) Portland Cement (CAS 65997-15-1)

US. New Jersey Worker and Community Right-to-Know Act

Not regulated.

US. Pennsylvania RTK - Hazardous Substances

Calcium hydroxide (CAS 1305-62-0) Portland Cement (CAS 65997-15-1)

US. Rhode Island RTK

Not regulated.

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Not listed.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No

^{*}A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

Toxic Substances Control Act (TSCA) Inventory

16. Other information, including date of preparation or last revision

Issue date 05-December-2013

Revision date - 01

United States & Puerto Rico

NFPA Ratings



References HSDB® - Hazardous Substances Data Bank

Registry of Toxic Effects of Chemical Substances (RTECS)

Disclaimer The information in this (M)SDS was obtained from sources which we believe are reliable but

cannot guarantee. Additionally, your use of this information is beyond our control and may be beyond our knowledge. Therefore, the information is provided without any representation or

warranty express or implied.

LATICRETE 1600 Unsanded Grout SDS US

Yes

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).