

SAFETY DATA SHEET

1. Identification

Product identifier	LATICRETE® 253 Gold Rapid
Other means of identification	None.
Recommended use	Tile adhesive.
Recommended restrictions	Workers (and your customers or users in the case of resale) should be informed of the potential presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required under applicable regulations.
Manufacturer/Importer/Supplier/	Distributor information
Company Name	LATICRETE International
Address	1 Laticrete Park, N
	Bethany, CT 06524
Telephone	(203)-393-0010
Contact person	Steve Fine
Website	www.laticrete.com
Emergency phone number	Call CHEMTREC day or night
	USA/Canada - 1.800.424.9300
	Mexico - 1.800.681.9531
	Outside USA/Canada
	1.703.527.3887

2. Hazard(s) identification

Physical hazards	Not classified.	
Health hazards	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 1
	Sensitization, skin	Category 1
	Carcinogenicity	Category 1A
	Reproductive toxicity	Category 1B
	Specific target organ toxicity, single exposure	Category 3 respiratory tract irritation
	Specific target organ toxicity, repeated exposure	Category 2 (lung)
Environmental hazards	Not classified.	

Label elements



Danger

Signal word Hazard statement

Causes skin irritation. Causes serious eye damage. May cause an allergic skin reaction. May cause cancer. May damage fertility or the unborn child. May cause respiratory irritation. May cause damage to organs (lung) through prolonged or repeated exposure.

Precautionary statement Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Contaminated work clothing must not be allowed out of the workplace.

Response	IF exposed or concerned: Get medical advice/attention. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor.
Storage	Store in a well-ventilated place. Keep container tightly closed. Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Other hazards	None known.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name		CAS number	%
Silica Sand		14808-60-7	55 - 60
Portland Cement		65997-15-1	14 - 22
Calcium aluminate cement		65997-16-2	8 - 12
Calcium sulfate		7778-18-9	2 - 5
Lithium Carbonate		554-13-2	0.25 - 0.35
Composition comments	All concentrations are in percent by wei percent by volume.	ight unless ingredient is a gas. Ga	s concentrations are
4. First-aid measures			
Inhalation	Remove victim to fresh air and keep at if symptoms develop or persist.	rest in a position comfortable for b	reathing. Call a phys
Skin contact	Wash off with soap and plenty of water. advice/attention. Take off contaminated		et medical
Eye contact	Do not rub eyes. Immediately flush eye contact lenses, if present and easy to d center immediately.		
ngestion	Rinse mouth. Get medical attention if s	ymptoms occur.	
Most important symptoms/effects, acute and delayed	Rash. Coughing. Irritant effects. Sympto blurred vision. Permanent eye damage cause chronic effects.		
Indication of immediate medical attention and special treatment needed	Provide general supportive measures a	nd treat symptomatically. Sympton	ns may be delayed.
General information	Ensure that medical personnel are awa protect themselves. IF exposed or conc clothing before reuse.		
5. Fire-fighting measures			
Suitable extinguishing media	Water fog. Foam. Dry chemical powder	. Carbon dioxide (CO2).	
Unsuitable extinguishing media	None known.		
Specific hazards arising from the chemical	During fire, gases hazardous to health i	may be formed.	
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and	I full protective clothing must be w	orn in case of fire.
Fire fighting	In case of fire and/or explosion do not b	preathe fumes.	
equipment/instructions			

6. Accidental release measures

Personal precautions,
protective equipment and
emergency proceduresKeep unnecessary personnel away. Keep upwind. Avoid formation of dust. Wear appropriate
protective equipment and clothing during clean-up. Do not touch damaged containers or spilled
material unless wearing appropriate protective clothing. Ensure adequate ventilation.

Methods and materials for	Stop the flow of material, if this is without risk. Sweep or shovel up material and place in a clearly
containment and cleaning up	labeled container for waste. Collect dust using a vacuum cleaner. Following product recovery,
• •	flush area with water.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Minimize dust generation and accumulation. Wear appropriate personal protective equipment. Do not breathe dust. Avoid contact with eyes, skin, and clothing. Provide adequate ventilation. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Keep container tightly closed. Store in a cool, dry place out of direct sunlight.

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Values

Components	Туре	Value	Form
Calcium sulfate (CAS 7778-18-9)	TWA	10 mg/m3	Inhalable fraction.
Portland Cement (CAS 65997-15-1)	TWA	1 mg/m3	Respirable fraction.
Silica Sand (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Туре	Value	Form
Calcium sulfate (CAS 7778-18-9)	TWA	10 mg/m3	
Portland Cement (CAS 65997-15-1)	TWA	10 mg/m3	
Silica Sand (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable particles.

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Туре	Value	Form
Calcium sulfate (CAS 7778-18-9)	TWA	10 mg/m3	Inhalable
Portland Cement (CAS 65997-15-1)	TWA	3 mg/m3	Respirable fraction.
		10 mg/m3	Total dust.
Silica Sand (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Туре	Value	Form
Calcium sulfate (CAS 7778-18-9)	TWA	10 mg/m3	Inhalable fraction.
Portland Cement (CAS 65997-15-1)	TWA	1 mg/m3	Respirable fraction.
Silica Sand (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Туре	Value	Form
Calcium sulfate (CAS 7778-18-9)	TWA	10 mg/m3	Inhalable fraction.
Portland Cement (CAS 65997-15-1)	TWA	1 mg/m3	Respirable fraction.
Silica Sand (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable fraction.

Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)

Components	Туре	Value	Form	
Calcium sulfate (CAS 7778-18-9)	TWA	5 mg/m3	Respirable dust.	
		10 mg/m3	Total dust.	
Portland Cement (CAS 65997-15-1)	TWA	5 mg/m3	Respirable dust.	
		10 mg/m3	Total dust.	
Silica Sand (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable dust.	
Biological limit values	No biological exposure limits noted fo	r the ingredient(s).		
Exposure guidelines	Occupational exposure to nuisance d should be monitored and controlled.	Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled.		
Appropriate engineering controls	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.			
Individual protection measures	s, such as personal protective equipm	ent		
Eye/face protection	Wear safety glasses with side shields	(or goggles).		
Skin protection				
Hand protection	Wear chemical-resistant, impervious	Wear chemical-resistant, impervious gloves.		
Other	Wear appropriate chemical resistant of	clothing.		
Respiratory protection	Wear a dust mask if dust is generated	d above exposure limits.		
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.			
General hygiene considerations	Always observe good personal hygien and before eating, drinking, and/or sn equipment to remove contaminants. (workplace.	noking. Routinely wash work cl	othing and protective	

9. Physical and chemical properties

Appearance	
Physical state	Solid.
Form	Powder.
Color	Gray or off-white.
Odor	Odorless.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Flash point	Not flammable or combustible.
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	1.2 - 1.5
Solubility(ies)	
Solubility (water)	Insoluble

Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
VOC	0 %
10. Stability and reactivity	
Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.

Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition	No hazardous decomposition products are known.

11. Toxicological information

products

Information on likely routes of exposure

Inhalation	Dust irritates the respiratory system, and may cause coughing and difficulties in breathing.
Skin contact	Causes skin irritation. May cause an allergic skin reaction. Prolonged contact with wet cement/mixture may cause burns.
Eye contact	Causes serious eye damage. Prolonged contact with wet cement/mixture may cause burns.
Ingestion	Swallowing may cause gastrointestinal irritation.
Symptoms related to the physical, chemical and toxicological characteristics	Rash. Coughing. Irritant effects. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Prolonged exposure may cause chronic effects.

Information on toxicological effects

Acute toxicity	May cause respiratory irritation.	
Components	Species	Test Results
Calcium sulfate (CAS 7778-18-9))	
<u>Acute</u>		
Inhalation		
LC50	Rat	> 3.26 mg/l, 4 Hours
Oral		
LD50	Rat	> 1581 mg/kg
Lithium Carbonate (CAS 554-13-	2)	
<u>Acute</u>		
Inhalation		
LC50	Rat	> 2.17 mg/l, 4 Hours
Oral		
LD50	Rat	525 mg/kg
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye irritation	Causes serious eye damage.	
Respiratory or skin sensitization	on	
Respiratory sensitization	No data available.	
Skin sensitization	May cause an allergic skin reaction.	
Germ cell mutagenicity	No data available to indicate product or any mutagenic or genotoxic.	components present at greater than 0.1% are

Carcinogenicity	May cause cancer. In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk" (SCOEL SUM Doc 94-final, June 2003)	
ACGIH Carcinogens		
Portland Cement (CAS 65997-15-1) Silica Sand (CAS 14808-60-7) Canada - Alberta OELs: Carcinogen category		A4 Not classifiable as a human carcinogen. A2 Suspected human carcinogen.
Silica Sand (CAS 14808-60-7)		Suspected human carcinogen.
Canada - Manitoba OELs: carcinogenicity		
Portland Cement (CAS 65997-15-1)		Not classifiable as a human carcinogen.
Silica Sand (CAS 14808-60-7)		Suspected human carcinogen.
Canada - Quebec OELs: Carcinogen category		
Silica Sand (CAS 14808-60-7)		Suspected carcinogenic effect in humans.
IARC Monographs. Overall Evaluation of Carcinogenicity		
Silica Sand (CAS 14808-60-7) 1 Carcinogenic to humans. US. National Toxicology Program (NTP) Report on Carcinogens		
Silica Sand (CAS 14808-60-7) Known To Be Human Carcinogen.		
Reproductive toxicity	May damage fertility or the unb	C C
•		
Specific target organ toxicity - single exposure	May cause respiratory irritation	
Specific target organ toxicity - repeated exposure	May cause damage to organs (lung) through prolonged or repeated exposure.	
Aspiration hazard	Due to the physical form of the product it is not an aspiration hazard.	
Chronic effects	Prolonged or repeated exposure may cause lung injury, including silicosis.	
12. Ecological information		
Ecotoxicity	Not expected to be harmful to aquatic organisms.	
Componento	Species	Test Posulto

Components		Species	Test Results
Lithium Carbonate (CAS 554	I-13-2)		
Aquatic			
Fish	LC50	Mummichog (Fundulus heteroclitus)	8.1 mg/l, 96 hours
ersistence and degradability	No data i	s available on the degradability of this produc	t.
ioaccumulative potential	No data a	available for this product.	
obility in soil	The prod	uct is not mobile in soil.	
ther adverse effects		adverse environmental effects (e.g. ozone de endocrine disruption, global warming potentia	

13. Disposal considerations

Disposal instructions	Dispose of contents/container in accordance with local/regional/national/international regulations. Do not contaminate ponds, waterways or ditches with chemical or used container.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

TDG

Not regulated as dangerous goods.

ΙΑΤΑ

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not established. Annex II of MARPOL 73/78 and the IBC Code

15. Regulatory information

Canadian regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Calcium sulfate (CAS 7778-18-9)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information

Issue date	02-May-2017	
Revision date	-	
Version #	01	
LATICRETE® 253 Gold Rapid		SDS Canada

List of abbreviations	
References	HSDB® - Hazardous Substances Data Bank Registry of Toxic Effects of Chemical Substances (RTECS)
Disclaimer	The information in this (M)SDS was obtained from sources which we believe are reliable but cannot guarantee. Additionally, your use of this information is beyond our control and may be beyond our knowledge. Therefore, the information is provided without any representation or warranty express or implied.

LATICRETE® 253 Gold Rapid 916450 Version #: 01 Revision date: - Issue date: 02-May-2017