

Safety Data Sheet According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015). Revision Date: 08/29/2019 Date of Issue: 05/09/2019 Version: 2.0

## **SECTION 1: IDENTIFICATION**

1.1. **Product Identifier** 

Product Form: Mixture Product Name: L&M<sup>™</sup> DURACRETE<sup>™</sup> Product Code: 9-31-622-1574 (115), 9-31-622-1564 (115)

#### 1.2. Intended Use of the Product

Patching Agent. For professional use only.

#### 1.3. Name, Address, and Telephone of the Responsible Party

#### Company

LATICRETE International 1 Laticrete Park, N Bethany, CT 06524 T (203)-393-0010

Company LATICRETE Canada ULC PO Box 129, Emeryville, Ontario, Canada NOR-1A0 (833)-254-9255

#### www.laticrete.com

#### 1.4. **Emergency Telephone Number**

**Emergency Number** : For chemical emergency call ChemTel day or night: (800)255-3924 (North America) (800)-099-0731 (Mexico) +1 (813)248-0585 (International - collect calls accepted)

### **SECTION 2: HAZARDS IDENTIFICATION**

#### **Classification of the Substance or Mixture** 2.1. **GHS-US/CA** Classification

| Skin Corr. 1C | H314 |
|---------------|------|
| Eye Dam. 1    | H318 |
| Skin Sens. 1  | H317 |
| Carc. 1A      | H350 |
| STOT SE 3     | H335 |
| STOT RE 1     | H372 |
|               |      |

Full text of hazard classes and H-statements : see section 16

#### 2.2. Label Elements

#### **GHS-US/CA Labeling**

Hazard Pictograms (GHS-US/CA)



| Signal Word (GHS-US/CA)              | : Danger   |
|--------------------------------------|--|
| Hazard Statements (GHS-US/CA)        | : H314 - Causes severe skin burns and eye damage.                                |
|                                      | H317 - May cause an allergic skin reaction.                                      |
|                                      | H318 - Causes serious eye damage.  |
|                                      | H335 - May cause respiratory irritation.   |
|                                      | H350 - May cause cancer (Inhalation).  |
|                                      | H372 - Causes damage to organs (lungs) through prolonged or repeated exposure    |
|                                      | (Inhalation).  |
| Precautionary Statements (GHS-US/CA) | : P201 - Obtain special instructions before use.                                 |
|                                      | P202 - Do not handle until all safety precautions have been read and understood. |
|                                      | P260 - Do not breathe vapors, mist, or spray.                                    |
|                                      | P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.  |
|                                      | P270 - Do not eat, drink or smoke when using this product.                       |
|                                      | P271 - Use only outdoors or in a well-ventilated area.                           |
| 08/30/2010                           | EN (English LIS)   |

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

P272 - Contaminated work clothing should not be allowed out of the workplace.
P280 - Wear protective gloves, protective clothing, and eye protection.
P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 - If exposed or concerned: Get medical advice/attention.

P310 - Immediately call a POISON CENTER or doctor.

P314 - Get medical advice/attention if you feel unwell.

P321 - Specific treatment (see section 4 on this SDS).

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

P362+P364 - Take off contaminated clothing and wash it before reuse.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P405 - Store locked up.

P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations.

#### 2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

2.4. Unknown Acute Toxicity (GHS-US/CA)

No data available

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1. Substance

Not applicable

#### 3.2. Mixture

| Name   | Product Identifier     | % *       | GHS Ingredient Classification |
|--|------------------------|-----------|-------------------------------|
| Quartz                                       | (CAS-No.) 14808-60-7   | < 63      | Carc. 1A, H350                |
|  |                        |           | STOT SE 3, H335               |
|  |                        |           | STOT RE 1, H372               |
| Cement, portland, chemicals                  | (CAS-No.) 65997-15-1   | 15 - 40   | Skin Irrit. 2, H315           |
|  |                        |           | Eye Dam. 1, H318              |
|  |                        |           | Skin Sens. 1, H317            |
|  |                        |           | STOT SE 3, H335               |
| Calcium oxide                                | (CAS-No.) 1305-78-8    | 18 - 24   | Skin Irrit. 2, H315           |
|  |                        |           | Eye Dam. 1, H318              |
|  |                        |           | STOT SE 3, H335               |
|  |                        |           | Aquatic Acute 3, H402         |
| Copolymer of vinyl acetate and ethylene with | (CAS-No.) Not assigned | 1 - 5     | Comb. Dust                    |
| mineral additives and protective colloid     |                        |           |                               |
| Limestone                                    | (CAS-No.) 1317-65-3    | <= 2      | Not classified                |
| Silicic acid (H4SiO4), calcium salt (1:2)    | (CAS-No.) 10034-77-2   | 1 - 2     | Eye Irrit. 2A, H319           |
| Calcium sulfate dihydrate                    | (CAS-No.) 13397-24-5   | <= 2      | Not classified                |
| Magnesium oxide (MgO)                        | (CAS-No.) 1309-48-4    | <= 2      | Not classified                |
| Chromium, ion (Cr6+)                         | (CAS-No.) 18540-29-9   | < 0.00003 | Skin Sens. 1, H317            |
|  |                        |           | Carc. 1B, H350                |
|  |                        |           | Aquatic Acute 1, H400         |
|  |                        |           | Aquatic Chronic 1, H410       |

Full text of H-phrases: see section 16

\*Percentages are listed in weight by weight percentage (w/w%) for liquid and solid ingredients. Gas ingredients are listed in volume by volume percentage (v/v%).

#### Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

\*\* The actual concentration of ingredient(s) is withheld as a trade secret in accordance with the Hazardous Products Regulations (HPR) SOR/2015-17 and 29 CFR 1910.1200.

### **SECTION 4: FIRST AID MEASURES**

#### 4.1. Description of First-aid Measures

**General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

**Inhalation:** Remove to fresh air and keep at rest in a position comfortable for breathing. Immediately call a poison center or doctor/physician.

**Skin Contact:** Immediately remove contaminated clothing. Immediately flush skin with plenty of water for at least 30 minutes. Get immediate medical advice/attention.

**Eye Contact:** Immediately rinse with water for at least 30 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.

Ingestion: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

#### 4.2. Most Important Symptoms and Effects Both Acute and Delayed

**General:** Causes severe skin burns and eye damage. Skin sensitization. May cause respiratory irritation. Causes damage to organs through prolonged or repeated exposure. May cause cancer.

**Inhalation:** Irritation of the respiratory tract and the other mucous membranes. May be corrosive to the respiratory tract. Accelerated Silicosis can occur with exposure to high concentrations of respirable crystalline silica over a relatively short period; lung lesions can appear within five years of the initial exposure. The progression can be rapid. Accelerated silicosis is similar to chronic or

ordinary silicosis, except that lung lesions appear earlier and the progression is more rapid. Acute Silicosis can occur with exposures to very high concentrations of respirable crystalline silica over a very short time period, sometimes as short as a few months. The symptoms of acute silicosis include progressive shortness of breath, fever, cough and weight loss. Acute silicosis can be fatal.

**Skin Contact:** When this product is wet it is corrosive. Causes severe irritation which will progress to chemical burns. May cause an allergic skin reaction. Concrete may cause dry skin, discomfort, irritation, severe burns, and dermatitis. Unhardened concrete is capable of causing dermatitis by irritation and allergy. Concrete dust, in association with sweat and friction, can lead to skin irritation and dermatitis. Skin affected by dermatitis may include symptoms such as, redness, itching, rash, scaling, and cracking. Allergic contact dermatitis is caused by sensitization to hexavalent chromium (chromate) present in concrete. The reaction can range from a mild rash to severe skin ulcers.

**Eye Contact:** Causes permanent damage to the cornea, iris, or conjunctiva. Concrete may cause immediate or delayed irritation or inflammation. Eye contact with wet concrete can cause moderate eye irritation, chemical burns and blindness. Eye exposures require immediate first aid and medical attention to prevent significant damage to the eye.

Ingestion: May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.

**Chronic Symptoms:** Causes damage to organs (lungs) through prolonged or repeated exposure (Inhalation). May cause cancer by inhalation. Long term exposure to respirable crystalline silica results in a significant risk of developing silicosis and other non-malignant respiratory disease, lung cancer, kidney effects, and immune system effects.

#### 4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

# SECTION 5: FIRE-FIGHTING MEASURES

## 5.1. Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

### 5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not considered flammable but may burn at high temperatures.

Explosion Hazard: Product is not explosive.

**Reactivity:** May react exothermically with water releasing heat. Adding an acid to a base or base to an acid may cause a violent reaction.

#### 5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection. **Hazardous Combustion Products**: Silicon oxides. Carbon oxides (CO, CO<sub>2</sub>). Sulfur oxides. Calcium oxides.

#### Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

### 5.4. Reference to Other Sections

Refer to Section 9 for flammability properties.

# SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal Precautions, Protective Equipment and Emergency Procedures

**General Measures:** Do not breathe dust. Do not get in eyes, on skin, or on clothing. Do not handle until all safety precautions have been read and understood.

#### 6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protective equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel.

#### 6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

**Emergency Procedures:** Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area.

#### 6.2. Environmental Precautions

Prevent entry to sewers and public waters.

#### 6.3. Methods and Materials for Containment and Cleaning Up

**For Containment:** Contain solid spills with appropriate barriers and prevent migration and entry into sewers or streams. As an immediate precautionary measure, isolate spill or leak area in all directions.

**Methods for Cleaning Up:** Clean up spills immediately and dispose of waste safely. Cautiously neutralize spilled solid. Recover the product by vacuuming, shoveling or sweeping. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

#### 6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

### SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for Safe Handling

#### Additional Hazards When Processed: May release corrosive vapors.

**Precautions for Safe Handling:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust. Do not get in eyes, on skin, or on clothing. Handle empty containers with care because they may still present a hazard. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

#### 7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

**Storage Conditions:** Store in a dry, cool place. Store locked up/in a secure area. Store in original container or corrosive resistant and/or lined container. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Keep container closed when not in use.

**Incompatible Materials:** Acids, ammonium salts and aluminum metal. Cement dissolves in hydrofluoric acid, producing corrosive silicon tetrafluoride gas. Cement reacts with water to form silicates and calcium hydroxide. Silicates react with powerful oxidizers such as fluorine, boron trifluoride, chlorine trifluoride, manganese trifluoride, and oxygen difluoride.

#### 7.3. Specific End Use(s)

Patching Agent. For professional use only.

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), or Canadian provincial governments.

| Cement, portland, chemicals (65997-15-1) |                         |  |
|--|-------------------------|--|
| USA ACGIH                                | ACGIH TWA (mg/m³)       | 1 mg/m <sup>3</sup> (particulate matter containing no asbestos and |
|  |                         | <1% crystalline silica, respirable particulate matter)             |
| USA ACGIH                                | ACGIH chemical category | Not Classifiable as a Human Carcinogen                             |

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

|                           | OSHA PEL (TWA) (mg/m <sup>3</sup> )  | 15 mg/m <sup>3</sup> (total dust)  |
|---------------------------|--------------------------------------|--|
| USA OSHA                  | OSHA PEL (TWA) (mg/m²)               | 5 mg/m <sup>3</sup> (respirable fraction)  |
| USA NIOSH                 | NIOSH REL (TWA) (mg/m <sup>3</sup> ) | 10 mg/m <sup>3</sup> (total dust)  |
| USA NIUSH                 | NIOSH KEL (TWA) (IIIg/III )          | 5 mg/m <sup>3</sup> (respirable dust)  |
| USA IDLH                  | US IDLH (mg/m <sup>3</sup> )         | 5000 mg/m <sup>3</sup>   |
| Alberta                   | OEL TWA (mg/m <sup>3</sup> )         | 10 mg/m <sup>3</sup>   |
| British Columbia          | OEL TWA (mg/m <sup>3</sup> )         | 1 mg/m <sup>3</sup> (particulate matter containing no Asbestos and   |
|                           |                                      | <1% Crystalline silica-respirable particulate)   |
| Manitoba                  | OEL TWA (mg/m³)                      | 1 mg/m <sup>3</sup> (particulate matter containing no Asbestos and   |
|                           |                                      | <1% Crystalline silica, respirable particulate matter-   |
|                           |                                      | particulate matter, respirable particulate matter)   |
| New Brunswick             | OEL TWA (mg/m <sup>3</sup> )         | 10 mg/m <sup>3</sup> (particulate matter containing no Asbestos and  |
|                           |                                      | <1% Crystalline silica)  |
| Newfoundland & Labrador   | OEL TWA (mg/m³)                      | 1 mg/m <sup>3</sup> (particulate matter containing no Asbestos and   |
|                           |                                      | <1% Crystalline silica, respirable particulate matter-   |
|                           |                                      | particulate matter, respirable particulate matter)   |
| Nova Scotia               | OEL TWA (mg/m³)                      | 1 mg/m <sup>3</sup> (particulate matter containing no Asbestos and   |
|                           |                                      | <1% Crystalline silica, respirable particulate matter-   |
|                           |                                      | particulate matter, respirable particulate matter)   |
| Nunavut                   | OEL STEL (mg/m <sup>3</sup> )        | 20 mg/m <sup>3</sup>   |
| Nunavut                   | OEL TWA (mg/m <sup>3</sup> )         | 10 mg/m <sup>3</sup>   |
| Northwest Territories     | OEL STEL (mg/m <sup>3</sup> )        | 20 mg/m <sup>3</sup>   |
| Northwest Territories     | OEL TWA (mg/m <sup>3</sup> )         | 10 mg/m <sup>3</sup>   |
| Ontario                   | OEL TWA (mg/m³)                      | 1 mg/m <sup>3</sup> (containing no Asbestos and <1% Crystalline  |
| Prince Edward Island      | OEL TWA (mg/m³)                      | silica-respirable)<br>1 mg/m <sup>3</sup> (particulate matter containing no Asbestos and                         |
| Prince Edward Island      | OEL I WA (mg/m²)                     | 1 mg/m² (particulate matter containing no Asbestos and<br><1% Crystalline silica, respirable particulate matter- |
|                           |                                      | particulate matter, respirable particulate matter)   |
| Québec                    | VEMP (mg/m <sup>3</sup> )            | 10 mg/m <sup>3</sup> (containing no Asbestos and <1% Crystalline   |
|                           | (8, )                                | silica-total dust)   |
|                           |                                      | 5 mg/m <sup>3</sup> (containing no Asbestos and <1% Crystalline  |
|                           |                                      | silica-respirable dust)  |
| Saskatchewan              | OEL STEL (mg/m <sup>3</sup> )        | 20 mg/m <sup>3</sup>   |
| Saskatchewan              | OEL TWA (mg/m <sup>3</sup> )         | 10 mg/m <sup>3</sup>   |
| Yukon                     | OEL STEL (mg/m <sup>3</sup> )        | 20 mg/m <sup>3</sup>   |
| Yukon                     | OEL TWA (mg/m³)                      | 30 mppcf   |
|                           |                                      | 10 mg/m³   |
| Calcium oxide (1305-78-8) |                                      |  |
| USA ACGIH                 | ACGIH TWA (mg/m <sup>3</sup> )       | 2 mg/m <sup>3</sup>  |
| USA OSHA                  | OSHA PEL (TWA) (mg/m³)               | 5 mg/m <sup>3</sup>  |
| USA NIOSH                 | NIOSH REL (TWA) (mg/m <sup>3</sup> ) | 2 mg/m <sup>3</sup>  |
| USA IDLH                  | US IDLH (mg/m <sup>3</sup> )         | 25 mg/m <sup>3</sup>   |
| Alberta                   | OEL TWA (mg/m³)                      | 2 mg/m <sup>3</sup>  |
| British Columbia          | OEL TWA (mg/m³)                      | 2 mg/m <sup>3</sup>  |
| Manitoba                  | OEL TWA (mg/m <sup>3</sup> )         | 2 mg/m <sup>3</sup>  |
| New Brunswick             | OEL TWA (mg/m <sup>3</sup> )         | 2 mg/m <sup>3</sup>  |
| Newfoundland & Labrador   | OEL TWA (mg/m <sup>3</sup> )         | 2 mg/m <sup>3</sup>  |
| Nova Scotia               | OEL TWA (mg/m <sup>3</sup> )         | 2 mg/m <sup>3</sup>  |
| Nunavut                   | OEL STEL (mg/m <sup>3</sup> )        | 4 mg/m <sup>3</sup>  |
| Nunavut                   | OEL TWA (mg/m <sup>3</sup> )         | 2 mg/m <sup>3</sup>  |
| Northwest Territories     | OEL STEL (mg/m <sup>3</sup> )        | 4 mg/m <sup>3</sup>  |
| Northwest Territories     | OEL TWA (mg/m³)                      | 2 mg/m <sup>3</sup>  |

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

|                           |                                      | d According To The Hazardous Products Regulation (February 11, 2015). |
|---------------------------|--------------------------------------|---|
| Ontario                   | OEL TWA (mg/m <sup>3</sup> )         | 2 mg/m <sup>3</sup>   |
| Prince Edward Island      | OEL TWA (mg/m <sup>3</sup> )         | 2 mg/m <sup>3</sup>   |
| Québec                    | VEMP (mg/m <sup>3</sup> )            | 2 mg/m <sup>3</sup>   |
| Saskatchewan              | OEL STEL (mg/m <sup>3</sup> )        | 4 mg/m <sup>3</sup>   |
| Saskatchewan              | OEL TWA (mg/m <sup>3</sup> )         | 2 mg/m <sup>3</sup>   |
| Yukon                     | OEL STEL (mg/m <sup>3</sup> )        | 4 mg/m <sup>3</sup>   |
| Yukon                     | OEL TWA (mg/m³)                      | 2 mg/m <sup>3</sup>   |
| Quartz (14808-60-7)       |                                      |   |
| USA ACGIH                 | ACGIH TWA (mg/m <sup>3</sup> )       | 0.025 mg/m <sup>3</sup> (respirable particulate matter)               |
| USA ACGIH                 | ACGIH chemical category              | A2 - Suspected Human Carcinogen                                       |
| USA OSHA                  | OSHA PEL (TWA) (mg/m³)               | 50 μg/m <sup>3</sup> (Respirable crystalline silica)                  |
| USA NIOSH                 | NIOSH REL (TWA) (mg/m <sup>3</sup> ) | 0.05 mg/m <sup>3</sup> (respirable dust)                              |
| USA IDLH                  | US IDLH (mg/m <sup>3</sup> )         | 50 mg/m <sup>3</sup> (respirable dust)                                |
| Alberta                   | OEL TWA (mg/m³)                      | 0.025 mg/m <sup>3</sup> (respirable particulate)                      |
| British Columbia          | OEL TWA (mg/m³)                      | 0.025 mg/m <sup>3</sup> (respirable)                                  |
| Manitoba                  | OEL TWA (mg/m <sup>3</sup> )         | 0.025 mg/m <sup>3</sup> (respirable particulate matter)               |
| New Brunswick             | OEL TWA (mg/m <sup>3</sup> )         | 0.1 mg/m <sup>3</sup> (respirable fraction)                           |
| Newfoundland & Labrador   | OEL TWA (mg/m <sup>3</sup> )         | 0.025 mg/m <sup>3</sup> (respirable particulate matter)               |
| Nova Scotia               | OEL TWA (mg/m <sup>3</sup> )         | 0.025 mg/m <sup>3</sup> (respirable particulate matter)               |
| Nunavut                   | OEL TWA (mg/m <sup>3</sup> )         | 0.05 mg/m <sup>3</sup> (respirable fraction (Silica - crystalline)    |
| Northwest Territories     | OEL TWA (mg/m³)                      | 0.05 mg/m <sup>3</sup> (respirable fraction (Silica - crystalline)    |
| Ontario                   | OEL TWA (mg/m³)                      | 0.1 mg/m <sup>3</sup> (designated substances regulation-respirable    |
|                           |                                      | (Silica, crystalline)   |
| Prince Edward Island      | OEL TWA (mg/m³)                      | 0.025 mg/m <sup>3</sup> (respirable particulate matter)               |
| Québec                    | VEMP (mg/m <sup>3</sup> )            | 0.1 mg/m <sup>3</sup> (respirable dust)                               |
| Saskatchewan              | OEL TWA (mg/m³)                      | 0.05 mg/m <sup>3</sup> (respirable fraction (Silica - crystalline     |
|                           |                                      | (Trydimite removed))  |
| Yukon                     | OEL TWA (mg/m³)                      | 300 particle/mL (Silica - Quartz, crystalline)                        |
| Limestone (1317-65-3)     |                                      |   |
| USA OSHA                  | OSHA PEL (TWA) (mg/m³)               | 15 mg/m <sup>3</sup> (total dust)                                     |
|                           |                                      | 5 mg/m <sup>3</sup> (respirable fraction)                             |
| USA NIOSH                 | NIOSH REL (TWA) (mg/m³)              | 10 mg/m <sup>3</sup> (total dust)                                     |
|                           |                                      | 5 mg/m <sup>3</sup> (respirable dust)                                 |
| Alberta                   | OEL TWA (mg/m <sup>3</sup> )         | 10 mg/m <sup>3</sup>  |
| British Columbia          | OEL STEL (mg/m <sup>3</sup> )        | 20 mg/m <sup>3</sup> (total)  |
| British Columbia          | OEL TWA (mg/m³)                      | 10 mg/m <sup>3</sup> (total dust)                                     |
|                           |                                      | 3 mg/m <sup>3</sup> (respirable fraction)                             |
| New Brunswick             | OEL TWA (mg/m³)                      | 10 mg/m <sup>3</sup> (particulate matter containing no Asbestos and   |
|                           |                                      | <1% Crystalline silica)   |
| Nunavut                   | OEL STEL (mg/m <sup>3</sup> )        | 20 mg/m <sup>3</sup>  |
| Nunavut                   | OEL TWA (mg/m <sup>3</sup> )         | 10 mg/m <sup>3</sup>  |
| Northwest Territories     | OEL STEL (mg/m <sup>3</sup> )        | 20 mg/m <sup>3</sup>  |
| Northwest Territories     | OEL TWA (mg/m <sup>3</sup> )         | 10 mg/m <sup>3</sup>  |
| Québec                    | VEMP (mg/m <sup>3</sup> )            | 10 mg/m <sup>3</sup> (Limestone, containing no Asbestos and <1%       |
| Cashataha                 |                                      | Crystalline silica-total dust)  |
| Saskatchewan              | OEL STEL (mg/m <sup>3</sup> )        | 20 mg/m <sup>3</sup>  |
| Saskatchewan              | OEL TWA (mg/m <sup>3</sup> )         | 10 mg/m <sup>3</sup>  |
| Yukon                     | OEL STEL (mg/m <sup>3</sup> )        | 20 mg/m <sup>3</sup>  |
| Yukon                     | OEL TWA (mg/m³)                      | 30 mppcf  |
|                           |                                      | 10 mg/m <sup>3</sup>  |
| Magnesium oxide (MgO) (13 |                                      |   |
| USA ACGIH                 | ACGIH TWA (mg/m <sup>3</sup> )       | 10 mg/m <sup>3</sup> (inhalable particulate matter)                   |
| 08/29/2019                | EN (English US)                      | 6/12  |

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

|                              | 58 / WOTLDAY, WATCH 20, 2012 / Rules Allu Regulation | ns And According To The Hazardous Products Regulation (February 11, 2015). |
|------------------------------|--|--|
| USA ACGIH                    | ACGIH chemical category                              | Not Classifiable as a Human Carcinogen                                     |
| USA OSHA                     | OSHA PEL (TWA) (mg/m³)                               | 15 mg/m <sup>3</sup> (fume, total particulate)                             |
| USA IDLH                     | US IDLH (mg/m <sup>3</sup> )                         | 750 mg/m³ (fume)   |
| Alberta                      | OEL TWA (mg/m <sup>3</sup> )                         | 10 mg/m <sup>3</sup> (fume)  |
| British Columbia             | OEL STEL (mg/m <sup>3</sup> )                        | 10 mg/m <sup>3</sup> (respirable dust and fume)                            |
| British Columbia             | OEL TWA (mg/m³)                                      | 10 mg/m <sup>3</sup> (fume, inhalable)                                     |
|                              |  | 3 mg/m <sup>3</sup> (respirable dust and fume)                             |
| Manitoba                     | OEL TWA (mg/m³)                                      | 10 mg/m <sup>3</sup> (inhalable particulate matter)                        |
| New Brunswick                | OEL TWA (mg/m <sup>3</sup> )                         | 10 mg/m³ (fume)  |
| Newfoundland & Labrador      | OEL TWA (mg/m <sup>3</sup> )                         | 10 mg/m <sup>3</sup> (inhalable particulate matter)                        |
| Nova Scotia                  | OEL TWA (mg/m³)                                      | 10 mg/m <sup>3</sup> (inhalable particulate matter)                        |
| Nunavut                      | OEL STEL (mg/m <sup>3</sup> )                        | 20 mg/m <sup>3</sup> (inhalable fraction)                                  |
| Nunavut                      | OEL TWA (mg/m <sup>3</sup> )                         | 10 mg/m <sup>3</sup> (inhalable fraction)                                  |
| Northwest Territories        | OEL STEL (mg/m <sup>3</sup> )                        | 20 mg/m <sup>3</sup> (inhalable fraction)                                  |
| Northwest Territories        | OEL TWA (mg/m <sup>3</sup> )                         | 10 mg/m <sup>3</sup> (inhalable fraction)                                  |
| Ontario                      | OEL TWA (mg/m <sup>3</sup> )                         | 10 mg/m <sup>3</sup> (inhalable)   |
| Prince Edward Island         | OEL TWA (mg/m <sup>3</sup> )                         | 10 mg/m <sup>3</sup> (inhalable particulate matter)                        |
| Québec                       | VEMP (mg/m <sup>3</sup> )                            | 10 mg/m <sup>3</sup> (fume)  |
| Saskatchewan                 | OEL STEL (mg/m <sup>3</sup> )                        | 20 mg/m <sup>3</sup> (inhalable fraction)                                  |
| Saskatchewan                 | OEL TWA (mg/m <sup>3</sup> )                         | 10 mg/m <sup>3</sup> (inhalable fraction)                                  |
| Yukon                        | OEL STEL (mg/m <sup>3</sup> )                        | 10 mg/m <sup>3</sup> (fume)  |
| Yukon                        | OEL TWA (mg/m <sup>3</sup> )                         | 10 mg/m <sup>3</sup> (fume)  |
| Chromium, ion (Cr6+) (1854   | 0-29-9)  |  |
| USA OSHA                     | OSHA PEL (TWA) (mg/m <sup>3</sup> )                  | 5 μg/m³  |
| Calcium sulfate dihydrate (1 | .3397-24-5)  |  |
| USA ACGIH                    | ACGIH TWA (mg/m <sup>3</sup> )                       | 10 mg/m <sup>3</sup> (inhalable particulate matter (Calcium sulfate)       |
| USA OSHA                     | OSHA PEL (TWA) (mg/m <sup>3</sup> )                  | 15 mg/m <sup>3</sup> (total dust)  |
|                              |  | 5 mg/m <sup>3</sup> (respirable fraction)                                  |
| USA NIOSH                    | NIOSH REL (TWA) (mg/m <sup>3</sup> )                 | 10 mg/m <sup>3</sup> (total dust)  |
|                              |  | 5 mg/m <sup>3</sup> (respirable dust)                                      |
| Alberta                      | OEL TWA (mg/m³)                                      | 10 mg/m <sup>3</sup> (Calcium sulphate)                                    |
| British Columbia             | OEL STEL (mg/m <sup>3</sup> )                        | 20 mg/m <sup>3</sup> (total)   |
| British Columbia             | OEL TWA (mg/m³)                                      | 10 mg/m <sup>3</sup> (total dust)  |
|                              |  | 3 mg/m <sup>3</sup> (respirable fraction)                                  |
| Manitoba                     | OEL TWA (mg/m³)                                      | 10 mg/m <sup>3</sup> (inhalable particulate matter (Calcium sulfate)       |
| Newfoundland & Labrador      | OEL TWA (mg/m³)                                      | 10 mg/m <sup>3</sup> (inhalable particulate matter (Calcium sulfate)       |
| Nova Scotia                  | OEL TWA (mg/m³)                                      | 10 mg/m <sup>3</sup> (inhalable particulate matter (Calcium sulfate)       |
| Ontario                      | OEL TWA (mg/m³)                                      | 10 mg/m <sup>3</sup> (inhalable (Calcium sulfate)                          |
| Prince Edward Island         | OEL TWA (mg/m³)                                      | 10 mg/m <sup>3</sup> (inhalable particulate matter (Calcium sulfate)       |
| Québec                       | VEMP (mg/m <sup>3</sup> )                            | 10 mg/m <sup>3</sup> (containing no Asbestos and <1% Crystalline           |
|                              |  | silica-total dust)   |
|                              |  | 5 mg/m <sup>3</sup> (containing no Asbestos and <1% Crystalline            |
|                              |  | silica-respirable dust)  |
| Saskatchewan                 | OEL STEL (mg/m <sup>3</sup> )                        | 20 mg/m <sup>3</sup>   |
| Saskatchewan                 | OEL TWA (mg/m <sup>3</sup> )                         | 10 mg/m <sup>3</sup>   |
| Yukon                        | OEL STEL (mg/m <sup>3</sup> )                        | 20 mg/m <sup>3</sup>   |
| Yukon                        | OEL TWA (mg/m³)                                      | 30 mppcf   |
|                              |  | 10 mg/m <sup>3</sup>   |

# 8.2. Exposure Controls

**Appropriate Engineering Controls:** Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

**Personal Protective Equipment:** Gloves. Protective clothing. Protective goggles. Face shield. Insufficient ventilation: wear respiratory protection.



Materials for Protective Clothing: Chemically resistant materials and fabrics. Corrosion-proof clothing.

Hand Protection: Wear protective gloves.

Eye and Face Protection: Chemical safety goggles and face shield.

Skin and Body Protection: Wear suitable protective clothing.

**Respiratory Protection:** If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

Other Information: When using, do not eat, drink or smoke.

#### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

| 9.1. Information on Basic Physical and Chem | ical | Properties    |
|---|------|---------------|
| Physical State                              | :    | Solid         |
| Appearance                                  | :    | Gray powder   |
| Odor  | :    | None          |
| Odor Threshold                              | :    | Not available |
| рН  | :    | Not available |
| Evaporation Rate                            | :    | Not available |
| Melting Point                               | :    | Not available |
| Freezing Point                              | :    | Not available |
| Boiling Point                               | :    | Not available |
| Flash Point                                 | :    | Not available |
| Auto-ignition Temperature                   | :    | Not available |
| Decomposition Temperature                   | :    | Not available |
| Flammability (solid, gas)                   | :    | Not available |
| Lower Flammable Limit                       | :    | Not available |
| Upper Flammable Limit                       | :    | Not available |
| Vapor Pressure                              | :    | Not available |
| Relative Vapor Density at 20°C              | :    | Not available |
| Relative Density                            | :    | Not available |
| Specific Gravity                            | :    | 2.65          |
| Solubility                                  | :    | Not available |
| Partition Coefficient: N-Octanol/Water      | :    | Not available |
| Viscosity                                   | :    | Not available |
| CECTION 10, CTABILITY AND DEACTIVITY        |      |               |

### SECTION 10: STABILITY AND REACTIVITY

**10.1. Reactivity:** May react exothermically with water releasing heat. Adding an acid to a base or base to an acid may cause a violent reaction.

**10.2.** Chemical Stability: Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

**10.4.** Conditions to Avoid: Direct sunlight, extremely high or low temperatures, and incompatible materials.

**10.5. Incompatible Materials:** Acids, ammonium salts and aluminum metal. Cement dissolves in hydrofluoric acid, producing corrosive silicon tetrafluoride gas. Cement reacts with water to form silicates and calcium hydroxide. Silicates react with powerful oxidizers such as fluorine, boron trifluoride, chlorine trifluoride, manganese trifluoride, and oxygen difluoride.

**10.6. Hazardous Decomposition Products:** Under normal conditions of storage and use, hazardous decomposition products should not be produced.

#### SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on Toxicological Effects - Product

Acute Toxicity (Oral): Not classified

Acute Toxicity (Dermal): Not classified

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Acute Toxicity (Inhalation): Not classified

LD50 and LC50 Data: Not available

Skin Corrosion/Irritation: Causes severe skin burns and eye damage.

**Eye Damage/Irritation:** Causes serious eye damage.

**Respiratory or Skin Sensitization:** May cause an allergic skin reaction.

Germ Cell Mutagenicity: Not classified

Carcinogenicity: May cause cancer (Inhalation).

**Specific Target Organ Toxicity (Repeated Exposure):** Causes damage to organs (lungs) through prolonged or repeated exposure (Inhalation).

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): May cause respiratory irritation.

Aspiration Hazard: Not classified

**Symptoms/Injuries After Inhalation:** Irritation of the respiratory tract and the other mucous membranes. May be corrosive to the respiratory tract. Accelerated Silicosis can occur with exposure to high concentrations of respirable crystalline silica over a relatively short period; lung lesions can appear within five years of the initial exposure. The progression can be rapid. Accelerated silicosis is similar to chronic or ordinary silicosis, except that lung lesions appear earlier and the progression is more rapid.

Acute Silicosis can occur with exposures to very high concentrations of respirable crystalline silica over a very short time period, sometimes as short as a few months. The symptoms of acute silicosis include progressive shortness of breath, fever, cough and weight loss. Acute silicosis can be fatal.

**Symptoms/Injuries After Skin Contact:** When this product is wet it is corrosive. Causes severe irritation which will progress to chemical burns. May cause an allergic skin reaction. Concrete may cause dry skin, discomfort, irritation, severe burns, and dermatitis. Unhardened concrete is capable of causing dermatitis by irritation and allergy. Concrete dust, in association with sweat and friction, can lead to skin irritation and dermatitis. Skin affected by dermatitis may include symptoms such as, redness, itching, rash, scaling, and cracking. Allergic contact dermatitis is caused by sensitization to hexavalent chromium (chromate) present in concrete. The reaction can range from a mild rash to severe skin ulcers.

**Symptoms/Injuries After Eye Contact:** Causes permanent damage to the cornea, iris, or conjunctiva. Concrete may cause immediate or delayed irritation or inflammation. Eye contact with wet concrete can cause moderate eye irritation, chemical burns and blindness. Eye exposures require immediate first aid and medical attention to prevent significant damage to the eye.

**Symptoms/Injuries After Ingestion:** May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract. **Chronic Symptoms:** Causes damage to organs (lungs) through prolonged or repeated exposure (Inhalation). May cause cancer by inhalation. Long term exposure to respirable crystalline silica results in a significant risk of developing silicosis and other non-malignant respiratory disease, lung cancer, kidney effects, and immune system effects.

#### **11.2.** Information on Toxicological Effects - Ingredient(s)

#### LD50 and LC50 Data:

| Calcium oxide (1305-78-8)                        |   |
|--|---|
| LD50 Oral Rat                                    | > 2000 mg/kg                                    |
| LD50 Dermal Rabbit                               | > 2500 mg/kg                                    |
| Quartz (14808-60-7)                              |   |
| LD50 Oral Rat                                    | > 5000 mg/kg                                    |
| LD50 Dermal Rat                                  | > 5000 mg/kg                                    |
| Magnesium oxide (MgO) (1309-48-4)                |   |
| LD50 Oral Rat                                    | 3870 mg/kg                                      |
| Quartz (14808-60-7)                              |   |
| IARC Group                                       | 1   |
| National Toxicology Program (NTP) Status         | Known Human Carcinogens.                        |
| <b>OSHA Hazard Communication Carcinogen List</b> | In OSHA Hazard Communication Carcinogen list.   |
| Chromium, ion (Cr6+) (18540-29-9)                |   |
| IARC Group                                       | 1   |
| OSHA Hazard Communication Carcinogen List        | In OSHA Hazard Communication Carcinogen list.   |
| OSHA Specifically Regulated Carcinogen List      | In OSHA Specifically Regulated Carcinogen list. |
|  |   |

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

### SECTION 12: ECOLOGICAL INFORMATION

#### 12.1. Toxicity

Ecology - General: Not classified.

| Calcium oxide (1305-78-8)  |           |  |
|--|-----------|--|
| LC50 Fish 1  | 50.6 mg/l |  |
| Chromium, ion (Cr6+) (18540-2  | 29-9)     |  |
| LC50 Fish 1 36.2 mg/l (Exposure time: 96 h - Species: Pimephales promelas) |           |  |
| LC50 Fish 2 7.6 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)  |           |  |

#### **12.2.** Persistence and Degradability

|                                      | ······································ |  |
|--------------------------------------|--|--|
| L&M™ DURACRETE™                      |  |  |
| Persistence and Degradability        | Not established.                       |  |
| 12.3. Bioaccumulative Potenti        | I                                      |  |
| L&M™ DURACRETE™                      |  |  |
| Bioaccumulative Potential            | Not established.                       |  |
| Calcium oxide (1305-78-8)            |  |  |
| BCF Fish 1 (no bioaccumulation)      |  |  |
| 12.4. Mobility in Soil Not available |  |  |

**12.4. Mobility in Soil** Not available

### **12.5.** Other Adverse Effects

**Other Information:** Avoid release to the environment.

### SECTION 13: DISPOSAL CONSIDERATIONS

#### 13.1. Waste treatment methods

Waste Disposal Recommendations: Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

Ecology - Waste Materials: Avoid release to the environment.

### SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

- 14.1. In Accordance with DOT Not regulated for transport
- 14.2. In Accordance with IMDG Not regulated for transport
- 14.3. In Accordance with IATA Not regulated for transport
- **14.4.** In Accordance with TDG Not regulated for transport

## **SECTION 15: REGULATORY INFORMATION**

15.1. US Federal Regulations

| L&M™ DURACRETE™                          |  |
|--|--|
| SARA Section 311/312 Hazard Classes      | Health hazard - Specific target organ toxicity (single or repeated exposure) |
|  | Health hazard - Carcinogenicity  |
|  | Health hazard - Respiratory or skin sensitization                            |
|  | Health hazard - Serious eye damage or eye irritation                         |
|  | Health hazard - Skin corrosion or Irritation                                 |
| Cement, portland, chemicals (65997-15-1) |  |

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### Calcium oxide (1305-78-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### Quartz (14808-60-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### Limestone (1317-65-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Magnesium oxide (MgO) (1309-48-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Silicic acid (H4SiO4), calcium salt (1:2) (10034-77-2)

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Listed on the United States TSCA (Toxic Substances Control Act) inventory

### 15.2. US State Regulations

### **California Proposition 65**

**WARNING:** This product can expose you to Chromium, ion (Cr6+), which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

| cancer and birth defects or ot   | -                    |               |                     |                   |  |
|--|----------------------|---------------|---------------------|-------------------|--|
| Chemical Name (CAS No.)  | Carcinogenicity      | Developmental | Female Reproductive | Male Reproductive |  |
| Querte (14808.60.7)  | V                    | Toxicity      | Toxicity            | Toxicity          |  |
| Quartz (14808-60-7)  | X<br>X               | х             |                     |                   |  |
| Chromium, ion (Cr6+) (18540-29-9)  |                      | X             |                     |                   |  |
| Cement, portland, chemicals (65997-  |                      |               |                     |                   |  |
| U.S Massachusetts - Right To Know  |                      |               |                     |                   |  |
| U.S New Jersey - Right to Know Haz   |                      | st            |                     |                   |  |
| U.S Pennsylvania - RTK (Right to Kno   | DW) LIST             |               |                     |                   |  |
| Calcium oxide (1305-78-8)  | 1:-+                 |               |                     |                   |  |
| U.S Massachusetts - Right To Know  |                      | - <b>h</b>    |                     |                   |  |
| U.S New Jersey - Right to Know Haz   |                      | st            |                     |                   |  |
| U.S Pennsylvania - RTK (Right to Kno   | DW) LIST             |               |                     |                   |  |
| Quartz (14808-60-7)  |                      |               |                     |                   |  |
| U.S Massachusetts - Right To Know List   |                      |               |                     |                   |  |
| U.S New Jersey - Right to Know Hazardous Substance List<br>U.S Pennsylvania - RTK (Right to Know) List |                      |               |                     |                   |  |
|  | JW) LIST             |               |                     |                   |  |
| Limestone (1317-65-3)  | 1:04                 |               |                     |                   |  |
| U.S Massachusetts - Right To Know List<br>U.S New Jersey - Right to Know Hazardous Substance List      |                      |               |                     |                   |  |
| U.S Pennsylvania - RTK (Right to Know Haz  |                      | SL            |                     |                   |  |
|  |                      |               |                     |                   |  |
| Magnesium oxide (MgO) (1309-48-4)  |                      |               |                     |                   |  |
| U.S Massachusetts - Right To Know  |                      | ct.           |                     |                   |  |
| U.S New Jersey - Right to Know Haz<br>U.S Pennsylvania - RTK (Right to Kno                             |                      | SL            |                     |                   |  |
|  | Jw) List             |               |                     |                   |  |
| Chromium, ion (Cr6+) (18540-29-9)  | ow) Environmental    | Llazard List  |                     |                   |  |
| U.S Pennsylvania - RTK (Right to Kno   | •                    | Hazard List   |                     |                   |  |
| U.S Pennsylvania - RTK (Right to Kno   |                      |               |                     |                   |  |
| Calcium sulfate dihydrate (13397-24  |                      | -+            |                     |                   |  |
| U.S New Jersey - Right to Know Hazardous Substance List  |                      |               |                     |                   |  |
| U.S Pennsylvania - RTK (Right to Kno   | ow) List             |               |                     |                   |  |
| 15.3. Canadian Regulations   | 45 4)                |               |                     |                   |  |
| Cement, portland, chemicals (65997-  |                      |               |                     |                   |  |
| Listed on the Canadian DSL (Domestic   | Substances List)     |               |                     |                   |  |
| Calcium oxide (1305-78-8)  |                      |               |                     |                   |  |
| Listed on the Canadian DSL (Domestic   | c Substances List)   |               |                     |                   |  |
| Quartz (14808-60-7)  |                      |               |                     |                   |  |
| Listed on the Canadian DSL (Domestic   | c Substances List)   |               |                     |                   |  |
| Limestone (1317-65-3)  |                      |               |                     |                   |  |
| Listed on the Canadian NDSL (Non-Do  | omestic Substances I | _ist)         |                     |                   |  |
| Magnesium oxide (MgO) (1309-48-4)  |                      |               |                     |                   |  |
| Listed on the Canadian DSL (Domestic   | c Substances List)   |               |                     |                   |  |
| Silicic acid (H4SiO4), calcium salt (1:2   | 2) (10034-77-2)      |               |                     |                   |  |
| Listed on the Canadian DSL (Domestic   | c Substances List)   |               |                     |                   |  |
| Calcium sulfate dihydrate (13397-24-   | -5)                  |               |                     |                   |  |
| Listed on the Canadian DSL (Domestic   | c Substances List)   |               |                     |                   |  |

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

#### SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Date of Preparation or Latest Revision: 08/29/2019Other Information: This docume

: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200 and Canada's Hazardous Products Regulations (HPR) SOR/2015-17.

#### **GHS Full Text Phrases:**

| Aquatic Acute 1   | Hazardous to the aquatic environment - Acute Hazard Category 1   |  |  |
|-------------------|--|--|--|
| Aquatic Acute 3   | Hazardous to the aquatic environment - Acute Hazard Category 3   |  |  |
| Aquatic Chronic 1 | Hazardous to the aquatic environment - Chronic Hazard Category 1 |  |  |
| Carc. 1A          | Carcinogenicity Category 1A                                      |  |  |
| Carc. 1B          | Carcinogenicity Category 1B                                      |  |  |
| Comb. Dust        | Combustible Dust   |  |  |
| Eye Dam. 1        | Serious eye damage/eye irritation Category 1                     |  |  |
| Eye Irrit. 2A     | Serious eye damage/eye irritation Category 2A                    |  |  |
| Skin Corr. 1C     | Skin corrosion/irritation Category 1C                            |  |  |
| Skin Irrit. 2     | Skin corrosion/irritation Category 2                             |  |  |
| Skin Sens. 1      | Skin sensitization, Category 1                                   |  |  |
| STOT RE 1         | Specific target organ toxicity (repeated exposure) Category 1    |  |  |
| STOT SE 3         | Specific target organ toxicity (single exposure) Category 3      |  |  |
| H314              | Causes severe skin burns and eye damage                          |  |  |
| H315              | Causes skin irritation   |  |  |
| H317              | May cause an allergic skin reaction                              |  |  |
| H318              | Causes serious eye damage  |  |  |
| H319              | Causes serious eye irritation                                    |  |  |
| H335              | May cause respiratory irritation                                 |  |  |
| H350              | May cause cancer   |  |  |
| H372              | Causes damage to organs through prolonged or repeated exposure   |  |  |
| H400              | Very toxic to aquatic life                                       |  |  |
| H402              | Harmful to aquatic life  |  |  |
| H410              | Very toxic to aquatic life with long lasting effects             |  |  |

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

NA GHS SDS 2015 (Can, US)