

Safety Data Sheet According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015). Revision Date: 07/08/2019 Date of Issue: 06/13/2019 Version: 1.1

SECTION 1: IDENTIFICATION

1.1. **Product Identifier** Product Form: Mixture

Product Name: MVIS[™] Premium Mortar Bed

Product Code: 0229-0060-21 (108), 0229-0060-41 (108)

1.2. Intended Use of the Product

Mortar

1.3. Name, Address, and Telephone of the Responsible Party

Company

LATICRETE International 1 Laticrete Park, N Bethany, CT 06524 T (203)-393-0010

Company LATICRETE Canada ULC PO Box 129, Emeryville, Ontario, Canada NOR-1A0 (833)-254-9255

www.laticrete.com

1.4. **Emergency Telephone Number**

Emergency Number : For Chemical Emergency Call ChemTel day or night Within USA and Canada: 1.800.255.3924 Mexico: 1.800.099.0731 Outside USA and Canada: 1.813.248.0585 (collect calls accepted)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture 2.1.

GHS-US/CA Classification

Skin Corr. 1C	H314
Eye Dam. 1	H318
Skin Sens. 1	H317
Carc. 1A	H350
STOT SE 3	H335
STOT RE 1	H372

Full text of hazard classes and H-statements : see section 16

2.2. Label Elements

GHS-US/CA Labeling

Hazard Pictograms (GHS-US/CA)



Signal Word (GHS-US/CA)	: Danger
Hazard Statements (GHS-US/CA)	: H314 - Causes severe skin burns and eye damage.
	H317 - May cause an allergic skin reaction.
	H318 - Causes serious eye damage.
	H335 - May cause respiratory irritation.
	H350 - May cause cancer (Inhalation).
	H372 - Causes damage to organs (lungs) through prolonged or repeated exposure
	(Inhalation).
Precautionary Statements (GHS-US/CA)	: P201 - Obtain special instructions before use.
	P202 - Do not handle until all safety precautions have been read and understood.
	P260 - Do not breathe dust.
	P264 - Wash hands, forearms and face thoroughly after handling.
	P270 - Do not eat, drink or smoke when using this product.
	P271 - Use only outdoors or in a well-ventilated area.

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

P272 - Contaminated work clothing should not be allowed out of the workplace.

P280 - Wear protective gloves, protective clothing, and eye protection.

P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 - If exposed or concerned: Get medical advice/attention.

P310 - Immediately call a POISON CENTER or doctor.

P314 - Get medical advice/attention if you feel unwell.

P321 - Specific treatment (see section 4 on this SDS).

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

P362+P364 - Take off contaminated clothing and wash it before reuse.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P405 - Store locked up.

P501 - Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

2.4. Unknown Acute Toxicity (GHS-US/CA)

No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

3.2. Mixture

Name	Product Identifier	% *	GHS Ingredient Classification
Quartz	(CAS-No.) 14808-60-7	67 - 68	Carc. 1A, H350
			STOT SE 3, H335
			STOT RE 1, H372
Cement, portland, chemicals	(CAS-No.) 65997-15-1	10 - 30	Skin Irrit. 2, H315
			Eye Dam. 1, H318
			Skin Sens. 1, H317
			STOT SE 3, H335
Calcium oxide	(CAS-No.) 1305-78-8	14 - 18	Skin Irrit. 2, H315
			Eye Dam. 1, H318
			STOT SE 3, H335
			Aquatic Acute 3, H402
Limestone	(CAS-No.) 1317-65-3	<= 1.3	Not classified
Silicic acid (H4SiO4), calcium salt (1:2)	(CAS-No.) 10034-77-2	<= 1.3	Eye Irrit. 2A, H319
Magnesium oxide (MgO)	(CAS-No.) 1309-48-4	<= 0.8	Not classified
Potassium oxide (K2O)	(CAS-No.) 12136-45-7	0.01 - 0.06	PHNOC 1
			Skin Corr. 1A, H314
			Eye Dam. 1, H318
Phosphorus oxide (P2O5)	(CAS-No.) 1314-56-3	< 0.02	Skin Corr. 1A, H314
			Eye Dam. 1, H318
Chromium, ion (Cr6+)	(CAS-No.) 18540-29-9	<= 0.00003	Skin Sens. 1, H317
			Carc. 1B, H350
			Aquatic Acute 1, H400
			Aquatic Chronic 1, H410

Full text of H-phrases: see section 16

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

*Percentages are listed in weight by weight percentage (w/w%) for liquid and solid ingredients. Gas ingredients are listed in volume by volume percentage (v/v%).

** The actual concentration of ingredient(s) is withheld as a trade secret in accordance with the Hazardous Products Regulations (HPR) SOR/2015-17 and 29 CFR 1910.1200.

SECTION 4: FIRST AID MEASURES

4.1. Description of First-aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Inhalation: Remove to fresh air and keep at rest in a position comfortable for breathing. Immediately call a poison center or doctor/physician.

Skin Contact: Immediately remove contaminated clothing. Immediately flush skin with plenty of water for at least 30 minutes. Get immediate medical advice/attention.

Eye Contact: Immediately rinse with water for at least 30 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.

Ingestion: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

General: May cause respiratory irritation. May cause cancer. Causes damage to organs through prolonged or repeated exposure. Skin sensitization. Causes severe skin burns and eye damage.

Inhalation: Irritation of the respiratory tract and the other mucous membranes. Dust may be harmful or cause irritation.

Skin Contact: When this product is wet it is corrosive. Cement may cause dry skin, discomfort, irritation, severe burns, and dermatitis. Exposure of sufficient duration to wet cement, or to dry cement on moist areas of the body, can cause serious, potentially irreversible damage to skin, eye, respiratory and digestive tracts due to chemical (caustic) burns, including third degree burns. A skin exposure may be hazardous even if there is no pain or discomfort. Cement is capable of causing dermatitis by irritation and allergy. Skin affected by dermatitis may include symptoms such as, redness, itching, rash, scaling, and cracking. Irritant dermatitis is caused by the physical properties of cement including alkalinity and abrasion. Allergic contact dermatitis is caused by sensitization to hexavalent chromium (chromate) present in cement. The reaction can range from a mild rash to severe skin ulcers. Persons already sensitized may react to the first contact with cement. Others may develop allergic dermatitis after years of repeated contact with cement.

Eye Contact: Concrete may cause immediate or delayed irritation or inflammation. Eye contact with wet concrete can cause moderate eye irritation, chemical burns and blindness. Eye exposures require immediate first aid and medical attention to prevent significant damage to the eye.

Ingestion: May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.

Chronic Symptoms: May cause cancer. Causes damage to organs through prolonged or repeated exposure. Long term exposure to respirable crystalline silica results in a significant risk of developing silicosis and other non-malignant respiratory disease, lung cancer, kidney effects, and immune system effects.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not considered flammable but may burn at high temperatures.

Explosion Hazard: Product is not explosive.

Reactivity: Calcium oxide reacts with water to form corrosive calcium hydroxide, with evolution of much heat. Temperatures as high as 800° C (1472 °F) have been reached with addition of water (moisture in air or soil). Quartz (silica) will dissolve in hydroflouric acid producing a corrosive gas, silicon tetrafluoride.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Hazardous Combustion Products: Carbon oxides (CO, CO₂). Crystalline silica exists in several forms, the most common of which is quartz. If crystalline silica (quartz) is heated to more than 870°C (1598 °F), it can change to a form of crystalline silica known as trydimite, and if crystalline silica (quartz) is heated to more than 1470°C (2678 °F), it can change to a form of crystalline silica known as cristobalite. The OSHA PEL for crystalline silica as trydimite and cristobalite is one-half of the OSHA PEL for crystalline silica (quartz).

5.4. Reference to Other Sections

Refer to Section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not breathe dust. Do not get in eyes, on skin, or on clothing. Do not handle until all safety precautions have been read and understood.

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protective equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area.

6.2. Environmental Precautions

Prevent entry to sewers and public waters.

6.3. Methods and Materials for Containment and Cleaning Up

For Containment: Contain solid spills with appropriate barriers and prevent migration and entry into sewers or streams. As an immediate precautionary measure, isolate spill or leak area in all directions.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Recover the product by vacuuming, shoveling or sweeping. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill. Cautiously neutralize spilled solid.

6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Additional Hazards When Processed: May release corrosive vapors.

Precautions for Safe Handling: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid contact with eyes, skin and clothing. Do not breathe dust. Handle empty containers with care because they may still present a hazard.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store locked up/in a secure area. Store in original container or corrosive resistant and/or lined container.

Incompatible Materials: Strong acid. Strong oxidizers. Calcium oxide reacts with water to form corrosive calcium hydroxide, with evolution of much heat. Temperatures as high as 800° C (1472 °F) have been reached with addition of water (moisture in air or soil).

7.3. Specific End Use(s)

Mortar

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), or Canadian provincial governments.

Quartz (14808-60-7)

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

		According To The Hazardous Products Regulation (February 11, 2015).
USA ACGIH	ACGIH TWA (mg/m ³)	0.025 mg/m ³ (respirable particulate matter)
USA ACGIH	ACGIH chemical category	A2 - Suspected Human Carcinogen
USA OSHA	OSHA PEL (TWA) (mg/m³)	50 μg/m ³ (Respirable crystalline silica)
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	0.05 mg/m ³ (respirable dust)
USA IDLH	US IDLH (mg/m ³)	50 mg/m ³ (respirable dust)
Alberta	OEL TWA (mg/m³)	0.025 mg/m ³ (respirable particulate)
British Columbia	OEL TWA (mg/m³)	0.025 mg/m ³ (respirable)
Manitoba	OEL TWA (mg/m³)	0.025 mg/m ³ (respirable particulate matter)
New Brunswick	OEL TWA (mg/m³)	0.1 mg/m ³ (respirable fraction)
Newfoundland & Labrador	OEL TWA (mg/m³)	0.025 mg/m ³ (respirable particulate matter)
Nova Scotia	OEL TWA (mg/m³)	0.025 mg/m ³ (respirable particulate matter)
Nunavut	OEL TWA (mg/m³)	0.05 mg/m ³ (respirable fraction (Silica - crystalline)
Northwest Territories	OEL TWA (mg/m³)	0.05 mg/m ³ (respirable fraction (Silica - crystalline)
Ontario	OEL TWA (mg/m³)	0.1 mg/m ³ (designated substances regulation-respirable (Silica, crystalline)
Prince Edward Island	OEL TWA (mg/m³)	0.025 mg/m ³ (respirable particulate matter)
Québec	VEMP (mg/m ³)	0.1 mg/m ³ (respirable dust)
Saskatchewan	OEL TWA (mg/m ³)	0.05 mg/m ³ (respirable fraction (Silica - crystalline
		(Trydimite removed))
Yukon	OEL TWA (mg/m ³)	300 particle/mL (Silica - Quartz, crystalline)
Cement, portland, chemicals	(6,)	
USA ACGIH	ACGIH TWA (mg/m ³)	1 mg/m ³ (particulate matter containing no asbestos and
		<1% crystalline silica, respirable particulate matter)
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (total dust)
		5 mg/m ³ (respirable fraction)
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	10 mg/m ³ (total dust)
		5 mg/m ³ (respirable dust)
USA IDLH	US IDLH (mg/m ³)	5000 mg/m ³
Alberta	OEL TWA (mg/m ³)	10 mg/m ³
British Columbia	OEL TWA (mg/m ³)	1 mg/m ³ (particulate matter containing no Asbestos and
		<1% Crystalline silica-respirable particulate)
Manitoba	OEL TWA (mg/m ³)	1 mg/m ³ (particulate matter containing no Asbestos and
		<1% Crystalline silica, respirable particulate matter-
		particulate matter, respirable particulate matter)
New Brunswick	OEL TWA (mg/m ³)	10 mg/m ³ (particulate matter containing no Asbestos and
		<1% Crystalline silica)
Newfoundland & Labrador	OEL TWA (mg/m ³)	1 mg/m ³ (particulate matter containing no Asbestos and
		<1% Crystalline silica, respirable particulate matter-
		particulate matter, respirable particulate matter)
Nova Scotia	OEL TWA (mg/m³)	1 mg/m ³ (particulate matter containing no Asbestos and
		<1% Crystalline silica, respirable particulate matter-
		particulate matter, respirable particulate matter)
Nunavut	OEL STEL (mg/m³)	20 mg/m ³
Nunavut	OEL TWA (mg/m³)	10 mg/m ³
Northwest Territories	OEL STEL (mg/m ³)	20 mg/m ³
Northwest Territories	OEL TWA (mg/m ³)	10 mg/m ³
Northwest Territories Ontario		10 mg/m³ 1 mg/m³ (containing no Asbestos and <1% Crystalline
	OEL TWA (mg/m ³)	
	OEL TWA (mg/m ³)	1 mg/m ³ (containing no Asbestos and <1% Crystalline
Ontario	OEL TWA (mg/m ³) OEL TWA (mg/m ³)	1 mg/m ³ (containing no Asbestos and <1% Crystalline silica-respirable)

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Québec	VEMP (mg/m ³)	ons And According To The Hazardous Products Regulation (February 11, 2015). 10 mg/m ³ (containing no Asbestos and <1% Crystalline
-		silica-total dust)
		5 mg/m ³ (containing no Asbestos and <1% Crystalline
		silica-respirable dust)
Saskatchewan	OEL STEL (mg/m ³)	20 mg/m ³
Saskatchewan	OEL TWA (mg/m³)	10 mg/m ³
Yukon	OEL STEL (mg/m ³)	20 mg/m ³
Yukon	OEL TWA (mg/m³)	30 mppcf
		10 mg/m ³
Calcium oxide (1305-78-8)		
USA ACGIH	ACGIH TWA (mg/m ³)	2 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	2 mg/m ³
USA IDLH	US IDLH (mg/m ³)	25 mg/m ³
Alberta	OEL TWA (mg/m ³)	2 mg/m ³
British Columbia	OEL TWA (mg/m ³)	2 mg/m ³
Manitoba	OEL TWA (mg/m ³)	2 mg/m ³
New Brunswick	OEL TWA (mg/m ³)	2 mg/m ³
Newfoundland & Labrador	OEL TWA (mg/m ³)	2 mg/m ³
Nova Scotia	OEL TWA (mg/m ³)	2 mg/m ³
Nunavut	OEL STEL (mg/m ³)	4 mg/m ³
Nunavut	OEL TWA (mg/m ³)	2 mg/m ³
Northwest Territories	OEL STEL (mg/m ³)	4 mg/m ³
Northwest Territories	OEL TWA (mg/m ³)	2 mg/m ³
Ontario	OEL TWA (mg/m³)	2 mg/m ³
Prince Edward Island	OEL TWA (mg/m ³)	2 mg/m ³
Québec	VEMP (mg/m ³)	2 mg/m ³
Saskatchewan	OEL STEL (mg/m ³)	4 mg/m ³
Saskatchewan	OEL TWA (mg/m³)	2 mg/m ³
Yukon	OEL STEL (mg/m ³)	4 mg/m ³
Yukon	OEL TWA (mg/m³)	2 mg/m ³
Limestone (1317-65-3)	·	
USA OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (total dust)
		5 mg/m ³ (respirable fraction)
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	10 mg/m ³ (total dust)
		5 mg/m ³ (respirable dust)
Alberta	OEL TWA (mg/m ³)	10 mg/m ³
British Columbia	OEL STEL (mg/m ³)	20 mg/m ³ (total)
British Columbia	OEL TWA (mg/m ³)	10 mg/m ³ (total dust)
		3 mg/m ³ (respirable fraction)
New Brunswick	OEL TWA (mg/m³)	10 mg/m ³ (particulate matter containing no Asbestos and
		<1% Crystalline silica)
Nunavut	OEL STEL (mg/m ³)	20 mg/m ³
Nunavut	OEL TWA (mg/m³)	10 mg/m ³
Northwest Territories	OEL STEL (mg/m ³)	20 mg/m ³
Northwest Territories	OEL TWA (mg/m³)	10 mg/m ³
Québec	VEMP (mg/m ³)	10 mg/m ³ (Limestone, containing no Asbestos and <1%
		Crystalline silica-total dust)
Saskatchewan	OEL STEL (mg/m ³)	20 mg/m ³
Saskatchewan	OEL TWA (mg/m³)	10 mg/m ³
Yukon	OEL STEL (mg/m ³)	20 mg/m ³
Yukon	OEL TWA (mg/m ³)	30 mppcf

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

		10 mg/m ³
Magnesium oxide (MgO) (13	200-48-4)	10 mg/m
USA ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³ (inhalable particulate matter)
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (fume, total particulate)
	US IDLH (mg/m ³)	750 mg/m ³ (fume)
USA IDLH		10 mg/m ³ (fume)
Alberta	OEL TWA (mg/m ³)	
British Columbia	OEL STEL (mg/m ³)	10 mg/m ³ (respirable dust and fume)
British Columbia	OEL TWA (mg/m³)	10 mg/m ³ (fume, inhalable)
Manitoba	$O[1, T] \lambda (\lambda (mg/m^3))$	3 mg/m ³ (respirable dust and fume)
	OEL TWA (mg/m ³) OEL TWA (mg/m ³)	10 mg/m ³ (inhalable particulate matter)
New Brunswick		10 mg/m ³ (fume)
Newfoundland & Labrador	OEL TWA (mg/m ³)	10 mg/m ³ (inhalable particulate matter)
Nova Scotia	OEL TWA (mg/m ³)	10 mg/m ³ (inhalable particulate matter)
Nunavut	OEL STEL (mg/m ³)	20 mg/m ³ (inhalable fraction)
Nunavut	OEL TWA (mg/m ³)	10 mg/m ³ (inhalable fraction)
Northwest Territories	OEL STEL (mg/m ³)	20 mg/m ³ (inhalable fraction)
Northwest Territories	OEL TWA (mg/m³)	10 mg/m ³ (inhalable fraction)
Ontario	OEL TWA (mg/m ³)	10 mg/m ³ (inhalable)
Prince Edward Island	OEL TWA (mg/m ³)	10 mg/m ³ (inhalable particulate matter)
Québec	VEMP (mg/m ³)	10 mg/m ³ (fume)
Saskatchewan	OEL STEL (mg/m ³)	20 mg/m ³ (inhalable fraction)
Saskatchewan	OEL TWA (mg/m ³)	10 mg/m ³ (inhalable fraction)
Yukon	OEL STEL (mg/m³)	10 mg/m ³ (fume)
Yukon	OEL TWA (mg/m³)	10 mg/m ³ (fume)
Chromium, ion (Cr6+) (1854	0-29-9)	
USA OSHA	OSHA PEL (TWA) (mg/m³)	5 μg/m³
Particulates not otherwise c	lassified (PNOC) (Not applicable)	
USA ACGIH	ACGIH TWA (mg/m ³)	3 mg/m ³ Respirable fraction
		10 mg/m ³ Total Dust
USA OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³ Respirable fraction
		15 mg/m ³ Total Dust
Alberta	OEL TWA (mg/m³)	10 mg/m ³ (total)
		3 mg/m ³ (respirable)
British Columbia	OEL TWA (mg/m³)	10 mg/m ³ (nuisance dust-total dust)
		3 mg/m ³ (nuisance dust-respirable fraction)
Manitoba	OEL TWA (mg/m³)	10 mg/m ³ (inhalable particles, recommended)
		3 mg/m ³ (respirable particles, recommended)
New Brunswick	OEL TWA (mg/m³)	3 mg/m ³ (particulate matter containing no Asbestos and
		<1% Crystalline silica, respirable fraction)
		10 mg/m ³ (particulate matter containing no Asbestos and
		<1% Crystalline silica, inhalable fraction)
Newfoundland & Labrador	OEL TWA (mg/m³)	10 mg/m ³ (inhalable particles, recommended)
		3 mg/m ³ (respirable particles, recommended)
Nova Scotia	OEL TWA (mg/m³)	10 mg/m ³ (inhalable particles, recommended)
		3 mg/m ³ (respirable particles, recommended)
Nunavut	OEL STEL (mg/m³)	20 mg/m ³ (insoluble or poorly soluble-inhalable fraction)
		6 mg/m ³ (insoluble or poorly soluble-respirable fraction)
Nunavut	OEL TWA (mg/m³)	10 mg/m ³ (insoluble or poorly soluble-inhalable fraction)
		3 mg/m ³ (insoluble or poorly soluble-respirable fraction)
Northwest Territories	OEL STEL (mg/m³)	20 mg/m ³ (insoluble or poorly soluble-inhalable fraction)
		6 mg/m ³ (insoluble or poorly soluble-respirable fraction)

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Northwest Territories	OEL TWA (mg/m ³)	10 mg/m ³ (insoluble or poorly soluble-inhalable fraction)
		3 mg/m ³ (insoluble or poorly soluble-respirable fraction)
Ontario	OEL TWA (mg/m ³)	10 mg/m ³ (inhalable)
		3 mg/m ³ (respirable)
Prince Edward Island	OEL TWA (mg/m ³)	10 mg/m ³ (inhalable particles, recommended)
		3 mg/m ³ (respirable particles, recommended)
Québec	VEMP (mg/m ³)	10 mg/m ³ (including dust, inert or nuisance particulates-
		total dust)
Saskatchewan	OEL STEL (mg/m ³)	20 mg/m ³ (insoluble or poorly soluble-inhalable fraction)
		6 mg/m ³ (insoluble or poorly soluble-respirable fraction)
Saskatchewan	OEL TWA (mg/m ³)	10 mg/m ³ (insoluble or poorly soluble-inhalable fraction)
		3 mg/m ³ (insoluble or poorly soluble-respirable fraction)

8.2. Exposure Controls

Appropriate Engineering Controls: Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Personal Protective Equipment: Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection. Face shield.



Materials for Protective Clothing: Chemically resistant materials and fabrics. Corrosion-proof clothing.

Hand Protection: Wear protective gloves.

Eye and Face Protection: Chemical safety goggles and face shield.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

Other Information: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties		
Physical State	:	Solid
Appearance	:	Grey Powder
Odor	:	Not available
Odor Threshold	:	Not available
рН	:	Not available
Evaporation Rate	:	Not available
Melting Point	:	Not available
Freezing Point	:	Not available
Boiling Point	:	Not available
Flash Point	:	Not available
Auto-ignition Temperature	:	Not available
Decomposition Temperature	:	Not available
Flammability (solid, gas)	:	Not available
Lower Flammable Limit	:	Not available
Upper Flammable Limit	:	Not available
Vapor Pressure	:	Not available
Relative Vapor Density at 20°C	:	Not available
Relative Density	:	Not available
Specific Gravity	:	Not available
07/00/2010 EN//		116)

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Sol	ubi	itv
30	ubi	iity

Partition Coefficient: N-Octanol/Water

: Water: Insoluble Not available • Not available

Viscosity

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity: Calcium oxide reacts with water to form corrosive calcium hydroxide, with evolution of much heat. Temperatures as high as 800° C (1472 °F) have been reached with addition of water (moisture in air or soil). Quartz (silica) will dissolve in hydroflouric acid producing a corrosive gas, silicon tetrafluoride.

10.2. Chemical Stability: Stable under recommended handling and storage conditions (see section 7).

:

10.3. Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

10.4. **Conditions to Avoid:** Direct sunlight, extremely high or low temperatures, and incompatible materials.

10.5. Incompatible Materials: Strong acid. Strong oxidizers. Calcium oxide reacts with water to form corrosive calcium hydroxide, with evolution of much heat. Temperatures as high as 800° C (1472 °F) have been reached with addition of water (moisture in air or soil).

10.6. Hazardous Decomposition Products: Thermal decomposition generates : Corrosive vapors. Limestone and Dolomite decomposes at 825 °C (1517 °F) producing Calcium and Magnesium Oxide. Adding water produces (caustic) calcium hydroxide.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. **Information on Toxicological Effects - Product**

Acute Toxicity (Oral): Not classified Acute Toxicity (Dermal): Not classified

Acute Toxicity (Inhalation): Not classified

LD50 and LC50 Data: Not available

Skin Corrosion/Irritation: Causes severe skin burns and eye damage.

Eye Damage/Irritation: Causes serious eye damage.

Respiratory or Skin Sensitization: May cause an allergic skin reaction.

Germ Cell Mutagenicity: Not classified

Carcinogenicity: May cause cancer (Inhalation).

Specific Target Organ Toxicity (Repeated Exposure): Causes damage to organs (lungs) through prolonged or repeated exposure (Inhalation).

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): May cause respiratory irritation.

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: Irritation of the respiratory tract and the other mucous membranes. Dust may be harmful or cause irritation.

Symptoms/Injuries After Skin Contact: When this product is wet it is corrosive. Cement may cause dry skin, discomfort, irritation, severe burns, and dermatitis. Exposure of sufficient duration to wet cement, or to dry cement on moist areas of the body, can cause serious, potentially irreversible damage to skin, eye, respiratory and digestive tracts due to chemical (caustic) burns, including third degree burns. A skin exposure may be hazardous even if there is no pain or discomfort. Cement is capable of causing dermatitis by irritation and allergy. Skin affected by dermatitis may include symptoms such as, redness, itching, rash, scaling, and cracking. Irritant dermatitis is caused by the physical properties of cement including alkalinity and abrasion. Allergic contact dermatitis is caused by sensitization to hexavalent chromium (chromate) present in cement. The reaction can range from a mild rash to severe skin ulcers. Persons already sensitized may react to the first contact with cement. Others may develop allergic dermatitis after years of repeated contact with cement.

Symptoms/Injuries After Eye Contact: Concrete may cause immediate or delayed irritation or inflammation. Eye contact with wet concrete can cause moderate eye irritation, chemical burns and blindness. Eye exposures require immediate first aid and medical attention to prevent significant damage to the eye.

Symptoms/Injuries After Ingestion: May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract. Chronic Symptoms: May cause cancer. Causes damage to organs through prolonged or repeated exposure. Long term exposure to respirable crystalline silica results in a significant risk of developing silicosis and other non-malignant respiratory disease, lung cancer, kidney effects, and immune system effects.

Information on Toxicological Effects - Ingredient(s) 11.2. LD50 and LC50 Data:

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Quartz (14808-60-7)		
LD50 Oral Rat	> 5000 mg/kg	
LD50 Dermal Rat	> 5000 mg/kg	
Calcium oxide (1305-78-8)		
LD50 Oral Rat	> 2000 mg/kg	
LD50 Dermal Rabbit	> 2500 mg/kg	
Magnesium oxide (MgO) (1309-48-4)		
LD50 Oral Rat	3870 mg/kg	
Phosphorus oxide (P2O5) (1314-56-3)		
LC50 Inhalation Rat	1217 mg/m³ (Exposure time: 1 h)	
ATE US/CA (vapors)	1,217.00 mg/l/4h	
ATE US/CA (dust, mist)	1,217.00 mg/l/4h	
Quartz (14808-60-7)		
IARC Group	1	
National Toxicology Program (NTP) Status	Known Human Carcinogens.	
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.	
Chromium, ion (Cr6+) (18540-29-9)		
IARC Group	1	
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.	
OSHA Specifically Regulated Carcinogen List	In OSHA Specifically Regulated Carcinogen list.	

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - General: Not classified.

Calcium oxide (1305-78-8)	
LC50 Fish 1	50.6 mg/l
Chromium, ion (Cr6+) (18540-29-9)	
LC50 Fish 1	36.2 mg/l (Exposure time: 96 h - Species: Pimephales promelas)
LC50 Fish 2	7.6 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)

12.2. Persistence and Degradability

MVIS [™] Premium Mortar Bed	
Persistence and Degradability	Not established.
12.3. Bioaccumulative Potential	
MVIS [™] Premium Mortar Bed	
Bioaccumulative Potential	Not established.
Calcium oxide (1305-78-8)	
BCF Fish 1	(no bioaccumulation)
12.4. Mobility in Soil Not av	vailable

Mobility in Soil 12.4.

12.5. **Other Adverse Effects**

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste Disposal Recommendations: Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

Additional Information: Container may remain hazardous when empty. Continue to observe all precautions.

Ecology - Waste Materials: Avoid release to the environment.

SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

- 14.1. In Accordance with DOT Not regulated for transport
- 14.2. In Accordance with IMDG Not regulated for transport
- 14.3. In Accordance with IATA Not regulated for transport
- 14.4. In Accordance with TDG Not regulated for transport

SECTION 15: REGULATORY INFORMATION

US Federal Regulations 15.1.

MVIS[™] Premium Mortar Bed

SARA Section 311/312 Hazard Classes	Health hazard - Specific target organ toxicity (single or repeated
	exposure)
	Health hazard - Carcinogenicity
	Health hazard - Respiratory or skin sensitization
	Health hazard - Serious eye damage or eye irritation
	Health hazard - Skin corrosion or Irritation
Quarte (14000 CO 7)	

Quartz (14808-60-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Cement, portland, chemicals (65997-15-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Calcium oxide (1305-78-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Silicic acid (H4SiO4), calcium salt (1:2) (10034-77-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Limestone (1317-65-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Magnesium oxide (MgO) (1309-48-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Phosphorus oxide (P2O5) (1314-56-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Potassium oxide (K2O) (12136-45-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. **US State Regulations**

California Proposition 65

WARNING: This product can expose you to Chromium, ion (Cr6+), which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Chemical Name (CAS No.)	Carcinogenicity	Developmental Toxicity	Female Reproductive Toxicity	Male Reproductive Toxicity
Quartz (14808-60-7)	Х			
Chromium, ion (Cr6+) (18540-	Х	Х		
29-9)				
Quartz (14808-60-7)				
U.S Massachusetts - Right To K	now List			
U.S New Jersey - Right to Know	/ Hazardous Substance I	_ist		
U.S Pennsylvania - RTK (Right to	o Know) List			
Cement, portland, chemicals (65	997-15-1)			
U.S Massachusetts - Right To K	now List			
U.S New Jersey - Right to Know	/ Hazardous Substance I	_ist		
U.S Pennsylvania - RTK (Right te	o Know) List			
Calcium oxide (1305-78-8)				
U.S Massachusetts - Right To K	now List			
U.S New Jersey - Right to Know	/ Hazardous Substance I	_ist		
U.S Pennsylvania - RTK (Right to	o Know) List			
07/08/2019	EN (English U	IS)		11/

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Limestone (1317-65-3)
U.S Massachusetts - Right To Know List
U.S New Jersey - Right to Know Hazardous Substance List
U.S Pennsylvania - RTK (Right to Know) List
Magnesium oxide (MgO) (1309-48-4)
U.S Massachusetts - Right To Know List
U.S New Jersey - Right to Know Hazardous Substance List
U.S Pennsylvania - RTK (Right to Know) List
Chromium, ion (Cr6+) (18540-29-9)
U.S Pennsylvania - RTK (Right to Know) - Environmental Hazard List
U.S Pennsylvania - RTK (Right to Know) List
Phosphorus oxide (P2O5) (1314-56-3)
U.S Massachusetts - Right To Know List
U.S New Jersey - Right to Know Hazardous Substance List
U.S Pennsylvania - RTK (Right to Know) - Environmental Hazard List
U.S Pennsylvania - RTK (Right to Know) List
Potassium oxide (K2O) (12136-45-7)
U.S New Jersey - Right to Know Hazardous Substance List

15.3. Canadian Regulations

Quartz (14808-60-7)	
isted on the Canadian DSL (Domestic Substances List)	
Cement, portland, chemicals (65997-15-1)	
isted on the Canadian DSL (Domestic Substances List)	
Calcium oxide (1305-78-8)	
isted on the Canadian DSL (Domestic Substances List)	
Silicic acid (H4SiO4), calcium salt (1:2) (10034-77-2)	
isted on the Canadian DSL (Domestic Substances List)	
imestone (1317-65-3)	
isted on the Canadian NDSL (Non-Domestic Substances List)	
Magnesium oxide (MgO) (1309-48-4)	
isted on the Canadian DSL (Domestic Substances List)	
Phosphorus oxide (P2O5) (1314-56-3)	
Listed on the Canadian DSL (Domestic Substances List)	
Potassium oxide (K2O) (12136-45-7)	
isted on the Canadian DSL (Domestic Substances List)	
	_

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Regulations (HPR) SOR/2015-17.

Date of Preparation or Latest	: 07/08/2019
Revision	
Other Information	: This document has been prepared in accordance with the SDS requirements of the OSHA
	Hazard Communication Standard 29 CFR 1910.1200 and Canada's Hazardous Products

GHS Full Text Phrases:

Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Carc. 1A	Carcinogenicity Category 1A
Carc. 1B	Carcinogenicity Category 1B
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

PHNOC 1	Physical hazard not otherwise classified, category 1
Skin Corr. 1A	Skin corrosion/irritation Category 1A
Skin Corr. 1C	Skin corrosion/irritation Category 1C
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization, Category 1
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H350	May cause cancer
H372	Causes damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

NA GHS SDS 2015 (Can, US)