

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous

Products Regulation (February 11, 2015).

Revision Date: 03/02/2022 Date of Issue: 10/26/2020 Version: 1.1

#### **SECTION 1: IDENTIFICATION**

## 1.1. Product Identifier

**Product Form:** Mixture

Product Name: SPARTACOTE® FLEX SB™ Part A

#### 1.2. Intended Use of the Product

Decorative coating.

#### 1.3. Name, Address, and Telephone of the Responsible Party

Company Company

LATICRETE International LATICRETE Canada ULC

1 Laticrete Park, N PO Box 129, Emeryville, Ontario, Canada

Bethany, CT 06524 NOR-1A0 T (203)-393-0010 (833)-254-9255

www.laticrete.com

#### 1.4. Emergency Telephone Number

**Emergency Number**: For Chemical Emergency call ChemTel Inc. day or night:

(800)255-3924 (North America) (800)-099-0731 (Mexico)

+1 (813)248-0585 (International - collect calls accepted)

#### **SECTION 2: HAZARDS IDENTIFICATION**

#### 2.1. Classification of the Substance or Mixture

#### **GHS-US/CA Classification**

Flam. Liq. 3 H226 Skin Irrit. 2 H315 Skin Sens. 1 H317 Muta. 1B H340 Carc. 1B H350 Repr. 2 H361 STOT SE 3 H336 Asp. Tox. 1 H304 H401 Aquatic Acute 2 Aquatic Chronic 2 H411

Full text of hazard classes and H-statements: see section 16

#### 2.2. Label Elements

#### **GHS-US/CA Labeling**

Hazard Pictograms (GHS-US/CA)



GH507





Signal Word (GHS-US/CA) : Danger

Hazard Statements (GHS-US/CA) : H226 - Flammable liquid and vapor.

H304 - May be fatal if swallowed and enters airways.

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction. H336 - May cause drowsiness or dizziness.

H340 - May cause genetic defects.

H350 - May cause cancer.

H361 - Suspected of damaging fertility or the unborn child.

H401 - Toxic to aquatic life.

H411 - Toxic to aquatic life with long lasting effects.

03/02/2022 EN (English US) 1/10

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

#### Precautionary Statements (GHS-US/CA): P201 - Obtain special instructions before use.

- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical, ventilating, and lighting equipment.
- P242 Use only non-sparking tools.
- P243 Take action to prevent static discharges.
- P261 Avoid breathing vapors, mist, or spray.
- P264 Wash hands, forearms, and other exposed areas thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P273 Avoid release to the environment.
- P280 Wear protective gloves, protective clothing, and eye protection.
- P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P308+P313 If exposed or concerned: Get medical advice/attention.
- P312 Call a POISON CENTER or doctor if you feel unwell.
- P321 Specific treatment (see section 4 on this SDS).
- P331 Do NOT induce vomiting.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P370+P378 In case of fire: Use appropriate media (see section 5) to extinguish.
- P391 Collect spillage.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local, regional, national, and international regulations.

#### 2.3. **Other Hazards**

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

#### **Unknown Acute Toxicity (GHS-US/CA)**

No data available

#### **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

#### 3.1. **Substance**

Not applicable

#### 3.2. Mixture

Name	Product Identifier	% *	<b>GHS Ingredient Classification</b>
DL-Aspartic acid, N,N'-(methylenedi-	(CAS-No.) 136210-30-5	50 - 63	Skin Sens. 1, H317
4,1-cyclohexanediyl)bis-, tetraethyl			Aquatic Chronic 3, H412
ester			
Solvent naphtha, petroleum, light	(CAS-No.) 64742-95-6	15 - 40	Flam. Liq. 1, H224
aromatic			Skin Irrit. 2, H315
			Muta. 1B, H340
			Carc. 1B, H350
			Repr. 2, H361
			STOT SE 3, H336
			Asp. Tox. 1, H304
			Aguatic Acute 2, H401

03/02/2022 EN (English US) 2/10

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

			Aquatic Chronic 2, H411
Fumaric acid, diethyl ester	(CAS-No.) 623-91-6	1 - 3	Acute Tox. 4 (Oral), H302
			Skin Sens. 1, H317
			Aquatic Acute 2, H401
			Aquatic Chronic 3, H412
D-Limonene	(CAS-No.) 5989-27-5	0.5 - 1.5	Flam. Liq. 3, H226
			Skin Irrit. 2, H315
			Skin Sens. 1B, H317
			Asp. Tox. 1, H304
			Aquatic Acute 1, H400
			Aquatic Chronic 1, H410
Stoddard solvent	(CAS-No.) 8052-41-3	0.21 - 0.215	Flam. Liq. 3, H226
			Skin Irrit. 2, H315
			Muta. 1B, H340
			Carc. 1B, H350
			STOT RE 1, H372
			Asp. Tox. 1, H304
			Aquatic Chronic 2, H411

Full text of H-phrases: see section 16

## **SECTION 4: FIRST AID MEASURES**

#### 4.1. Description of First-aid Measures

**General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

**Inhalation:** When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

**Skin Contact:** Immediately remove contaminated clothing. Immediately drench affected area with water for at least 15 minutes. If exposed or concerned: Get medical advice/attention.

**Eye Contact:** Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with water for at least 15 minutes. Obtain medical attention.

Ingestion: Do NOT induce vomiting. Rinse mouth. Immediately call a POISON CENTER or doctor/physician.

#### 4.2. Most Important Symptoms and Effects Both Acute and Delayed

**General:** May cause drowsiness and dizziness. May cause cancer. Suspected of damaging fertility or the unborn child. Skin sensitization. Causes skin irritation. May cause genetic defects. May be fatal if swallowed and enters airways.

**Inhalation:** High concentrations may cause central nervous system depression such as dizziness, vomiting, numbness, drowsiness, headache, and similar narcotic symptoms.

Skin Contact: May cause an allergic skin reaction. Redness, pain, swelling, itching, burning, dryness, and dermatitis.

**Eye Contact:** May cause slight irritation to eyes.

Ingestion: Aspiration into the lungs can occur during ingestion or vomiting and may cause lung injury.

Chronic Symptoms: May cause cancer. Suspected of damaging fertility or the unborn child. May cause genetic defects.

#### 4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

## **SECTION 5: FIRE-FIGHTING MEASURES**

#### 5.1. Extinguishing Media

**Suitable Extinguishing Media:** Dry chemical powder, alcohol-resistant foam, carbon dioxide (CO<sub>2</sub>). Water may be ineffective but water should be used to keep fire-exposed container cool.

Unsuitable Extinguishing Media: Do not use a heavy water stream. A heavy water stream may spread burning liquid.

#### 5.2. Special Hazards Arising From the Substance or Mixture

**Fire Hazard:** Flammable liquid and vapor. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks).

03/02/2022 EN (English US) 3/10

<sup>\*</sup>Percentages are listed in weight by weight percentage (w/w%) for liquid and solid ingredients. Gas ingredients are listed in volume by volume percentage (v/v%).

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

**Explosion Hazard:** May form flammable or explosive vapor-air mixture.

**Reactivity:** Reacts violently with strong oxidizers. Increased risk of fire or explosion.

#### 5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

**Firefighting Instructions:** Use water spray or fog for cooling exposed containers. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Smoke. Carbon oxides (CO, CO<sub>2</sub>).

Other Information: Do not allow run-off from fire fighting to enter drains or water courses.

#### 5.4. Reference to Other Sections

Refer to Section 9 for flammability properties.

#### **SECTION 6: ACCIDENTAL RELEASE MEASURES**

#### 6.1. Personal Precautions, Protective Equipment and Emergency Procedures

**General Measures:** Do not get in eyes, on skin, or on clothing. Do not breathe vapor, mist or spray. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Use special care to avoid static electric charges.

#### 6.1.1. For Non-Emergency Personnel

**Protective Equipment:** Use appropriate personal protective equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel. Stop leak if safe to do so.

#### 6.1.2. For Emergency Personnel

**Protective Equipment:** Equip cleanup crew with proper protection.

**Emergency Procedures:** Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area. Eliminate ignition sources.

#### 6.2. Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment. Collect spillage.

#### 6.3. Methods and Materials for Containment and Cleaning Up

**For Containment:** Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. As an immediate precautionary measure, isolate spill or leak area in all directions.

**Methods for Cleaning Up:** Clean up spills immediately and dispose of waste safely. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill. Absorb and/or contain spill with inert material. Do not take up in combustible material such as: saw dust or cellulosic material. Use only non-sparking tools.

#### 6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

#### **SECTION 7: HANDLING AND STORAGE**

## 7.1. Precautions for Safe Handling

Additional Hazards When Processed: Handle empty containers with care because residual vapors are flammable.

**Precautions for Safe Handling:** Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not handle until all safety precautions have been read and understood. Do not breathe mist, spray, vapors. Obtain special instructions before use. Do not get in eyes, on skin, or on clothing. Take precautionary measures against static discharge. Use only non-sparking tools.

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures.

#### 7.2. Conditions for Safe Storage, Including Any Incompatibilities

**Technical Measures:** Comply with applicable regulations. Take action to prevent static discharges. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating, and lighting equipment.

**Storage Conditions:** Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store locked up/in a secure area. Store in a well-ventilated place. Keep container tightly closed. Keep in fireproof place.

**Incompatible Materials:** Strong acids, strong bases, strong oxidizers.

#### 7.3. Specific End Use(s)

Decorative coating.

#### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1. Control Parameters

03/02/2022 EN (English US) 4/10

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), or Canadian provincial governments.

D-Limonene (5989-27-5)			
USA AIHA	WEEL TWA [ppm]	30 ppm	
Stoddard solvent (8052-41-3			
USA ACGIH	ACGIH TWA (ppm)	100 ppm	
USA OSHA	OSHA PEL (TWA) (mg/m³)	2900 mg/m³	
USA OSHA	OSHA PEL (TWA) (ppm)	500 ppm	
USA NIOSH	NIOSH REL (TWA) (mg/m³)	350 mg/m³	
USA NIOSH	NIOSH REL (ceiling) (mg/m³)	1800 mg/m³	
USA IDLH	US IDLH (mg/m³)	20000 mg/m <sup>3</sup>	
Alberta	OEL TWA (mg/m³)	572 mg/m³	
Alberta	OEL TWA (ppm)	100 ppm	
British Columbia	OEL STEL (mg/m³)	580 mg/m³	
British Columbia	OEL TWA (mg/m³)	290 mg/m³	
Manitoba	OEL TWA (ppm)	100 ppm	
New Brunswick	OEL TWA (mg/m³)	525 mg/m³	
New Brunswick	OEL TWA (ppm)	100 ppm	
Newfoundland & Labrador	OEL TWA (ppm)	100 ppm	
Nova Scotia	OEL TWA (ppm)	100 ppm	
Nunavut	OEL STEL (ppm)	125 ppm	
Nunavut	OEL TWA (ppm)	100 ppm	
Northwest Territories	OEL STEL (ppm)	125 ppm	
Northwest Territories	OEL TWA (ppm)	100 ppm	
Ontario	OEL TWA (mg/m³)	525 mg/m³ (140°F Flash aliphatic solvent)	
Prince Edward Island	OEL TWA (ppm)	100 ppm	
Québec	VEMP (mg/m³)	525 mg/m³	
Québec	VEMP (ppm)	100 ppm	
Saskatchewan	OEL STEL (ppm)	125 ppm	
Saskatchewan	OEL TWA (ppm)	100 ppm	
Yukon	OEL STEL (mg/m³)	720 mg/m <sup>3</sup>	
Yukon	OEL STEL (ppm)	150 ppm	
Yukon	OEL TWA (mg/m³)	575 mg/m³	
Yukon	OEL TWA (ppm)	100 ppm	

#### 8.2. Exposure Controls

**Appropriate Engineering Controls:** Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. Gas detectors should be used when flammable gases or vapors may be released. Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof equipment.

Personal Protective Equipment: Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.









Materials for Protective Clothing: Chemically resistant materials and fabrics. Wear fire/flame resistant/retardant clothing.

Hand Protection: Wear protective gloves.

Eye and Face Protection: Chemical safety goggles.

**Skin and Body Protection:** Wear suitable protective clothing.

03/02/2022 EN (English US) 5/10

Safety Data Sheet

**Boiling Point** 

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

**Respiratory Protection:** If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

138 °C (280.4 °F)

Other Information: When using, do not eat, drink or smoke.

#### **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

## 9.1. Information on Basic Physical and Chemical Properties

Physical State : Liquid

Appearance: Not availableOdor: Not availableOdor Threshold: Not availablepH: Not availableEvaporation Rate: Not availableMelting Point: Not availableFreezing Point: Not available

Flash Point : 51.7 °C Tag Closed Cup (125.06 °F)

**Auto-ignition Temperature** Not available **Decomposition Temperature** Not available Flammability (solid, gas) Not applicable **Lower Flammable Limit** Not available **Upper Flammable Limit** Not available Not available **Vapor Pressure** Not available Relative Vapor Density at 20°C **Relative Density** Not available

Specific Gravity : 0.99

Solubility : Not available
Partition Coefficient: N-Octanol/Water : Not available
Viscosity : Not available

#### **SECTION 10: STABILITY AND REACTIVITY**

- **10.1. Reactivity:** Reacts violently with strong oxidizers. Increased risk of fire or explosion.
- 10.2. Chemical Stability: Flammable liquid and vapor. May form flammable or explosive vapor-air mixture.
- **10.3.** Possibility of Hazardous Reactions: Hazardous polymerization will not occur.
- **10.4. Conditions to Avoid:** Direct sunlight, extremely high or low temperatures, heat, hot surfaces, sparks, open flames, incompatible materials, and other ignition sources.
- **10.5. Incompatible Materials:** Strong acids, strong bases, strong oxidizers.
- 10.6. Hazardous Decomposition Products: Thermal decomposition may produce: Smoke. Carbon oxides (CO, CO<sub>2</sub>).

### **SECTION 11: TOXICOLOGICAL INFORMATION**

#### 11.1. Information on Toxicological Effects - Product

Acute Toxicity (Oral): Not classified
Acute Toxicity (Dermal): Not classified
Acute Toxicity (Inhalation): Not classified

LD50 and LC50 Data: Not available

Skin Corrosion/Irritation: Causes skin irritation.

Eye Damage/Irritation: Not classified

Respiratory or Skin Sensitization: May cause an allergic skin reaction.

Germ Cell Mutagenicity: May cause genetic defects.

Carcinogenicity: May cause cancer.

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: Suspected of damaging fertility or the unborn child.

03/02/2022 EN (English US) 6/10

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Specific Target Organ Toxicity (Single Exposure): May cause drowsiness or dizziness.

Aspiration Hazard: May be fatal if swallowed and enters airways.

**Symptoms/Injuries After Inhalation:** High concentrations may cause central nervous system depression such as dizziness, vomiting, numbness, drowsiness, headache, and similar narcotic symptoms.

**Symptoms/Injuries After Skin Contact:** May cause an allergic skin reaction. Redness, pain, swelling, itching, burning, dryness, and dermatitis.

Symptoms/Injuries After Eye Contact: May cause slight irritation to eyes.

Symptoms/Injuries After Ingestion: Aspiration into the lungs can occur during ingestion or vomiting and may cause lung injury.

Chronic Symptoms: May cause cancer. Suspected of damaging fertility or the unborn child. May cause genetic defects.

#### 11.2. Information on Toxicological Effects - Ingredient(s)

#### LD50 and LC50 Data:

Solvent naphtha, petroleum, light aromatic (64742-95-6)		
LD50 Oral Rat	8400 mg/kg	
LD50 Dermal Rabbit	> 2000 mg/kg	
LC50 Inhalation Rat	3400 ppm/4h	
Fumaric acid, diethyl ester (623-91-6)		
LD50 Oral Rat	1780 mg/kg	
D-Limonene (5989-27-5)		
LD50 Oral Rat	4400 mg/kg	
LD50 Dermal Rabbit	> 5 g/kg	
Stoddard solvent (8052-41-3)		
LD50 Oral Rat	> 5 g/kg Behavioral somnolence	
LD50 Dermal Rabbit	> 3 g/kg	
LC50 Inhalation Rat	> 5500 mg/l/4h Behavioral somnolence	
D-Limonene (5989-27-5)		
IARC Group	3	
National Toxicology Program (NTP) Status	Evidence of Carcinogenicity.	

#### **SECTION 12: ECOLOGICAL INFORMATION**

#### 12.1. Toxicity

**Ecology - General:** Toxic to aquatic life with long lasting effects.

Solvent naphtha, petroleum, light aromatic (64742-95-6)		
LC50 Fish 1	9.22 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)	
EC50 Daphnia 1	6.14 mg/l (Exposure time: 48 h - Species: Daphnia magna)	
Fumaric acid, diethyl ester (623-91-6)		
LC50 Fish 1	2.4 mg/l	
ErC50 (algae)	1.1 mg/l	
D-Limonene (5989-27-5)		
LC50 Fish 1	0.619 (0.619 – 0.796) mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])	
EC50 Daphnia 1	0.421 mg/l	
LC50 Fish 2	35 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)	
Stoddard solvent (8052-41-3)		
NOEC Chronic Algae	0.16 mg/l	

### 12.2. Persistence and Degradability

SPARTACOTE® FLEX SB™ Part A	
Persistence and Degradability	May cause long-term adverse effects in the environment.

#### 12.3. Bioaccumulative Potential

SPARTACOTE® FLEX SB™ Part A	
Bioaccumulative Potential	Not established.

03/02/2022 EN (English US) 7/10

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Stoddard solvent (8052-41-3)		
Partition coefficient n-octanol/water	3.16 (Octanol/water partition coefficient 3.16/7.06)	
(Log Pow)		

**12.4. Mobility in Soil** Not available

#### 12.5. Other Adverse Effects

Other Information: Avoid release to the environment.

#### **SECTION 13: DISPOSAL CONSIDERATIONS**

#### 13.1. Waste treatment methods

**Waste Disposal Recommendations:** Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

Additional Information: Handle empty containers with care because residual vapors are flammable.

**Ecology - Waste Materials:** Avoid release to the environment. This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

#### **SECTION 14: TRANSPORT INFORMATION**

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

#### 14.1. In Accordance with DOT

Proper Shipping Name : COATING SOLUTION

Hazard Class : 3

**Identification Number** : UN1139

Label Codes : 3
Packing Group : III

Marine Pollutant : Marine pollutant

ERG Number : 127

14.2. In Accordance with IMDG

Proper Shipping Name : COATING SOLUTION

Hazard Class : 3

**Identification Number** : UN1139

Label Codes: 3Packing Group: IIIEmS-No. (Fire): F-EEmS-No. (Spillage): S-E

Marine pollutant : Marine pollutant

#### 14.3. In Accordance with IATA

Proper Shipping Name : COATING SOLUTION

Hazard Class : 3
Identification Number : UN1139

Label Codes: 3Packing Group: IIIERG Code (IATA): 3L



Proper Shipping Name : COATING SOLUTION

Hazard Class : 3
Identification Number : UN1139
Label Codes : 3

Packing Group : III

Marine Pollutant (TDG) : Marine pollutant

## **SECTION 15: REGULATORY INFORMATION**

## 15.1. US Federal Regulations

ςD	ΛRΤΛ	COTE®	FIFY	<b>CR</b> TM	Dart A
ЭP.	ARIA	COIE	LLEV	30	Parla

03/02/2022 EN (English US) 8/10







Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

CADA C	Uselah hasand. Constitutional assessment distribution in a second of	
SARA Section 311/312 Hazard Classes	Health hazard - Specific target organ toxicity (single or repeated	
	exposure)	
	Health hazard - Carcinogenicity	
	Health hazard - Reproductive toxicity	
	Health hazard - Respiratory or skin sensitization	
	Health hazard - Skin corrosion or Irritation	
	Physical hazard - Flammable (gases, aerosols, liquids, or solids)	
	Health hazard - Germ cell mutagenicity	
	Health hazard - Aspiration hazard	
DL-Aspartic acid, N,N'-(methylenedi-4,1-cyclohexanediyl)bis-,	tetraethyl ester (136210-30-5)	
Listed on the United States TSCA (Toxic Substances Control Act	) inventory	
EPA TSCA Regulatory Flag PMN - PMN - indicates a commenced PMN substance.		
Solvent naphtha, petroleum, light aromatic (64742-95-6)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
Fumaric acid, diethyl ester (623-91-6)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
D-Limonene (5989-27-5)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
Stoddard solvent (8052-41-3)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
4F.2 UC Chaha Danulations	· · · · · · · · · · · · · · · · · · ·	

#### 15.2. US State Regulations

#### Stoddard solvent (8052-41-3)

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

U.S. - Massachusetts - Right To Know List

#### 15.3. Canadian Regulations

#### DL-Aspartic acid, N,N'-(methylenedi-4,1-cyclohexanediyl)bis-, tetraethyl ester (136210-30-5)

Listed on the Canadian DSL (Domestic Substances List)

#### Solvent naphtha, petroleum, light aromatic (64742-95-6)

Listed on the Canadian DSL (Domestic Substances List)

#### Fumaric acid, diethyl ester (623-91-6)

Listed on the Canadian NDSL (Non-Domestic Substances List)

#### D-Limonene (5989-27-5)

Listed on the Canadian DSL (Domestic Substances List)

#### Stoddard solvent (8052-41-3)

Listed on the Canadian DSL (Domestic Substances List)

## SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

**Date of Preparation or Latest** : 03/02/2022

Revision

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA

Hazard Communication Standard 29 CFR 1910.1200 and Canada's Hazardous Products

Regulations (HPR) SOR/2015-17.

#### **GHS Full Text Phrases:**

Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3

03/02/2022 EN (English US) 9/10

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Asp. Tox. 1	Aspiration hazard Category 1
Carc. 1B	Carcinogenicity Category 1B
Flam. Liq. 1	Flammable liquids Category 1
Flam. Liq. 3	Flammable liquids Category 3
Muta. 1B	Germ cell mutagenicity Category 1B
Repr. 2	Reproductive toxicity Category 2
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization, Category 1
Skin Sens. 1B	Skin sensitization, category 1B
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H224	Extremely flammable liquid and vapor
H226	Flammable liquid and vapor
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H336	May cause drowsiness or dizziness
H340	May cause genetic defects
H350	May cause cancer
H361	Suspected of damaging fertility or the unborn child
H372	Causes damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

NA GHS SDS 2015 (Can, US)

03/02/2022 EN (English US) 10/10