

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous

Products Regulation (February 11, 2015).

Revision Date: 01/02/2020 Date of Issue: 04/03/2019 Version: 2.0

SECTION 1: IDENTIFICATION

Product Identifier

Product Form: Mixture

Product Name: STONETECH® Stone Polish 1.2. Intended Use of the Product Treatment of natural stone surfaces

Name, Address, and Telephone of the Responsible Party 1.3.

Company Company

LATICRETE International LATICRETE Canada ULC

1 Laticrete Park, N PO Box 129, Emeryville, Ontario, Canada

Bethany, CT 06524 NOR-1A0 T (203)-393-0010 (833)-254-9255

www.laticrete.com

Emergency Telephone Number 1.4.

Emergency Number: For Chemical Emergency call ChemTel Inc. day or night:

(800)255-3924 (North America) (800)-099-0731 (Mexico)

+1 (813)248-0585 (International - collect calls accepted)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

GHS-US/CA Classification

Skin Sens. 1 H317 H402 Aquatic Acute 3 Aquatic Chronic 3 H412

Full text of hazard classes and H-statements: see section 16

2.2. **Label Elements**

GHS-US/CA Labeling

Hazard Pictograms (GHS-US/CA)



Signal Word (GHS-US/CA) : Warning

Hazard Statements (GHS-US/CA) : H317 - May cause an allergic skin reaction.

H402 - Harmful to aquatic life.

H412 - Harmful to aquatic life with long lasting effects.

Precautionary Statements (GHS-US/CA): P261 - Avoid breathing vapors, mist, or spray.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P273 - Avoid release to the environment.

P280 - Wear protective gloves, protective clothing, and eye protection.

P302+P352 - IF ON SKIN: Wash with plenty of water. P321 - Specific treatment (see section 4 on this SDS).

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P362+P364 - Take off contaminated clothing and wash it before reuse.

P501 - Dispose of contents/container in accordance with local, regional, national,

territorial, provincial, and international regulations.

2.3. **Other Hazards**

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

Unknown Acute Toxicity (GHS-US/CA)

No data available

01/02/2020 EN (English US) 1/9

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

3.2. Mixture

Name	Product Identifier	% *	GHS Ingredient Classification
Isopropyl alcohol	(CAS-No.) 67-63-0	0.5 – 1.5	Flam. Liq. 2, H225
			Eye Irrit. 2A, H319
			STOT SE 3, H336
Alcohols, C12-14-secondary,	(CAS-No.) 84133-50-6	0.03 - 0.14	Skin Irrit. 2, H315
ethoxylated			Eye Dam. 1, H318
			Aquatic Acute 1, H400
			Aquatic Chronic 1, H410
3(2H)-Isothiazolone, 2-methyl-	(CAS-No.) 2682-20-4	0.0047 -	Acute Tox. 3 (Oral), H301
		0.0053	Acute Tox. 3 (Dermal), H311
			Acute Tox. 2 (Inhalation:dust,mist), H330
			Skin Corr. 1B, H314
			Eye Dam. 1, H318
			Skin Sens. 1A, H317
			STOT SE 3, H335
			Aquatic Acute 1, H400
1,2-Benzisothiazol-3(2H)-one	(CAS-No.) 2634-33-5	0.0047 -	Acute Tox. 4 (Oral), H302
		0.0053	Skin Irrit. 2, H315
			Eye Dam. 1, H318
			Skin Sens. 1, H317
			Aquatic Acute 1, H400
			Aquatic Chronic 1, H410
			Comb. Dust

Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of First-aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Inhalation: When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Obtain medical attention if irritation/rash develops or persists.

Eye Contact: Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with water for at least 15 minutes. Obtain medical attention.

Ingestion: Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

General: Skin sensitization.

Inhalation: Prolonged exposure may cause irritation.
Skin Contact: May cause an allergic skin reaction.
Eye Contact: May cause slight irritation to eyes.
Ingestion: Ingestion may cause adverse effects.

Chronic Symptoms: None expected.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

01/02/2020 EN (English US) 2/9

^{*}Percentages are listed in weight by weight percentage (w/w%) for liquid and solid ingredients. Gas ingredients are listed in volume by volume percentage (v/v%).

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Water spray, fog, carbon dioxide (CO₂), alcohol-resistant foam, or dry chemical. **Unsuitable Extinguishing Media:** Do not use a heavy water stream. Use of heavy stream of water may spread fire.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not considered flammable but may burn at high temperatures.

Explosion Hazard: Product is not explosive.

Reactivity: Hazardous reactions will not occur under normal conditions.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Nitrogen oxides. Carbon oxides (CO, CO₂). Sulfur oxides. Formaldehyde. Silicon oxides.

Other Information: Do not allow run-off from fire fighting to enter drains or water courses.

5.4. Reference to Other Sections

Refer to Section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Avoid breathing (vapor, mist, spray). Do not get in eyes, on skin, or on clothing.

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protective equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area.

6.2. Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

6.3. Methods and Materials for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Precautions for Safe Handling: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid prolonged contact with eyes, skin and clothing. Avoid breathing vapors, mist, spray.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

Incompatible Materials: Strong acids, strong bases, strong oxidizers.

7.3. Specific End Use(s)

Treatment of natural stone surfaces

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

01/02/2020 EN (English US) 3/9

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), or Canadian provincial governments.

governments.		
Isopropyl alcohol (67-63-0)		
USA ACGIH	ACGIH TWA (ppm)	200 ppm
USA ACGIH	ACGIH STEL (ppm)	400 ppm
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA ACGIH	Biological Exposure Indices (BEI)	40 mg/l Parameter: Acetone - Medium: urine - Sampling time: end of shift at end of workweek (background,
		nonspecific)
USA OSHA	OSHA PEL (TWA) (mg/m³)	980 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	400 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m³)	980 mg/m³
USA NIOSH	NIOSH REL (TWA) (ppm)	400 ppm
USA NIOSH	NIOSH REL (STEL) (mg/m³)	1225 mg/m³
USA NIOSH	NIOSH REL (STEL) (ppm)	500 ppm
USA IDLH	US IDLH (ppm)	2000 ppm (10% LEL)
Alberta	OEL STEL (mg/m³)	984 mg/m³
Alberta	OEL STEL (ppm)	400 ppm
Alberta	OEL TWA (mg/m³)	492 mg/m³
Alberta	OEL TWA (ppm)	200 ppm
British Columbia	OEL STEL (ppm)	400 ppm
British Columbia	OEL TWA (ppm)	200 ppm
Manitoba	OEL STEL (ppm)	400 ppm
Manitoba	OEL TWA (ppm)	200 ppm
New Brunswick	OEL STEL (mg/m³)	1230 mg/m³
New Brunswick	OEL STEL (ppm)	500 ppm
New Brunswick	OEL TWA (mg/m³)	983 mg/m³
New Brunswick	OEL TWA (ppm)	400 ppm
Newfoundland & Labrador	OEL STEL (ppm)	400 ppm
Newfoundland & Labrador	OEL TWA (ppm)	200 ppm
Nova Scotia	OEL STEL (ppm)	400 ppm
Nova Scotia	OEL TWA (ppm)	200 ppm
Nunavut	OEL STEL (ppm)	400 ppm
Nunavut	OEL TWA (ppm)	200 ppm
Northwest Territories	OEL STEL (ppm)	400 ppm
Northwest Territories	OEL TWA (ppm)	200 ppm
Ontario	OEL STEL (ppm)	400 ppm
Ontario	OEL TWA (ppm)	200 ppm
Prince Edward Island	OEL STEL (ppm)	400 ppm
Prince Edward Island	OEL TWA (ppm)	200 ppm
Québec	VECD (mg/m³)	1230 mg/m ³
Québec	VECD (ppm)	500 ppm
Québec	VEMP (mg/m³)	985 mg/m³
Québec	VEMP (ppm)	400 ppm
Saskatchewan	OEL STEL (ppm)	400 ppm
Saskatchewan	OEL TWA (ppm)	200 ppm
Yukon	OEL STEL (mg/m³)	1225 mg/m³
Yukon	OEL STEL (ppm)	500 ppm
Yukon	OEL TWA (mg/m³)	980 mg/m³
Yukon	OEL TWA (ppm)	400 ppm

01/02/2020 EN (English US) 4/9

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

8.2. Exposure Controls

Appropriate Engineering Controls: Suitable eye/body wash equipment should be available in the vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed.

Personal Protective Equipment: Gloves. Protective clothing. Protective goggles.







Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear protective gloves.

Eye and Face Protection: Chemical safety goggles.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

Other Information: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State: LiquidAppearance: White liquidOdor: Not applicableOdor Threshold: Not available

pH : 8.7

Evaporation Rate Not available **Melting Point** Not applicable **Freezing Point** Not available **Boiling Point** Not applicable Flash Point > 93 °C (199.4 °F) **Auto-ignition Temperature** Not available **Decomposition Temperature** Not available Flammability (solid, gas) Not applicable **Lower Flammable Limit** Not available **Upper Flammable Limit** Not available Not available **Vapor Pressure** Relative Vapor Density at 20°C Not available **Relative Density** Not available **Specific Gravity** 0.996

Solubility : Water: Not applicable

Partition Coefficient: N-Octanol/Water : Not available Viscosity : Not available

SECTION 10: STABILITY AND REACTIVITY

- **10.1. Reactivity:** Hazardous reactions will not occur under normal conditions.
- **10.2. Chemical Stability:** Stable under recommended handling and storage conditions (see section 7).
- 10.3. Possibility of Hazardous Reactions: Hazardous polymerization will not occur.
- **10.4. Conditions to Avoid:** Direct sunlight, extremely high or low temperatures, and incompatible materials.
- **10.5. Incompatible Materials:** Strong acids, strong bases, strong oxidizers.
- **10.6. Hazardous Decomposition Products:** Nitrogen oxides. Carbon oxides (CO, CO₂). Sulfur oxides. Formaldehyde. aldehydes, ketones.

01/02/2020 EN (English US) 5/9

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on Toxicological Effects - Product

Acute Toxicity (Oral): Not classified
Acute Toxicity (Dermal): Not classified
Acute Toxicity (Inhalation): Not classified

LD50 and LC50 Data: Not available
Skin Corrosion/Irritation: Not classified

pH: 8.7

Eye Damage/Irritation: Not classified

pH: 8.7

Respiratory or Skin Sensitization: May cause an allergic skin reaction.

Germ Cell Mutagenicity: Not classified

Carcinogenicity: Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: Prolonged exposure may cause irritation. Symptoms/Injuries After Skin Contact: May cause an allergic skin reaction. Symptoms/Injuries After Eye Contact: May cause slight irritation to eyes. Symptoms/Injuries After Ingestion: Ingestion may cause adverse effects.

11.2. Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

LD30 and LC30 Data.		
Isopropyl alcohol (67-63-0)		
LD50 Dermal Rabbit	12956 mg/kg (16.4 mL/kg bw)	
LC50 Inhalation Rat	72600 mg/m³ (Exposure time: 4 h)	
ATE US/CA (dermal)	12,956.00 mg/kg body weight	
ATE US/CA (vapors)	72,600.00 mg/l/4h	
ATE US/CA (dust, mist)	72,600.00 mg/l/4h	
Alcohols, C12-14-secondary, ethoxylated (84133-50-6)		
LD50 Oral Rat	2100 mg/kg	
3(2H)-Isothiazolone, 2-methyl- (2682-20-4)		
LD50 Oral Rat	120 mg/kg	
LD50 Dermal Rabbit	200 mg/kg	
LC50 Inhalation Rat	0.11 mg/l/4h	
ATE US/CA (dermal)	200.00 mg/kg body weight	
ATE US/CA (vapors)	0.11 mg/l/4h	
ATE US/CA (dust, mist)	0.11 mg/l/4h	
1,2-Benzisothiazol-3(2H)-one (2634-33-5)		
LD50 Oral Rat	1020 mg/kg	
Isopropyl alcohol (67-63-0)		
IARC Group	3	

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - General: Harmful to aquatic life with long lasting effects.

Isopropyl alcohol (67-63-0)	
LC50 Fish 1	9640 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	13299 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 Other Aquatic Organisms 1	1000 mg/l (Exposure time: 96 h - Species: Desmodesmus subspicatus)

01/02/2020 EN (English US) 6/9

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

LC50 Fish 2	11130 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])	
EC50 Other Aquatic Organisms 2	1000 mg/l (Exposure time: 72 h - Species: Desmodesmus subspicatus)	
Alcohols, C12-14-secondary, ethoxylated (84133-50-6)		
LC50 Fish 1	3.7 (3 - 4) mg/l (Exposure time: 96 h - Species: Lepomis macrochirus)	
EC50 Daphnia 1	0.29 mg/l (Exposure time: 48 h - Species: Daphnia magna)	
LC50 Fish 2	1.7 (Exposure time: 96 h - Species: Fathead Minnow)	
EC50 Daphnia 2	0.9 mg/l (Exposure time: 48 h - Species: Daphnia magna)	
1,2-Benzisothiazol-3(2H)-one (2634-33-5)		
EC50 Daphnia 1	0.99 mg/l	

12.2. Persistence and Degradability

STONETECH® Stone Polish	
Persistence and Degradability	May cause long-term adverse effects in the environment.

12.3. Bioaccumulative Potential

STONETECH® Stone Polish	
Bioaccumulative Potential	Not established.
Isopropyl alcohol (67-63-0)	
Log Pow	0.05 (at 25 °C)
1,2-Benzisothiazol-3(2H)-one (2634-33-5)	
Log Pow	1.3 (at 25 °C)

12.4. Mobility in Soil Not available

12.5. Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste Disposal Recommendations: Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

Additional Information: Container may remain hazardous when empty. Continue to observe all precautions.

Ecology - Waste Materials: Avoid release to the environment. This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

14.1. In Accordance with DOT Not regulated for transport

14.2. In Accordance with IMDG Not regulated for transport

14.3. In Accordance with IATA Not regulated for transport

14.4. In Accordance with TDG Not regulated for transport

SECTION 15: REGULATORY INFORMATION

15.1. US Federal Regulations

EPA TSCA Regulatory Flag

STONETECH® Stone Polish	
SARA Section 311/312 Hazard Classes	Health hazard - Respiratory or skin sensitization
Isopropyl alcohol (67-63-0)	
Listed on the United States TSCA (Toxic Substances C	Control Act) inventory
Subject to reporting requirements of United States S	ARA Section 313
SARA Section 313 - Emission Reporting	1 % (only if manufactured by the strong acid process, no supplier notification)
Alcohols, C12-14-secondary, ethoxylated (84133-50	-6)
Listed on the United States TSCA (Toxic Substances C	Control Act) inventory

01/02/2020 EN (English US) 7/9

XU - XU - indicates a substance exempt from reporting under the

Chemical Data Reporting Rule, (40 CFR 711).

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

3(2H)-Isothiazolone, 2-methyl- (2682-20-4)	
Listed on the United States TSCA (Toxic Substa	nces Control Act) inventory
EPA TSCA Regulatory Flag	PMN - PMN - indicates a commenced PMN substance. SP - SP - indicates a substance that is identified in a proposed Significant New Uses Rule.
1,2-Benzisothiazol-3(2H)-one (2634-33-5)	
Listed on the United States TSCA (Toxic Substa	nces Control Act) inventory

15.2. US State Regulations

Isopropyl alcohol (67-63-0)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List

15.3. Canadian Regulations

Isopropyl alcohol (67-63-0)	
Listed on the Canadian DSL (Domestic Substances List)	

Alcohols, C12-14-secondary, ethoxylated (84133-50-6)

Listed on the Canadian DSL (Domestic Substances List)

3(2H)-Isothiazolone, 2-methyl- (2682-20-4)

Listed on the Canadian DSL (Domestic Substances List)

1,2-Benzisothiazol-3(2H)-one (2634-33-5)

Listed on the Canadian DSL (Domestic Substances List)

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Date of Preparation or Latest : 01/02/2020

Revision

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA

Hazard Communication Standard 29 CFR 1910.1200 and Canada's Hazardous Products

Regulations (HPR) SOR/2015-17.

GHS Full Text Phrases:

Acute Tox. 2	Acute toxicity (inhalation:dust,mist) Category 2
(Inhalation:dust,mist)	
Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Comb. Dust	Combustible Dust
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2	Serious eye damage/eye irritation Category 2
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 2	Flammable liquids Category 2
Flam. Liq. 4	Flammable liquids Category 4
Skin Corr. 1B	Skin corrosion/irritation Category 1B
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization, Category 1
Skin Sens. 1A	Skin sensitization, category 1A

01/02/2020 EN (English US) 8/9

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

STOT SE 3	Specific target organ toxicity (single exposure) Category 3
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapour
H227	Combustible liquid
H301	Toxic if swallowed
H302	Harmful if swallowed
H311	Toxic in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H330	Fatal if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H400	Very toxic to aquatic life
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

NA GHS SDS 2015 (Can, US)

01/02/2020 EN (English US) 9/9