

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Date of Issue: 08/05/2020 Version: 1.0

### **SECTION 1: IDENTIFICATION**

# 1.1. Product Identifier

Product Form: Mixture

Product Name: TRI-LITE™ RAPID

#### 1.2. Intended Use of the Product

Rapid tile adhesive. For professional use only.

### 1.3. Name, Address, and Telephone of the Responsible Party

Company Company

LATICRETE International LATICRETE Canada ULC

1 Laticrete Park, N PO Box 129, Emeryville, Ontario, Canada

Bethany, CT 06524 NOR-1A0 T (203)-393-0010 (833)-254-9255

www.laticrete.com

## 1.4. Emergency Telephone Number

**Emergency Number**: For Chemical Emergency call ChemTel Inc. day or night:

(800)255-3924 (North America) (800)-099-0731 (Mexico)

+1 (813)248-0585 (International - collect calls accepted)

### **SECTION 2: HAZARDS IDENTIFICATION**

### 2.1. Classification of the Substance or Mixture

#### **GHS-US/CA Classification**

 Skin Corr. 1C
 H314

 Eye Dam. 1
 H318

 Skin Sens. 1
 H317

 Carc. 1A
 H350

 Repr. 1A
 H360

 Lact
 H362

Full text of hazard classes and H-statements: see section 16

# 2.2. Label Elements

**GHS-US/CA Labeling** 

Hazard Pictograms (GHS-US/CA)







Signal Word (GHS-US/CA) : Danger

Hazard Statements (GHS-US/CA) : H314 - Causes severe skin burns and eye damage.

H317 - May cause an allergic skin reaction.

H318 - Causes serious eye damage. H350 - May cause cancer (Inhalation).

H360 - May damage fertility or the unborn child. H362 - May cause harm to breast-fed children.

**Precautionary Statements (GHS-US/CA)**: P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P260 - Do not breathe dust.

P263 - Avoid contact during pregnancy/while nursing.

P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P280 - Wear protective gloves, protective clothing, and eye protection.

08/05/2020 EN (English US) 1/16

### Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 - If exposed or concerned: Get medical advice/attention.

P310 - Immediately call a POISON CENTER or doctor.

P321 - Specific treatment (see section 4 on this SDS).

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

P362+P364 - Take off contaminated clothing and wash it before reuse.

P405 - Store locked up.

P501 - Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

#### 2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

## 2.4. Unknown Acute Toxicity (GHS-US/CA)

No data available

# **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

#### 3.1. Substance

Not applicable

### 3.2. Mixture

| Name                        | Product Identifier   | % *       | <b>GHS Ingredient Classification</b>      |
|-----------------------------|----------------------|-----------|---|
| Cement, alumina, chemicals  | (CAS-No.) 65997-16-2 | 30 - 60   | Eye Irrit. 2A, H319                       |
| Limestone                   | (CAS-No.) 1317-65-3  | 21 - 31   | Not classified                            |
| Plaster of Paris            | (CAS-No.) 26499-65-0 | 14 - 15   | Not classified                            |
| Kaolin                      | (CAS-No.) 1332-58-7  | < 9       | Not classified                            |
| Perlite                     | (CAS-No.) 93763-70-3 | 3 - 7     | Not classified                            |
| Cement, portland, chemicals | (CAS-No.) 65997-15-1 | 3 - 7     | Skin Irrit. 2, H315                       |
|                             |                      |           | Eye Dam. 1, H318                          |
|                             |                      |           | Skin Sens. 1, H317                        |
|                             |                      |           | STOT SE 3, H335                           |
| Calcium oxide               | (CAS-No.) 1305-78-8  | 3 - 4     | Skin Irrit. 2, H315                       |
|                             |                      |           | Eye Dam. 1, H318                          |
|                             |                      |           | STOT SE 3, H335                           |
|                             |                      |           | Aquatic Acute 3, H402                     |
|                             |                      |           | Aquatic Chronic 3, H412                   |
| Quartz                      | (CAS-No.) 14808-60-7 | 0.2 - 0.4 | Carc. 1A, H350                            |
|                             |                      |           | STOT SE 3, H335                           |
|                             |                      |           | STOT RE 1, H372                           |
| Calcium sulfate dihydrate   | (CAS-No.) 13397-24-5 | ≤ 0.4     | Not classified                            |
| Lithium carbonate           | (CAS-No.) 554-13-2   | 0.1 - 1   | Acute Tox. 4 (Oral), H302                 |
|                             |                      |           | Acute Tox. 4 (Inhalation:dust,mist), H332 |
|                             |                      |           | Eye Irrit. 2B, H320                       |
|                             |                      |           | Lact, H362                                |
|                             |                      |           | Repr. 1A, H360                            |
|                             |                      |           | STOT SE 3, H335                           |
|                             |                      |           | STOT SE 1, H370                           |
|                             |                      |           | STOT RE 1, H372                           |
|                             |                      |           | Aquatic Acute 2, H401                     |
|                             |                      |           | Aquatic Chronic 2, H411                   |

08/05/2020 EN (English US) 2/16

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

| Magnesium oxide (MgO) | (CAS-No.) 1309-48-4  | ≤ 0.2      | Not classified          |
|-----------------------|----------------------|------------|-------------------------|
| Chromium, ion (Cr6+)  | (CAS-No.) 18540-29-9 | < 0.000006 | Skin Sens. 1, H317      |
|                       |                      |            | Carc. 1B, H350          |
|                       |                      |            | Aquatic Acute 1, H400   |
|                       |                      |            | Aquatic Chronic 1, H410 |

Full text of H-phrases: see section 16

# **SECTION 4: FIRST AID MEASURES**

### 4.1. Description of First-aid Measures

**General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

**Inhalation:** Remove to fresh air and keep at rest in a position comfortable for breathing. Immediately call a poison center or doctor/physician.

**Skin Contact:** Immediately remove contaminated clothing. Immediately flush skin with plenty of water for at least 30 minutes. Get immediate medical advice/attention.

**Eye Contact:** Immediately rinse with water for at least 30 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.

Ingestion: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

### 4.2. Most Important Symptoms and Effects Both Acute and Delayed

**General:** May cause cancer (Inhalation). Skin sensitization. May damage fertility. May damage the unborn child. May cause harm to breast-fed children. Causes severe skin burns and eye damage.

Inhalation: May be corrosive to the respiratory tract. The three types of silicosis include: 1) Simple chronic silicosis – which results from long-term exposure (more than 20 years) to low amounts of respirable crystalline silica. Nodules of chronic inflammation and scarring provoked by the respirable crystalline silica form in the lungs and chest lymph nodes. This disease may feature breathlessness and may resemble chronic obstructive pulmonary disease (COPD); 2) Accelerated silicosis – occurs after exposure to larger amounts of respirable crystalline silica over a shorter period of time (5-15 years); 3) Acute silicosis – results from short-term exposure to very large amounts of respirable crystalline silica. The lungs become very inflamed and may fill with fluid, causing severe shortness of breath and low blood oxygen levels. Inflammation, scarring, and symptoms progress faster in accelerated silicosis than in simple silicosis. Progressive massive fibrosis may occur in simple or accelerated silicosis, but is more common in the accelerated form. Progressive massive fibrosis results from severe scarring and leads to the destruction of normal lung structures.

**Skin Contact:** Concrete may cause dry skin, discomfort, irritation, severe burns, and dermatitis. Unhardened concrete is capable of causing dermatitis by irritation and allergy. Concrete dust, in association with sweat and friction, can lead to skin irritation and dermatitis. Skin affected by dermatitis may include symptoms such as, redness, itching, rash, scaling, and cracking. Allergic contact dermatitis is caused by sensitization to hexavalent chromium (chromate) present in concrete. The reaction can range from a mild rash to severe skin ulcers.

**Eye Contact:** Concrete may cause immediate or delayed irritation or inflammation. Eye contact with wet concrete can cause moderate eye irritation, chemical burns and blindness. Eye contact with large amounts of concrete dust can cause moderate eye irritation and abrasion. Eye exposures require immediate first aid and medical attention to prevent significant damage to the eye. **Ingestion:** May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.

**Chronic Symptoms:** May cause cancer by inhalation. May damage fertility or the unborn child. Some studies show that exposure to respirable crystalline silica (without silicosis) or that the disease silicosis may be associated with the increased incidence of several autoimmune disorders such as scleroderma (thickening of the skin), systemic lupus erythematosus, rheumatoid arthritis and diseases affecting the kidneys. Silicosis increases the risk of tuberculosis. Some studies show an increased incidence of chronic kidney disease and end-stage renal disease in workers exposed to respirable crystalline silica.

### 4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

# **SECTION 5: FIRE-FIGHTING MEASURES**

# 5.1. Extinguishing Media

Suitable Extinguishing Media: Water spray, fog, carbon dioxide (CO<sub>2</sub>), alcohol-resistant foam, or dry chemical.

08/05/2020 EN (English US) 3/16

<sup>\*</sup>Percentages are listed in weight by weight percentage (w/w%) for liquid and solid ingredients. Gas ingredients are listed in volume by volume percentage (v/v%).

<sup>\*\*</sup> The actual concentration of ingredient(s) is withheld as a trade secret in accordance with the Hazardous Products Regulations (HPR) SOR/2015-17 and 29 CFR 1910.1200.

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

### 5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not considered flammable but may burn at high temperatures.

**Explosion Hazard:** Product is not explosive.

**Reactivity:** Calcium oxide reacts with water to form corrosive calcium hydroxide, with evolution of much heat. Temperatures as high as 800° C (1472 °F) have been reached with addition of water (moisture in air or soil). Wet portland cement is alkaline. As such it is incompatible with acids, ammonium salts and phosphorus. Quartz (silica) will dissolve in hydroflouric acid producing a corrosive gas, silicon tetrafluoride.

### 5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection. **Hazardous Combustion Products:** Carbon oxides (CO, CO<sub>2</sub>). Metal oxides. Sulfur oxides. Crystalline silica exists in several forms, the most common of which is quartz. If crystalline silica (quartz) is heated to more than 870°C (1598°F), it can change to a form of crystalline silica known as trydimite, and if crystalline silica (quartz) is heated to more than 1470°C (2678°F), it can change to a form of crystalline silica known as cristobalite. The OSHA PEL for crystalline silica as trydimite and cristobalite is one-half of the OSHA PEL for crystalline silica (quartz).

#### 5.4. Reference to Other Sections

Refer to Section 9 for flammability properties.

### **SECTION 6: ACCIDENTAL RELEASE MEASURES**

### 6.1. Personal Precautions, Protective Equipment and Emergency Procedures

**General Measures:** Do not breathe dust. Do not get in eyes, on skin, or on clothing. Do not handle until all safety precautions have been read and understood.

#### 6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protective equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel.

#### 6.1.2. For Emergency Personnel

**Protective Equipment:** Equip cleanup crew with proper protection.

**Emergency Procedures:** Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area.

# 6.2. Environmental Precautions

Prevent entry to sewers and public waters.

### 6.3. Methods and Materials for Containment and Cleaning Up

**For Containment:** Contain solid spills with appropriate barriers and prevent migration and entry into sewers or streams. As an immediate precautionary measure, isolate spill or leak area in all directions.

**Methods for Cleaning Up:** Clean up spills immediately and dispose of waste safely. Recover the product by vacuuming, shoveling or sweeping. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill. Cautiously neutralize spilled solid.

### 6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

### **SECTION 7: HANDLING AND STORAGE**

# 7.1. Precautions for Safe Handling

Additional Hazards When Processed: May release corrosive vapors.

**Precautions for Safe Handling:** Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust. Avoid contact during pregnancy/while nursing. Do not get in eyes, on skin, or on clothing. Handle empty containers with care because they may still present a hazard.

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures.

## 7.2. Conditions for Safe Storage, Including Any Incompatibilities

**Technical Measures:** Comply with applicable regulations.

08/05/2020 EN (English US) 4/16

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015)

**Storage Conditions:** Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store locked up/in a secure area. Store in original container or corrosive resistant and/or lined container.

**Incompatible Materials:** Reactive or incompatible with the following materials: oxidizing materials, acids, aluminum and ammonium salt.

Portland cement is highly alkaline and will react with acids to produce a violent, heat-generating reaction. Toxic gases or vapors may be given off depending on the acid involved. Reacts with acids, aluminum metals and ammonium salts. Aluminum powder and other alkali and alkaline earth elements will react in wet mortar or concrete, liberating hydrogen gas. Limestone ignites on contact with fluorine and is incompatible with acids, alum, ammonium salts, and magnesium. Silica reacts violently with powerful oxidizing agents such as fluorine, boron trifluoride, chlorine trifluoride, manganese trifluoride, and oxygen difluoride yielding possible fire and/or explosions. Silicates dissolve readily in hydrofluoric acid producing a corrosive gas — silicon tetrafluoride.

### 7.3. Specific End Use(s)

Rapid tile adhesive. For professional use only.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), or Canadian provincial governments.

| Limestone (1317-65-3)       |                         |   |
|-----------------------------|-------------------------|---|
| USA OSHA                    | OSHA PEL (TWA) (mg/m³)  | 15 mg/m³ (total dust)                                   |
|                             |                         | 5 mg/m³ (respirable fraction)                           |
| USA NIOSH                   | NIOSH REL (TWA) (mg/m³) | 10 mg/m³ (total dust)                                   |
|                             |                         | 5 mg/m³ (respirable dust)                               |
| Alberta                     | OEL TWA (mg/m³)         | 10 mg/m <sup>3</sup>                                    |
| British Columbia            | OEL STEL (mg/m³)        | 20 mg/m³ (total)  |
| British Columbia            | OEL TWA (mg/m³)         | 10 mg/m³ (total dust)                                   |
|                             |                         | 3 mg/m³ (respirable fraction)                           |
| New Brunswick               | OEL TWA (mg/m³)         | 10 mg/m³ (particulate matter containing no Asbestos and |
|                             |                         | <1% Crystalline silica)                                 |
| Nunavut                     | OEL STEL (mg/m³)        | 20 mg/m <sup>3</sup>                                    |
| Nunavut                     | OEL TWA (mg/m³)         | 10 mg/m <sup>3</sup>                                    |
| Northwest Territories       | OEL STEL (mg/m³)        | 20 mg/m <sup>3</sup>                                    |
| Northwest Territories       | OEL TWA (mg/m³)         | 10 mg/m <sup>3</sup>                                    |
| Québec                      | VEMP (mg/m³)            | 10 mg/m³ (Limestone, containing no Asbestos and <1%     |
|                             |                         | Crystalline silica-total dust)                          |
| Saskatchewan                | OEL STEL (mg/m³)        | 20 mg/m <sup>3</sup>                                    |
| Saskatchewan                | OEL TWA (mg/m³)         | 10 mg/m <sup>3</sup>                                    |
| Yukon                       | OEL STEL (mg/m³)        | 20 mg/m <sup>3</sup>                                    |
| Yukon                       | OEL TWA (mg/m³)         | 30 mppcf  |
|                             |                         | 10 mg/m <sup>3</sup>                                    |
| Plaster of Paris (26499-65- | 0)                      |   |
| USA OSHA                    | OSHA PEL (TWA) (mg/m³)  | 15 mg/m³ (total dust)                                   |
|                             |                         | 5 mg/m³ (respirable fraction)                           |
| USA NIOSH                   | NIOSH REL (TWA) (mg/m³) | 10 mg/m³ (total dust)                                   |
|                             |                         | 5 mg/m³ (respirable dust)                               |
| Alberta                     | OEL TWA (mg/m³)         | 10 mg/m³ (Calcium sulphate)                             |
| British Columbia            | OEL STEL (mg/m³)        | 20 mg/m³ (total)  |
| British Columbia            | OEL TWA (mg/m³)         | 10 mg/m³ (total dust)                                   |
|                             |                         | 3 mg/m³ (respirable fraction)                           |
| Québec                      | VEMP (mg/m³)            | 10 mg/m³ (containing no Asbestos and <1% Crystalline    |
|                             |                         | silica-total dust)                                      |

08/05/2020 EN (English US) 5/16

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

|                                  |                         | 5 mg/m³ (containing no Asbestos and <1% Crystalline  |
|----------------------------------|-------------------------|--|
|                                  |                         | silica-respirable dust)  |
| Saskatchewan                     | OEL STEL (mg/m³)        | 20 mg/m <sup>3</sup>   |
| Saskatchewan                     | OEL TWA (mg/m³)         | 10 mg/m <sup>3</sup>   |
| Yukon                            | OEL STEL (mg/m³)        | 20 mg/m <sup>3</sup>   |
| Yukon                            | OEL TWA (mg/m³)         | 30 mppcf   |
|                                  |                         | 10 mg/m <sup>3</sup>   |
| Perlite (93763-70-3)             |                         |  |
| USA OSHA                         | OSHA PEL (TWA) (mg/m³)  | 15 mg/m³ (General Industry - total dust)   |
| USA NIOSH                        | NIOSH REL (TWA) (mg/m³) | 10 mg/m³ (total dust)  |
|                                  |                         | 5 mg/m³ (respirable dust)  |
| British Columbia                 | OEL TWA (mg/m³)         | 10 mg/m³ (total dust)  |
|                                  |                         | 3 mg/m³ (respirable fraction)  |
| New Brunswick                    | OEL TWA (mg/m³)         | 10 mg/m³ (particulate matter containing no Asbestos and  |
|                                  |                         | <1% Crystalline silica)  |
| Nunavut                          | OEL STEL (mg/m³)        | 20 mg/m <sup>3</sup>   |
| Nunavut                          | OEL TWA (mg/m³)         | 10 mg/m <sup>3</sup>   |
| Northwest Territories            | OEL STEL (mg/m³)        | 20 mg/m <sup>3</sup>   |
| Northwest Territories            | OEL TWA (mg/m³)         | 10 mg/m <sup>3</sup>   |
| Saskatchewan                     | OEL STEL (mg/m³)        | 20 mg/m <sup>3</sup>   |
| Saskatchewan                     | OEL TWA (mg/m³)         | 10 mg/m <sup>3</sup>   |
| Yukon                            | OEL TWA (mg/m³)         | 30 mppcf   |
| Cement, portland, chemical       | s (65997-15-1)          |  |
| USA ACGIH                        | ACGIH TWA (mg/m³)       | 1 mg/m³ (particulate matter containing no asbestos and   |
|                                  |                         | <1% crystalline silica, respirable particulate matter)   |
| USA ACGIH                        | ACGIH chemical category | Not Classifiable as a Human Carcinogen   |
| USA OSHA                         | OSHA PEL (TWA) (mg/m³)  | 15 mg/m³ (total dust)  |
|                                  |                         | 5 mg/m³ (respirable fraction)  |
| USA NIOSH                        | NIOSH REL (TWA) (mg/m³) | 10 mg/m³ (total dust)  |
|                                  |                         | 5 mg/m³ (respirable dust)  |
| USA IDLH                         | US IDLH (mg/m³)         | 5000 mg/m <sup>3</sup>   |
| Alberta                          | OEL TWA (mg/m³)         | 10 mg/m <sup>3</sup>   |
| British Columbia                 | OEL TWA (mg/m³)         | 1 mg/m³ (particulate matter containing no Asbestos and   |
|                                  |                         | <1% Crystalline silica-respirable particulate)   |
| Manitoba                         | OEL TWA (mg/m³)         | 1 mg/m³ (particulate matter containing no Asbestos and   |
|                                  |                         | <1% Crystalline silica, respirable particulate matter-   |
|                                  |                         | particulate matter, respirable particulate matter)   |
| New Brunswick                    | OEL TWA (mg/m³)         | 10 mg/m³ (particulate matter containing no Asbestos and  |
| No. of condition 10 to 1         | OFI TIMA ( /3)          | <1% Crystalline silica)  |
| Newfoundland & Labrador          | OEL TWA (mg/m³)         | 1 mg/m³ (particulate matter containing no Asbestos and   |
|                                  |                         | <1% Crystalline silica, respirable particulate matter-   |
| Nove Cookie                      | OFI TIMA (mag/mg3)      | particulate matter, respirable particulate matter)   |
| Nova Scotia                      | OEL TWA (mg/m³)         | 1 mg/m³ (particulate matter containing no Asbestos and   |
|                                  |                         | <1% Crystalline silica, respirable particulate matter-<br>particulate matter, respirable particulate matter) |
| Nunavut                          | OEL STEL (mg/m³)        | 20 mg/m <sup>3</sup>   |
|                                  |                         | 10 mg/m³   |
| Nunavut<br>Northwest Torritories | OEL TWA (mg/m³)         | <u>.                                    </u>   |
| Northwest Territories            | OEL STEL (mg/m³)        | 20 mg/m³   |
| Northwest Territories            | OEL TWA (mg/m³)         | 10 mg/m³   |
| Ontario                          | OEL TWA (mg/m³)         | 1 mg/m³ (containing no Asbestos and <1% Crystalline  |
| Buture Educated 1                | OFI TIMA ( /3)          | silica-respirable)   |
| Prince Edward Island             | OEL TWA (mg/m³)         | 1 mg/m³ (particulate matter containing no Asbestos and   |

08/05/2020 EN (English US) 6/16

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

| According to rederal negister / vol. 77, No | . 307 Monady, March 20, 2012 / Naics And Regulations And A | According to the Hazardous Products Regulation (February 11, 2015). |
|---|--|---|
|   |  | <1% Crystalline silica, respirable particulate matter-              |
|   |  | particulate matter, respirable particulate matter)                  |
| Québec                                      | VEMP (mg/m³)   | 10 mg/m³ (containing no Asbestos and <1% Crystalline                |
|   |  | silica-total dust)  |
|   |  | 5 mg/m³ (containing no Asbestos and <1% Crystalline                 |
|   |  | silica-respirable dust)   |
| Saskatchewan                                | OEL STEL (mg/m³)   | 20 mg/m <sup>3</sup>  |
| Saskatchewan                                | OEL TWA (mg/m³)  | 10 mg/m <sup>3</sup>  |
| Yukon                                       | OEL STEL (mg/m³)   | 20 mg/m <sup>3</sup>  |
| Yukon                                       | OEL TWA (mg/m³)  | 30 mppcf  |
|   |  | 10 mg/m <sup>3</sup>  |
| Calcium oxide (1305-78-8)                   |  |   |
| USA ACGIH                                   | ACGIH TWA (mg/m³)  | 2 mg/m³   |
| USA OSHA                                    | OSHA PEL (TWA) (mg/m³)                                     | 5 mg/m <sup>3</sup>   |
| USA NIOSH                                   | NIOSH REL (TWA) (mg/m³)                                    | 2 mg/m <sup>3</sup>   |
| USA IDLH                                    | US IDLH (mg/m³)  | 25 mg/m <sup>3</sup>  |
| Alberta                                     | OEL TWA (mg/m³)  | 2 mg/m³   |
| British Columbia                            | OEL TWA (mg/m³)  | 2 mg/m³   |
| Manitoba                                    | OEL TWA (mg/m³)  | 2 mg/m³   |
| New Brunswick                               | OEL TWA (mg/m³)  | 2 mg/m³   |
| Newfoundland & Labrador                     | OEL TWA (mg/m³)  | 2 mg/m³   |
| Nova Scotia                                 | OEL TWA (mg/m³)  | 2 mg/m³   |
| Nunavut                                     | OEL STEL (mg/m³)   | 4 mg/m <sup>3</sup>   |
| Nunavut                                     | OEL TWA (mg/m³)  | 2 mg/m³   |
| Northwest Territories                       | OEL STEL (mg/m³)   | 4 mg/m <sup>3</sup>   |
| Northwest Territories                       | OEL TWA (mg/m³)  | 2 mg/m³   |
| Ontario                                     | OEL TWA (mg/m³)  | 2 mg/m³   |
| Prince Edward Island                        | OEL TWA (mg/m³)  | 2 mg/m³   |
| Québec                                      | VEMP (mg/m³)   | 2 mg/m³   |
| Saskatchewan                                | OEL STEL (mg/m³)   | 4 mg/m³   |
| Saskatchewan                                | OEL TWA (mg/m³)  | 2 mg/m³   |
| Yukon                                       | OEL STEL (mg/m³)   | 4 mg/m <sup>3</sup>   |
| Yukon                                       | OEL TWA (mg/m³)  | 2 mg/m³   |
| Quartz (14808-60-7)                         | , ,  |   |
| USA ACGIH                                   | ACGIH TWA (mg/m³)  | 0.025 mg/m³ (respirable particulate matter)                         |
| USA ACGIH                                   | ACGIH chemical category                                    | A2 - Suspected Human Carcinogen                                     |
| USA OSHA                                    | OSHA PEL (TWA) (mg/m³)                                     | 50 μg/m³ (Respirable crystalline silica)                            |
| USA NIOSH                                   | NIOSH REL (TWA) (mg/m³)                                    | 0.05 mg/m³ (respirable dust)  |
| USA IDLH                                    | US IDLH (mg/m³)  | 50 mg/m³ (respirable dust)  |
| Alberta                                     | OEL TWA (mg/m³)  | 0.025 mg/m³ (respirable particulate)                                |
| British Columbia                            | OEL TWA (mg/m³)  | 0.025 mg/m³ (respirable)  |
| Manitoba                                    | OEL TWA (mg/m³)  | 0.025 mg/m³ (respirable particulate matter)                         |
| New Brunswick                               | OEL TWA (mg/m³)  | 0.1 mg/m³ (respirable fraction)                                     |
| Newfoundland & Labrador                     | OEL TWA (mg/m³)  | 0.025 mg/m³ (respirable particulate matter)                         |
| Nova Scotia                                 | OELTWA (mg/m <sup>3</sup> )                                | 0.025 mg/m³ (respirable particulate matter)                         |
| Nunavut                                     | OELTWA (mg/m <sup>3</sup> )                                | 0.05 mg/m³ (respirable fraction (Silica - crystalline)              |
| Northwest Territories                       | OELTWA (mg/m <sup>3</sup> )                                | 0.05 mg/m³ (respirable fraction (Silica - crystalline)              |
| Ontario                                     | OELTWA (mg/m²)   | 0.1 mg/m³ (designated substances regulation-respirable              |
| Siltatio                                    | OLL I WA (IIIB/III /                                       | (Silica, crystalline)   |
| Prince Edward Island                        | OEL TWA (mg/m³)  | 0.025 mg/m³ (respirable particulate matter)                         |
| Québec                                      | VEMP (mg/m³)   | 0.1 mg/m³ (respirable dust)   |
| Saskatchewan                                | OELTWA (mg/m³)   | 0.05 mg/m³ (respirable fraction (Silica - crystalline               |
| Jaskateriewali                              | OFF 1 AND (1118/111 )                                      | 1 0.05 mg/m (respirable traction (sinca - crystalline               |

08/05/2020 EN (English US) 7/16

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

| Tieses amb Te Teachar Register / Vol. 77/110 | . 367 Monday, March 20, 2012 / Rules And Regulation | ons And According To The Hazardous Products Regulation (February 11, 2015).      |
|--|---|--|
|  | 0 - 1 - 1 - 1 - 2 1                                 | (Trydimite removed))   |
| Yukon  | OEL TWA (mg/m³)                                     | 300 particle/mL (Silica - Quartz, crystalline)                                   |
| Calcium sulfate dihydrate (1                 | -   |  |
| USA ACGIH                                    | ACGIH TWA (mg/m³)                                   | 10 mg/m³ (inhalable particulate matter (Calcium sulfate)                         |
| USA OSHA                                     | OSHA PEL (TWA) (mg/m³)                              | 15 mg/m³ (total dust)  |
|  |   | 5 mg/m³ (respirable fraction)  |
| USA NIOSH                                    | NIOSH REL (TWA) (mg/m³)                             | 10 mg/m³ (total dust)  |
|  |   | 5 mg/m³ (respirable dust)  |
| Alberta                                      | OEL TWA (mg/m³)                                     | 10 mg/m³ (Calcium sulphate)  |
| British Columbia                             | OEL STEL (mg/m³)                                    | 20 mg/m³ (total)   |
| British Columbia                             | OEL TWA (mg/m³)                                     | 10 mg/m³ (total dust)  |
|  |   | 3 mg/m³ (respirable fraction)  |
|  | 27. 7.1.1.1.1.2.2.2.2.2.2.2.2.2.2.2.2.2.2.2.        | 10 mg/m³ (regulated under Calcium sulfate-inhalable)                             |
| Manitoba                                     | OEL TWA (mg/m³)                                     | 10 mg/m³ (inhalable particulate matter (Calcium sulfate)                         |
| Newfoundland & Labrador                      | OEL TWA (mg/m³)                                     | 10 mg/m³ (inhalable particulate matter (Calcium sulfate)                         |
| Nova Scotia                                  | OEL TWA (mg/m³)                                     | 10 mg/m³ (inhalable particulate matter (Calcium sulfate)                         |
| Ontario                                      | OEL TWA (mg/m³)                                     | 10 mg/m³ (inhalable (Calcium sulfate)  |
| Prince Edward Island                         | OEL TWA (mg/m³)                                     | 10 mg/m³ (inhalable particulate matter (Calcium sulfate)                         |
| Québec                                       | VEMP (mg/m³)  | 10 mg/m³ (containing no Asbestos and <1% Crystalline                             |
|  |   | silica-total dust)   |
|  |   | 5 mg/m³ (containing no Asbestos and <1% Crystalline                              |
| Carlandahaaaaa                               | OFI CTEL //3\                                       | silica-respirable dust)  |
| Saskatchewan                                 | OEL STEL (mg/m³)                                    | 20 mg/m³   |
| Saskatchewan                                 | OEL TWA (mg/m³)                                     | 10 mg/m³   |
| Yukon  | OEL STEL (mg/m³)                                    | 20 mg/m³   |
| Yukon  | OEL TWA (mg/m³)                                     | 30 mppcf   |
|  | 100.40.4)   | 10 mg/m <sup>3</sup>   |
| Magnesium oxide (MgO) (13                    |   | 40 / 3/: 1 1 1 1 1 1 1 1   |
| USA ACGIH                                    | ACGIH TWA (mg/m³)                                   | 10 mg/m³ (inhalable particulate matter)  |
| USA ACGIH                                    | ACGIH chemical category                             | Not Classifiable as a Human Carcinogen   |
| USA OSHA                                     | OSHA PEL (TWA) (mg/m³)                              | 15 mg/m³ (fume, total particulate)   |
| USA IDLH                                     | US IDLH (mg/m³)                                     | 750 mg/m³ (fume)   |
| Alberta                                      | OEL TWA (mg/m³)                                     | 10 mg/m³ (fume)  |
| British Columbia                             | OEL STEL (mg/m³)                                    | 10 mg/m³ (respirable dust and fume)  |
| British Columbia                             | OEL TWA (mg/m³)                                     | 10 mg/m³ (fume, inhalable) 3 mg/m³ (respirable dust and fume)                    |
| Manitoba                                     | OEL TWA (mg/m³)                                     | 10 mg/m³ (inhalable particulate matter)  |
| New Brunswick                                | OEL TWA (mg/m³)                                     | 10 mg/m² (fume)  |
| Newfoundland & Labrador                      | OEL TWA (mg/m³)                                     | 10 mg/m² (iume)  10 mg/m³ (inhalable particulate matter)                         |
| Nova Scotia                                  | OEL TWA (mg/m³)                                     | 10 mg/m³ (inhalable particulate matter)  10 mg/m³ (inhalable particulate matter) |
| Nunavut                                      | OEL TWA (IIIg/III )  OEL STEL (mg/m³)               | 20 mg/m³ (inhalable fraction)  |
| Nunavut                                      | OEL TWA (mg/m³)                                     | 10 mg/m³ (inhalable fraction)  |
| Northwest Territories                        | OEL STEL (mg/m³)                                    | 20 mg/m³ (inhalable fraction)  |
| Northwest Territories                        | OEL TWA (mg/m³)                                     | 10 mg/m³ (inhalable fraction)  |
| Ontario                                      | OEL TWA (mg/m³)                                     | 10 mg/m³ (inhalable)   |
| Prince Edward Island                         | OEL TWA (mg/m³)                                     | 10 mg/m³ (inhalable)  10 mg/m³ (inhalable particulate matter)                    |
| Québec                                       | VEMP (mg/m³)  | 10 mg/m³ (fume)  |
| Saskatchewan                                 | OEL STEL (mg/m³)                                    | 20 mg/m³ (inhalable fraction)  |
| Saskatchewan                                 | OEL TWA (mg/m³)                                     | 10 mg/m³ (inhalable fraction)  |
| Yukon  | OEL STEL (mg/m³)                                    | 10 mg/m³ (fume)  |
| Yukon  | OEL TWA (mg/m³)                                     | 10 mg/m³ (fume)  |
| Chromium, ion (Cr6+) (1854)                  | , . ,   | ±0 m8/m (rame)   |
| Cin Officiali, 10ff (Cro+) (1854)            | J-4J-J  |  |

08/05/2020 EN (English US) 8/16

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

|   |                         | ions and according to the Hazardous Products Regulation (February 11, 2015).  |
|---|-------------------------|---|
| USA OSHA  | OSHA PEL (TWA) (mg/m³)  | 5 μg/m³   |
| Kaolin (1332-58-7)  |                         |   |
| USA ACGIH   | ACGIH TWA (mg/m³)       | 2 mg/m³ (particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter)   |
| USA ACGIH   | ACGIH chemical category | Not Classifiable as a Human Carcinogen  |
| USA OSHA  | OSHA PEL (TWA) (mg/m³)  | 15 mg/m³ (total dust)   |
|   |                         | 5 mg/m³ (respirable fraction)   |
| USA NIOSH   | NIOSH REL (TWA) (mg/m³) | 10 mg/m³ (total dust)   |
|   |                         | 5 mg/m³ (respirable dust)   |
| Alberta   | OEL TWA (mg/m³)         | 2 mg/m³ (respirable)  |
| British Columbia  | OEL TWA (mg/m³)         | 2 mg/m³ (particulate matter containing no Asbestos and <1% Crystalline silica-respirable particulate)   |
| Manitoba  | OEL TWA (mg/m³)         | 2 mg/m³ (particulate matter containing no Asbestos and <1% Crystalline silica, respirable particulate matter-particulate matter, respirable particulate matter) |
| New Brunswick   | OEL TWA (mg/m³)         | 2 mg/m³ (particulate matter containing no Asbestos and <1% Crystalline silica, respirable fraction)   |
| Newfoundland & Labrador                                       | OEL TWA (mg/m³)         | 2 mg/m³ (particulate matter containing no Asbestos and <1% Crystalline silica, respirable particulate matter-particulate matter, respirable particulate matter) |
| Nova Scotia   | OEL TWA (mg/m³)         | 2 mg/m³ (particulate matter containing no Asbestos and <1% Crystalline silica, respirable particulate matter-particulate matter, respirable particulate matter) |
| Nunavut   | OEL STEL (mg/m³)        | 4 mg/m³ (respirable fraction)   |
| Nunavut   | OEL TWA (mg/m³)         | 2 mg/m³ (respirable fraction)   |
| Northwest Territories   | OEL STEL (mg/m³)        | 4 mg/m³ (respirable fraction)   |
| Northwest Territories   | OEL TWA (mg/m³)         | 2 mg/m³ (respirable fraction)   |
| Ontario   | OEL TWA (mg/m³)         | 2 mg/m³ (containing no Asbestos and <1% Crystalline silica-respirable)  |
| Prince Edward Island  | OEL TWA (mg/m³)         | 2 mg/m³ (particulate matter containing no Asbestos and <1% Crystalline silica, respirable particulate matter-particulate matter, respirable particulate matter) |
| Québec  | VEMP (mg/m³)            | 5 mg/m³ (containing no Asbestos and <1% Crystalline silica-respirable dust)   |
| Saskatchewan  | OEL STEL (mg/m³)        | 4 mg/m³ (respirable fraction)   |
| Saskatchewan  | OEL TWA (mg/m³)         | 2 mg/m³ (respirable fraction)   |
| Yukon   | OEL STEL (mg/m³)        | 20 mg/m <sup>3</sup>  |
| Yukon   | OEL TWA (mg/m³)         | 30 mppcf<br>10 mg/m <sup>3</sup>  |
| Particulates not otherwise classified (PNOC) (Not applicable) |                         |   |
| USA ACGIH   | ACGIH TWA (mg/m³)       | 3 mg/m <sup>3</sup> Respirable fraction<br>10 mg/m <sup>3</sup> Total Dust  |
| USA OSHA  | OSHA PEL (TWA) (mg/m³)  | 5 mg/m³ Respirable fraction 15 mg/m³ Total Dust   |
| Alberta   | OEL TWA (mg/m³)         | 10 mg/m³ (total)<br>3 mg/m³ (respirable)  |
| British Columbia  | OEL TWA (mg/m³)         | 10 mg/m³ (including nuisance dusts-total dust) 3 mg/m³ (including nuisance dusts-respirable fraction)   |
| Manitoba  | OEL TWA (mg/m³)         | 10 mg/m³ (inhalable particles, recommended) 3 mg/m³ (respirable particles, recommended)   |
| New Brunswick   | OEL TWA (mg/m³)         | 3 mg/m³ (particulate matter containing no Asbestos and <1% Crystalline silica, respirable fraction)   |

08/05/2020 EN (English US) 9/16

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

| recording to reactar negister / voi. //, ive | I                 | And According to the nazardous Products Regulation (Pebruary 11, 2013). |
|--|-------------------|---|
|  |                   | 10 mg/m³ (particulate matter containing no Asbestos and                 |
|  |                   | <1% Crystalline silica, inhalable fraction)                             |
| Newfoundland & Labrador                      | OEL TWA (mg/m³)   | 10 mg/m³ (inhalable particles, recommended)                             |
|  |                   | 3 mg/m³ (respirable particles, recommended)                             |
| Nova Scotia                                  | OEL TWA (mg/m³)   | 10 mg/m³ (inhalable particles, recommended)                             |
|  |                   | 3 mg/m³ (respirable particles, recommended)                             |
| Nunavut                                      | OEL STEL (mg/m³)  | 20 mg/m³ (insoluble or poorly soluble-inhalable fraction)               |
|  |                   | 6 mg/m³ (insoluble or poorly soluble-respirable fraction)               |
| Nunavut                                      | OEL TWA (mg/m³)   | 10 mg/m³ (insoluble or poorly soluble-inhalable fraction)               |
|  |                   | 3 mg/m³ (insoluble or poorly soluble-respirable fraction)               |
| Northwest Territories                        | OEL STEL (mg/m³)  | 20 mg/m³ (insoluble or poorly soluble-inhalable fraction)               |
|  |                   | 6 mg/m³ (insoluble or poorly soluble-respirable fraction)               |
| Northwest Territories                        | OEL TWA (mg/m³)   | 10 mg/m³ (insoluble or poorly soluble-inhalable fraction)               |
|  |                   | 3 mg/m³ (insoluble or poorly soluble-respirable fraction)               |
| Ontario                                      | OEL TWA (mg/m³)   | 10 mg/m³ (inhalable)  |
|  |                   | 3 mg/m³ (respirable)  |
| Prince Edward Island                         | OEL TWA (mg/m³)   | 10 mg/m³ (inhalable particles, recommended)                             |
|  |                   | 3 mg/m³ (respirable particles, recommended)                             |
| Québec                                       | VEMP (mg/m³)      | 10 mg/m³ (including dust, inert or nuisance particulates-               |
|  |                   | total dust)   |
| Saskatchewan                                 | OEL STEL (mg/m³)  | 20 mg/m³ (insoluble or poorly soluble-inhalable fraction)               |
|  |                   | 6 mg/m³ (insoluble or poorly soluble-respirable fraction)               |
| Saskatchewan                                 | OEL TWA (mg/m³)   | 10 mg/m³ (insoluble or poorly soluble-inhalable fraction)               |
|  |                   | 3 mg/m³ (insoluble or poorly soluble-respirable fraction)               |
| Calcium sulfate hemihydrate (10034-76-1)     |                   |   |
| USA ACGIH                                    | ACGIH TWA (mg/m³) | 10 mg/m³ (inhalable particulate matter (Calcium sulfate)                |
| British Columbia                             | OEL TWA (mg/m³)   | 10 mg/m³ (inhalable (Calcium sulfate)                                   |
| Manitoba                                     | OEL TWA (mg/m³)   | 10 mg/m³ (inhalable particulate matter (Calcium sulfate)                |
| Newfoundland & Labrador                      | OEL TWA (mg/m³)   | 10 mg/m³ (inhalable particulate matter (Calcium sulfate)                |
| Nova Scotia                                  | OEL TWA (mg/m³)   | 10 mg/m³ (inhalable particulate matter (Calcium sulfate)                |
| Ontario                                      | OEL TWA (mg/m³)   | 10 mg/m³ (inhalable)  |
| Prince Edward Island                         | OEL TWA (mg/m³)   | 10 mg/m³ (inhalable particulate matter (Calcium sulfate)                |

# 8.2. Exposure Controls

**Appropriate Engineering Controls:** Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

**Personal Protective Equipment:** Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.









Materials for Protective Clothing: Chemically resistant materials and fabrics. Corrosion-proof clothing.

Hand Protection: Wear protective gloves.

Eye and Face Protection: Chemical safety goggles.

Skin and Body Protection: Wear suitable protective clothing.

**Respiratory Protection:** If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

Consumer Exposure Controls: Avoid contact during pregnancy/while nursing

Other Information: When using, do not eat, drink or smoke.

### **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

### 9.1. Information on Basic Physical and Chemical Properties

08/05/2020 EN (English US) 10/16

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

**Physical State** Solid

**Appearance** White powder

Odor None

**Odor Threshold** Not available Not available **Evaporation Rate** Not available **Melting Point** Not available **Freezing Point** Not available **Boiling Point** Not available **Flash Point** Not available Not available **Auto-ignition Temperature Decomposition Temperature** Not available Flammability (solid, gas) Not available **Lower Flammable Limit** Not available

**Upper Flammable Limit** Not available Not available **Vapor Pressure** Relative Vapor Density at 20°C Not available **Relative Density** Not available **Specific Gravity** Not available Not available Solubility

Partition Coefficient: N-Octanol/Water Not available Viscosity Not available

### **SECTION 10: STABILITY AND REACTIVITY**

Reactivity: Calcium oxide reacts with water to form corrosive calcium hydroxide, with evolution of much heat. Temperatures as high as 800° C (1472 °F) have been reached with addition of water (moisture in air or soil). Wet portland cement is alkaline. As such it is incompatible with acids, ammonium salts and phosphorus. Quartz (silica) will dissolve in hydroflouric acid producing a corrosive gas, silicon tetrafluoride.

- 10.2. Chemical Stability: Stable under recommended handling and storage conditions (see section 7).
- 10.3. Possibility of Hazardous Reactions: Hazardous polymerization will not occur.
- 10.4. **Conditions to Avoid:** Direct sunlight, extremely high or low temperatures, and incompatible materials.
- 10.5. Incompatible Materials: Reactive or incompatible with the following materials: oxidizing materials, acids, aluminum and ammonium salt.

Portland cement is highly alkaline and will react with acids to produce a violent, heat-generating reaction. Toxic gases or vapors may be given off depending on the acid involved. Reacts with acids, aluminum metals and ammonium salts. Aluminum powder and other alkali and alkaline earth elements will react in wet mortar or concrete, liberating hydrogen gas. Limestone ignites on contact with fluorine and is incompatible with acids, alum, ammonium salts, and magnesium. Silica reacts violently with powerful oxidizing agents such as fluorine, boron trifluoride, chlorine trifluoride, manganese trifluoride, and oxygen difluoride yielding possible fire and/or explosions. Silicates dissolve readily in hydrofluoric acid producing a corrosive gas — silicon tetrafluoride.

10.6. Hazardous Decomposition Products: Not expected to decompose under ambient conditions. Thermal decomposition generates: Corrosive vapors.

# **SECTION 11: TOXICOLOGICAL INFORMATION**

11.1. Information on Toxicological Effects - Product

Acute Toxicity (Oral): Not classified Acute Toxicity (Dermal): Not classified Acute Toxicity (Inhalation): Not classified LD50 and LC50 Data: Not available

Skin Corrosion/Irritation: Causes severe skin burns. Eye Damage/Irritation: Causes serious eye damage.

Respiratory or Skin Sensitization: May cause an allergic skin reaction.

08/05/2020 EN (English US) 11/16

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Germ Cell Mutagenicity: Not classified

Carcinogenicity: May cause cancer (Inhalation).

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: May damage fertility or the unborn child. May cause harm to breast-fed children.

Specific Target Organ Toxicity (Single Exposure): Not classified

**Aspiration Hazard:** Not classified

Symptoms/Injuries After Inhalation: May be corrosive to the respiratory tract. The three types of silicosis include: 1) Simple chronic silicosis – which results from long-term exposure (more than 20 years) to low amounts of respirable crystalline silica. Nodules of chronic inflammation and scarring provoked by the respirable crystalline silica form in the lungs and chest lymph nodes. This disease may feature breathlessness and may resemble chronic obstructive pulmonary disease (COPD); 2) Accelerated silicosis – occurs after exposure to larger amounts of respirable crystalline silica over a shorter period of time (5-15 years); 3) Acute silicosis – results from short-term exposure to very large amounts of respirable crystalline silica. The lungs become very inflamed and may fill with fluid, causing severe shortness of breath and low blood oxygen levels. Inflammation, scarring, and symptoms progress faster in accelerated silicosis than in simple silicosis. Progressive massive fibrosis may occur in simple or accelerated silicosis, but is more common in the accelerated form. Progressive massive fibrosis results from severe scarring and leads to the destruction of normal lung structures. Symptoms/Injuries After Skin Contact: Concrete may cause dry skin, discomfort, irritation, severe burns, and dermatitis. Unhardened concrete is capable of causing dermatitis by irritation and allergy. Concrete dust, in association with sweat and friction, can lead to skin irritation and dermatitis. Skin affected by dermatitis may include symptoms such as, redness, itching, rash, scaling, and cracking. Allergic contact dermatitis is caused by sensitization to hexavalent chromium (chromate) present in concrete. The reaction can range from a mild rash to severe skin ulcers.

**Symptoms/Injuries After Eye Contact:** Concrete may cause immediate or delayed irritation or inflammation. Eye contact with wet concrete can cause moderate eye irritation, chemical burns and blindness. Eye contact with large amounts of concrete dust can cause moderate eye irritation and abrasion. Eye exposures require immediate first aid and medical attention to prevent significant damage to the eye.

Symptoms/Injuries After Ingestion: May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract. Chronic Symptoms: May cause cancer by inhalation. May damage fertility or the unborn child. Some studies show that exposure to respirable crystalline silica (without silicosis) or that the disease silicosis may be associated with the increased incidence of several autoimmune disorders such as scleroderma (thickening of the skin), systemic lupus erythematosus, rheumatoid arthritis and diseases affecting the kidneys. Silicosis increases the risk of tuberculosis. Some studies show an increased incidence of chronic kidney disease and end-stage renal disease in workers exposed to respirable crystalline silica.

### 11.2. Information on Toxicological Effects - Ingredient(s)

### LD50 and LC50 Data:

| Perlite (93763-70-3)              |                     |   |
|-----------------------------------|---------------------|---|
| LD50 Oral Rat                     | 12960 mg/kg (Mouse) |   |
| Calcium oxide (1305-78-8)         |                     |   |
| LD50 Oral Rat                     | > 2000 mg/kg        |   |
| LD50 Dermal Rabbit                | > 2500 mg/kg        |   |
| Quartz (14808-60-7)               |                     |   |
| LD50 Oral Rat                     | > 5000 mg/kg        |   |
| LD50 Dermal Rat                   | > 5000 mg/kg        |   |
| Lithium carbonate (554-13-2)      |                     | · |
| LD50 Oral Rat                     | 525 mg/kg           |   |
| LD50 Dermal Rabbit                | > 3000 mg/kg        |   |
| LC50 Inhalation Rat               | > 2.17 mg/l/4h      |   |
| ATE US/CA (dust, mist)            | 1.50 mg/l/4h        |   |
| Magnesium oxide (MgO) (1309-48-4) |                     |   |
| LD50 Oral Rat                     | 3870 mg/kg          |   |
| Kaolin (1332-58-7)                |                     |   |
| LD50 Oral Rat                     | > 5000 mg/kg        |   |
| LD50 Dermal Rat                   | > 5000 mg/kg        |   |
| LD50 Dermal Rabbit                | > 5000 mg/kg        | • |

08/05/2020 EN (English US) 12/16

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

| Quartz (14808-60-7)                         |   |
|---|---|
| IARC Group                                  | 1   |
| National Toxicology Program (NTP) Status    | Known Human Carcinogens.                        |
| OSHA Hazard Communication Carcinogen List   | In OSHA Hazard Communication Carcinogen list.   |
| Chromium, ion (Cr6+) (18540-29-9)           |   |
| IARC Group                                  | 1   |
| OSHA Hazard Communication Carcinogen List   | In OSHA Hazard Communication Carcinogen list.   |
| OSHA Specifically Regulated Carcinogen List | In OSHA Specifically Regulated Carcinogen list. |

# SECTION 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity

Ecology - General: Not classified.

| Calcium oxide (1305-78-8)         |  |  |
|-----------------------------------|--|--|
| LC50 Fish 1                       | 50.6 mg/l  |  |
| Lithium carbonate (554-13-2)      |  |  |
| LC50 Fish 1                       | 8.1 mg/l   |  |
| Chromium, ion (Cr6+) (18540-29-9) |  |  |
| LC50 Fish 1                       | 36.2 mg/l (Exposure time: 96 h - Species: Pimephales promelas) |  |
| LC50 Fish 2                       | 7.6 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)  |  |

### 12.2. Persistence and Degradability

| TRI-LITE™ RAPID               |                  |
|-------------------------------|------------------|
| Persistence and Degradability | Not established. |

#### 12.3. Bioaccumulative Potential

| TRI-LITE™ RAPID           |                      |
|---------------------------|----------------------|
| Bioaccumulative Potential | Not established.     |
| Calcium oxide (1305-78-8) |                      |
| BCF Fish 1                | (no bioaccumulation) |

**12.4. Mobility in Soil** Not available

### 12.5. Other Adverse Effects

Other Information: Avoid release to the environment.

### **SECTION 13: DISPOSAL CONSIDERATIONS**

# 13.1. Waste treatment methods

**Waste Disposal Recommendations:** Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

**Ecology - Waste Materials:** Avoid release to the environment.

# **SECTION 14: TRANSPORT INFORMATION**

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

14.1. In Accordance with DOT
 14.2. In Accordance with IMDG
 14.3. In Accordance with IATA
 14.4. In Accordance with TDG
 Not regulated for transport
 Not regulated for transport
 Not regulated for transport

### **SECTION 15: REGULATORY INFORMATION**

### 15.1. US Federal Regulations

| TRI-LITE™ RAPID                     |  |  |
|-------------------------------------|--|--|
| SARA Section 311/312 Hazard Classes | Health hazard - Carcinogenicity                      |  |
|                                     | Health hazard - Respiratory or skin sensitization    |  |
|                                     | Health hazard - Reproductive toxicity                |  |
|                                     | Health hazard - Serious eye damage or eye irritation |  |

08/05/2020 EN (English US) 13/16

#### Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Health hazard - Skin corrosion or Irritation

## Cement, alumina, chemicals (65997-16-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### Limestone (1317-65-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

### Cement, portland, chemicals (65997-15-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### Calcium oxide (1305-78-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

### Quartz (14808-60-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

### Lithium carbonate (554-13-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Subject to reporting requirements of United States SARA Section 313

SARA Section 313 - Emission Reporting

#### Magnesium oxide (MgO) (1309-48-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### Kaolin (1332-58-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

### 15.2. US State Regulations

### **California Proposition 65**



**WARNING:** This product can expose you to Chromium, ion (Cr6+), which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

| Chemical Name (CAS No.)      | Carcinogenicity | Developmental | Female Reproductive | Male Reproductive |
|------------------------------|-----------------|---------------|---------------------|-------------------|
|                              |                 | Toxicity      | Toxicity            | Toxicity          |
| Quartz (14808-60-7)          | Х               |               |                     |                   |
| Lithium carbonate (554-13-2) |                 | Х             |                     |                   |
| Chromium, ion (Cr6+) (18540- | X               | X             |                     |                   |
| 29-9)                        |                 |               |                     |                   |

### Limestone (1317-65-3)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

### Plaster of Paris (26499-65-0)

- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

### Perlite (93763-70-3)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

### Cement, portland, chemicals (65997-15-1)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

### Calcium oxide (1305-78-8)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

### Quartz (14808-60-7)

U.S. - Massachusetts - Right To Know List

08/05/2020 EN (English US) 14/16

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

### Calcium sulfate dihydrate (13397-24-5)

- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

#### Lithium carbonate (554-13-2)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List

### Magnesium oxide (MgO) (1309-48-4)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

### Chromium, ion (Cr6+) (18540-29-9)

- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List

### Kaolin (1332-58-7)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

#### 15.3. Canadian Regulations

### Cement, alumina, chemicals (65997-16-2)

Listed on the Canadian DSL (Domestic Substances List)

#### Limestone (1317-65-3)

Listed on the Canadian NDSL (Non-Domestic Substances List)

### Perlite (93763-70-3)

Listed on the Canadian DSL (Domestic Substances List)

### Cement, portland, chemicals (65997-15-1)

Listed on the Canadian DSL (Domestic Substances List)

### Calcium oxide (1305-78-8)

Listed on the Canadian DSL (Domestic Substances List)

### Quartz (14808-60-7)

Listed on the Canadian DSL (Domestic Substances List)

### Calcium sulfate dihydrate (13397-24-5)

Listed on the Canadian DSL (Domestic Substances List)

# Lithium carbonate (554-13-2)

Listed on the Canadian DSL (Domestic Substances List)

### Magnesium oxide (MgO) (1309-48-4)

Listed on the Canadian DSL (Domestic Substances List)

#### Kaolin (1332-58-7)

Listed on the Canadian DSL (Domestic Substances List)

## SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

**Date of Preparation or Latest** 

Revision

: 08/05/2020

**Other Information** 

: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200 and Canada's Hazardous Products

Regulations (HPR) SOR/2015-17.

### **GHS Full Text Phrases:**

| Acute Tox. 4           | Acute toxicity (inhalation:dust,mist) Category 4 |
|------------------------|--|
| (Inhalation:dust,mist) |  |

08/05/2020 EN (English US) 15/16

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

| 3 TO Federal Register / Vol. 77, No. 58 / Monday, M | larch 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015). |
|---|--|
| Acute Tox. 4 (Oral)                                 | Acute toxicity (oral) Category 4   |
| Aquatic Acute 1                                     | Hazardous to the aquatic environment - Acute Hazard Category 1   |
| Aquatic Acute 2                                     | Hazardous to the aquatic environment - Acute Hazard Category 2   |
| Aquatic Acute 3                                     | Hazardous to the aquatic environment - Acute Hazard Category 3   |
| Aquatic Chronic 1                                   | Hazardous to the aquatic environment - Chronic Hazard Category 1   |
| Aquatic Chronic 2                                   | Hazardous to the aquatic environment - Chronic Hazard Category 2   |
| Aquatic Chronic 3                                   | Hazardous to the aquatic environment - Chronic Hazard Category 3   |
| Carc. 1A  | Carcinogenicity Category 1A  |
| Carc. 1B  | Carcinogenicity Category 1B  |
| Eye Dam. 1  | Serious eye damage/eye irritation Category 1   |
| Eye Irrit. 2A                                       | Serious eye damage/eye irritation Category 2A  |
| Eye Irrit. 2B                                       | Serious eye damage/eye irritation Category 2B  |
| Lact  | Reproductive toxicity (Lact.)  |
| Repr. 1A  | Reproductive toxicity Category 1A  |
| Skin Corr. 1C                                       | Skin corrosion/irritation Category 1C  |
| Skin Irrit. 2                                       | Skin corrosion/irritation Category 2   |
| Skin Sens. 1  | Skin sensitization, Category 1   |
| STOT RE 1   | Specific target organ toxicity (repeated exposure) Category 1  |
| STOT SE 1   | Specific target organ toxicity (single exposure) Category 1  |
| STOT SE 3   | Specific target organ toxicity (single exposure) Category 3  |
| H302  | Harmful if swallowed   |
| H314  | Causes severe skin burns and eye damage  |
| H315  | Causes skin irritation   |
| H317  | May cause an allergic skin reaction  |
| H318  | Causes serious eye damage  |
| H319  | Causes serious eye irritation  |
| H320  | Causes eye irritation  |
| H332  | Harmful if inhaled   |
| H335  | May cause respiratory irritation   |
| H350  | May cause cancer   |
| H360  | May damage fertility or the unborn child   |
| H362  | May cause harm to breast-fed children  |
| H370  | Causes damage to organs  |
| H372  | Causes damage to organs through prolonged or repeated exposure   |
| H400  | Very toxic to aquatic life   |
| H401  | Toxic to aquatic life  |
| H402  | Harmful to aquatic life  |
| H410  | Very toxic to aquatic life with long lasting effects   |
| H411  | Toxic to aquatic life with long lasting effects  |
| H412  | Harmful to aquatic life with long lasting effects  |
| •   |  |

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

NA GHS SDS 2015 (Can, US)

08/05/2020 EN (English US) 16/16