



SPECTRALOCK® PRO Premium Grout Part B

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Date of Issue: 11/07/2019

Version: 1.0

SECTION 1: IDENTIFICATION

1.1. Product Identifier

Product Form: Mixture

Product Name: SPECTRALOCK® PRO Premium Grout Part B

1.2. Intended Use of the Product

Grout.

1.3. Name, Address, and Telephone of the Responsible Party

Company

LATICRETE International

1 Laticrete Park, N

Bethany, CT 06524

T (203)-393-0010

www.laticrete.com

Company

LATICRETE Canada ULC

PO Box 129, Emeryville, Ontario, Canada

NOR-1A0

(833)-254-9255

1.4. Emergency Telephone Number

Emergency Number : For Chemical Emergency call ChemTel Inc. day or night:

(800)255-3924 (North America)

(800)-099-0731 (Mexico)

+1 (813)248-0585 (International - collect calls accepted)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

GHS-US/CA Classification

Skin Irrit. 2 H315

Eye Irrit. 2A H319

Skin Sens. 1 H317

Aquatic Acute 2 H401

Aquatic Chronic 2 H411

Full text of hazard classes and H-statements : see section 16

2.2. Label Elements

GHS-US/CA Labeling

Hazard Pictograms (GHS-US/CA)



Signal Word (GHS-US/CA)

: Warning

Hazard Statements (GHS-US/CA)

: H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.

H319 - Causes serious eye irritation.

H401 - Toxic to aquatic life.

H411 - Toxic to aquatic life with long lasting effects.

Precautionary Statements (GHS-US/CA)

: P261 - Avoid breathing vapors, mist, or spray.

P264 - Wash hands, forearms and face thoroughly after handling.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P273 - Avoid release to the environment.

P280 - Wear protective gloves, protective clothing, and eye protection.

P302+P352 - IF ON SKIN: Wash with plenty of water.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P321 - Specific treatment (see section 4 on this SDS).

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

SPECTRALOCK® PRO Premium Grout Part B

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

P337+P313 - If eye irritation persists: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P391 - Collect spillage.
P501 - Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

2.4. Unknown Acute Toxicity (GHS-US/CA)

No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

3.2. Mixture

Name	Product Identifier	% *	GHS Ingredient Classification
Oxirane, 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis-, homopolymer	(CAS-No.) 25085-99-8	45 - 52	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Skin Sens. 1, H317 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Formaldehyde, polymer with (chloromethyl)oxirane and phenol	(CAS-No.) 9003-36-5	10 - 17	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Alkyl (C12-14) glycidyl ether	(CAS-No.) 68609-97-2	7 - 14	Skin Irrit. 2, H315 Skin Sens. 1, H317
Petroleum distillates, hydrotreated light	(CAS-No.) 64742-47-8	0.1 - 1	Flam. Liq. 3, H226 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Polyethylene glycol	(CAS-No.) 25322-68-3	<= 0.039	STOT SE 3, H335
Potassium hydroxide	(CAS-No.) 1310-58-3	0.0225	Met. Corr. 1, H290 Acute Tox. 3 (Oral), H301 Skin Corr. 1A, H314 Eye Dam. 1, H318 STOT SE 1, H370

Full text of H-phrases: see section 16

*Percentages are listed in weight by weight percentage (w/w%) for liquid and solid ingredients. Gas ingredients are listed in volume by volume percentage (v/v%).

** The actual concentration of ingredient(s) is withheld as a trade secret in accordance with the Hazardous Products Regulations (HPR) SOR/2015-17 and 29 CFR 1910.1200.

SECTION 4: FIRST AID MEASURES

4.1. Description of First-aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Inhalation: When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

Skin Contact: Remove contaminated clothing. Immediately drench affected area with water for at least 15 minutes. Obtain medical attention if irritation/rash develops or persists.

Eye Contact: Immediately rinse with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

Ingestion: Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

SPECTRALOCK® PRO Premium Grout Part B

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

4.2. Most Important Symptoms and Effects Both Acute and Delayed

General: Skin sensitization. Causes skin irritation. Causes serious eye irritation.

Inhalation: Prolonged exposure may cause irritation.

Skin Contact: May cause an allergic skin reaction. Redness, pain, swelling, itching, burning, dryness, and dermatitis.

Eye Contact: Contact causes severe irritation with redness and swelling of the conjunctiva.

Ingestion: Ingestion may cause adverse effects.

Chronic Symptoms: None expected under normal conditions of use.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Water spray, fog, carbon dioxide (CO₂), alcohol-resistant foam, or dry chemical.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not considered flammable but may burn at high temperatures.

Explosion Hazard: Product is not explosive.

Reactivity: Hazardous reactions will not occur under normal conditions.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO₂). Nitrogen oxides. Sulfur oxides. Phenolic compounds.

Other Information: Do not allow run-off from fire fighting to enter drains or water courses.

5.4. Reference to Other Sections

Refer to Section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Avoid breathing (vapor, mist, spray). Do not get in eyes, on skin, or on clothing. Avoid all contact with skin, eyes, or clothing.

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protective equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area.

6.2. Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment. Collect spillage.

6.3. Methods and Materials for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Precautions for Safe Handling: Avoid contact with skin, eyes and clothing. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid breathing vapors, mist, spray.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

SPECTRALOCK® PRO Premium Grout Part B

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Technical Measures: Comply with applicable regulations.

Storage Conditions: Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

Incompatible Materials: Strong acids, strong bases, strong oxidizers.

7.3. Specific End Use(s)

Grout.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), or Canadian provincial governments.

Petroleum distillates, hydrotreated light (64742-47-8)		
British Columbia	OEL TWA (mg/m ³)	200 mg/m ³ (application restricted to conditions in which there are negligible aerosol exposures)
Potassium hydroxide (1310-58-3)		
USA ACGIH	ACGIH Ceiling (mg/m ³)	2 mg/m ³
USA NIOSH	NIOSH REL (ceiling) (mg/m ³)	2 mg/m ³
Alberta	OEL Ceiling (mg/m ³)	2 mg/m ³
British Columbia	OEL Ceiling (mg/m ³)	2 mg/m ³
Manitoba	OEL Ceiling (mg/m ³)	2 mg/m ³
New Brunswick	OEL Ceiling (mg/m ³)	2 mg/m ³
Newfoundland & Labrador	OEL Ceiling (mg/m ³)	2 mg/m ³
Nova Scotia	OEL Ceiling (mg/m ³)	2 mg/m ³
Nunavut	OEL Ceiling (mg/m ³)	2 mg/m ³
Northwest Territories	OEL Ceiling (mg/m ³)	2 mg/m ³
Ontario	OEL Ceiling (mg/m ³)	2 mg/m ³
Prince Edward Island	OEL Ceiling (mg/m ³)	2 mg/m ³
Québec	PLAFOND (mg/m ³)	2 mg/m ³
Saskatchewan	OEL Ceiling (mg/m ³)	2 mg/m ³
Yukon	OEL Ceiling (mg/m ³)	2 mg/m ³
Polyethylene glycol (25322-68-3)		
USA AIHA	WEEL TWA (mg/m ³)	10 mg/m ³ (molecular weight>200-aerosol)

8.2. Exposure Controls

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed.

Personal Protective Equipment: Gloves. Protective clothing. Protective goggles.



Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear protective gloves.

Eye and Face Protection: Chemical safety goggles.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

Other Information: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

SPECTRALOCK® PRO Premium Grout Part B

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Physical State	: Liquid
Appearance	: White
Odor	: Ammonia
Odor Threshold	: Not available
pH	: Not available
Evaporation Rate	: Not available
Melting Point	: 0 °C (32 °F)
Freezing Point	: Not available
Boiling Point	: 100 °C (212 °F)
Flash Point	: Not available
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not applicable
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: Not available
Relative Vapor Density at 20°C	: Not available
Relative Density	: Not available
Specific Gravity	: 1.09
Solubility	: Water: Soluble
Partition Coefficient: N-Octanol/Water	: Not available
Viscosity	: Not available

SECTION 10: STABILITY AND REACTIVITY

- 10.1. **Reactivity:** Hazardous reactions will not occur under normal conditions.
- 10.2. **Chemical Stability:** Stable under recommended handling and storage conditions (see section 7).
- 10.3. **Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.
- 10.4. **Conditions to Avoid:** Direct sunlight, extremely high or low temperatures, and incompatible materials.
- 10.5. **Incompatible Materials:** Strong acids, strong bases, strong oxidizers.
- 10.6. **Hazardous Decomposition Products:** Not expected to decompose under ambient conditions.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on Toxicological Effects - Product

Acute Toxicity (Oral): Not classified

Acute Toxicity (Dermal): Not classified

Acute Toxicity (Inhalation): Not classified

LD50 and LC50 Data: Not available

Skin Corrosion/Irritation: Causes skin irritation.

Eye Damage/Irritation: Causes serious eye irritation.

Respiratory or Skin Sensitization: May cause an allergic skin reaction.

Germ Cell Mutagenicity: Not classified

Carcinogenicity: Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: Prolonged exposure may cause irritation.

Symptoms/Injuries After Skin Contact: May cause an allergic skin reaction. Redness, pain, swelling, itching, burning, dryness, and dermatitis.

Symptoms/Injuries After Eye Contact: Contact causes severe irritation with redness and swelling of the conjunctiva.

Symptoms/Injuries After Ingestion: Ingestion may cause adverse effects.

SPECTRALOCK® PRO Premium Grout Part B

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Chronic Symptoms: None expected under normal conditions of use.

11.2. Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Petroleum distillates, hydrotreated light (64742-47-8)	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rabbit	> 2000 mg/kg
LC50 Inhalation Rat	> 5.3 mg/l/4h
Potassium hydroxide (1310-58-3)	
LD50 Oral Rat	284 mg/kg
Polyethylene glycol (25322-68-3)	
LD50 Oral Rat	22 g/kg
LD50 Dermal Rabbit	> 20 g/kg
Alkyl (C12-14) glycidyl ether (68609-97-2)	
LD50 Oral Rat	17100 mg/kg
LD50 Dermal Rabbit	> 3987 mg/kg
Formaldehyde, polymer with (chloromethyl)oxirane and phenol (9003-36-5)	
LD50 Oral Rat	> 2 g/kg

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - General: Toxic to aquatic life with long lasting effects.

Petroleum distillates, hydrotreated light (64742-47-8)	
LC50 Fish 1	45 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 Fish 2	2.2 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
Formaldehyde, polymer with (chloromethyl)oxirane and phenol (9003-36-5)	
LOEC (Acute)	0.3 mg/l Daphnia magna
NOEC Chronic Crustacea	0.3 mg/l Daphnia magna

12.2. Persistence and Degradability

SPECTRALOCK® PRO Premium Grout Part B	
Persistence and Degradability	May cause long-term adverse effects in the environment.

12.3. Bioaccumulative Potential

SPECTRALOCK® PRO Premium Grout Part B	
Bioaccumulative Potential	Not established.
Petroleum distillates, hydrotreated light (64742-47-8)	
BCF Fish 1	61 - 159
Potassium hydroxide (1310-58-3)	
Log Pow	0.65

12.4. Mobility in Soil Not available

12.5. Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste Disposal Recommendations: Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

Additional Information: Container may remain hazardous when empty. Continue to observe all precautions.

Ecology - Waste Materials: Avoid release to the environment. This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

SPECTRALOCK® PRO Premium Grout Part B

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

14.1. In Accordance with DOT

Proper Shipping Name : ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S.Oxirane, 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis-, homopolymer; Formaldehyde, polymer with (chloromethyl)oxirane and phenol)

Hazard Class : 9

Identification Number : UN3082

Label Codes : 9

Packing Group : III

Marine Pollutant : Marine pollutant

ERG Number : 171



14.2. In Accordance with IMDG

Proper Shipping Name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.Oxirane, 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis-, homopolymer; Formaldehyde, polymer with (chloromethyl)oxirane and phenol)

Hazard Class : 9

Identification Number : UN3082

Label Codes : 9

Packing Group : III

EmS-No. (Fire) : F-A

EmS-No. (Spillage) : S-F

Marine pollutant : Marine pollutant



14.3. In Accordance with IATA

Proper Shipping Name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.Oxirane, 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis-, homopolymer; Formaldehyde, polymer with (chloromethyl)oxirane and phenol)


Hazard Class : 9

Identification Number : UN3082

Label Codes : 9

Packing Group : III

ERG Code (IATA) : 9L



14.4. In Accordance with TDG

Proper Shipping Name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.Oxirane, 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis-, homopolymer; Formaldehyde, polymer with (chloromethyl)oxirane and phenol)

Hazard Class : 9

Identification Number : UN3082

Label Codes : 9

Packing Group : III

Marine Pollutant (TDG) : Marine pollutant



SECTION 15: REGULATORY INFORMATION

15.1. US Federal Regulations

SPECTRALOCK® PRO Premium Grout Part B	
SARA Section 311/312 Hazard Classes	Health hazard - Respiratory or skin sensitization Health hazard - Skin corrosion or Irritation Health hazard - Serious eye damage or eye irritation
Petroleum distillates, hydrotreated light (64742-47-8)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Potassium hydroxide (1310-58-3)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
CERCLA RQ	1000 lb
Polyethylene glycol (25322-68-3)	

SPECTRALOCK® PRO Premium Grout Part B

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711).
Alkyl (C12-14) glycidyl ether (68609-97-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Formaldehyde, polymer with (chloromethyl)oxirane and phenol (9003-36-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711).
Oxirane, 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis-, homopolymer (25085-99-8)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711).

15.2. US State Regulations

Potassium hydroxide (1310-58-3)
U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
U.S. - Pennsylvania - RTK (Right to Know) List

15.3. Canadian Regulations

Petroleum distillates, hydrotreated light (64742-47-8)
Listed on the Canadian DSL (Domestic Substances List)
Potassium hydroxide (1310-58-3)
Listed on the Canadian DSL (Domestic Substances List)
Polyethylene glycol (25322-68-3)
Listed on the Canadian DSL (Domestic Substances List)
Alkyl (C12-14) glycidyl ether (68609-97-2)
Listed on the Canadian DSL (Domestic Substances List)
Formaldehyde, polymer with (chloromethyl)oxirane and phenol (9003-36-5)
Listed on the Canadian DSL (Domestic Substances List)
Oxirane, 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis-, homopolymer (25085-99-8)
Listed on the Canadian DSL (Domestic Substances List)

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Date of Preparation or Latest Revision	: 11/07/2019
Other Information	: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200 and Canada's Hazardous Products Regulations (HPR) SOR/2015-17.

GHS Full Text Phrases:

Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Asp. Tox. 1	Aspiration hazard Category 1
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 3	Flammable liquids Category 3
Met. Corr. 1	Corrosive to metals Category 1
Skin Corr. 1A	Skin corrosion/irritation Category 1A

SPECTRALOCK® PRO Premium Grout Part B

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization, Category 1
STOT SE 1	Specific target organ toxicity (single exposure) Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H226	Flammable liquid and vapor
H290	May be corrosive to metals
H301	Toxic if swallowed
H304	May be fatal if swallowed and enters airways
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H370	Causes damage to organs
H401	Toxic to aquatic life
H411	Toxic to aquatic life with long lasting effects

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

NA GHS SDS 2015 (Can, US)