



# MVIS™ Epoxy Pointing Mortar Part A

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Date of Issue: 10/29/2019

Version: 1.0

### SECTION 1: IDENTIFICATION

#### 1.1. Product Identifier

**Product Form:** Mixture

**Product Name:** MVIS™ Epoxy Pointing Mortar Part A

#### 1.2. Intended Use of the Product

Mortar.

#### 1.3. Name, Address, and Telephone of the Responsible Party

##### Company

LATICRETE International

1 Laticrete Park, N

Bethany, CT 06524

T (203)-393-0010

[www.laticrete.com](http://www.laticrete.com)

##### Company

LATICRETE Canada ULC

PO Box 129, Emeryville, Ontario, Canada

NOR-1A0

(833)-254-9255

#### 1.4. Emergency Telephone Number

**Emergency Number** : For Chemical Emergency call ChemTel Inc. day or night:

(800)255-3924 (North America)

(800)-099-0731 (Mexico)

+1 (813)248-0585 (International - collect calls accepted)

### SECTION 2: HAZARDS IDENTIFICATION

#### 2.1. Classification of the Substance or Mixture

##### GHS-US/CA Classification

Skin Corr. 1C H314

Eye Dam. 1 H318

Skin Sens. 1 H317

Repr. 1B H360

Aquatic Acute 2 H401

Aquatic Chronic 2 H411

Full text of hazard classes and H-statements : see section 16

#### 2.2. Label Elements

##### GHS-US/CA Labeling

##### Hazard Pictograms (GHS-US/CA)



##### Signal Word (GHS-US/CA)

: Danger

##### Hazard Statements (GHS-US/CA)

: H314 - Causes severe skin burns and eye damage.

H317 - May cause an allergic skin reaction.

H318 - Causes serious eye damage.

H360 - May damage fertility or the unborn child.

H401 - Toxic to aquatic life.

H411 - Toxic to aquatic life with long lasting effects.

##### Precautionary Statements (GHS-US/CA)

: P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P260 - Do not breathe mist, spray, vapors.

P264 - Wash hands, forearms and face thoroughly after handling.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P273 - Avoid release to the environment.

P280 - Wear protective gloves, protective clothing, and eye protection.

P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

# MVIS™ Epoxy Pointing Mortar Part A

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 - If exposed or concerned: Get medical advice/attention.

P310 - Immediately call a POISON CENTER or doctor.

P321 - Specific treatment (see section 4 on this SDS).

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

P362+P364 - Take off contaminated clothing and wash it before reuse.

P391 - Collect spillage.

P405 - Store locked up.

P501 - Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

### 2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

### 2.4. Unknown Acute Toxicity (GHS-US/CA)

No data available

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product Identifier	% *	GHS Ingredient Classification
Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-(2-aminomethylethyl)- .omega.-(2-aminomethylethoxy)-	(CAS-No.) 9046-10-0	2 - 4	Skin Corr. 1C, H314 Eye Dam. 1, H318 Aquatic Acute 3, H402 Aquatic Chronic 3, H412
Tetraethylenepentamine	(CAS-No.) 112-57-2	1 - 3	Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
2,4,6- Tri(dimethylaminomethyl)phenol	(CAS-No.) 90-72-2	< 0.9	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1B, H317 Aquatic Acute 3, H402
Bis[(dimethylamino)methyl]phenol	(CAS-No.) 71074-89-0	< 0.15	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335
1-Methyl-2-pyrrolidone	(CAS-No.) 872-50-4	0.13 - 0.14	Flam. Liq. 4, H227 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Repr. 1B, H360 STOT SE 3, H335
1,2-Propanediol	(CAS-No.) 57-55-6	0.05 - 0.09	Not classified

Full text of H-phrases: see section 16

# MVIS™ Epoxy Pointing Mortar Part A

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

\*Percentages are listed in weight by weight percentage (w/w%) for liquid and solid ingredients. Gas ingredients are listed in volume by volume percentage (v/v%).

### SECTION 4: FIRST AID MEASURES

#### 4.1. Description of First-aid Measures

**General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

**Inhalation:** Remove to fresh air and keep at rest in a position comfortable for breathing. Immediately call a poison center or doctor/physician.

**Skin Contact:** Immediately remove contaminated clothing. Immediately flush skin with plenty of water for at least 30 minutes. Get immediate medical advice/attention.

**Eye Contact:** Immediately rinse with water for at least 30 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.

**Ingestion:** Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

#### 4.2. Most Important Symptoms and Effects Both Acute and Delayed

**General:** Skin sensitization. May damage fertility. May damage the unborn child. Causes severe skin burns and eye damage.

**Inhalation:** May be corrosive to the respiratory tract.

**Skin Contact:** May cause an allergic skin reaction. Causes severe irritation which will progress to chemical burns.

**Eye Contact:** Causes permanent damage to the cornea, iris, or conjunctiva.

**Ingestion:** May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.

**Chronic Symptoms:** May damage fertility or the unborn child.

#### 4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

### SECTION 5: FIRE-FIGHTING MEASURES

#### 5.1. Extinguishing Media

**Suitable Extinguishing Media:** Water spray, fog, carbon dioxide (CO<sub>2</sub>), alcohol-resistant foam, or dry chemical.

**Unsuitable Extinguishing Media:** Do not use a heavy water stream. Use of heavy stream of water may spread fire.

#### 5.2. Special Hazards Arising From the Substance or Mixture

**Fire Hazard:** Not considered flammable but may burn at high temperatures.

**Explosion Hazard:** Product is not explosive.

**Reactivity:** May react exothermically with water releasing heat. Adding an acid to a base or base to an acid may cause a violent reaction.

#### 5.3. Advice for Firefighters

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire.

**Firefighting Instructions:** Use water spray or fog for cooling exposed containers.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

**Hazardous Combustion Products:** Carbon oxides (CO, CO<sub>2</sub>). Nitrogen oxides. Nitrous gases may be produced. Chlorine. Ammonia.

**Other Information:** Do not allow run-off from fire fighting to enter drains or water courses.

#### 5.4. Reference to Other Sections

Refer to Section 9 for flammability properties.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

#### 6.1. Personal Precautions, Protective Equipment and Emergency Procedures

**General Measures:** Do not get in eyes, on skin, or on clothing. Do not breathe vapor, mist or spray.

##### 6.1.1. For Non-Emergency Personnel

**Protective Equipment:** Use appropriate personal protective equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel.

##### 6.1.2. For Emergency Personnel

**Protective Equipment:** Equip cleanup crew with proper protection.

**Emergency Procedures:** Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area.

# MVIS™ Epoxy Pointing Mortar Part A

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

### 6.2. Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment. Collect spillage.

### 6.3. Methods and Materials for Containment and Cleaning Up

**For Containment:** Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. As an immediate precautionary measure, isolate spill or leak area in all directions.

**Methods for Cleaning Up:** Clean up spills immediately and dispose of waste safely. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill. Cautiously neutralize spilled liquid.

### 6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

## SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for Safe Handling

**Additional Hazards When Processed:** May release corrosive vapors.

**Precautions for Safe Handling:** Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe mist, spray, vapors. Do not get in eyes, on skin, or on clothing. Handle empty containers with care because they may still present a hazard.

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures.

### 7.2. Conditions for Safe Storage, Including Any Incompatibilities

**Technical Measures:** Comply with applicable regulations.

**Storage Conditions:** Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store locked up/in a secure area. Store in original container or corrosive resistant and/or lined container.

**Incompatible Materials:** N-Nitrosamines, many of which are known to be potent carcinogens, may be formed when the product comes in contact with nitrous acid, nitrites or atmospheres with high nitrous oxide concentrations. Nitrous acid and other nitrosating agents, organic acids (i.e. acetic acid, citric acid, etc.), Mineral acids, Oxidizing agents and Sodium hypochlorite. Products slowly corrodes copper, aluminum, zinc, and galvanized surfaces. Reaction with peroxides may result in violent decomposition of peroxide, possibly creating an explosion.

### 7.3. Specific End Use(s)

Mortar.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), or Canadian provincial governments.

Tetraethylenepentamine (112-57-2)		
USA AIHA	WEEL TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
USA AIHA	AIHA chemical category	skin notation, Skin sensitizer
1,2-Propanediol (57-55-6)		
USA AIHA	WEEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Ontario	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (for assessing the visibility in a work environment where 1,2-Propylene glycol aerosol is present-aerosol only) 155 mg/m <sup>3</sup> (aerosol and vapor)
Ontario	OEL TWA (ppm)	50 ppm (aerosol and vapor)
1-Methyl-2-pyrrolidone (872-50-4)		
USA ACGIH	Biological Exposure Indices (BEI)	100 mg/l Parameter: 5-Hydroxy-N-methyl-2-pyrrolidone - Medium: urine - Sampling time: end of shift
USA AIHA	WEEL TWA (ppm)	10 ppm
USA AIHA	AIHA chemical category	skin notation
Ontario	OEL TWA (mg/m <sup>3</sup> )	400 mg/m <sup>3</sup>
Yukon	OEL STEL (mg/m <sup>3</sup> )	500 mg/m <sup>3</sup>

# MVIS™ Epoxy Pointing Mortar Part A

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Yukon	OEL STEL (ppm)	125 ppm
Yukon	OEL TWA (mg/m <sup>3</sup> )	400 mg/m <sup>3</sup>
Yukon	OEL TWA (ppm)	100 ppm

### 8.2. Exposure Controls

**Appropriate Engineering Controls:** Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

**Personal Protective Equipment:** Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection. Face shield.



**Materials for Protective Clothing:** Chemically resistant materials and fabrics. Corrosion-proof clothing.

**Hand Protection:** Wear protective gloves.

**Eye and Face Protection:** Chemical safety goggles and face shield.

**Skin and Body Protection:** Wear suitable protective clothing.

**Respiratory Protection:** If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

**Other Information:** When using, do not eat, drink or smoke.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Yellow
Odor	: Ammonia
Odor Threshold	: Not available
pH	: Not available
Evaporation Rate	: Not available
Melting Point	: 0 °C (32 °F)
Freezing Point	: Not available
Boiling Point	: 100 °C (212 °F)
Flash Point	: Not available
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not applicable
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: Not available
Relative Vapor Density at 20°C	: Not available
Relative Density	: Not available
Specific Gravity	: 1.1
Solubility	: Water: Soluble
Partition Coefficient: N-Octanol/Water	: Not available
Viscosity	: Not available

## SECTION 10: STABILITY AND REACTIVITY

**10.1. Reactivity:** May react exothermically with water releasing heat. Adding an acid to a base or base to an acid may cause a violent reaction.

**10.2. Chemical Stability:** Stable under recommended handling and storage conditions (see section 7).

**10.3. Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.

# MVIS™ Epoxy Pointing Mortar Part A

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

**10.4. Conditions to Avoid:** Direct sunlight, extremely high or low temperatures, and incompatible materials.

**10.5. Incompatible Materials:** N-Nitrosamines, many of which are known to be potent carcinogens, may be formed when the product comes in contact with nitrous acid, nitrites or atmospheres with high nitrous oxide concentrations. Nitrous acid and other nitosating agents, organic acids (i.e. acetic acid, citric acid, etc.), Mineral acids, Oxidizing agents and Sodium hypochlorite. Products slowly corrodes copper, aluminum, zinc, and galvanized surfaces. Reaction with peroxides may result in violent decomposition of peroxide, possibly creating an explosion.

**10.6. Hazardous Decomposition Products:** Thermal decomposition generates : Corrosive vapors.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on Toxicological Effects - Product

**Acute Toxicity (Oral):** Not classified

**Acute Toxicity (Dermal):** Not classified

**Acute Toxicity (Inhalation):** Not classified

**LD50 and LC50 Data:** Not available

**Skin Corrosion/Irritation:** Causes severe skin burns and eye damage.

**Eye Damage/Irritation:** Causes serious eye damage.

**Respiratory or Skin Sensitization:** May cause an allergic skin reaction.

**Germ Cell Mutagenicity:** Not classified

**Carcinogenicity:** Not classified

**Specific Target Organ Toxicity (Repeated Exposure):** Not classified

**Reproductive Toxicity:** May damage fertility or the unborn child.

**Specific Target Organ Toxicity (Single Exposure):** Not classified

**Aspiration Hazard:** Not classified

**Symptoms/Injuries After Inhalation:** May be corrosive to the respiratory tract.

**Symptoms/Injuries After Skin Contact:** May cause an allergic skin reaction. Causes severe irritation which will progress to chemical burns.

**Symptoms/Injuries After Eye Contact:** Causes permanent damage to the cornea, iris, or conjunctiva.

**Symptoms/Injuries After Ingestion:** May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.

**Chronic Symptoms:** May damage fertility or the unborn child.

### 11.2. Information on Toxicological Effects - Ingredient(s)

**LD50 and LC50 Data:**

<b>Bis[(dimethylamino)methyl]phenol (71074-89-0)</b>	
<b>ATE US/CA (oral)</b>	500.00 mg/kg body weight
<b>ATE US/CA (dermal)</b>	1,100.00 mg/kg body weight
<b>2,4,6-Tri(dimethylaminomethyl)phenol (90-72-2)</b>	
<b>LD50 Oral Rat</b>	1200 mg/kg
<b>LD50 Dermal Rat</b>	1280 mg/kg
<b>Tetraethylenepentamine (112-57-2)</b>	
<b>LD50 Dermal Rabbit</b>	660 - 1260 mg/kg
<b>ATE US/CA (oral)</b>	500.00 mg/kg body weight
<b>Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-(2-aminomethylethyl)-.omega.-(2-aminomethylethoxy)- (9046-10-0)</b>	
<b>LD50 Oral Rat</b>	2885 mg/kg (Specoes: Sprague-Dawley)
<b>1,2-Propanediol (57-55-6)</b>	
<b>LD50 Oral Rat</b>	20 g/kg
<b>LD50 Dermal Rabbit</b>	20800 mg/kg
<b>1-Methyl-2-pyrrolidone (872-50-4)</b>	
<b>LD50 Oral Rat</b>	4150 mg/kg
<b>LD50 Dermal Rabbit</b>	> 5000 mg/kg
<b>LC50 Inhalation Rat</b>	5.1 mg/l/4h

# MVIS™ Epoxy Pointing Mortar Part A

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

### SECTION 12: ECOLOGICAL INFORMATION

#### 12.1. Toxicity

Ecology - General: Toxic to aquatic life with long lasting effects.

<b>2,4,6-Tri(dimethylaminomethyl)phenol (90-72-2)</b>	
ErC50 (algae)	84 mg/l
NOEC Chronic Algae	6.25 g/l
<b>Tetraethylenepentamine (112-57-2)</b>	
LC50 Fish 1	420 mg/l (Exposure time: 96 h - Species: Poecilia reticulata [static])
EC50 Daphnia 1	24.1 mg/l (Exposure time: 48 h - Species: Daphnia magna)
ErC50 (algae)	0.12 mg/l
<b>Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-(2-aminomethylethyl)-.omega.-(2-aminomethylethoxy)- (9046-10-0)</b>	
EC50 Daphnia 1	80 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
NOEC Chronic Crustacea	18 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
<b>1,2-Propanediol (57-55-6)</b>	
LC50 Fish 1	51600 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 1	10000 mg/l (Exposure time: 24 h - Species: Daphnia magna)
LC50 Fish 2	41 - 47 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 2	1000 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
<b>1-Methyl-2-pyrrolidone (872-50-4)</b>	
LC50 Fish 1	832 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
EC50 Daphnia 1	4897 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 Fish 2	1072 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
NOEC Chronic Crustacea	12.5 mg/l

#### 12.2. Persistence and Degradability

<b>MVIS™ Epoxy Pointing Mortar Part A</b>	
Persistence and Degradability	May cause long-term adverse effects in the environment.

#### 12.3. Bioaccumulative Potential

<b>MVIS™ Epoxy Pointing Mortar Part A</b>	
Bioaccumulative Potential	Not established.
<b>Tetraethylenepentamine (112-57-2)</b>	
BCF Fish 1	(no bioaccumulation expected)
Log Pow	< 1
<b>Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-(2-aminomethylethyl)-.omega.-(2-aminomethylethoxy)- (9046-10-0)</b>	
Log Kow	0
<b>1,2-Propanediol (57-55-6)</b>	
BCF Fish 1	< 1
Log Pow	-0.92
<b>1-Methyl-2-pyrrolidone (872-50-4)</b>	
Log Pow	-0.46 (at 25 °C)

12.4. Mobility in Soil Not available

#### 12.5. Other Adverse Effects

Other Information: Avoid release to the environment.

### SECTION 13: DISPOSAL CONSIDERATIONS

#### 13.1. Waste treatment methods

**Waste Disposal Recommendations:** Dispose of contents/container in accordance with local, regional, national, and international regulations

**Additional Information:** Container may remain hazardous when empty. Continue to observe all precautions.

**Ecology - Waste Materials:** Avoid release to the environment. This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

# MVIS™ Epoxy Pointing Mortar Part A

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

## SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

### 14.1. In Accordance with DOT

**Proper Shipping Name** : CORROSIVE LIQUIDS, N.O.S.(Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-(2-aminomethylethyl)-.omega.-(2-aminomethylethoxy)-; Tetraethylenepentamine)

**Hazard Class** : 8

**Identification Number** : UN1760

**Label Codes** : 8

**Packing Group** : III

**Marine Pollutant** : Marine pollutant

**ERG Number** : 154



### 14.2. In Accordance with IMDG

**Proper Shipping Name** : CORROSIVE LIQUID, N.O.S.(Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-(2-aminomethylethyl)-.omega.-(2-aminomethylethoxy)-; Tetraethylenepentamine)

**Hazard Class** : 8

**Identification Number** : UN1760

**Label Codes** : 8

**Packing Group** : III

**EmS-No. (Fire)** : F-A

**EmS-No. (Spillage)** : S-B

**Marine pollutant** : Marine pollutant



### 14.3. In Accordance with IATA

**Proper Shipping Name** : CORROSIVE LIQUID, N.O.S.(Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-(2-aminomethylethyl)-.omega.-(2-aminomethylethoxy)-; Tetraethylenepentamine)

**Hazard Class** : 8

**Identification Number** : UN1760

**Label Codes** : 8

**Packing Group** : III

**ERG Code (IATA)** : 8L



### 14.4. In Accordance with TDG

**Proper Shipping Name** : CORROSIVE LIQUID, N.O.S.(Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-(2-aminomethylethyl)-.omega.-(2-aminomethylethoxy)-; Tetraethylenepentamine)

**Hazard Class** : 8

**Identification Number** : UN1760

**Label Codes** : 8

**Packing Group** : III

**Marine Pollutant (TDG)** : Marine pollutant



## SECTION 15: REGULATORY INFORMATION

### 15.1. US Federal Regulations

<b>MVIS™ Epoxy Pointing Mortar Part A</b>	
<b>SARA Section 311/312 Hazard Classes</b>	Health hazard - Respiratory or skin sensitization Health hazard - Reproductive toxicity Health hazard - Serious eye damage or eye irritation Health hazard - Skin corrosion or Irritation
<b>2,4,6-Tri(dimethylaminomethyl)phenol (90-72-2)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Tetraethylenepentamine (112-57-2)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-(2-aminomethylethyl)-.omega.-(2-aminomethylethoxy)- (9046-10-0)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	



# MVIS™ Epoxy Pointing Mortar Part A

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

<b>EPA TSCA Regulatory Flag</b>	XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711).
<b>1,2-Propanediol (57-55-6)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>1-Methyl-2-pyrrolidone (872-50-4)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313	
<b>EPA TSCA Regulatory Flag</b>	R - R - indicates a substance that is the subject of a TSCA section 6 risk management rule.
<b>SARA Section 313 - Emission Reporting</b>	1 %

### 15.2. US State Regulations

#### California Proposition 65



**WARNING:** This product can expose you to 1-Methyl-2-pyrrolidone, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Chemical Name (CAS No.)	Carcinogenicity	Developmental Toxicity	Female Reproductive Toxicity	Male Reproductive Toxicity
1-Methyl-2-pyrrolidone (872-50-4)		X		

#### Tetraethylenepentamine (112-57-2)

U.S. - Massachusetts - Right To Know List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List

#### 1,2-Propanediol (57-55-6)

U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List

#### 1-Methyl-2-pyrrolidone (872-50-4)

U.S. - Massachusetts - Right To Know List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List

### 15.3. Canadian Regulations

#### 2,4,6-Tri(dimethylaminomethyl)phenol (90-72-2)

Listed on the Canadian DSL (Domestic Substances List)

#### Tetraethylenepentamine (112-57-2)

Listed on the Canadian DSL (Domestic Substances List)

#### Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-(2-aminomethylethyl)-.omega.-(2-aminomethylethoxy)- (9046-10-0)

Listed on the Canadian DSL (Domestic Substances List)

#### 1,2-Propanediol (57-55-6)

Listed on the Canadian DSL (Domestic Substances List)

#### 1-Methyl-2-pyrrolidone (872-50-4)

Listed on the Canadian DSL (Domestic Substances List)

## SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

**Date of Preparation or Latest Revision** : 10/29/2019

**Revision**

**Other Information** : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200 and Canada's Hazardous Products Regulations (HPR) SOR/2015-17.

#### GHS Full Text Phrases:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4

# MVIS™ Epoxy Pointing Mortar Part A

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 4	Flammable liquids Category 4
Repr. 1B	Reproductive toxicity Category 1B
Skin Corr. 1B	Skin corrosion/irritation Category 1B
Skin Corr. 1C	Skin corrosion/irritation Category 1C
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization, Category 1
Skin Sens. 1B	Skin sensitization, category 1B
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H227	Combustible liquid
H302	Harmful if swallowed
H311	Toxic in contact with skin
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H360	May damage fertility or the unborn child
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*

NA GHS SDS 2015 (Can, US)