



NXT® Level

Fire-rated, high-strength self-leveling underlayment



Data Sheet 504

NXT® Level is a fire-rated, high-strength cement-based self-leveling underlayment designed to level interior floor substrates and allow floor covering installations in just 16 hours. Pumpable or pourable to as deep as 3 inches (76 mm) in a single lift and walkable in 2 to 3 hours, it reduces project time and cost. A solution for fire-rated construction, NXT Level is UL-certified for fire resistance for up to 2-hours in fire-rated floor-to-ceiling assemblies. Its faster cure times, superior durability, and direct compatibility with adhesives make it a high-performance alternative to traditional gypsum underlayments. Choose NXT Level for efficient, durable and code-compliant installations.



FEATURES	BENEFITS
High strength with 5000 psi (34 MPa)	Long-lasting, durable, and resists construction traffic
Rapid cure times - walkable in 2-3 hours with final flooring in 16 hours	Minimizes downtime and reduces project timeline
UL certification for Type "LAT": Tested in accordance to ANSI/UL 263 (ASTM E119) & ASTM E84 - Fire-rated up to 2 hours	Meets building codes offering safety assurances to occupants
Pump or pour from 1/8 to 3 in (76 mm) deep	Eliminates the need for additional lifts
Moisture resistant	Will not break down when exposed to water
Compatibility with adhesives allows for direct application of adhesives without a sealer	Saves time and cost, and reduces the risk of failure by simplifying the installation process

Uses

- Commercial, retail (malls & shops)
- Healthcare
- Education (schools & universities)
- Residential, multifamily
- Hospitality, hotels
- Office

Suitable Substrates

- Concrete
- Gypsum
- Exterior glue plywood
- Resilient flooring
- Ceramic tile
- Stone
- Vinyl tile

UL floor/ceiling assembly designs:

L501, L502, L511, L512, L518, L525, L527, L528, L529, L530, L541, L570, L573, M509, M510
See productiq.ulprospector.com for design details.

Item #	Packaging
0900-0050-21	50 lb (22.7 kg) bag, 56 bags per pallet
0900-2500-21	2500 lb (1,134 kg) sack, 1 sack per pallet



Scan for more information.

