




NXT[®] Patch

Cement based underlayment patching and repair product



Data Sheet 501



NXT[®] Patch is a premium quality, fast-drying underlayment patch designed for use over most substrates and can be used for interior or exterior applications. The cement-based formula is excellent for deep fills from 1/8" - 1 1/2" (3 - 38 mm) per application.

| FEATURES | BENEFITS |
|---|---|
| Interior or exterior applications | Wide range of applications |
| Excellent bond strength | Long lasting repair |
| Easy to mix and apply | User friendly |
| Fast drying | Apply finish floor goods in as soon as 40 minutes |
| Can be applied over concrete testing up to RH of 100% | Robust formula |

Suitable Substrates

- Cement Backer Board
- Cement Mortar Bed
- Cement Terrazzo
- Ceramic Tile and Stone
- Concrete
- Gypsum Underlayments

Uses

Repairing uneven or broken concrete to create a smooth substrate for finished goods.

Packaging

25 lbs (11.3 kg)/64 per pallet/Item

Item

0904-0025-21




Scan for more information.





NXT® Parche

Producto para reparación y parcheo de solado a base de cemento



Especificación 501



NXT® Parche es un parche para base de piso de secado rápido y calidad prémium diseñado para usar sobre la mayoría de los sustratos y se puede usar para aplicaciones interiores o exteriores. La fórmula a base de cemento es ideal para rellenos profundos de 3 a 38 mm (1/8 a 1 1/2 pulg.) por aplicación.

| CARACTERÍSTICAS | BENEFICIOS |
|---|---|
| Aplicaciones en interiores y exteriores | Amplia gama de aplicaciones |
| Resistencia adhesiva excepcional | Reparaciones duraderas |
| Fácil de mezclar y aplicar | Fácil de usar |
| Secado rápido | Permite la instalación de acabados de piso en solo 40 minutos |
| Se puede aplicar sobre concreto para pruebas con el 100 % de humedad relativa (Relative humidity, RH) | Fórmula robusta |

Sustratos adecuados

- Panel de cemento
- Capa de mortero de cemento
- Terrazo de cemento
- Revestimiento cerámico y piedra
- Concreto
- Solados de yeso

Usos

Reparación de concreto disperejo o roto para crear un sustrato liso para productos terminados.

Presentación

11.3 kg (25 libras)/64 por paleta/N.º

Artículo N.º

0904-0025-21

Para obtener más información, tome una fotografía con su dispositivo móvil.

